Comprehensive Long-term Environmental Action Talvay

CONTRACT NUMBER N62467-04-D-0055



Rev. 0 01/08

N00210.AR.000221

Electric Resistance Heating (ERH) Treatability Study Report for Site 22 Former Building 105 Old Dry Cleaning Facility

Naval Station Great Lakes Great Lakes, Illinois

Contract Task Order 0009

January 2008



Midwest
201 Decatur Avenue, Building 1A
Great Lakes, Illinois 60088

ELECTRIC RESISTANCE HEATING (ERH) TREATABILITY STUDY REPORT FOR SITE 22 FORMER BUILDING 105 OLD DRY CLEANING FACILITY

NAVAL STATION GREAT LAKES GREAT LAKES, ILLINOIS

COMPREHENSIVE LONG-TERM ENVIRONMENTAL ACTION NAVY (CLEAN) CONTRACT

Submitted to:
Naval Facilities Engineering Command Midwest
201 Decatur Avenue, Building 1A
Great Lakes, Illinois 60088

Submitted by:
Tetra Tech NUS, Inc.
661 Andersen Drive
Foster Plaza 7
Pittsburgh, Pennsylvania 15220

CONTRACT NUMBER N62467-04-D-0055 CONTRACT TASK ORDER 0009

JANUARY 2008

PREPARED UNDER THE SUPERVISION OF:

ROBERT DAVIS, PE TASK ORDER MANAGER TETRA TECH NUS, INC. APPROVED FOR SUBMITTAL BY:

DEBRA M. HUMBERT PROGRAM MANAGER TETRA TECH NUS, INC.

IR PROGRAM MANAGER

NAVAL STATION GREAT LAKES

TABLE OF CONTENTS

SEC1	<u>ION</u>		PAGE NO.							
ACR	ONYMS		4							
1.0	INTRODUCTION									
	1.1	DOCUMENT ORGANIZATION	1-1							
	1.2	SITE DESCRIPTION								
	1.2.1	Site History								
	1.2.2	Geology and Hydrogeology								
	1.2.3	Summary of Source Area Contamination Assessment	1-4							
	1.3	ERH TECHNOLOGY DESCRIPTION	1-5							
	1.4	TREATABILITY STUDY EXPECTATIONS AND GOALS	1-6							
2.0	TECHN	OLOGY IMPLEMENTATION	2-1							
	2.1	ERH TREATABILITY STUDY DESIGN								
	2.1.1	Pre-Remediation Sampling								
	2.1.2	ERH Treatability Study System Design								
	2.2	FIELD IMPLEMENTATION CHRONOLOGY								
	2.3	FIELD IMPLEMENTATION AND PROCEDURES								
	2.3.1	Electrode and Surface Equipment Installation								
	2.3.2	Monitoring Well Abandonment								
	2.3.3	System Start-Up and Operation								
	2.3.4	System Demobilization and Site Restoration								
	2.3.5	Remediation-Derived Waste Disposal								
	2.4	DATA COLLECTION FOR EVALUATION OF ERH TREATABILITY STUDY								
	۷.٦	SYSTEM								
	2.4.1	Temperature Monitoring								
	2.4.2	Vapor Stream Sampling								
	2.4.2	Soil Sampling								
	2.4.4	Pore Water Sampling								
3.0	TECHN	OLOGY PERFORMANCE	3-1							
0.0	3.1	TEMPERATURE MONITORING RESULTS AND EVALUATION	3-1							
	3.2	VAPOR SAMPLING RESULTS AND EVALUATION								
	3.3	SOIL SAMPLING RESULTS AND EVALUATION								
	3.4	PORE WATER SAMPLING RESULTS AND EVALUATION								
	3.5	ACHIEVEMENT OF STUDY GOALS								
4.0	HUMAN	N HEALTH RISK ASSESSMENT FOR POST-TREATMENT CONDITIONS	4-1							
	4.1	DATA EVALUATION	4-1							
	4.2	EXPOSURE POINT CONCENTRATIONS	4-1							
	4.3	POTENTIAL RECEPTORS								
	4.4	EXPOSURE ROUTES AND PATHWAYS								
	4.5	GROUNDWATER MODELING								
	4.6	POST-TREATMENT RISK ASSESSMENT RESULTS								
5.0	CONCL	USIONS AND RECOMMENDATIONS	5-1							
	5.1	SUMMARY AND CONCLUSIONS	5-1							
	5.2	RECOMMENDATIONS	5-2							

120711/P

Revision: 1
Date: January 2008

Section: Table of Contents Page 2 of 4

TABLE OF CONTENTS (Continued)

SECTIO	<u>PAGE NO.</u>
REFER	ENCESR-1
	APPENDICES
APPEN	<u>DICES</u>
	A FINAL ERH REPORT – TRS, 2006 B WELL ABANDONMENT AND WELL CONSTRUCTION FORMS C WASTE DISPOSAL DOCUMENTATION D FIELD LOG SHEETS E SURVEY DATA F LABORATORY ANALYTICAL DATA, CHAIN OF CUSTODY RECORDS, AND VALIDATION INFORMATION G NAVAL STATION GREAT LAKES GROUNDWATER USE RESTRICTIONS MEMORANDUM H GROUNDWATER MODELING CALCULATIONS I RESOURCE CONSERVATION AND RECOVERY ACT (RCRA) CLOSURE FORMS
	TABLES
NUMBE	<u>ER</u>
2-1 2-2 2-3 2-4 3-1 3-2 3-3 4-1	Summary of Pre-Treatability Study Soil Sample Results Summary of Pre-Treatability Study and Historical Pore Water Sample Results Summary of Baseline Treatment Area Soil Sample Results Chronology of Field Events Summary of Soil Vapor and cVOC Removal Data Summary of Soil Performance Sampling Data Summary of Pore Water Data Summary of Descriptive Statistics and Comparisons for Treatability Study – Surface/Subsurface Soil Data – Rounds 3/4 Summary of Descriptive Statistics and Comparisons for Treatability Study – Groundwater (Pore

120711/P CTO 0009

Post-Treatment PCE Modeling Input Parameters and Results

Summary of Human Health Risks

4-3

4-4

Naval Station Great Lakes ERH Treatability Study Report - Site 22 Revision: 1 Date: January 2008 Section: Table of Contents Page 3 of 4

FIGURES

NUMBER

1-1	Site Location Map
1-2	Site Map
2-1	Pre-Remediation Sampling Soil Concentrations
2-2	Baseline Soil Concentrations
2-3	As-Built ERH System Layout
3-1	Subsurface Temperature Profile – Area 1
3-2	Subsurface Temperature Profile – Area 2
3-3	Subsurface Temperature Profile – Area 3
3-4	Average Soil cVOC Concentrations – Baseline and Performance Sampling
3-5	Soil Sample Concentrations – First Performance Sampling
3-6	Soil Sample Concentrations – Second Performance Sampling
3-7	Soil Sample Concentrations – Third Performance Sampling
3-8	Soil Sample Concentrations – Fourth Performance Sampling
3-9	Pore Water Sample Concentrations – Pre and Post Treatability Study

120711/P CTO 0009

Revision: 1 Date: January 2008

Page 4 of 4

Section: Table of Contents

ACRONYMS

bgs Below ground surface
COC Chemical of concern
cVOC Chlorinated VOC

EPC Exposure point concentration
ERH Electrical Resistance Heating

Ft/day Feet per day
HI Hazard index

HHRA Human Health Risk Assessment
ILCR Incremental lifetime cancer risk
IAC Illinois Administrative Code

Illinois EPA Illinois Environmental Protection Agency

ISGS Illinois State Geological Survey

LUC Land use control

MCL Maximum contaminant limit mg/kg Milligram per kilogram

NAVFAC MW Naval Facilities Engineering Command Midwest

NS Naval Station

PCE Tetrachloroethene

PID Photoionization detector

ppm Parts per million

RCRA Resource Conservation and Recovery Act
RI/RA Remedial Investigation/Risk Assessment

TACO Tiered Approach to Corrective Action Objectives

TMP Temperature monitoring point

TRS Thermal Remediation Services, Inc.

TtNUS Tetra Tech NUS, Inc.
UCL Upper confidence limit

U.S. EPA United States Environmental Protection Agency

VOC Volatile organic compound

VR Vapor recovery µg/L Micrograms per liter

120711/P CTO 0009

Revision: 1 Date: January 2008

Section: 1.0 Page: 1 of 6

1.0 INTRODUCTION

This Electric Resistance Heating (ERH) Treatability Study Report has been prepared for Site 22, Former

Building 105 Old Dry Cleaning Facility, at Naval Station (NS) Great Lakes located in Lake County, Illinois.

The report has been prepared by Tetra Tech NUS, Inc. (TtNUS) for the Department of the Navy, Naval

Facilities Engineering Command Midwest (NAVFAC MW) under the Comprehensive Long-Term

Environmental Action Navy IV Contract No. N62467-04-D-0055, Contract Task Order 0009.

The purpose of the study was to demonstrate the effectiveness of ERH in remediating source area

contaminants present at the former dry cleaning facility. The primary goal of the study was to reduce the

average concentration of chlorinated volatile organic compounds (cVOCs) in soil to less than

20 milligrams per kilogram (mg/kg). It was calculated that doing so would reduce cVOC concentrations

by 95.5 percent. This report summarizes the methodology and results of this study.

1.1 DOCUMENT ORGANIZATION

Section 1.0 of this report presents an introduction to the project, a site description, and a summary of the

technology that was demonstrated. Section 2.0 summarizes the design and procedures conducted in the

field to implement this technology demonstration. Section 3.0 summarizes the data and evaluates the

performance of the ERH system. Section 4.0 includes an update to the Human Health Risk Assessment

(HHRA) for the site utilizing the post-remediation data. Section 5.0 summarizes the conclusions of this

study and provides recommendations for additional site activities. Appendix A includes the final

and provides recommendations for additional site delivines. Appendix A mondaes the initial

subcontractor ERH Report prepared by Thermal Remediation Services, Inc (TRS). Appendix B includes

well abandonment forms and monitoring well construction diagrams for the re-installed wells. Appendix C

contains the investigation- and remediation-derived waste disposal documentation. Appendix D contains

field log sheets completed during the study. Appendix E presents survey data for the re-installed

monitoring wells. Appendix F presents the laboratory analytical data, chain-of-custody forms, and data

validation information associated with the study. Appendix G includes the Resource Conservation and

Recovery Act (RCRA) forms for closure of the drum storage area associated with Building 105 and the

dry cleaning facility.

1.2 SITE DESCRIPTION

NS Great Lakes is located in Lake County, Illinois, north of the City of Chicago, and encompasses

1.5 miles of Lake Michigan shoreline (see Figure 1-1). NS Great Lakes is used to support naval training

and consists of the Administrative Command, the Recruit Training Command, and the Service School

120711/P 1-1 CTO 0009

Revision: 1 Date: January 2008

Section: 1.0 Page: 2 of 6

Command. In 1986, an Initial Assessment Study conducted at NS Great Lakes identified 14 potentially

contaminated sites. Each site was evaluated with respect to contamination characteristics, migration

pathways, and pollutant receptors. The study concluded that seven of these sites warranted further

investigation to assess potential long-term impacts. Although Site 22 was not included as one of these

seven sites, investigations to close the hazardous waste storage area at Site 22 through the RCRA

program identified soil contamination that warranted further investigation.

Site 22, Former Building 105, Old Dry Cleaning Facility, at NS Great Lakes is bounded on the south by

Porter Street, on the west by a vacant asphalt-paved lot, on the north by Bronson Avenue, and on the

east by Sampson Street, as shown on Figure 1-2. The building was a slab-on-grade structure measuring

approximately 150 feet by 70 feet. The former 10,500-square-foot building occupied a lot measuring

approximately 250 feet by 115 feet. NS Great Lakes (United States Environmental Protection Agency

[U.S. EPA] # IL7170024577) has operated with RCRA interim status authorization since November 19,

1980. Building 105 was originally included in a RCRA Part A permit that has been modified over the past

25 years. This RCRA drum storage unit is located in the southeastern quarter of the northwestern quarter

of the southwestern quarter of Section 4, Township 44 North, Range 12 East (TtNUS, 2003).

1.2.1 Site History

Building 105 was constructed in 1939 and was utilized as a dry cleaning facility until 1993 or 1994 when it

was converted to a vending machine supply and repair station. From 1993 or 1994 until February 2001,

the building was used to warehouse and repair vending equipment and products. The vending machine

supply and repair operations ceased in February 2001, and the building was vacant until it was

demolished in March 2003.

The RCRA unit in Building 105 (SO1) consisted of a drum storage area located inside the building along

the eastern wall. Hazardous waste consisting of spent tetrachloroethene (PCE) from the laundry facilities

was stored in this area from 1980 until 1987. The maximum quantity of waste stored at this unit is

unknown; however, according to the revised RCRA permit, 165 gallons (three 55-gallon drums) was the

maximum amount of waste stored at one time. The storage area consisted of the concrete floor (no

berms or curbs were present) within the building adjoining the concrete block exterior wall. Near the

storage area, two cracks and construction joints were observed in the concrete floor, as well as a garage-

type entry door and several floor drains. Historical building foundation plans show that the floor drains

type entry door and several floor drains. Thistorical ballating foundation plans show that the floor drains

were connected to the storm sewer system located outside of the building. No visual evidence of spillage (staining) was observed or reported in this area, and the floor was in good condition in February 2003 as

indicated in the Remedial Investigation and Risk Assessment (RI/RA) Report (TtNUS, 2004).

120711/P 1-2 CTO 0009

Revision: 1 Date: January 2008

Section: 1.0 Page: 3 of 6

The building foundation plans also show two 6-inch-diameter drains running from the gutter under the

washing machines associated with the previous laundry operations. These drains were connected to a

grease catch basin located outside the southeastern corner of the building. The grease catch basin was

approximately 5 feet by 7.5 feet by 5.5 feet deep and had a 6-inch-diameter tile effluent pipe. It is

speculated that the effluent line from the grease catch basin was connected to a manhole located outside

of the building along Sampson Street for the sanitary lines for NS Great Lakes and that the soil and

groundwater contamination at the site is derived from this aspect of the dry cleaner operations (TtNUS,

2006a).

1.2.2 Geology and Hydrogeology

Fill material consisting of gravel, sand, silt, cinders, and occasionally bricks is present over most of

Site 22 to thicknesses of up to approximately 5 feet. Below the fill material layer is a heterogeneous

mixture of sandy clays, gravelly clays, and silty clays with discontinuous silt and sand stringers to a depth

of 30 feet below ground surface (bgs) that is considered the undisturbed, shallow subsurface lithology of

Site 22. Immediately below this is a fine- to coarse-grained sand layer that appears to be laterally

extensive over much of the site. The thickness of this sand layer varies slightly, ranging from

approximately 7 to 10 feet thick. Immediately below this sand layer are clays and silty clays. Laboratory

sieve analysis of composite samples from the undisturbed, shallow subsurface lithology indicates that the

Unified Soil Classification System descriptions of these soils are ML (sandy silt) to CL (silty clay).

Two separate aquifers are present at Site 22, a shallow (water table) and a deep confined aquifer. The

shallow aquifer ranges from 4 to 30 feet bgs and is composed primarily of unconsolidated clays, silts, and

silty clays with discontinuous sand and gravel lenses interspersed throughout. In general, the water table

within these heterogeneous soils is shallow and is typically encountered at a depth of 4 to 18 feet bgs at

the site. Groundwater can be expected to migrate horizontally in the more permeable materials found in

the silts and clays.

The groundwater flow pattern for the shallow aquifer is fairly complicated. The horizontal groundwater

gradient is very similar across most of the site, although the direction varies widely. Groundwater flow in

the shallow aquifer is to the west, east, and south. From a very general perspective (considering the four

monitoring wells located around the perimeter of the site - MW01S, MW02S, MW07S, and MW08S),

groundwater migrates southwest in the general direction of Pettibone Creek. However, based on the

undisturbed, shallow subsurface lithology, horizontal groundwater flow occurs only in the discontinuous

120711/P 1-3 CTO 0009

Revision: 1 Date: January 2008

January 2008 Section: 1.0 Page: 4 of 6

sand and gravel lenses. Therefore, large-scale site-wide (and off-site) transport of the contaminants is

not likely.

Horizontal hydraulic conductivity in the shallow aquifer ranged from 0.00248 feet per day (ft/day) to

3.53 feet per day, with a geometric mean of 0.186 ft/day. Using the geometric mean hydraulic

conductivity, the hydraulic gradient for the site (ranging from 0.03 to 0.04, and a porosity of 0.35, a

groundwater velocity ranging from 6.21 to 8.25 feet per year was calculated (TtNUS, 2006a).

The deep aguifer ranges from 30 to 40 feet bgs and is composed of fine to coarse sand. Static

groundwater levels in wells screened in the deep aquifer ranged from 5 to 8 feet bgs.

Based on the low permeability, lack of large-scale site-wide transport, and the fact that the majority of the

water remains on site, the water present in the subsurface is considered "pore water" and is referred to as

such throughout this report.

1.2.3 Summary of Source Area Contamination Assessment

Soil and groundwater sampling was conducted at Site 22 by several contractors over the last 10 years.

According to these investigations, the chemicals of concern (COCs) are PCE and cis-1,2-dichloroethene

in soil and groundwater. The source area/"hot spot" of contamination is located near the southeastern

corner of the Building 105 along Sampson Street near the former grease catch basin and consists mainly

of PCE-contaminated soil with PCE-contaminated pore water in the area of the highly contaminated soil.

PCE and its degradation products, trichloroethene, cis-1,2-dichloroethene, and vinyl chloride, were

detected in surface and subsurface soil at concentrations exceeding screening levels for groundwater

protection. The cVOC concentrations reported for soil in the southeastern corner of the site also exceed

the Illinois Environmental Protection Agency (Illinois EPA) Tiered Approach to Corrective Action

Objectives (TACO) criteria for human exposure by incidental ingestion and inhalation (Illinois EPA, 2004).

The Illinois EPA has classified the contaminated media (soil and pore water) at Site 22 as a listed

hazardous waste for PCE (F002). If the contaminated media are removed from the site, they would have

to be identified as a listed hazardous waste. Impacted soil and groundwater around the former drains

and grease catch basin are limited to shallow depths (up to 20 feet deep), with the highest concentrations

being between 8 to 20 feet bgs. Impacts to the deeper aquifer are limited both in concentration and

migration potential due to the geology of the site. Historical surface and near surface soil samples north

of the hot spot, in areas subsequently regraded during site demolition and construction activities, also

contained contamination exceeding TACO criteria.

120711/P 1-4 CTO 0009

Revision: 1 Date: January 2008

Section: 1.0 Page: 5 of 6

Prior to remedial activities, additional soil samples were collected to better delineate the site

contamination and allow for design of an effective ERH treatment system. More information on this

sampling is included in Section 2.1.1.

1.3 ERH TECHNOLOGY DESCRIPTION

Based on the factors presented in the Feasibility Study (TtNUS, 2006a), the Navy, with concurrence from

Illinois EPA, decided to implement a treatability study utilizing ERH to address the cVOC contamination in

the subsurface. This section provides a general description of the technology. Details on design and

implementation at this site are presented in Section 2.0.

Developed in early 1990s by the Pacific Northwest National Laboratory, ERH uses an electrical current to

heat less permeable soils such as clays and other fine-grained sediments so that water and contaminants

trapped in these relatively conductive regions are vaporized and available for vacuum extraction. This

technology has been demonstrated as an effective technology for the removal of volatile and some

semivolatile contaminants from soil and groundwater. Such contaminants generally include dense, non-

aqueous-phase liquids consisting of cVOCs such as trichloroethene and PCE, and also the light, non-

aqueous-phase liquids such as the petroleum hydrocarbon products.

During ERH application, electric current is passed into the subsurface through vertical, angled, or

horizontal electrodes. Electrodes are generally installed in the less permeable subsurface soil matrix

through conventional drilling techniques that are used to install monitoring wells. Electric current, passed

through the electrodes into the subsurface is conducted through the moisture present in the subsurface

soil where the resistance it encounters leads to a uniform heating of the subsurface. This heating of the

soil boils the groundwater rendering the subsurface dry and fractured and thus more permeable.

Contaminants present in these fractures and the groundwater are consequently vaporized and then

vacuum extracted by the above-ground vapor recovery system. Although silt and clay soils exhibit low

permeability, they are more electrically conductive than sand due to increased porosity and moisture

content. In addition, the surface of clay particles is naturally charged. Electrically conductive regions of

the soil heat up more vigorously and quickly as they attract a greater electric current. Thus, ERH is an

effective method of heating less permeable soils where dense non-aqueous-phase liquid tends to

accumulate.

120711/P 1-5 CTO 0009

Naval Station Great Lakes

ERH Treatability Study Report - Site 22

Revision: 1 Date: January 2008

Section: 1.0 Page: 6 of 6

The increase in the temperature of the subsurface is measured by thermocouples installed throughout the

treatment area. Typically, thermocouples are placed at various depths and readings obtained throughout

ERH operation are utilized to optimize electrical input to the subsurface.

Vapor recovery (VR) wells and a vacuum blower are used to create a negative pressure in the subsurface

and extract volatized vapor and steam created during the heating of the vadose and saturated zone. The

extracted vapor/steam mixture passes through a condenser; the condensed steam is then cooled before

being reinjected into the subsurface to help maintain moisture content in the electrode borings to enhance

electrical conductivity between the electrodes and the soil matrix. The recovered vapor then passes

through a heat exchanger and cooling tower before passing through a granular activated carbon (or other

treatment) unit, if necessary, and discharged to the atmosphere (Battelle, 2006).

1.4 TREATABILITY STUDY EXPECTATIONS AND GOALS

An ERH treatability study was implemented at Site 22. The primary focus of this study was to significantly

reduce the mass of cVOCs in the source area and to determine the design parameters for a full-scale

implementation. The results of the study were also evaluated to determine the effectiveness of the ERH

in reducing the concentrations at the site sufficiently to allow implementation of a closure plan that

incorporates land use controls (LUCs) for the soil and pore water at the site.

Goals for the study included achieving and maintaining adequate temperatures throughout the treatment


zone, recovery of a significant portion of the cVOC mass in the subsurface, and reductions in cVOC soil

and pore water concentrations at the site. More details on the goals of the study are presented in

Section 2.4. The performance of the system in reaching these goals is presented in Section 3.0.

120711/P 1-6 CTO 0009





Revision: 1

Date: January 2008 Section: 2.0 Page: 1 of 10

2.0 TECHNOLOGY IMPLEMENTATION

2.1 ERH TREATABILITY STUDY DESIGN

Prior to implementing the ERH treatability study, pre-remediation sampling was conducted to delineate

the treatment area and determine baseline soil and pore water concentrations. Utilizing the results of this

pre-remediation sampling and previous sampling events, the ERH treatability study system design was

completed.

2.1.1 <u>Pre-Remediation Sampling</u>

In November 2005, prior to design of the ERH treatability study system, TtNUS conducted soil and pore

water sampling to determine the optimal extent of the ERH treatability study and to provide baseline data

for evaluation of the effectiveness of the study in reducing cVOC concentrations at the site. The sampling

included the following:

Collection of six surface and near surface soil samples in areas shown to contain contamination prior

to site demolition and regrading activities in the area north of the hot spot. These samples were

utilized to determine if contamination was still present in these areas and whether it would have to be

addressed.

Collection of eight soil samples in the vicinity of the hot spot in the southeastern portion of the site

(the projected ERH treatability study area). These samples were intended to delineate the area to be

remediated vertically and horizontally and to provide baseline data from within the hot spot area to

allow for comparison with post-remediation samples.

Collection of pore water samples from four wells inside the hot spot area. Data from three of the

wells were also compared to data from treatability performance samples to determine reductions in

cVOC concentrations in the pore water. Results for the pore water samples from monitoring well

MW05S have historically been less than TACO criteria and were not used to determine reductions in

cVOC concentrations.

The samples were laboratory analyzed for VOCs. The rationale for collection of each of the soil samples

and analytical results from the soil sampling are summarized in Table 2-1 and presented in Figure 2-1;

pore water results are summarized in Table 2-2.

120711/P 2-1 CTO 0009

Naval Station Great Lakes

ERH Treatability Study Report - Site 22

Revision: 1 Date: January 2008

Section: 2.0 Page: 2 of 10

The results of the sampling indicated that the surface and near surface contamination previously

observed north of the hot spot area was no longer present; therefore, no remedial action was proposed

for this area.

Based on a review of the data, it was determined that the areas with soil concentrations greater than

20 mg/kg of PCE would be addressed via the ERH treatability study system. This incorporated a surface

area of 2,400 square feet and three depth intervals; surface to 8 feet in the western portion of the area,

surface to 18 feet in the center portion, and surface to 25 feet in the northeastern portion. Utilizing these

depths, a total of 1,400 cubic yards of soil would be addressed by the system.

Additionally, as part of the data analysis, 15 soil samples from recent and historical sampling activities

were selected to provide the pre-remediation baseline sample set. These samples are from a total of

nine locations; at six locations, multiple sample depths were included in the set. This sample set provided

a basis for comparison with samples collected during the treatability study to determine overall

contaminant reduction. These samples represented locations throughout the entire remedial area at

various depths. Total cVOC concentrations of the samples ranged from 16.9 to 1,500 mg/kg; the average

total cVOC concentration was approximately 445 mg/kg. The cVOC concentrations of these samples are

summarized in Table 2-3; sample locations and concentrations are presented on Figure 2-2.

A detailed evaluation of these results was presented in the Work Plan for ERH Treatability Study (TtNUS,

2006b).

2.1.2 ERH Treatability Study System Design

TRS was subcontracted by TtNUS to design, install, and operate the equipment for the ERH treatability

study. The contract was performance based, requiring a reduction of the average soil cVOC

concentration to 20 mg/kg or less (a reduction of 95.5 percent). Based on the final design by TRS, 16

electrodes (installed to various depths), with co-located VR points were required to address the hot spot

area as shown on Figure 2-3. Each electrode consisted of a 3-inch-diameter steel pipe installed to the

appropriate depth in a 12-inch-diameter borehole. The annular space of the borehole was backfilled with

steel shot and graphite to aid in conducting electricity to the surrounding soil matrix. The steel pipe was

slotted from 2 to 5 feet bgs to allow vapor recovery.

The amount of energy needed to be input to the area during the ERH treatability study was originally

estimated to be 325,000 kilowatt-hours (see Section 2.3.3). It was also estimated that 12 weeks of ERH

operations would be required to input the energy necessary for a successful cleanup.

120711/P 2-2 CTO 0009

Revision: 1 Date: January 2008

Section: 2.0 Page: 3 of 10

Above-grade equipment included a 500-kilowatt Power Control Unit, a 15-horsepower vacuum blower, a

condenser, a cooling tower, and two granular activated carbon vessels.

To monitor subsurface temperatures, three temperature monitoring points (TMPs) were installed within

the treatment area. Within each TMP, individual thermocouples were spaced every 5 feet through the

zone of heating to automatically record subsurface temperatures in the treatment volume and allow for

the creation of subsurface heating profiles.

Due to buried utilities along Sampson Street, the original design was altered and two electrodes in the "H"

row were moved 2 feet into Sampson Street (see Figure 2-3). These electrodes were completed

18 inches below grade to isolate them from the vehicle and pedestrian traffic on Sampson Street. The

other electrodes were completed above grade in accordance with the original system design.

Four electrodes and one TMP were installed to a depth of 9 feet bgs on the western side of the site,

designated as Area 3. Temperature monitoring depths in Area 3 were established at 1, 5 and 8 feet bgs.

The central portion of the site was designated as Area 2, and nine electrodes and one TMP were installed

to 18 feet bgs. Temperature monitoring depths were set at 1, 5, 10, 15, and 18 feet bgs. Treatment in

the northeastern area of the site, Area 1, extended the deepest, with three electrodes and one TMP

installed to 26 feet bgs. Thermocouples in the Area 1 TMP were placed at 1, 5, 10, 15, 20, and 25 feet

bgs. A design change was made to the electrodes in the "G" row resulting in the conductive interval of

each electrode being lowered from 1 foot bgs to 6 feet bgs due to the presence of an abandoned steam

chase.

Additional information on the system design (including design drawings of the electrode/TMP locations

and construction and a process flow diagram showing the above-grade equipment) is included in the

Final Report issued by TRS in December 2006 (Appendix A) and the Work Plan for ERH Treatability

Study (TtNUS, 2006b). Photographs of the ERH treatability study system are included at the end of this

section.

2.2 FIELD IMPLEMENTATION CHRONOLOGY

The chronology of field events is summarized in Table 2-4. Construction of the ERH treatability study

system began on April 17, 2006, and the system was completed and ready for operational testing May 8,

2006. The installation was approved for operation and energized on May 22, 2006, and system start-up

120711/P 2-3 CTO 0009

Naval Station Great Lakes

ERH Treatability Study Report - Site 22 Revision: 1

Revision: 1 Date: January 2008

Section: 2.0 Page: 4 of 10

began. Power was applied to the subsurface until October 4, 2006, and the VR blower and condenser

remained operational until October 16, 2006.

As described in Section 2.4, numerous soil sampling rounds were performed to evaluate the performance

of the treatability study. Soil sampling was conducted during system operation to measure the amount of

remaining contamination in the treatment area and to guide operational changes intended to optimize

remediation efforts towards the most impacted portions of the site. This included a baseline sampling

event (described above) and four performance sampling rounds that took place on July 11, August 8,

September 12, and September 28, 2006.

2.3 FIELD IMPLEMENTATION AND PROCEDURES

2.3.1 Electrode and Surface Equipment Installation

Sixteen electrodes with co-located VR wells were installed across the treatment area from April 24

through May 1, 2006. TTL, Inc. used a hollow-stem auger rig to advance the boreholes for each co-

located electrode/VR well to their design depths. Due to buried utilities oriented along Sampson Street,

the 2 electrodes in the "H" row were moved two feet into Sampson Street. As-built locations of the

electrodes and TMPs are presented on Figure 2-3.

Surface construction, including VR piping and electrical supply cabling to the electrodes/VR wells, was

completed during the week following drilling. TRS installed vapor-phase granulated activated carbon

vessels for the potential treatment of extracted cVOCs on May 8, 2006. The system was fully constructed

and ready for operational testing on May 8, 2006.

From May 8 to May 22, 2006, an electrical contractor installed a 500-kilowatt step-down transformer,

service disconnect switch and meter inside the fenced treatment area. They also used horizontal boring

methods to connect a nearby 13,200-volt service to the step-down transformer. TRS completed the

installation of the power from the service disconnect switch and meter to the Power Control Unit before

final inspection by NS Great Lakes facility electricians.

2.3.2 Monitoring Well Abandonment

Because of the high subsurface temperatures achieved by ERH, the integrity of monitoring wells in the

vicinity of the treatment area would be compromised. Therefore, four monitoring wells were abandoned

prior to remediation (MW05S, MW010D, MW010S, and MW06S) on April 25 and 27, 2006. Water Well

Sealing Forms are included in Appendix B.

120711/P 2-4 CTO 0009

Revision: 1 Date: January 2008

Section: 2.0 Page: 5 of 10

Monitoring wells MW010D, MW010S, and MW06S were reinstalled in approximately the same locations

(see Figure 2-3) and with the same depth and construction characteristics on March 6 and 7, 2007. The

monitoring well construction logs for these wells are provided in Appendix B. Due to historically low pore

water concentrations exhibited at MW05S [less than 1 microgram per liter (µg/L)], this well was not

reinstalled.

2.3.3 System Start-Up and Operation

Start-up and shakedown of the ERH treatability study system began on May 22 and 23, 2006. After the

electrical and VR connections were complete, power was applied to the VR blower and steam condenser

so that they could be tested. After proper operation of the internal and external interlocks for each system

component was verified, power was applied to the electrodes so that start-up step-and-touch voltage

safety testing could be performed. Interlocks were connected between each unit of equipment to make

sure that the electrodes were de-energized if there was a loss of vapor recovery or an internal

malfunction. No voltage potentials greater than the 15-volt limit established by TRS were found at the

site.

With the initial voltage safety survey complete, the applied voltage to the subsurface was slowly

increased throughout the remainder of the day. With each voltage increase, checks for surface voltage

were performed and results recorded. In no instance did readings exceed the TRS 15-volt limit.

The ERH treatability study system was left off line overnight and additional performance and safety

testing was conducted the following day. The ERH treatability study system was deemed fully operational

on May 24, 2006, and the project status moved from the start-up phase to the operations phase. During

ERH start-up and early operations, step-and-touch voltage potentials in and around the electrode field

were monitored frequently to make sure that public and worker safety from electrical hazards was

maintained.

When the applied voltage to the subsurface was raised to 240 volts, step-and-touch voltage readings that

were nearing the established 15-volt limit were obtained on the perimeter fence in the vicinity of

electrodes H3 and H4. To address this concern, a portion of the metal fence along Sampson Street was

replaced with a wooden panel fence that extended 15 feet north and south of electrode row "H". As an

additional precaution, the concrete and asphalt extending 3 feet on either side of the wooden fence were

painted with an isolating dielectric paint. The wooden fence eliminated potential voltage hazards from

ground to the fence, and the paint insulated the surface from the pavement underneath. To monitor

120711/P 2-5 CTO 0009

Revision: 1

Date: January 2008 Section: 2.0

Page: 6 of 10

surface voltages over time, step-and-touch readings in and around the entire electrode field were

collected during the site visits. These efforts were taken to make sure on-going site safety.

Additionally during the start-up procedures, multiple noise measurements were obtained throughout the

vicinity of the site to make sure that the Base noise limits were not exceeded and that the operation of the

system did not effect personnel at the fire station across Sampson Street. These readings, and

conversations with the fire station personnel, indicated that there were no issues with noise.

Except for brief periods of shut down for soil sampling and maintenance, the ERH treatability study

system operated continuously through October 4, 2006; operation of the VR system continued through

October 16, 2006, to recover additional vapor created in the heated soil. Energy input was adjusted

throughout the system operation based on vapor recovery and soil sampling data to optimize system

performance. The amount of energy utilized was 632,866 kilowatt-hours over 19 weeks of operation.

More information on system operation is presented in the TRS Final Report (Appendix A).

During operation of the ERH treatability study system, data were obtained to determine the system's

success in obtaining the goals of the study. Section 2.4 describes the data collection, and Section 3.0

discusses the results.

2.3.4 <u>System Demobilization and Site Restoration</u>

Following shut down of the VR system on October 16, 2006, system demobilization activities began. The

Power Control Unit, steam condenser, VR blower, and cooling tower were removed from the site on

October 19, 2007 (the GAC and excess water tank had been removed from the site in August 2006).

Additionally, the electrodes were abandoned and the piping from the VR and drip piping systems and

electrode well heads were decontaminated and disposed as construction/demolition debris.

During the week of November 6, 2006, site restoration activities were completed. The site fencing and

electrical transformer were removed, and the asphalt, concrete, and grass surfaces were restored to pre-

existing conditions (see Appendix A for more details).

2.3.5 Remediation-Derived Waste Disposal

Several waste streams were generated during the treatability study. The following summarizes the

disposition of each of these streams:

120711/P 2-6 CTO 0009

Revision: 1

Revision: 1 Date: January 2008

Section: 2.0 Page: 7 of 10

Purge and decontamination water from the initial pre-remediation sampling event (15 gallons) were

disposed at Pollution Control Industries in East Chicago, Indiana, as F002 listed hazardous waste on

February 10, 2006.

Soil from the installation of the electrodes and TMPs (15.7 tons) was disposed as listed F002

hazardous waste at Pollution Control Industries in East Chicago, Indiana on May 9, 2006.

Soil from the reinstallation of monitoring wells following remediation (10 drums) was disposed as

listed F002 hazardous waste at Pollution Control Industries in East Chicago, Indiana on March 14,

2007.

Water from the cooling tower, equipment decontamination, and monitoring well development and

purging (four drums) was disposed as non-hazardous waste at Pollution Control Industries in East

Chicago, Indiana on March 14, 2007. Due to site remediation activities, this water was not

considered listed waste, and the cVOC concentrations were significantly less than the threshold for

characteristic waste.

Waste manifests for each of these streams are included in Appendix C.

2.4 DATA COLLECTION FOR EVALUATION OF ERH TREATABILITY STUDY SYSTEM

As stated in Section 1.4, the following four criteria were used to evaluate the effectiveness of the ERH

treatability study system at Site 22:

Ability of the system to achieve and maintain temperatures of 90 degrees Celsius throughout the

treatment volume. The temperature profile in the subsurface has been shown to be the most

important metric in determining the success of treatment via ERH (Batelle, 2006).

Ability of the system to remove a significant amount of the site cVOC mass via the recovered vapor

stream.

Ability of the system to reduce average total cVOC concentrations in subsurface soil by 95.5 percent,

to an average of 20 mg/kg or less.

120711/P 2-7 CTO 0009

Revision: 1

Date: January 2008 Section: 2.0 Page: 8 of 10

• Ability of the system to reduce pore water cVOC concentrations at the site. Because LUCs currently

in place at Naval Station Great Lakes prevent pore water use, no specific pore water reduction goals

were set.

The sections below detail data collection activities associated with evaluating the ERH treatability study

system with respect to these goals. The success of the system in meeting the stated goals is evaluated

in Section 3.0.

2.4.1 <u>Temperature Monitoring</u>

As stated above, the temperature of the subsurface was measured throughout the treatment area. One

TMP, with thermocouples installed at multiple depths, was installed in each section of the treatment area.

The TMPs were placed in areas nearly equidistant from the surrounding electrodes to provide

conservative temperature data. The TMPs and thermocouples were placed as follows (Figure 1 of

Appendix A):

Treatment in the northeastern corner of the site, Area 1, extended to approximately 25 feet.

Thermocouples in the Area 1 TMP were placed at 1, 5, 10, 15, 20, and 25 feet bgs.

The central portion of the site was designated as Area 2. In this area, temperature monitoring depths

were set at 1, 5, 10, 15, and 18 feet bgs.

Temperature monitoring depths in Area 3 (the western portion of the treatment area) were

established at 1, 5 and 8 feet bgs.

Temperature data from the thermocouples were processed continuously. The data were then graphed to

provide a simple method of analyzing temperature trends throughout the treatment volume. An

evaluation of the success of the ERH treatability study system in achieving and maintaining temperatures

of 90 degrees C in the subsurface is presented in Section 3.1.

2.4.2 <u>Vapor Stream Sampling</u>

Soil vapor and steam were continuously removed from the subsurface during ERH treatability study

system operation. The steam was then condensed, and the resultant water stream was then cooled and

reinjected in to the annular space of the electrodes to maintain moist/conductive conditions in the

120711/P 2-8 CTO 0009

Revision: 1 Date: January 2008

Section: 2.0 Page: 9 of 10

graphite/steel shot backfill. The remaining vapor stream was then cooled and discharged to the

atmosphere. Periodic monitoring of the vapor stream was conducted to:

Make sure that the maximum permitted rate of uncontrolled cVOC emissions of 8 pounds per hour

was not exceeded. If the discharge rate had approached that value, the stream would have been

passed through the granular activated carbon system prior to discharge. Since the discharge rate

stayed well below this value, the granular activated carbon was not utilized.

Provide data to estimate cVOCs removed via the ERH treatability study system.

• Determine when vapor recovery had reached an asymptotic level and continued operation of the

system would lead to minimal additional cVOC recovery.

To allow a general evaluation of vapor recovery and the third criterion above, measurements of the cVOC

concentration of the vapor stream were obtained with a photoionization detector (PID). These

measurements were obtained three to four times a week during the first 4 weeks of system operation and

approximately weekly thereafter. Vapor stream samples were collected in Tedlar bags for laboratory

analysis on an approximately weekly basis for the first 13 weeks of operation to provide more quantitative

data to evaluate the performance criteria. These samples were analyzed by Test America Analytical

Testing Corporation (Buffalo Grove, Illinois) for cVOCs via U.S. EPA Method 8260B.

Results of the vapor stream monitoring and sampling and achievement of the related site goals are

presented in Section 3.2.

2.4.3 Soil Sampling

Following the start of remedial activities at the site, soil sampling activities were conducted periodically to

determine the reductions in soil concentrations throughout the site to optimize system performance and to

determine when remedial activities were considered complete. During these performance sampling

events, the soil samples were collected as closely as possible to the locations and depths of the

respective pre-remediation samples. The following summarizes these events:

• The first performance sampling event took place on July 11, 2006, as proposed in the ERH Work

Plan (TtNUS, 2006b), after it was estimated that remediation was approximately 70 percent complete

based on power consumption. Samples were collected from the 15 pre-remediation locations and

depths.

120711/P 2-9 CTO 0009

Revision: 1 Date: January 2008

Section: 2.0 Page: 10 of 10

• The second event took place on August 8, 2006. Samples were collected from the five locations and

depths exhibiting the highest concentrations of cVOCs during the July sampling event.

The third event took place on September 12, 2006. Because this was expected to be the final

sampling event, a full round of 15 samples was collected.

The fourth and final event took place on September 28, 2006. This event included the three

locations and depths that exhibited elevated concentrations during the September 12 event.

During each performance sampling event, the soil samples were collected utilizing the protocol from the

ERH Work Plan and site-wide Quality Assurance Project Plan. The samples were laboratory analyzed at

Severn Trent Laboratory in Canton, Ohio, for cVOCs via U.S. EPA Method 8260B. The results of the

performance soil sampling and achievement of the related site goals are presented in Section 3.3. Field

logs from these sampling events are provided in Appendix D.

2.4.4 Pore Water Sampling

Following completion of the ERH treatability study, three of the abandoned monitoring wells (Section

2.3.2) were reinstalled. Reinstallation of these wells was delayed until March 6 and 7, 2007 to allow the

soil to cool sufficiently for the use of polyvinyl chloride wells in the subsurface. Following installation, the

locations and elevations of the monitoring wells were surveyed by James Anderson Company

(Appendix E). Pore water samples were collected from these wells on March 10, 2007, via low-flow

sampling techniques per the protocol in the ERH Work Plan and site-wide Quality Assurance Project

Plan. The samples were laboratory analyzed at Severn Trent Laboratory in Canton, Ohio, for cVOCs via

U.S. EPA Method 8260B.

The results of the pore water sampling and achievement of the related site goals are presented in Section

3.4. Field logs from the pore water sampling event are provided in Appendix D.

120711/P 2-10 CTO 0009

TABLE 2-1

SUMMARY OF PRE-TREATABILITY STUDY SOIL SAMPLE RESULTS SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

		Depth from Surface	Depth from Top of Native Soil	PCE	TCE	cis-1,2-DCE	VC	Total cVOCs ^a
Sample No.	Rationale for Sample Location	(feet)	(feet)	(μg/kg)	(μg/kg)	(μg/kg)	(μg/kg)	(μg/kg)
NTC22SB200203	Confirm historical concentrations at GL95-105S-13	6 - 7	2 - 3	26,000	ND (f)	ND	ND	26,000
NTC22SB200506	Delineate depth at historical boring GL95-105S-13	9 - 10	5 - 6	ND	ND	ND	ND	ND
NTC22SB2102	Provide additional baseline data in remediation area	8 - 9	1 - 2	9,300	1,800	5,800	ND	16,900
NTC22SB210405	Provide additional baseline data in remediation area	11 - 12	4 - 5	160,000	10,000	13,000	ND	183,000
NTC22SB211112	Provide additional baseline data in remediation area	18 - 19	11 - 12	ND	ND	ND	ND	ND
NTC22SB220203	Provide additional baseline data in remediation area	9 - 10	2 - 3	19,000	ND	ND	ND	19,000
NTC22SB220708	Provide additional baseline data in remediation area	14 - 15	7 - 8	ND	ND	ND	ND	ND
NTC22SB221112	Provide additional baseline data in remediation area	18 - 19	11 - 12	200,000	ND	ND	ND	200,000
NTC22SB230102	Confirm historical surface sample at GL95-105S-8	4 - 5	0 - 1	400	ND	ND	ND	400
NCT22SB230203	Confirm historical surface sample at GL95-105S-8	6 - 7	2 - 3	1200	ND	ND	ND	1,200
NTC22SB240102	Confirm historical surface sample at GL95-105S-2	5 - 6	1 - 2	720	ND	ND	ND	720
NTC22SB240203	Confirm historical surface sample at GL95-105S-2	6 - 7	2 - 3	1,200	ND	ND	ND	1,200
NTC22SB250102	Confirm historical surface sample at GL95-105S-10	5 - 6	1 - 2	2,800	ND	ND	ND	2,800
NTC22SB250203	Confirm historical surface sample at GL95-105S-10	6 - 7	2 - 3	ND	ND	ND	ND	ND

PCE - Tetrachloroethene

VC - Vinyl chloride

TCE - Trichloroethene

ND - Non-detect

Cis-1,2-dichloroethene

^a CVOCs - Chlorinated volatile organic compounds (PCE, TCE, cis-1,2-DCE ,and VC)

TABLE 2-2

SUMMARY OF PRE-TREATABILITY STUDY AND HISTORICAL PORE WATER SAMPLE RESULTS SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

	Illinois TACO	INTOZZIVIVVO33	NTC22MW05S	NTC22MW05S	NTC22MW06S	NTC22MW06S	NTC22MW06S	NTC22MW10S	NTC22MW10S	NTC22MW10D	NTC22MW10D
PARAMETER	Groundwater Ingestion	SAMPLE	DUPLICATE	SAMPLE	SAMPLE	SAMPLE	DUPLICATE	SAMPLE	SAMPLE	SAMPLE	SAMPLE
	Criterion	8/11/2003	8/11/2003	11/22/2005	10/21/2003	11/20/2005	11/20/2005	10/25/2003	11/20/2005	10/24/2003	11/20/2005
Chlorinated Volatiles (μg/L)											
CHLOROMETHANE	NC	1 U	1 U	1 U	2000 U	1400 U	1400 U	1 U	2 U	0.21 J	1 U
CIS-1,2-DICHLOROETHENE	70	1 U	1 U	1 U	2000 U	1400 U	1400 U	2.6	52	1 U	4
TETRACHLOROETHENE	5	0.58 J	0.55 J	1 U	59000	45000	43000	62	3.5 J	8.9	1 U
TRANS-1,2-DICHLOROETHENE	NC	1 U	1 U	1 U	2000 U	1400 U	1400 U	1 U	2 U	1 U	1 U
TRICHLOROETHENE	5	1 U	1 U	1 U	2000 U	1400 U	1400 U	1.3	2 U	1 U	1 U
VINYL CHLORIDE	2	1 U	1 U	1 U	2000 U	1400 U	1400 U	1 U	2 U	1 U	1.3

J = Result is estimated as a result of a value less than the reporting limit or a technical noncompliance.
U = Value is a nondetected result as reported by the laboratory and should not be considered present.
Shaded cells exceed the Illinois TACO Groundwater Ingestion Tier 1 criteria and Federal Maximum Contaminant Limits.

NC = No Criterion

SUMMARY OF BASELINE TREATMENT AREA SOIL SAMPLE RESULTS
SITE 22 - BUILDING 105 DRY CLEANING FACILITY
NAVAL STATION GREAT LAKES, ILLINOIS

TABLE 2-3

	Depth	PCE	TCE	cis-1,2-DCE	VC	Total CVOCs ^a
Sample No.	(feet bgs)	(μg/kg)	(μg/kg)	(μg/kg)	(μg/kg)	(μg/kg)
NTC22SB20	6 - 7	26,000	ND	ND	ND	26,000
NTC22SB21	9 - 10	9,300	1,800	5,800	ND	16,900
NTC22SB21	13 - 14	160,000	10,000	13,000	ND	183,000
NTC22SB22	7 - 8	19,000	ND	ND	ND	19,000
NTC22SB22	18 - 19	200,000	ND	ND	ND	200,000
GL95-105S-13	2.5 - 3	1,500,000	ND	ND	ND	1,500,000
NTC22MW05S	0 - 1	190,000	ND	ND	ND	190,000
GL95-105S-12	0 - 0.5	370,000	ND	ND	ND	370,000
GL95-105S-12	2.5 - 3	600,000	ND	ND	ND	600,000
NTC22SB19	19 - 20	570,000	5,600	9,300	ND	584,900
TOL01-GP04	8 - 12	550,000	ND	820	ND	550,820
NTC22MW10D	9 - 11	130,000	1,300	1,700	ND	133,000
NTC22SB15	0 - 1	770,000	7,700	52,000	ND	829,700
NTC22SB15	11 - 12	590,000	ND	ND ND		590,000
NTC22MW06D	7 - 8	870,000	7,300	9,100	ND	886,400
AVER	AGE	436,953	2,247	6,115	ND	445,315

Notes:


PCE - Tetrachloroethene VC - Vinyl chloride TCE - Trichloroethene ND - Non-detect


cis-1,2-dichloroethene a CVOCs - Chlorinated volatile organic compounds (PCE, TCE, cis-1,2-DCE and VC)


TABLE 2-4

CHRONOLOGY OF FIELD EVENTS SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

Da	ate	Event	Description		
Begin	End	170.11			
11/2005		Baseline Sampling	Baseline Soil Sampling Event		
4/17/2006	5/8/2006	Construction of ERH System	Placement of surface equipment		
4/0.4/0.000	E /4 /0000	D. 11	Drilled boreholes and installed each co-		
4/24/2006	5/1/2006	Drilling and Electrode Installation	located electrode/VR well		
			Surface piping and electrical		
5/1/2006	5/22/2006	System Connection	connection		
5/22/2006	5/23/2006	System Startup and Shakedown	Power was applied and tested		
7/11/2006			Round 1 Soil Sampling Event		
8/8/2006		Interim Soil Sampling	Round 2 Soil Sampling Event		
9/12/2006		intenin 30ii 3ampiing	Round 3 Soil Sampling Event		
9/28/2006			Round 4 Soil Sampling Event		
10/4/2006	10/16/2006	System Shutdown	De-energized electrodes		
11/4/2006	11/16/2006	Site Restoration	Restored site to its original condition		
			Re-installed and sampled MW10D,		
			MW10S, and MW06S that were		
		Monitoring Well Re-Installation and	abandoned as part of system		
3/6/2007	3/10/2007	Sampling	installation activities		











Installation of Baker Tank



Drilling



Piping and Electrical Connection



Cooling Tower



Electrodes



Electrode Well Head



Site Layout and ERH System



Equipment



Wooden Fence Installed to Eliminate Step-and-Touch Voltage



Electrical Transformer and Breaker Panel



Interim Soil Sampling



Interim Soil Sampling – Close-up

Revision: 1 Date: January 2008 Section: 3.0

Page: 1 of 6

3.0 TECHNOLOGY PERFORMANCE

The performance of the ERH treatability study was evaluated based on the collection and analyses of temperature, vapor, soil, and pore water data. This section includes a summary of the data and an assessment of the performance of the ERH system compared to the criteria in Section 2.4, specifically:

- Ability of the system to achieve and maintain temperatures of 90 degrees Celsius throughout the treatment volume.
- Ability of the system to remove a significant amount of the site cVOC contamination through the vapor stream.
- Ability of the system to reduce average cVOC concentrations in subsurface soil by 95.5 percent, to an average of 20 mg/kg or less.
- Ability of the system to reduce pore water cVOC concentrations at the site.

3.1 TEMPERATURE MONITORING RESULTS AND EVALUATION

As stated in Section 2.4, the subsurface temperature profile is the most important metric in determining whether an ERH system will effectively reduce contaminant concentrations at a site. To that end, the subsurface temperature was continuously monitored throughout the remedial process at Site 22. Figures 3-1 through 3-3 show the temperature profile versus depth over time for the three TMPs at the site. The maximum temperature reached at each depth interval is provided below (TRS, 2006); the average temperature in the subsurface prior to treatment was 15.5 degrees Celsius.

Depth (ft bgs)	Area 1 Maximum Temp (degrees C)	Area 2 Maximum Temp (degrees C)	Area 3 Maximum Temp (degrees C)
1	100	61	82
5	103	100	100
10	105	102	96
15	109	103	NA
20	103	NA	NA
25	81	NA	NA

ERH Treatability Study Report - Site 22

Revision: 1 Date: January 2008

Section: 3.0 Page: 2 of 6

As is evident from the data above, the target temperature of 90 degrees Celsius was achieved, exceeded,

and maintained throughout the majority of the treatment area. The exceptions were the surface soil of

Areas 2 and 3, and the 25-foot bgs interval of Area 1. The surface soil at Areas 2 and 3 did not reach the

target temperature, primarily due to cooling at the surface (despite the presence of an insulating mat).

This cooling did not affect system performance because the temperature increase was sufficient to aid in

the volatilization and removal of contaminants from the high permeability fill just below the surface. The

vacuum applied to this interval by the VR system also created a reduced boiling point for the PCE/water

mixture at this interval, leading to contaminant reductions despite the lower temperatures.

The temperature at the deepest interval of Area 1 was also not a concern. The maximum depth at which

contamination was identified was 20 feet bgs; the treatment zone was extended 5 feet deeper to account

for cooling at depth. Therefore, the temperature of 103 degrees Celsius at 20 feet bgs in Area 1

represents the bottom of the contaminated zone.

Based on the data presented above, the temperature profile at the site exceeded the evaluation criteria

for the study.

3.2 VAPOR SAMPLING RESULTS AND EVALUATION

As stated in Section 2.4.2, recovered vapor stream samples were periodically measured for VOC

concentration via a PID and laboratory analyzed for cVOCs during treatability study system operation.

The maximum PID reading was 596 parts per million (ppm) on June 27, 2006; this corresponds with the

date of the collection of the sample with the maximum cVOC concentration as measured by the

laboratory (1,290 µg/L). Figure 6 of the TRS Final Report (Appendix A) shows that although the

magnitude of the concentrations was very different, the relative concentrations obtained by the PID and

laboratory analyses were highly correlated throughout the operation of the system. A small peak in

removal was observed at the end of May as the average subsurface temperature approached 35 degrees

Celsius. A second, higher peak was observed during the June 27 sampling as the average subsurface

temperature reached 80 degrees Celsius. Following collection of the August 1 vapor sample, cVOC

concentrations in the recovered vapor decreased quickly. This indicated that the cVOC mass recovery of

the system was becoming less efficient.

Table 3-1 summarizes the vapor data obtained from the analytical laboratory. This table also provides

the air flow rate measured at the time of sampling, the calculated amount of cVOC mass removed during

each period, and the cumulative cVOC removal. Based on the calculations, approximately 1,200 pounds

of cVOCs were removed from the subsurface via the recovered vapor stream. The total cVOC mass in

120711/P 3-2 CTO 0009

Revision: 1 Date: January 2008

Section: 3.0 Page: 3 of 6

the subsurface prior to remediation was estimated at approximately 1,350 pounds (Tetra Tech, 2006a).

This equates to an estimated removal of 89 percent of the cVOC mass via the recovered vapor stream.

This was an acceptable percentage, especially considering the following:

The potential error in the estimates of both the mass of cVOCs in the subsurface and the total cVOC

removal.

The estimate of initial cVOC mass included two surface and near-surface hot spots north of the

treatment area that were subsequently shown to contain minimal contamination.

Recovery via the VR system is only one mechanism (albeit the most prevalent) at work in reducing

cVOC concentrations in the subsurface during ERH operation. Other mechanisms include increased

hydrolysis and biodegradation occurring at higher temperatures.

In conjunction with the soil sampling detailed below, the mass in the recovered vapor stream

indicates substantial reduction in cVOC mass at the site.

Based on the data presented above, the vapor recovery at the site met the evaluation criteria for the

study.

3.3 SOIL SAMPLING RESULTS AND EVALUATION

As stated in Section 2.0, soil samples were collected prior to treatability study activities, and four

performance soil sampling events were conducted during treatability study operation. These soil samples

were collected from approximately the same locations and depths as the 15 baseline samples designated

to represent the treatment area (Table 2-3 and Figure 2-2). The average cVOC concentration of these

samples was 445 mg/kg prior to remediation; the goal of the ERH system was to reduce the average

concentration to less than 20 mg/kg. Data from the pre-remediation and post-remediation sampling

events and associated percent reduction values are summarized in Table 3-2. A graph showing

reductions in cVOC concentrations as remediation progressed is presented as Figure 3-4.

The first round of performance soil sampling, which consisted of collecting 15 samples, was conducted on

July 11, 2006. The concentrations of total cVOCs ranged from 0.002 to 3,306 mg/kg. Concentrations in

7 of the 15 samples were reduced to less than the cleanup goal of 20 mg/kg, and concentrations in 11

samples exhibited significant reductions. A significant increase in concentration (from 585 to

3,305 mg/kg) was measured at NTC22SB19 (18 to 19 feet bgs); this increase may have been due to

120711/P 3-3 CTO 0009

Revision: 1

Date: January 2008 Section: 3.0 Page: 4 of 6

sampling variability associated with source material present in the backfill of the nearby sanitary sewer.

The average total cVOC concentration from this sampling event indicated a 40-percent reduction in

average concentration to 267 mg/kg. It was determined that the soil concentration reduction criteria had

been achieved in portions of the treatment area, so the electrode field was reconfigured on July 20, 2006.

Energy input to four electrodes in Area 3 (the most western electrodes) was discontinued to reduce the

amount of energy being applied to areas that had achieved the soil concentration reduction criteria.

Results from this sampling event are presented on Figure 3-5.

The second performance sampling event was scheduled for August 8, 2006. At this time, cVOC removal

rates in the vapor stream were reduced from their highest levels, indicating that remediation was

approaching completion. During this sampling event, five soil samples were collected from the locations

and depths with the highest concentrations based on the first round of performance sampling. These

samples included the four locations/depths not showing significant reductions and GL-95-105S013, which

showed a significant reduction but still exhibited elevated cVOC concentrations. The concentrations of

cVOCs in three of the five samples were reduced to less than 1 mg/kg, with another soil sample

concentration reduced to 15.8 mg/kg. PCE soil concentrations in the fifth sample (SB-19 at 19 to 20 feet

bgs) decreased by 69 percent but remained greater than 20 mg/kg, so the treatment operation was

reconfigured to target just the northeastern portion of the treatment area. Including the five new results

with the 10 results from the first round of sampling, the average cVOC concentration of the soil samples

was calculated to be 77 mg/kg, equating to a reduction of 83 percent. Results from this sampling event

are presented on Figure 3-6.

On August 3, 2006, it was determined that the connection between the Power Control Unit and electrode

H3 had been lost and that the fault was within the 4-foot section of utility trenching extending from the site

under Sampson Street to the electrode. After the soil analytical results from the second round of

performance soil sampling indicated that the area surrounding electrode H3 was still impacted above the

remedial goal, the electrode was repaired on August 15, 2006 and placed back in service.

A third round of performance sampling was conducted after a 95-percent reduction in the peak vapor

stream concentrations of cVOCs had been achieved. During the third performance sampling event

(September 12, 2006) the 15 soil samples from the approximate locations and depths of the baseline

sampling event were resampled, with the results ranging from non-detect to 192 mg/kg, and 12 of 15

samples with concentrations less than 20 mg/kg, including SB19 (19 feet to 20 feet bgs). Three locations

showed increases from previously low PCE concentrations. The average cVOC concentration was

25.2 mg/kg (94.3-percent reduction). This was slightly greater than the cleanup goal, so the electrode

120711/P 3-4 CTO 0009

ERH Treatability Study Report - Site 22 Revision: 1

Date: January 2008 Section: 3.0

Page: 5 of 6

array was reconfigured to target the area of the three soil samples with remaining cVOC concentrations

greater than the cleanup goal. Results from this sampling event are presented on Figure 3-7.

The fourth, and final, performance sampling event was completed on September 28, 2006. The three soil

samples from the third round of performance sampling with remaining cVOC concentrations greater than

the cleanup goal were resampled. The concentrations of each of the re-sampled soil samples were less

than 20 mg/kg. Utilizing these sample results in conjunction with the other 12 samples from the third

round of performance sampling, the average cVOC concentration for the samples was calculated to be

4.1 mg/kg, equating to an overall reduction of 99.1 percent. Results from this sampling event are

presented on Figure 3-8.

This sampling event confirmed that the project goal for cVOC concentration reductions in site soil was

exceeded (99.1-percent reduction versus a goal of 95.5-percent reduction). In fact, with a total cVOC

concentration range between non-detect and 15.4 mg/kg, all sample concentrations were less than the

cleanup goal for the average sample. Therefore, based on the data presented above, the soil

concentration reductions at the site exceeded the evaluation criteria for the study.

3.4 PORE WATER SAMPLING RESULTS AND EVALUATION

As stated in Section 2.3.2, three monitoring wells located in the treatment area were abandoned prior to

remediation and were reinstalled in March 2007. On March 10, 2007, approximately 6 months after the

end of the ERH activities, samples were collected from the reinstalled wells (MW6S, MW10S, and

MW10D). The results are summarized in Table 3-3.

Monitoring well MW-6S is a shallow well located within the treatment volume. The total cVOC

concentration in this well was reduced from 45,000 µg/L to 17 µg/L. Monitoring wells MW-10S and

MW-10D are screened in the deeper sand aquifer (30 to 40 feet bgs). The pore water total cVOC

concentration for the sample from MW-10S (screened just below the clay/sand interface) decreased from

55.5 to 2.5 µg/L. The total cVOC concentration in MW-10D (screened at the bottom of the sand aquifer

from 35 to 40 feet bgs) rose slightly from 5.3 to 17 µg/L Pore water analytical data are summarized in

Table 3-3 and presented on Figure 3-9.

Based on the cVOC concentration reduction of greater than 99 percent for the monitoring wells within the

treatment area, the pore water concentration reductions at the site met the evaluation criteria for the

study.

120711/P 3-5 CTO 0009

Revision: 1

Date: January 2008

Section: 3.0 Page: 6 of 6

3.5 ACHIEVEMENT OF STUDY GOALS

As detailed above, the following four evaluation criteria for the study were met or exceeded:

• The temperature goal of 90 degrees Celsius throughout the treatment volume was exceeded, with

only a few exceptions that did not affect the overall system performance.

• Approximately 1,200 of 1,350 pounds (89 percent) of cVOC mass were removed in the vapor

recovery stream; this meets the study goals of providing significant cVOC removal, especially

considering the factors detailed in Section 3.2.

The average total cVOC concentration in the soil samples were reduced to 4.1 mg/kg (99.1-percent

reduction), exceeding the goal of 20 mg/kg (95.5-percent reduction). In fact, all individual soil

samples exhibited concentrations less than 16 mg/kg, less than the goal of 20 mg/kg for the average

sample.

Pore water cVOC concentrations inside the treatment area were reduced 99 percent, meeting the

goal of groundwater concentration reduction.

120711/P 3-6 CTO 0009

TABLE 3-1

SUMMARY OF SOIL VAPOR AND CVOC REMOVAL DATA SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

	PCE	TCE	Flow Rate	PID Reading	cVOC (d) Removal Rate	cVOCs Removed this period	Avg. Subsurface Temp
Sample Date	(μg/L)	(μg/L)	(scfm)	(ppm)	(pounds)	(pounds)	(degrees C)
05/25/06	84.9	ND	210	12	0.07	1	17
05/31/06	1060	ND	210	319	0.83	64	31
06/07/06	854	ND	225	198	0.72	134	53
06/13/06	780	ND	198	260	0.58	93	65
06/21/06	1140	ND	205	383	0.88	139	76
06/27/06	1290	ND	261	596	1.26	152	81
07/05/06	1050	ND	209	400	0.82	204	86
07/18/06	460	11.2	205	146	0.36	184	86
08/01/06	399	ND	210	69	0.31	113	89
08/16/06	40	ND	205	35	0.03	63	88
08/30/06	67.1	3.62	193	27	0.05	14	8
09/07/06			191	20	0.04	9	77
09/21/06	Samples not Collected		230	23	0.04	13	84
10/04/06			202	21	0.04	13	93
10/16/06			205	4	0.01	7	71
					TOTAL	1,201	

Notes:

PCE - Tetrachloroethene

TCE - Trichloroethene

PID - Photoionization detector reading

cVOC - Chlorinated volatile organic compound

mg/L - Microgram per liter

scfm - Standard cubic feet per minute

ppm - Parts per million

C - Celsius

TABLE 3-2

SUMMARY OF SOIL PERFORMANCE SAMPLING DATA
SITE 22 - BUILDING 105 DRY CLEANING FACILITY
NAVAL STATION GREAT LAKES, ILLINOIS

				Total CVOCs ^a			
	Depth	Baseline Sampling Nov 2005	1st Performance Sampling July 2006	2nd Performance Sampling Aug 7, 2006	3rd Performance Sampling Sept 11, 2006	4th Performance Sampling ^b Sept 28, 2006	Percent
Sample No.	(feet bgs)	(μg/kg)	(μg/kg)	(μg/kg)	(μg/kg)	(μg/kg)	Reduction ^c
NTC22SB20	6 - 7	26,000	11,047	NS	3,391	NS	86.96
NTC22SB21	9 - 10	16,900	57,700	920	420	NS	97.51
NTC22SB21	13 - 14	183,000	221,000	780	1,370	NS	99.25
NTC22SB22	7 - 8	19,000	2.1	NS	0	NS	100.00
NTC22SB22	18 - 19	200,000	796	NS	62,400	15,074	92.46
GL95-105S-13	2.5 - 3	1,500,000	58,160	1	1,100	NS	99.93
NTC22MW05S	0 - 1	190,000	4,500	NS	640	NS	99.66
GL95-105S-12	0 - 0.5	370,000	20,580	NS	19,310	NS	94.78
GL95-105S-12	2.5 - 3	600,000	21,158	NS	3,230	NS	99.46
NTC22SB19	19 - 20	584,900	3,305,700	1,033,000	5	NS	100.00
TOL01-GP04	8 - 12	550,820	36,120	NS	4	NS	100.00
NTC22MW10D	9 - 11	133,000	350	NS	192,200	15,380	88.44
NTC22SB15	0 - 1	829,700	3,164	NS	215	NS	99.97
NTC22SB15	11 - 12	590,000	255,300	15,200	94,100	1,016	99.83
NTC22MW06D	7 - 8	886,400	2,522	NS	265	NS	99.97
AVER	AGE	445,315	266,540	76,676	25,243	4,095	99.08

Notes:

NS - Not sampled.

a Total CVOCs - Chlorinated volatile organic compounds (PCE, TCE, cis-1,2-DCE and VC).

b Average calculated from 4th interim sample results for NTC22SB22, NTC22MW10D, and NTC22SB15 and 3rd interim sample results for all other samples.

c Percent reductions calculated from 4th interim sample results for NTC22SB22, NTC22MW10D, and NTC22SB15 and 3rd interim sample results for all other samples.


TABLE 3-3


SUMMARY OF PORE WATER DATA SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS


	Illinois TACO	NTC22MW06S	NTC22MW06S	NTC22MW10S	NTC22MW10S	NTC22MW10D	NTC22MW10D
	Groundwater						
PARAMETER	Ingestion						
	Criterion	11/20/2005	3/10/2007	11/20/2005	3/10/2007	11/20/2005	3/10/2007
Chlorinated Volatiles (ug/L)							
CHLOROMETHANE	NC	1400 U	0.38 J	2 U	1.0 U	1.0 U	1.0 U
CIS-1,2-DICHLOROETHENE	70	1400 U	2.3	52	1.3	4	0.21 J
TETRACHLOROETHENE	5	45000	9.2	3.5 J	1.0 U	1.0 U	16
TRANS-1,2-DICHLOROETHENE	NC	1400 U	1.0 U	2 U	1.0 U	1.0 U	1 U
TRICHLOROETHENE	5	1400 U	5.2	2 U	1.2	1.0 U	1.2
VINYL CHLORIDE	2	1400 U	1.0 U	2 U	1.0 U	1.3	1.0 U


J = Result is estimated as a result of a value less than the reporting limit or a technical noncompliance. U = Value is a nondetected result as reported by the laboratory and should not be considered present.


NC = No Criterion














This section presents a human health risk evaluation of post-treatment soil and groundwater/pore water

at Site 22. The risks were calculated using the same exposure equations, assumptions, and models

employed in the RI/RA (TtNUS, 2004). A comparison of post-treatment and pre-treatment risks is also

presented in this section.

4.1 DATA EVALUATION

Tables 4-1 and 4-2 present comparisons of compounds detected in post-treatment soil and

groundwater/pore water samples with Illinois EPA TACO and U.S. EPA criteria. As shown in the tables,

only the concentrations of PCE and trichloroethene exceeded one or more these criteria. Therefore, the

post-treatment risk assessment evaluated risks for PCE and trichloroethene only.

4.2 EXPOSURE POINT CONCENTRATIONS

Exposure point concentrations (EPCs) were determined as in the RI/RA. If a data set consisted of less

than 10 samples, the maximum detected concentration was used as the EPC. If a data set consisted of

more than 10 samples, the 95-percent upper confidence limit (UCL) was used as the EPC. For the post-

treatment risk evaluation, maximum concentrations were used as the EPCs for surface soil and

groundwater/pore water. The 95-percent UCL was used as the EPC for subsurface soil. The post-

treatment EPCs are as follows:

Surface Soil Subsurface Soil Groundwater/Pore Water

PCE - 19 mg/kg PCE - 12 mg/kg

PCE – 16 μg/L

TCE - 0.2 mg/kg

TCE – 2 mg/kg

TCE $-5.2 \mu g/L$

For purposes of comparison, the pre-treatment EPCs were as follows:

Surface Soil

Subsurface Soil

Groundwater/Pore Water

PCE – 770 mg/kg

PCE - 180 mg/kg

PCE $-59,000 \mu g/L$

TCE - 7.7 mg/kg

TCE – 2 mg/kg

TCE $-1.3 \mu g/L$

4.3 POTENTIAL RECEPTORS

Risks for the following potential receptors were evaluated in the post-treatment risk assessment:

120711/P 4-1 CTO 0009

Revision: 1 Date: January 2008

Section: 4.0 Page: 2 of 6

Construction workers

Future full-time occupational workers

Hypothetical future residents

4.4 EXPOSURE ROUTES AND PATHWAYS

The following exposure routes and pathways were quantitatively evaluated in the post-treatment risk

assessment:

Ingestion and dermal contact with surface and subsurface soil

Inhalation of vapors from surface and subsurface soil (ambient air)

Dermal contact with groundwater/pore water (construction workers only)

Inhalation of vapors from groundwater/pore water (ambient air)

• Inhalation of vapors from groundwater/pore water by vapor intrusion (indoors)

Risks for vapor intrusion from soil into indoor air (based on soil concentrations) were not included in this

evaluation because U.S. EPA in its Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway

from Groundwater and Soils (Subsurface Vapor Intrusion Guidance) recommends that this pathway not

be evaluated "because of the large uncertainties associated with measuring concentrations of volatile

contaminants introduced during soil sampling, preservation, and chemical analysis, as well as the

uncertainties associated with soil partitioning calculations" (U.S. EPA, 2002).

Based on the results of the post-treatment sampling events, an exclusion to the Groundwater Ingestion

Exposure Route, as provided in Subpart C of TACO, Part 742.320, applies at this site (i.e., groundwater

ingestion is not included as an exposure route or pathway). As shown below, the requirements of items

a) through f) of the exclusion in Part 742.320 are met:

• Part 742.320 a): The requirements of Subpart 742.300 and 742.305 are met; i.e., delineation of

groundwater contamination has been obtained as shown in the RI (TtNUS, July 2004) and in this

treatability study. No free product has been observed at the site during field activities.

Part 742.320 b): As stated above, no free product has been observed at the site.

• Part 742.320 c): The source of the release is not within the minimum or designated setback zone or

within a regulated recharge area of a potable supply well. As shown below, impact above drinking

120711/P 4-2 CTO 0009

Revision: 1 Date: January 2008

Section: 4.0 Page: 3 of 6

water standards does not migrate from the site. There are currently prohibitions on recovering water

for potable use on Naval Station Great Lakes and potable water for Naval Station Great Lakes is

obtained from Lake Michigan utilizing the Navy's drinking water treatment system. The surrounding

communities are also connected to public water systems supplied by Lake Michigan. The City of

North Chicago has its own treatment system. Other nearby communities, including Knollwood, Lake

Bluff, Libertyville, Vernon Hills, Wildwood, and Gurnee, are supplied by the Central Lake County Joint

Action Water Agency. Lake County provides an additional 20,000 customers with potable water from

Lake Michigan. Shallow aquifers in the region (found at 150 to 500 feet bgs) often have poor quality

water due to the presence of naturally occurring gas, oil, and hydrogen sulfide; the deep aquifer

system (900 to 1,500 feet bgs) typically exhibits high yields of good quality water (Guernsey, 2002).

The closest public water supply well that could be located was greater than 10 miles from the site. A

search of the Illinois State Geological Survey (ISGS) indicated one water well was located in the

Township and Range of the site; the well is 210 feet deep and the owner is listed as Sager Lock

Company. It does not appear that the company is still active at that location.

Although there may be some individual private supply wells in the vicinity that do not appear in the

ISGS database, it is highly unlikely, based on the depth of impact at the site and the low permeability

soil matrix, that the site is within a recharge area for such wells.

If additional information is required to meet this aspect of the exclusion, it will be provided in the

ROD.

Part 742.320 d): Groundwater contamination modeling was conducted to show that groundwater

concentrations above Tier 1 groundwater remediation objectives are not present outside of an area

where the local government has adopted an ordinance that effectively prohibits the installation of

potable water supply wells. In this case, the equivalent of that ordinance is Instruction 11130.1

instituted by Naval Station Great Lakes that prohibits the installation of groundwater supply wells

throughout Naval Station Great Lakes (Appendix G). Additionally, as part of the LUC Implementation

Plan for the site, Site 22 will be added to the LUC Memorandum of Agreement between Naval Station

Great Lakes and the Illinois EPA. A description of the modeling effort is included in Section 4.5.

Because the modeling shows that the groundwater at the site boundary contains concentrations

equal to or less than the Tier 1 objectives, this aspect of the exclusion is met.

• Part 742.320 e): Based on the information provided in response to c) and d) above, the

concentrations within the setback zone for a potable water supply will meet Tier 1 objectives.

120711/P 4-3 CTO 0009

Revision: 1

Date: January 2008 Section: 4.0

Page: 4 of 6

• Part 742.320 f): The modeling described in Section 4.5 indicates that the groundwater discharging

into Lake Michigan will meet the applicable criteria.

4.5 GROUNDWATER MODELING

Groundwater modeling for PCE detected in post-treatment groundwater at Site 22 was conducted to

determine exposure concentrations and potential drinking water risks at a point of compliance

downgradient of the site. The model used to predict the concentrations was the modified Domenico

transport equation that is listed as equation R26 in Appendix C, Table C, Part 742.810 of the Illinois

Administrative Code (IAC). This equation calculates the concentration of a contaminant downgradient of

a slab-type source of constant concentration after equilibrium in the system has been attained (i.e., plume

has achieved full expansion). The modeling was based on the maximum PCE concentration detected in

post-treatment groundwater at the site (16 µg/L at location NTC22MW10D). Site-specific data were used

for most of the input parameters. These included:

Source dimensions

Soil porosity

Hydraulic conductivity

Hydraulic gradient

Distance to exposure point

The chemical-specific First Order Degradation Constant for PCE was obtained from Table E in

Appendix C of TACO. The input parameters for each model run are presented in Table 4-3 and model

calculations are presented in Appendix H.

MODELING RESULTS

The results of six model simulations are summarized in Table 4-3. These include:

Two simulations to the east of the source

Two simulations to the west of the source

Two simulations south of the source

120711/P 4-4 CTO 0009

ERH Treatability Study Report - Site 22

Revision: 1 Date: January 2008

Section: 4.0 Page: 5 of 6

Two simulations were run in each direction to estimate concentrations at the site boundary located

approximately 75 feet from the source and at the facility boundary located approximately 1,300 feet from

the source.

As shown in Table 4-3, the estimated concentration at the site boundary is 5 µg/L and meets the Tier 1

objective for PCE and the predicted concentration at the facility boundary is several orders of magnitude

less than the Tier 1 objective in the three directions evaluated. Based on these modeling results, it can

be concluded that groundwater will not transport PCE in concentrations that will adversely impact water

quality at the boundaries of Site 22 or NS Great Lakes (i.e., at Lake Michigan).

The models used for this evaluation are analytical solutions for modeling groundwater transport of

contaminants in a very simplified manner. Certain assumptions inherent in these models cause a

significant amount of conservatism in the modeling results:

The source of PCE was assumed to be constant throughout each model simulation. The model, as

constructed, is overly conservative because it assumes that the concentrations of PCE at the source

will remain constant and will not be depleted over time.

The maximum concentration detected in post-treatment samples was conservatively used to

represent the contaminated groundwater.

POST-TREATMENT RISK ASSESSMENT RESULTS 4.6

This section presents the cancer and noncancer risk estimates for post-treatment soil and

groundwater/pore water samples at Site 22 (Table 4-4).

Quantitative risk estimates are compared to typical risk benchmarks to interpret the quantitative risks and

to aid risk managers in determining the need for remediation at a site. Calculated incremental lifetime

cancer risks (ILCRs) are interpreted using the U.S. EPA's "target range" (1x10⁻⁴ to 1x10⁻⁶) and the Illinois

EPA goal of 1x10⁻⁶, and noncarcinogenic hazard indices (HIs) are evaluated using a target value of 1.0.

U.S. EPA has defined the range of 1x10⁻⁴ to 1x10⁻⁶ as the ILCR target range for most hazardous waste

facilities addressed under the Comprehensive Environmental Response, Compensation and Liability Act

and RCRA. Individual or cumulative ILCRs greater than 1x10⁻⁴ are typically not considered as protective

of human health, and ILCRs less than 1x10⁻⁶ are generally regarded as protective. Risk management

4-5 120711/P CTO 0009

ERH Treatability Study Report - Site 22

Revision: 1 Date: January 2008

Section: 4.0

Page: 6 of 6

decisions are necessary when the ILCR is within the 1x10⁻⁴ to 1x10⁻⁶ cancer risk range. An HI exceeding

1.0 indicates that there may be potential noncarcinogenic health risks associated with exposure.

As shown in Table 4-4, post-treatment estimated cancer risks for construction workers and future

occupational workers are less than the U.S. EPA's target risk range (1x10⁻⁴ to 1x10⁻⁶) and the Illinois EPA

goal of 1x10⁻⁶. Cancer risks for hypothetical future residents are within the U.S. EPA target risk range and

slightly exceed the Illinois EPA goal. Post-treatment noncarcinogenic HIs are less than the U.S. EPA and

Illinois EPA goal of 1.0.

For purposes of comparison, pre-treatment risks calculated in the RI/RA are presented Table 4-3. As

indicated in Table 4-4, post-treatment cancer and noncarcinogenic risks are one to two orders of

magnitude less than the pre-treatment risks.

4-6 120711/P CTO 0009

TABLE 4-1

SUMMARY OF DESCRIPTIVE STATISTICS AND COMPARISONS FOR TREATABILITY STUDY SURFACE/SUBSURFACE SOIL DATA - ROUNDS 3/4 SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

Parameter	Frequency of Detection	Range of Detects	Range of Nondetects	Maximum	Sample with Maximum Concentration	Average of Positive Results	Average of All Results ⁽¹⁾	Illinois TACO for Soil Ingestion ⁽²⁾	Illinois TACO for Soil Inhalation- Residential ⁽²⁾	Illinois TACO for Soil Inhalation- Industrial ⁽²⁾	Soil Inhalation-	Illinois TACO Leachability to GW Residential ⁽²⁾	Region 9 Residential Soil PRGs ⁽³⁾
Volatiles (ug/kg)													
1,1-DICHLOROETHENE	1/15	1.1 J - 1.1 J	4.6 - 700	1.1	NTC22SB150001R2	1	110	700000	1500000	1500000	300000	60	120000
VINYL CHLORIDE	1/15	0.48 J - 0.48 J	4.6 - 700	0.48	NTC22SB150001R2	0.5	110	460	280	1100	1100	10	79
TRANS-1,2-DICHLOROETHENE	2/15	2.7 J-8	4.6 - 700	8	NTC22SB150001R2	5	110	1600000	3100000	3100000	3100000	700	69000
CIS-1,2-DICHLOROETHENE	6/15	2.5 J - 250	5.4 - 470	250	NTC22SB211314R2	120	120	780000	1200000	1200000	1200000	400	43000
TRICHLOROETHENE	11/15	0.55 J - 4000	5.4 - 280	4000	NTC22SB221819R3	470	370	58000	5000	8900	12000	60	2900
TETRACHLOROETHENE	13/15	3.5 J - 19000	4.6 - 5.4	19000	GL95105S120001R2	4300	3700	12000	11000	20000	28000	60	480
Miscellaneous Parameters													
PERCENT SOLIDS	15/15	79.3 - 89.7		79.3 - 89.7	NTC22SB191920R2	84.6	84.6	NA	NA	NA	NA	NA	NA

Shaded chemical names indicate that the maximum chemical concentration exceeds the minimum criteria.

The original and field duplicate samples are counted as one sample in the frequency of detections.

- 1 The average concentrations were calculated by using one-half the detection limit for non-detects.
- 2 Illinois EPA (February 2003).
- 3 U.S. EPA Region 9 PRGs (USEPA, October 2004).
- J Positive result is estimated as a result of a value less than the reporting limit or a technical noncompliance.

Associcated Samples:

GL95105S120001R2 NTC22SB10D1012R3 NTC22SB200607R2 GL95105S120203R2 NTC22SB150001R2 NTC22SB210910R2 NTC22SB151112R3 NTC22SB05S0001R2 NTC22SB211314R2 NTC22SB06D0708R2 NTC22SB191920R2 NTC22SB220708R2 NTC22SB06D0708R2-D NTC22SB191920R2-D NTC22SB221819R3 NTC22SB10D0708R2 NTC22SB200203R2

TABLE 4-2

SUMMARY OF DESCRIPTIVE STATISTICS AND COMPARISONS FOR TREATABILITY STUDY GROUNDWATER (PORE WATER) DATA SITE 22 - BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

Parameter	Frequency of Detections	Range of Detects	Range of Nondetects	Sample with Maximum Concentration	Average of Positive Results	Average of All Results ⁽¹⁾	Maximum	IL TACO Groundwater Ingestion Tier 1 ⁽¹⁾	Region 9 Tap Water ⁽²⁾
Volatiles (ug/L)									
CHLOROMETHANE	1/3	0.38 J	1	NTC22MW06SR	0.38	0.46	0.38	NA	160
CIS-1,2-DICHLOROETHENE	3/3	0.21 J - 2.3		NTC22MW06SR	1.3	1.3	2.3	70	61
TETRACHLOROETHENE	3/3	1.2 - 16		NTC22MW10DR	8.8	8.8	16	5	0.1
TRICHLOROETHENE	2/3	1.2 - 5.2	1	NTC22MW06SR	3.2	2.3	5.2	5	1.4

Shaded chemical names indicate that the maximum chemical concentration exceeds the minimum criteria.

The original and field duplicate samples are counted as one sample in the frequency of detections.

- 1 Illinois EPA (February 2003).
- 2 USEPA Region 9 PRGs (USEPA, October 2004).
- J Positive result is estimated as a result of a value less than the reporting limit or a technical noncompliance.

Associated Samples:

NTC22MW06SR

NTC22MW10SR

NTC22MW10DR

POST-TREATMENT PCE MODELING INPUT PARAMETERS AND RESULTS SITE 22 - FORMER BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

TABLE 4-3

Source Width	Source Depth or Thickness	Soil Porosity (site-specific)	Hydraulic Conductivity (1)	Hydraulic Gradient	1st Order Degradation Constant for PCE	Concentration of PCE at Source	Distance from Source to Exposure Point	Concentration of PCE at Exposure Point
(ft)	(ft)	(unitless)	(ft/day)	(ft/ft)	(days ⁻¹)	(ug/L)	(ft)	(ug/L)
20	15	0.35	0.796	0.264 (east)	0.00096	16	75	5
20	15	0.35	0.796	0.168 (south)	0.00096	16	75	5
20	15	0.35	0.796	0.119 (west)	0.00096	16	75	5
20	15	0.35	0.796	0.264 (east)	0.00096	16	1300	0.006
20	15	0.35	0.796	0.168 (south)	0.00096	16	1300	0.003
20	15	0.35	0.796	0.119 (west)	0.00096	16	1300	0.001

^{1.} Arithmetic mean conductivity for shallow groundwater.

TABLE 4-4

SUMMARY OF HUMAN HEALTH RISKS SITE 22 - FORMER BUILDING 105 OLD DRY CLEANING FACILITY NAVAL STATION GREAT LAKES, ILLINOIS

Pagantar	PRE-TRI	EATMENT CAI	NCER RISKS	POST TREATMENT CANCER RISKS			
Receptor	Surface Soil	Subsurface Soil	Groundwater/ Pore Water	Surface Soil	Subsurface Soil	Groundwater/ Pore Water	
Construction Worker	2x10-5	4x10-6	6x10-5	2x10-7	1x10-7	2x10-8	
Occupational Worker	3x10-5	1x10-5	2x10-6	1x10-6	9x10-7	1x10-7	
Future Child Resident	1x10-4	3x10-5	3x10-5	2x10-6	1x10-6	1x10-7	
Future Adult Resident	1x10-4	3x10-5	5x10-5	2x10-6	1x10-6	2x10-7	
Future Resident (Child + Adult)	2x10-4	6x10-5	8x10-5	3x10-6	2x10-6	3x10-7	

	PRE-TREA	TMENT NONC	ANCER RISKS	POST TREATMENT NONCANCER RISKS			
Receptor	Surface	Subsurface	Groundwater/	Surface	Subsurface	Groundwater/	
	Soil	Soil	Pore Water	Soil	Soil	Pore Water	
Construction Worker	26	4	8	0.4	0.6	0.06	
Occupational Worker	0.2	0.06	0.02	0.01	0.01	0.003	
Future Child Resident	3	1	1	0.06	0.06	0.01	
Future Adult Resident	1	0.2	0.5	0.01	0.02	0.004	
Future Resident (Child + Adult)	NA	NA	NA	NA	NA	NA	

NA - Not applicable.

Revision: 1 Date: January 2008

Section: 5.0 Page: 1 of 3

5.0 CONCLUSIONS AND RECOMMENDATIONS

5.1 SUMMARY AND CONCLUSIONS

The following is a summary of the results of the ERH treatability study and the conclusions drawn:

• The ERH technology was successfully designed, installed, operated, and removed with no

detrimental impact to NS Great Lakes facility operations.

Electricity was transferred to the subsurface via 16 electrodes installed at the site. The subsurface

temperature was measured by three sets of subsurface TMPs. Vapors were recovered from the

subsurface, and cVOC concentrations of the vapor stream were measured in the field and laboratory.

The maximum subsurface temperature achieved was 109 degrees Celsius, and subsurface

temperatures throughout the ERH treatment volume exceeded 90 degrees Celsius and were

maintained, providing evidence that boiling conditions were achieved at depth across the treatment

volume and exceeding the project goal.

Based on vapor stream sample concentrations obtained during the ERH treatability study, the

greatest mass of cVOCs was extracted during the period when the average temperature of the

treatment area was between 76 and 86 degrees Celsius.

An estimated 1,200 pounds of cVOCs were removed from the treatment area through the vapor

recovery system, meeting the project goals.

Data from a baseline sampling event and four interim soil sampling events were evaluated to

determine the performance of the demonstration. Fifteen soil samples were collected from nine

locations and several depths within the treatment area.

The average cVOC concentration in the soil within the treatment area was reduced by 99 percent

from a pre-remediation concentration of 445 mg/kg to 4 mg/kg. This exceeded the project goal of

95.5-percent reduction.

• Pore water concentrations in the monitoring well located in the treatment area were reduced by

99 percent, meeting the project goals.

120711/P 5-1 CTO 0009

Revision: 1 Date: January 2008

Section: 5.0

Page: 2 of 3

• Utilizing post-remediation sample concentrations, an HHRA was conducted. The noncancer risks

were less than the Illinois EPA goal of 1. The maximum cancer risk is 3 x 10⁻⁶, within the U.S. EPA

target risk range and only slightly greater than the Illinois EPA goal. Cancer risks for all receptors

were reduced by one to two orders of magnitude.

The exclusion of the Groundwater Ingestion Exposure Route, as provided in Subpart C of TACO, Part

742.320, applies at this site.

5.2 RECOMMENDATIONS

Based on the significant mass removal, concentration reductions, and risk reductions achieved, no

additional active remediation is recommended for this site. However, because of residual cVOC

concentrations, LUCs should be put in place to limit exposure to groundwater and soil at the site. These

LUCs will be detailed in the LUC Remedial Design document to be submitted following approval of the

Proposed Plan and Record of Decision (ROD) for the site, and in general will include the following:

Maintaining the prohibition on use of groundwater that is in force throughout NS Great Lakes as

detailed in the LUC Memorandum of Agreement (Naval Station Great Lakes, 2003). Site 22 will be

formally added to the Navy and Illinois EPA LUC Memorandum of Agreement.

• Requiring that the NS Great Lakes Environmental Department be notified prior to intrusive work

being conducted at or near the site. A site safety plan to address possible worker exposure to the

soil and shallow groundwater will be developed and implemented to address the intrusive work.

Maintaining the existing cap system (high-density polyethylene and asphalt parking lot) and

inspecting the area on an annual basis.

Restricting the property use to industrial and commercial purposes.

Requiring that soil removed from this area during future activities is managed in accordance with

35 Illinois Administrative Code, Subtitle G: Waste Disposal.

Based on the results of this treatability study and the recommendations above, corrective actions at

this site have been completed and RCRA interim status closure is appropriate for the RCRA

120711/P 5-2 CTO 0009

ERH Treatability Study Report - Site 22

Revision: 1 Date: January 2008

Section: 5.0 Page: 3 of 3

hazardous waste management unit associated with Site 22 and NS Great Lakes. Therefore, the following completed forms are included with this document (Appendix I):

• Illinois EPA RCRA Corrective Action Certification. This form certifies that the corrective action was completed in accordance with the requirements of the NS Great Lakes RCRA permit. This is certified by the owner/operator (NS Great Lakes), the licensed professional overseeing the activities (Robert Davis, PE, of TtNUS), and the analytical laboratory (Severn Trent Laboratories, Inc.).

RCRA Interim Status Closure Certification Form. This form certifies that the hazardous waste
management unit has been closed in accordance with a plan approved by Illinois EPA and must be
attached to the report that demonstrates closure. This is certified by the owner/operator and the
licensed professional overseeing the activities.

Revision:1

Date: January 2008 Section: References

Page: 1 of 2

REFERENCES

Battelle, February 2006. Review of Cost and Performance of ERH for Source Treatment, Battelle,

Columbus, Ohio. February 9.

C.H. Guernsey & Company, November 2002. Final Environmental Assessment, Willow Glen Golf

Course, Great Lakes Training Center, Great Lakes, Illinois.

Illinois Environmental Protection Agency (Illinois EPA), October 2004. TACO (Tiered Approach to

Corrective Action Objectives). Illinois Environmental Protection Agency, Bureau of Land, available at

http://www.epa.state.il.us/land/taco/, accessed online, May 2005.

Naval Station Great Lakes, September 2003. Memorandum of Agreement between the Illinois

Environmental Protection Agency, the U.S. Environmental Protection Agency, Region 5, and the U.S.

Department of Navy. Ground Water Use Restrictions. September 30.

Tetra Tech NUS, Inc. (TtNUS), June 2003. Quality Assurance Project Plan, Site 7 - RTC Silk Screening

Shop, Site 17 - Pettibone Creek & Boat Basin, Remedial Investigation & Risk Assessment, Naval Training

Center Great Lakes, Great Lakes Illinois.

TtNUS, July 2004. Remedial Investigation and Risk Assessment Report - Site 22 - Old Dry Cleaning

Facility, Naval Training Center Great Lakes, Great Lakes Illinois.

TtNUS, January 2006a. Feasibility Study Report, Site 22, Building 105, Old Dry Cleaning Facility, Naval

Station Great Lakes, Great Lakes Illinois.

TtNUS, April 2006b. Work Plan for Electrical Resistance Heating Treatability Study, Site 22, Naval

Station Great Lakes, Great Lakes Illinois.

Thermal Remediation Services, Inc. (TRS), December 2006. Final Report – Electrical Resistance

Heating, Naval Station Great Lakes, Longview, Washington. December.

U.S. EPA, November 2002. Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway from

Groundwater and Soils. Washington, D.C., November.

120711/P R-1 CTO 0009

Revision:1
Date: January 2008
Section: References
Page: 2 of 2

U.S. EPA, October 2004. "Region 9 Preliminary Remediation Goals (PRGs)", EPA Region 9, 75 Hawthorne Street, San Francisco, California, 94105.

APPENDIX A

FINAL ERH REPORT – TRS, 2006

Final Report Electrical Resistance Heating

Naval Station Great Lakes Great Lakes, Illinois

Date Issued—December 4, 2006

Prepared By
Thermal Remediation Services, Inc.
2325 Hudson Street
Longview, Washington 98362

Table of Contents

Execu	tive Summary	1
1.0	Introduction	2
2.0	ERH Performance Goals and Design Specifications	2
3.0	System Construction	2
4.0	System Startup	3
5.0	Noise Abatement	4
6.0	Soil Sampling	4
7.0	Water Balance	7
8.0	System Operations and Shutdown	7
9.0	Vapor Stream Analyses	8
10.0	Subsurface Temperatures	10
11.0	Power and Energy	12
12.0	System Demobilization	13
13.0	Conclusions	14
Table		5
Table 2	2. Vapor Stream Concentration Results	8
Table :	3. Maximum Temperature Achieved per TMP	11
Figur	res	
Figure	1. Treatment Area Plot Plan	15
Figure	2. Electrode Design	16
Figure	3. Trenched Electrode Design	17
Figure	4. Process Flow Diagram	18
Figure	5. Contaminant Concentrations with Time	6
Figure	6. Vapor Concentrations and Temperatures versus Time	10

i

Figure 7.	Average Subsurface Temperatures versus Time	12
Figure 8.	Average Weekly Power Input	13
Attachment A.	Vapor Stream Sample Results	
Attachment B.	Cooling Water Sample Results	

LIST OF ACRONYMS AND ABBREVIATIONS

<u>Term</u> <u>Definition</u>

bgs below grade surface

°C degrees Celsius

CVOC chlorinated volatile organic compound

dB decibel

ERH electrical resistance heating GAC granular activated carbon

kW kilowatt

kW-hr kilowatt hour

lbs pounds

lbs/hr pounds per hour

μg/l micrograms per liter

mg/kg milligram per kilogram

PCE tetrachloroethene
PCU power control unit

PID photo ionization detector

ppm parts per million

SCFM standard feet per minute

TCE trichloroethylene

TRS Thermal Remediation Services, Inc.

TTNUS Tetra Tech NUS

TMPs temperature monitoring points

VR vapor recovery

EXECUTIVE SUMMARY

This report presents the results of the Electrical Resistance Heating (ERH) project performed at the Naval Station Great Lakes in Great Lakes, Illinois. Based upon soil sampling over the life of the study, the ERH system successfully accomplished the project goal by reducing tetrachloroethene (PCE) concentrations in soil by an average of 99 percent.

Thermal Remediation Services, Inc. (TRS) has prepared this report on behalf of the Department of the Navy, Southern Division Naval Facilities Engineering Command under subcontract to Tetra Tech NUS (TTNUS). The information presented in this report is based on data collected from various media before and during ERH operations.

The ERH project was conducted by the Navy to remediate source area contaminants from a former dry cleaning facility. The goal of the project was to reduce baseline concentrations of PCE in soil to less than 20 milligrams per kilogram (mg/kg). It was calculated that doing so would remove 96% of the estimated PCE mass from source area soil.

Because previous investigations had identified contamination at variable depths, the ERH treatment volume was shaped as an elongated wedge. To effectively treat the most impacted portions of the source area, the electrodes were designed to heat portions of the site from as shallow as 1 foot below grade surface (bgs) to as deep as 26 feet bgs. The final treatment area and treatment volume measured 2,400 square feet and 1,400 cubic yards, respectively.

The ERH system incorporated 16 electrodes, each with a co-located vapor recovery (VR) well. Subsurface temperatures were measured using 14 thermocouples placed at set depth intervals within three temperature monitoring points (TMP).

Recovered steam and soil vapors were condensed in the ERH condenser before releasing the VOCs to the atmosphere. Condensed steam was either evaporated in the systems cooling tower, or returned to the subsurface at the electrodes. Vapor phase granular activated carbon (GAC) vessels were onsite to treat the vapor stream if the chlorinated volatile organic compounds (CVOC) emission rate exceeded 8 pounds per hour.

ERH operations lasted 134 days and a total of 632,866 kilowatt hours (kW-hrs) of energy were applied to the subsurface. The maximum subsurface temperature achieved was 109 degrees Celsius (°C), while the maximum average temperature within the treatment volume was 90.0 °C.

Based upon vapor sampling collected weekly or biweekly after the peak extraction, an estimated 1,200 pounds of total chlorinated volatile organic compounds (CVOCs) were removed by volatilization during the ERH Project. Samples obtained from fifteen separate locations indicated that the average concentration of PCE in treatment area soil had been reduced to 4.09 mg/kg, a 99% reduction from the average baseline value of 445.32 mg/kg.

1.0 Introduction

This report presents the results of the ERH project conducted at the Naval Station Great Lakes located in Great Lakes, Illinois. ERH was applied to decrease the average PCE concentration in soil within the treatment volume to less than 20 mg/kg. This document was prepared by TRS for TTNUS under Subcontract No.1007413 and the Department of the Navy, Southern Division Naval Facilities Engineering Command under Contract Number N62467-04-D-0055/ CTO0009.

2.0 ERH Performance Goals and Design Specifications

The Naval Station Great Lakes ERH project was a guaranteed cleanup with TRS operating until the goal was achieved with no change in cost. The primary performance goal of the project was to reduce the average concentration of PCE in soil within the treatment volume from 445 mg/kg to 20 mg/kg. Achieving this reduction in average PCE concentrations would effectively reduce contaminant mass in the source area by 96%.

The amount of energy needed to be input to the source area during the ERH remediation to achieve a 96% reduction in contaminant mass was originally estimated to be 325,000 kW-hr. It was also estimated that 8 weeks of ERH operations would be required to input the energy necessary for a successful cleanup. The actual amount of energy applied was 632,866 kW-hrs over 19 weeks of operations. A copy of the treatment area plot plan, electrode design, trenched electrode design and process flow have been attached as Figures 1-4.

The treatment volume was shaped like a long wedge measuring 2,400 square feet in surface area with a total volume of 1,400 cubic yards. The ERH system used 16 electrodes with the primary heating zone extending from 1 foot bgs to depths ranging from 9 to 26 feet bgs, depending on location.

3.0 System Construction

Construction of the ERH system began on April 17, 2006 with the placement of the surface equipment, including the Power Control Unit (PCU), steam condenser, cooling tower, 6,000 gallon holding tank and 40 horsepower vapor recovery blower package. Marking of the subsurface utilities, confirmatory soil sample locations and electrode locations was also performed.

To monitor subsurface temperatures, three TMPs were installed within the treatment area. Within each TMP, individual thermocouples were spaced every five feet through the zone of heating to automatically record subsurface temperatures in the treatment volume and allow for the creation of subsurface heating profiles.

A total of 16 electrodes with co-located VR wells were installed across the source area. A copy of the treatment area plot plan has been attached as Figure 1

Drilling started on April 24 and was completed on May 1, 2006. TTL, Inc. used a hollow stem auger rig to advance the boreholes for each co-located electrode/VR well to their design depths. Due to buried utilities oriented along Sampson Street, the two electrodes in the "H" row were moved two feet into Sampson Street and were finished below grade. These electrodes were completed 18 inches below grade to isolate them from the vehicle and pedestrian traffic on Sampson Street. The other electrodes were completed above grade in accordance with the original system design. A copy of the electrode design and trenched electrode design are attached as Figures 2 and 3.

Four electrodes and one TMP were installed to a total depth of 9 feet bgs on the western side of the site, designated as Area 3. Temperature monitoring depths in Area 3 were established at 1, 5 and 8 feet bgs. The central portion of the site was designated as Area 2 and a total of nine electrodes and one TMP were installed to 18 feet bgs. Temperature monitoring depths were set at 1, 5, 10, 15, and 18 feet bgs. Treatment in the eastern side of the site, Area 1, extended the deepest with three electrodes and one TMP installed to 26 feet bgs. Thermocouples in the Area 3 TMP were placed at 1, 5, 10, 15, 20, and 25 feet bgs. A design change was made to the electrodes in the "G" row resulting in the conductive interval of each electrode being lowered to 6 feet bgs due to the existence of an abandoned steam chase.

Surface construction, including VR piping and electrical supply cabling to the electrodes/VR wells, was completed during the week following drilling. TRS installed vapor phase GAC vessels for the potential treatment of extracted CVOCs on May 8, 2006. The system was fully constructed and ready for operational testing on May 8, 2006. A copy of the system process flow diagram has been attached as Figure 4.

The primary electrical service was delivered to the system from a high voltage switch located 200 feet west of the site along Porter Avenue. A horizontal boring was installed to carry the 13,200 volt service to a 500 kW step down transformer located inside the equipment compound. A service disconnect switch and meter were installed on transformer before final inspection by Great Lakes facility management. The installation was approved for operation and energized on May 22, 2006.

4.0 System Startup

System startup and shakedown began on May 22-23, 2006. Once the electrical and VR connections were complete, power was applied to the VR blower and steam condenser so that they could be tested. After proper operation of the internal and external interlocks for each system component was verified, TRS applied power to the electrodes so that startup step and touch voltage safety testing could be performed. Interlocks are connected between each unit of equipment to ensure the electrodes are de-energized in there is a lose of vapor recovery or an internal malfunction. No voltage potentials greater than the 15-volt limit established by TRS were found at the site.

With the initial voltage safety survey complete, the applied voltage to the subsurface was slowly increased throughout the remainder of the day. With each voltage increase, checks for surface voltage were performed and results recorded. In no instance did readings exceed the TRS 15-volt limit.

The ERH system was left offline overnight and additional performance and safety testing was conducted the following day. The ERH system was deemed fully operational on May 24, 2006 and the project status moved from the Startup phase to the Operations phase.

During ERH startup and early operations, step and touch voltage potentials in and around the electrode field were monitored frequently to make sure public and worker safety from electrical hazards. When the applied voltage to the subsurface was raised to 240 volts, TRS obtained step and touch voltage readings on the perimeter fence in the vicinity of electrodes H3 and H4 that were nearing the TRS established 15-volt limit.

To address this concern, TRS replaced a portion of the metal fence along Sampson Street with a wooden panel fence that extended 15 feet north and south of electrode row "H". As an additional precaution, the concrete and asphalt extending three feet on either side of the wooden fence was painted with an isolating dielectric paint. The wooden fence eliminated potential voltage hazards from ground to the fence and the paint insulated the surface from the pavement underneath. To monitor surface voltages over time, step and touch readings in and around the entire electrode field were collected during every TRS site visit. These efforts were taken to make sure on-going site safety.

5.0 Noise Abatement

To make sure that the system met the noise abatement criteria of 60 decibels (dB) at the perimeter fence, custom noise abatement mufflers were installed on each of the system's cooling fans and blowers. Noise testing conducted upon system startup verified that the 60 dB noise restriction had been met.

6.0 Soil Sampling

Soil sampling was conducted during the ERH system operations to measure the amount of contamination remaining in the treatment area and to guide operational changes intended to optimize remediation efforts towards the most impacted portions of the site. The results of each sampling event are presented in Table 1. The same data is shown graphically in Figure 5.

The first round of interim soil sampling was conducted on July 11, 2006. The electrode field was reconfigured on July 20, 2006 after sampling results indicated that the site cleanup criteria had been achieved in the western portion of the treatment area. TRS removed four electrodes from service in order to reduce the amount of energy being applied to areas that had achieved the cleanup goal.

The PCE concentration goal of 20 mg/kg had not been met at eight of the fifteen sampling locations and the reduction in treatment area size was intended to target the areas that required further remediation. One such location was the area surrounding SB-19, where concentrations of total CVOCs in soil measuring 3,305 mg/kg were recorded during the July 11, 2006 interim sampling event. This value was more than twice the highest total CVOC concentration previously reported at the site.

The second round of interim soil sampling was conducted on August 8, 2006. Only the five sampling locations that greatly exceeded the cleanup goal during the July 11, 2006 sampling event were re-sampled. Analytical results indicated that only one of these five sample locations remained above the cleanup criteria and the treatment area was reconfigured a second time to target that one location.

On August 3, 2006, TRS determined that the connection between the PCU and electrode H3 had been lost and that the fault was within the four foot section of utility trenching extending from the site under Sampson Street to the electrode. Once the soil analytical results from the second round of interim soil sampling indicated that the area surrounding electrode H3 was still impacted above the remedial goal, the electrode was repaired on August 15, 2006 and placed back in service.

A third round of interim sampling was conducted on September 12, 2006. The third interim sample event retested the 15 sampling locations, with the results indicating a decrease at location SB-19 from 1,033 mg/kg to 0.005 mg/kg. However, three locations showed an increase from previously low concentrations. The electrode array was again reconfigured to target the three sample locations that remained above the guaranteed cleanup goal.

A fourth and final round of sampling completed on September 28, 2006 indicated that the reductions in PCE concentration needed to meet the project cleanup goals had been achieved at every sample location.

Table 1. Summary of Soil Sampling Results, PCE (mg/kg)

	Depth	Baseline	Interim 7/11/06	Interim 8/8/06	Interim 9/12/06	Final 9/28/06	Percent
Sample ID	(feet bgs)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)	Reduction
SB-20	6-7	26	11	NS	3.3	NS	86.9%
SB-21	9-10	16	57.7	0.92	0.4	NS	97.5%
SB-21	13-14	183	221	0.78	1.3	NS	99.3%
SB-22	7-8	19	0.002	NS	0	NS	100%
SB-22	18-19	200	0.79	NS	62.4	15.0	92.5%
105S-13	2.5-3	1,500	58.1	0.01	1.1	NS	99.9%
MW-05S	0-1	190	4.5	NS	0.6	NS	99.6%
105S-12	0-0.5	370	20.9	NS	19.3	NS	94.8%
10-105S-12	2.5-3	600	21.2	NS	3.2	NS	99.4%
SB-19	19-20	584.9	3,305.7	1,033	0	NS	100%
SBGP-04	8-12	550.8	36.1	NS	0	NS	100%
MW-10D	9-11	133	0.35	NS	192.2	15.3	88.4%
SB-15	0-1	829.7	3.1	NS	0.2	NS	99.9%
SB-15	11-12	590	255.3	15.8	94.1	1.0	99.8%

MW-06D	7-8	886.4	2.5	NS	0.2	NS	99.9%
Average		445.3	266.5	76.6	25.2	4.09	99.08%

Notes:

NS-Not Sampled

The final average percent reduction was calculated by using the lowest concentration from the 9/12/06 and 9/28/06 sample events




Figure 5. Contaminant Concentrations with Time

The first round of interim soil sampling re-sampled the 15 baseline sampling locations once the ERH system had input the amount of energy initially estimated to be sufficient to achieve the cleanup criteria. The concentrations of PCE in soil at seven of the 15 sampling locations were reduced to below the cleanup guarantee of 20 mg/kg. The average PCE concentrations from the sampling locations indicated a 41% reduction to 266.5 mg/kg from a baseline value of 445.3 mg/kg.

The second interim sampling event was scheduled because the concentrations of PCE in the recovered vapor stream had decreased from a maximum of 1,290 micrograms per liter (μ g/l) to less than 400 μ g/l. During the second soil sample event, the five locations that greatly exceeded the guaranteed cleanup criteria during the initial interim sampling event were resampled. The concentrations of PCE in soil at three of the five sampling locations were reduced to less than 1 mg/kg, with another reduced to 15.8 mg/kg. PCE concentrations in soil at the fifth sampling location (SB-19 at 19-20 feet) decreased by 69% but remained

above the cleanup guarantee. The result of the second interim sampling event was an average site PCE in soil concentration of 76.6 mg/kg.

The third interim sampling event was performed once a 95% reduction in the peak vapor stream concentrations of PCE had been achieved. PCE concentrations at the one sampling location still exceeding cleanup criteria during the previous sampling event, SB-19 at 19-20 feet, decreased to less than 0.005 mg/kg. However, three sampling locations where PCE concentrations had previously been measured below the cleanup guarantee had increased enough to hold the site average PCE concentration in soil at 25.2 mg/kg.

The fourth, and final, sampling event showed that PCE concentrations at the three remaining sampling locations had decreased to less than 15.3 mg/kg and lowered the site average PCE concentration in soil to 4.09 mg/kg, which represented a reduction of 99% from baseline. That reduction met the projects goal of industrial land use criteria less than 20 mg/kg of PCE.

7.0 Water Balance

Operation of the ERH system produced a negative gradient on the groundwater table surrounding the treatment volume as the system extracted more water than was reintroduced as electrode re-wetting drip. The total volume of water entrained from the subsurface or removed from the treatment area as condensate was 195,368 gallons, while the ERH system returned only 179,140 gallons of water to the vadose zone to maintain proper moisture content in the subsurface for efficient ERH application.

Water removed from the treatment volume was treated by the condenser cooling tower. The cooling tower acts like an air stripper and recovered water makes hundreds of passes before being returned to the subsurface. Surplus water, combined with the potable makeup water initially added to the system at startup, was evaporated from the cooling tower during the operations period. Laboratory results from a sample of the cooling tower water collected on May 30, 2006 (approximately 1 week after startup) showed no CVOCs were detected in the cooling tower water. The laboratory results are provided in Attachment B.

8.0 System Operations and Shutdown

The ERH system operated for 134 days with power being applied on 125 of those days. Power input was stopped for a combined total of 6 days to allow for the four soil sampling events and an additional 3 days for general system maintenance and repair.

At the instruction of the Navy and TTNUS, power application to the field was stopped on October 4, 2006, following receipt of analytical data indicating that the guaranteed remedial goal for the project had been met. The vapor recovery blower and steam condenser remained operational until October 16, 2006 to make sure that additional contaminant vapors that may have been present in the subsurface were collected.

9.0 Vapor Stream Analyses

TRS collected CVOC vapor stream samples weekly during the first 7 weeks of the ERH operating period using Tedlar bags. These samples were then delivered to an off site laboratory for analyses and the laboratory reports are provided in Attachment A. The sampling frequency decreased to bi-monthly after the peak contaminant extraction rate had passed. The analytical results from these sampling events are summarized in Table 2. Based on the vapor data collected in the off-gas stream, TRS estimates that approximately 1,200 pounds of contaminants were removed by volatilization during the ERH application.

The vapor stream flow rate was measured daily by the PCU automated software and multiplied by the CVOC concentration for each sample date to calculate mass removal rates. Tracking of the total mass removed in the vapor stream began on May 24, 2006 using the assumption that the initial concentration of CVOCs in the vapor steam was zero. The mass removed between two subsequent sampling periods was calculated by averaging the rate of extraction between the two consecutive sampling events.

Table 2. Vapor Stream Concentration Results

Sampling	PCE	тсе	PID	CVOC Removal Rate	CVOCs Removed during period	Flow rate	Average Subsurface Temperature	Hours between sample
Date	μg/L)	μg/L)	(ppm)	(lbs/hr)	(lbs)	(scfm)	(°C)	events
5/25/05	84.9	ND	12	0.07	0.9	210	17	27
5/31/06	1,060	ND	319	0.83	63.7	210	31	142
6/7/06	854	ND	198	0.72	133.6	225	53	172
6/13/06	780	ND	260	0.58	93.0	198	65	143
6/21/06	1,140	ND	383	0.88	138.8	205	76	191
6/27/06	1,290	ND	596	1.26	152.4	261	81	143
7/5/06	1,050	ND	400	0.82	203.6	209	86	196
7/18/06	460	11.2	146	0.36	183.8	205	86	311
8/1/06	399	ND	68.5	0.31	112.5	210	89	333
8/16/06	40	ND	35	0.03	63.0	205	88	366
8/30/06	67.1	3.62	26.7	0.05	13.6	193	80	331
9/7/06			19.8	0.04	8.7	191	77	192
9/21/06			23	0.04	13.4	230	84	336
10/4/06			21	0.04	12.5	202	93	312
10/16/06			4	0.01	7.2	205	71	288
				Total	1,200.4			

Notes:

TCE = trichloroethylene

PID = photo ionization detector

ppm = parts per million lbs/hr = pounds per hour

lbs = pounds

SCFM = standard cubic feet per minute

TRS installed vapor phase GAC units to be used as a vapor treatment system if the rate of contaminant extraction from the subsurface exceeded 8 pounds of CVOCs per hour. Based on the results of vapor sampling, the GAC vessels were left off-line throughout the entire ERH application.

Weekly sampling included field measurements with a photo ionization detector (PID) and the collection of samples in Tedlar bags for laboratory analyses. These sampling events were used to make sure compliance with vapor release permits and to calculate CVOC mass removal rates and the cumulative CVOC mass removed during ERH operations. The weekly vapor stream sample results were a key indicator of changing subsurface conditions and helped to determine what, if any, adjustments needed to be made to the ERH system operating conditions.

On July 5, 2006, the laboratory CVOC concentrations and PID results showed a decrease indicating the peak vapor contaminant extraction rate had passed. PID readings continued to be collected on a weekly basis to verify the peak vapor rate had passed and biweekly laboratory analysis of the vapor stream was conducted. The PID results consistently mirrored laboratory results and gave sufficient indication as to whether the air emission limit was being approached. Had the PID vapor stream concentration increased significantly, the collection of samples for laboratory analysis would have been reinstated.

Figure 6 illustrates the concentration of PCE in the vapor stream, in $\mu g/l$, as determined by the laboratory samples over time. This data is compared to PID reading taken from the same stream at the same time. The average subsurface temperature at the time of sampling has been included for reference.




Figure 6. Vapor Concentrations and Temperature versus Time

10.0 Subsurface Temperatures

The subsurface temperature of the treatment area was measured using 14 thermocouples distributed among three TMPs. The PCU system control program was utilized to automatically read each thermocouple daily. The number of thermocouples per TMP corresponds to the depth of active heating where a specific TMP was located. At each TMP, thermocouples were separated by 5-foot depth intervals except for the 1-foot and 8-foot intervals.

The ³/₄-inch CPVC TMP casings were installed at the same time as the electrodes using hollow stem auger. The locations of the TMPs were selected to be spaced the furthest distance possible from the surrounding electrodes so as to monitor the coolest portions of the treatment area (Figure 1).

Prior to ERH application, the average subsurface temperature was 15.5°C. During ERH operations, subsurface temperatures in the treatment volume increased to an average of 90°C. The top and bottom of the treatment area typically appear cooler than the center primarily due to heat loss to the surrounding media. Additionally, airflow enhances evaporation within the shallow region of the site which, when combined with the applied vacuum, results in reduced boiling temperatures. When the top and bottom interval values are removed from the calculation of average temperatures, the subsurface temperature profile indicates that a

maximum average temperature of 100°C was achieved throughout most of the treatment volume.

The average heat-up rate naturally decreases as individual thermocouple locations reach their respective boiling temperature at depth. From May 26 through June 18, 2006, the average subsurface temperature increased from just above ambient (18°C) to 76°C. The 58°C increase over the 24 day period equals an average heat-up rate of 2.5°C/day. A maximum heat-up rate of 3.8°C/day was achieved from June 1 through June 3, 2006.

The average subsurface heat-up rate slowed significantly after June 19, 2006, ranging from 1.0°C/day to zero, as many of the subsurface locations achieved boiling temperatures. The temperature performance of each thermocouple within each TMP varies greatly as the dynamics of energy input versus heat loss combine with the heterogeneity of the subsurface to make each temperature monitoring location perform in a unique manner. The maximum temperature achieved at each individual thermocouple is listed in Table 3.

Table 3. Maximum Temperatures Achieved (°C)

Depth (ft bgs)	Area 1	Area 2	Area 3
1	100	61	82
5	103	100	100
10	105	102	96
15	109	103	
20	103	99	
25	81		

Figure 7 depicts the average temperatures at each TMP location over time from the initial baseline readings collected on May 23, 2006 through the last day of ERH operations on October 4, 2006. Rapid reductions in temperature are seen in those portions of the site (Area 2 and 3) that were removed from service and where active ERH application stopped. A rapid return to boiling conditions is also seen in Area 2 that were returned to service after increased concentrations were noted in the results from subsequent soil sampling events.




Figure 7. Average Subsurface Temperature versus Time

11.0 Power and Energy

From the start of power application to the treatment volume on May 23, 2006, a total of 632,866 kW-hrs of energy was applied to the subsurface. The energy required to remove the contamination was approximately twice the estimated amount of 328,000 kW-hr. This is due primarily to extending the operating time to target areas requiring treatment.

The average rate of power application over the entire project was 196 kilowatts (kW), with an application range of 130 kW to 318 kW over the course of the remediation. During the primary heat-up stage of operations, the system applied power at a rate of 250 to 318 kW in an attempt to get the best temperature increase versus time. After the treatment area average temperature reached 80°C, the applied power naturally decreased to a range of 180 to 220 kW as the reduction in soil moisture reduced electrical conductivity. Several changes were also made to the number of electrodes on service in an attempt to treat the area more efficiently and reduce energy consumption.

Figure 8 represents the average weekly power application over the life of the ERH application.




Figure 8. Average Weekly Power Input

12.0 System Demobilization

The electrodes were de-energized on Wednesday, October 4, 2006 and the electrical output from the PCU was locked out of service. The vapor recovery system continued operating until October 16, 2006, when it was shut down.

TRS personnel were on-site the week of October 16, 2006 for system demobilization, including decommissioning of the ERH equipment, electrode abandonment, and surface component decontamination and disposal. The PCU, steam condenser, and vapor recovery blower package were transferred offsite on October 19, 2006. The GAC and excess water holding tank had previously been taken offsite on August 18, 2006 as they were not needed to continue ongoing operations.

The piping from the vapor recovery system and electrode well heads were decontaminated using a steam powered pressure washer and these materials along with drip system piping were placed in a roll off for disposal as construction/demolition debris. The roll off box was inspected by Naval Station Great Lakes personnel and removed by Waste Management for transportation to the Countryside Landfill for disposal.

The remaining site restoration began four weeks later on November 6, 2006 with the removal of the electrical service transformer, site perimeter fence and the restoration of asphalt, concrete and grass surfaces. The area was cleared of debris and left in the same condition as before the remediation on November 16, 2006.

13.0 Conclusions

Based upon the data collected before and during the Naval Station Great Lakes ERH project, the following conclusions can be reached concerning this project:

- 1. Based upon results from fifteen sampling locations, the average concentration of PCE in soil was reduced by 99% from a pre-remediation concentration of 445.32 mg/kg to 4.09 mg/kg, exceeding the project goal of a 95.5% reduction.
- 2. The ERH technology was installed, operated, and removed with no detrimental impact to the local residents or Naval Station Great Lakes facility operations.
- 3. The maximum subsurface temperature achieved was 109°C, while the average subsurface temperature within the ERH treatment volume was 90°C, providing evidence that boiling conditions were achieved at depth across the treatment volume.
- 4. An estimated total of 1,200 pounds of CVOC was removed from the treatment area through the vapor recovery system.
- 5. Based on vapor stream sample concentrations obtained during the remediation, the greatest mass of CVOCs was extracted during the period when the average temperature of the treatment area was between 76°C and 86°C.




Figure 1. Treatment Area Plot Plan




Figure 2. Electrode Design




Figure 3. Trenched Electrode Design




Figure 4. System Process Flow

Attachment A



 uffalo Grove, Illinois 60089
 Fax: (847) 808-7772

 Project: GRE06
 Lab ID: B605392

Phone: (847) 808-7766

Reported: 06/02/06 09:02

Thermal Remediation Services Project: GRE06
1755 Afton Ave. Project Number: GRE06
Charleston, SC 29407 Project Manager: Paul Lansing

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06INF052506 (B605392-01) Air (Bag)	Sampled:	05/25/06 10:05	Rece	ived: 05/25	/06 11:47				QO
Acetone	ND	10.0	ug/l	1	6050621	05/30/06	05/30/06	8260 Mod.	
Benzene	ND	2.00	"	"	311	**	"	"	
Bromodichloromethane	ND	2.00	"	"	"	***	"	"	
Bromoform	ND	2.00	**	"	"	**	"	"	
Bromomethane	ND	2.00	"	"	11	11	"	"	
2-Butanone	ND	10.0				**	"	"	
Carbon disulfide	ND	2.00	**		311	"		".	
Carbon tetrachloride	ND	2.00		"	.11	""		"	
Chlorobenzene	ND	2.00	**	"	"	"	"	"	
Chlorodibromomethane	ND	2.00	"		"	**	*	"	
Chloroethane	ND	2.00		11	"	***	"	"	
Chloroform	ND	2.00	**			**	"	115	
Chloromethane	ND	2.00	200	"	.11	2.11		".	
1,1-Dichloroethane	ND	2.00	"	"	"	"	"	"	
1,2-Dichloroethane	ND	2.00	"	"	"	11	"	"	
1,1-Dichloroethene	ND	2.00	"	. 11	11	11	"	"	
cis-1,2-Dichloroethene	ND	2.00	**	**	"	11	"	"	
trans-1,2-Dichloroethene	ND	2.00	**	"	30	***	"	"	
1,2-Dichloropropane	ND	2.00	**	"	"	**	"	"	
1,3-Dichloropropene (cis + trans)	ND	2.00	**	"	"	**	"	,,	
Ethylbenzene	ND	2.00	**	"	11	11	"	"	
2-Hexanone	ND	10.0	"			**	"	"	
Methylene chloride	ND	2.00	**		311	***	"	"	
4-Methyl-2-pentanone	ND	10.0		"	.11		"	"	
Methyl tert-butyl ether	ND	2.00	"	"	"	**	"	,,	
Styrene	ND	2.00	"	"	"	11	,,	,,	
1,1,2,2-Tetrachloroethane	ND	2.00	"		"	**	"	"	
Tetrachloroethene	84.9	2.00		"		.11		115	
Toluene	ND	2.00	**			***	"	"	
1,1,1-Trichloroethane	ND	2.00		"				"	
1.1.2-Trichloroethane	ND	2.00	"	"	,,	**		,,	
Trichloroethene	ND	2.00	,,	"	,,	**	,,	,,	
Trichlorofluoromethane	ND ND	2.00	,,	"	,,	**	,,	,,	
Vinyl acetate	ND	10.0				"		,,	
				"	,,	"		,,	
Vinyl chloride	ND	2.00	,,	,,	,,			,,	
Total Xylenes	ND	4.00		18776	"	"	"	"	
Surrogate: Dibromofluoromethane		100 %		5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		119 %		0-155	"	"	"	"	
Surrogate: Toluene-d8		101 %		5-131					
Surrogate: 4-Bromofluorobenzene		100 %	64.2	2-126	"	"	"	"	



Phone: (847) 808-776 Fax: (847) 808-777

Thermal Remediation Services Project: GRE06 1755 Afton Ave. Project Number: GRE06

Lab ID: B605434 Charleston, SC 29407 Project Manager: Paul Lansing Reported: 06/06/06 15:06

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06INF053106 (B605434-01) Air (Bag)	Sampled:	05/31/06 09:0	05 Rece	ived: 05/31	/06 10:55	a C			Q
Acetone	ND	50.0	ug/l	5	6060027	06/01/06	06/01/06	8260 Mod.	
Benzene	ND	10.0	"	"	"	"	"	"	
Bromodichloromethane	ND	10.0	"	11	"	.11	"	"	
Bromoform	ND	10.0	**	"			"	"	
Bromomethane	ND	10.0	"	"		211	"	".	
2-Butanone	ND	50.0	"	"	"	"	**	"	
Carbon disulfide	ND	10.0	"	"	"	**	"	"	
Carbon tetrachloride	ND	10.0	"	"	"	"		"	
Chlorobenzene	ND	10.0	"	**			"	"	
Chlorodibromomethane	ND	10.0		"			"	"	
Chloroethane	ND	10.0	"	"	"	"	**	"	
Chloroform	ND	10.0	"	"	"	"	"	"	
Chloromethane	ND	10.0	"	.0	"	11	"	"	
1,1-Dichloroethane	ND	10.0	"	.00	"	.11	"	"	
1,2-Dichloroethane	ND	10.0		"	711		**	m.	
1,1-Dichloroethene	ND	10.0		"		"		75	
cis-1,2-Dichloroethene	ND	10.0	"	"	"	"	"	"	
trans-1,2-Dichloroethene	ND	10.0	"	"	"	"	"	"	
1,2-Dichloropropane	ND	10.0		"	**	.11	"	"	
1,3-Dichloropropene (cis + trans)	ND	10.0	"		"	.11	*	**	
Ethylbenzene	ND	10.0	"	"		"		".	
2-Hexanone	ND	50.0	**	"	"	"	**	"	
Methylene chloride	ND	10.0	"	"	"	"	"	"	
4-Methyl-2-pentanone	ND	50.0	"	11	"	11	w	"	
Methyl tert-butyl ether	ND	10.0	**	.00	"	.11	"	110	
Styrene	ND	10.0		"			"	".	
1,1,2,2-Tetrachloroethane	ND	10.0	**	"	"	"	**	"	
Tetrachloroethene	1060	10.0	"	"	"	"	"	"	
Toluene	ND	10.0	"	"	"	"	*	"	
1,1,1-Trichloroethane	ND	10.0	"	"	"	"	"	"	
1,1,2-Trichloroethane	ND	10.0					**	#.	
Trichloroethene	ND	10.0		"			**	m.	
Trichlorofluoromethane	ND	10.0	**	"	"	"	**	"	
Vinyl acetate	ND	50.0	**	n	"	"	"	"	
Vinyl chloride	ND	10.0	"		"	"	"	"	
Total Xylenes	ND	20.0					"	"	
Surrogate: Dibromofluoromethane		93.2 %	79.	5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		122 %	70.9	0-155	"	"	"	"	
Surrogate: Toluene-d8		101 %	61.6	5-131	"	"	"	"	
Surrogate: 4-Bromofluorobenzene		101 %	64.2	2-126	"	"	"	"	



ffalo Grove, Illinois 60089 Fax: (847) 808-7772

Project: GRE06

Phone: (847) 808-7766

 Thermal Remediation Services
 Project: GRE06

 2325 Hudson St.
 Project Number: GRE06
 Lab ID: B606078

 Longview, WA 98632
 Project Manager: Paul Lansing
 Reported: 06/14/06 16:06

Analyte	Rep Result	orting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GRE06INF060706 (B606078-01) Air (Bag)	Sampled: 06/07/06 13:30								Q
Acetone	ND	50.0	ug/l	5	6060153	06/08/06	06/09/06	8260 Mod.	
Benzene	ND	10.0	"	"	"	"	"	"	
Bromodichloromethane	ND	10.0	"	"	"	"	"	"	
Bromoform	ND	10.0	"	"	"	"	"	**	
Bromomethane	ND	10.0	"	"	"	"	"	"	
2-Butanone	ND	50.0	"	"	"	"	"	"	
Carbon disulfide	ND	10.0	"	"	"	"	"	**	
Carbon tetrachloride	ND	10.0	"	"	"	"	"	"	
Chlorobenzene	ND	10.0	"	11	"	"	"	**	
Chlorodibromomethane	ND	10.0	"	"	"	"	"	*	
Chloroethane	ND	10.0	"	"	"	"	"	"	
Chloroform	ND	10.0	"	11	"	"	"	"	
Chloromethane	ND	10.0	"	"	"	"	"	*	
1,1-Dichloroethane	ND	10.0	"	"	"	"	"	"	
1,2-Dichloroethane	ND	10.0	"	11	"	"	"	**	
1,1-Dichloroethene	ND	10.0	"	"	"	"	"	*	
cis-1,2-Dichloroethene	ND	10.0	"	"	"	"	"	"	
trans-1,2-Dichloroethene	ND	10.0	"	11	"	"	"	"	
1,2-Dichloropropane	ND	10.0	"	"	"	"	"	*	
1,3-Dichloropropene (cis + trans)	ND	10.0	"	"	"	"	"	"	
Ethylbenzene	ND	10.0	"	"	"	"	"	"	
2-Hexanone	ND	50.0	"	"	"	"	"	"	
Methylene chloride	ND	10.0	"	"	"	"	"	"	
4-Methyl-2-pentanone	ND	50.0	"	"	"	"	"	"	
Methyl tert-butyl ether	ND	10.0	"	"	"	"	"	"	
Styrene	ND	10.0	"	"	"	"	"	"	
1,1,2,2-Tetrachloroethane	ND	10.0	"	"	"	"	"	"	
Tetrachloroethene	854	10.0	"	"	"	"	"	"	
Toluene	ND	10.0	"	"	"	"	"	"	
1,1,1-Trichloroethane	ND	10.0	"	"	"	"	"	**	
1,1,2-Trichloroethane	ND	10.0	"	"	"	"	"	**	
Trichloroethene	ND	10.0	"	"	"	"	"	"	
Trichlorofluoromethane	ND	10.0	"	"	"	"	"	"	
Vinyl acetate	ND	50.0	"	"	"	"	"	"	
Vinyl chloride	ND	10.0	"	"	"	"	"	**	
Total Xylenes	ND	20.0	"	"	"	"	"	**	
Surrogate: Dibromofluoromethane	i	02 %	79.5-	-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4	I	28 %	70.9	155	"	"	"	"	
Surrogate: Toluene-d8	I	01%	61.6-	-131	"	"	"	"	
Surrogate: 4-Bromofluorobenzene	i	04 %	64.2-	-126	"	"	"	"	



Phone: (847) 808-7766

Fax: (847) 808-7772

 Thermal Remediation Services
 Project: GRE06

 2325 Hudson St.
 Project Number: GRE06
 Lab ID: B606164

 Longview, WA 98632
 Project Manager: Paul Lansing
 Reported: 06/19/06 19:32

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GRE INF 061306 (B606164-01) Air (Bag)	Sampled: 00	5/13/06 12:52	Recei	ived: 06/13/	06 13:50				G21, QC
Acetone	ND	50.0	ug/l	5	6060346	06/16/06	06/19/06	8260 Mod.	
Benzene	ND	10.0	**		**	**		"	
Bromodichloromethane	ND	10.0		"	"	22.	375	"	
Bromoform	ND	10.0	"	"	22.	"			
Bromomethane	ND	10.0	"	"	"	"	"	"	
2-Butanone	ND	50.0	"	"	"	"	"	"	
Carbon disulfide	ND	10.0	**	**	**	**		"	
Carbon tetrachloride	ND	10.0	"	".	200	91	"	"	
Chlorobenzene	ND	10.0	""	"	".	"			
Chlorodibromomethane	ND	10.0	"	"	"	"	"	"	
Chloroethane	ND	10.0	"	"	"	"	"	"	
Chloroform	ND	10.0	"	**	"	"		"	
Chloromethane	ND	10.0	"	"	200	**	,,,	"	
1,1-Dichloroethane	ND	10.0	.00.	"	"	77.			
1,2-Dichloroethane	ND	10.0	"	"	"	"	"	"	
1,1-Dichloroethene	ND	10.0	"	"	"	"	**	"	
cis-1,2-Dichloroethene	ND	10.0		"	"	11		"	
trans-1,2-Dichloroethene	ND	10.0	**	".	**	**		**	
1,2-Dichloropropane	ND	10.0	.00	"	"			**	
1,3-Dichloropropene (cis + trans)	ND	10.0	"	"	".	"			
Ethylbenzene	ND	10.0	"	"	,,	"	,,	"	
2-Hexanone	ND	50.0	"	"	"	"	"	"	
Methylene chloride	ND	10.0	"	**	"	11		"	
4-Methyl-2-pentanone	ND	50.0	"	".	200	911	**		
Methyl tert-butyl ether	ND	10.0	"	"	"				
Styrene	ND	10.0	"	"		"	"	"	
1,1,2,2-Tetrachloroethane	ND	10.0	"		**	"		"	
Tetrachloroethene	780	10.0		ii.	"	ii		"	
Toluene	ND	10.0	**	"	"	"		**	
1.1.1-Trichloroethane	ND	10.0	"	"	115	11	**		
1,1,2-Trichloroethane	ND	10.0	"	"	"	"			
Trichloroethene	ND	10.0	"	"	"	,,	,,	,,	
Trichlorofluoromethane	ND	10.0	"	ü	,,	"	**	"	
Vinyl acetate	ND	50.0		**	,,	"	,,	,,	
Vinyl chloride	ND	10.0	"		"	"	,,	"	
Total Xylenes	ND	20.0		"	"	11			
Surrogate: Dibromofluoromethane	110	98.4 %	70	5-119	"	"	"	"	
		98.4 % 116 %		5-119 9-155	,,	"	"	,,	
Surrogate: 1,2-Dichloroethane-d4		99.6 %		9-133 6-131	,,	"	"	"	
Surrogate: Toluene-d8		99.6 % 104 %			,,	"	"	,,	
Surrogate: 4-Bromofluorobenzene		104 %	04	2-126	200	377	1000	(35.7	



1380 Busch Parkway Buffalo Grove, Illinois 60089

Project: GRE06

2325 Hudson St. Project Number: GRE06 Longview, WA 98632 Project Manager: Paul Lansing Phone: (847) 808-7766 Fax: (847) 808-7772

Lab ID: B606252

Reported: 06/26/06 15:03

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06062106 (B606252-01) Air (Bag)	Sampled: 06/2	1/06 11:50	Received	1: 06/21/06	14:00				Q
Acetone	ND	50.0	ug/l	5	6060471	06/22/06	06/23/06	8260 Mod.	
Benzene	ND	10.0	"	"	"	**	**	"	
Bromodichloromethane	ND	10.0	"	"	"	31.	**	"	
Bromoform	ND	10.0	"	"			**	"	
Bromomethane	ND	10.0	"	"	"	"	"	"	
2-Butanone	ND	50.0	"	"	"	"	*	"	
Carbon disulfide	ND	10.0	"	. 11	"	**	"	"	
Carbon tetrachloride	ND	10.0		"	"	.11		".	
Chlorobenzene	ND	10.0	"	"		71.		".	
Chlorodibromomethane	ND	10.0	"	"	"	"	**	"	
Chloroethane	ND	10.0	"	"	"	"	*	"	
Chloroform	ND	10.0	"	11	"	"	"	"	
Chloromethane	ND	10.0	. 11	"		.11	"	115	
1,1-Dichloroethane	ND	10.0		"			**	"	
1,2-Dichloroethane	ND	10.0	"	"	"	"	**	"	
1,1-Dichloroethene	ND	10.0	"	"	"	"	**	"	
cis-1,2-Dichloroethene	ND	10.0	**	"	"	**		"	
trans-1,2-Dichloroethene	ND	10.0	"	"	"	**	**	"	
1,2-Dichloropropane	ND	10.0	"	"	"		**	"	
1,3-Dichloropropene (cis + trans)	ND	10.0		"	.11	21.	*	".	
Ethylbenzene	ND	10.0	"	"	"	"	**	"	
2-Hexanone	ND	50.0	"	"	"	"	*	"	
Methylene chloride	ND	10.0	"	"	"	.11	**	"	
4-Methyl-2-pentanone	ND	50.0		"	"	.11		".	
Methyl tert-butyl ether	ND	10.0		"	.11			"	
Styrene	ND	10.0	"	"	"	"	**	"	
1,1,2,2-Tetrachloroethane	ND	10.0	"	"	"	"	*	"	
Tetrachloroethene	1140	10.0	"	"	"	"		"	
Toluene	ND	10.0	"	**	"		**	"	
1.1.1-Trichloroethane	ND	10.0		"	"	.11	**	"	
1,1,2-Trichloroethane	ND	10.0		"		21.		"	
Trichloroethene	ND	10.0	"	"	"	"	*		
Trichlorofluoromethane	ND	10.0	"	"	"	"	*	"	
Vinyl acetate	ND	50.0	"	**	"	**		"	
Vinyl chloride	ND	10.0	11	**	"		*	"	
Total Xylenes	ND	20.0	"	"	"		**	"	
Surrogate: Dibromofluoromethane	11 (11 (11 (11 (11 (11 (11 (11 (11 (11	96.8 %	79.	5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		120 %		9-155	"	"	"	"	
Surrogate: Toluene-d8		100 %		6-131	"		"	"	
Surrogate: 4-Bromofluorobenzene		106 %		2-126	"	"	"	"	



Phone: (847) 808-7766 Fax: (847) 808-7772

Thermal Remediation Services Project: GRE06 2325 Hudson St. Project Number: GRE06 Lab ID: B606325 Reported: 06/30/06 15:30 Longview, WA 98632 Project Manager: C. Blundy

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GRE06 INF 062706 (B606325-01) Air (Bag)	Sampled	l: 06/27/06 10	:30 Re	ceived: 06/2	27/06 12:3	0			QC
Acetone	ND	100	ug/l	10	6060593	06/28/06	06/29/06	8260 Mod.	
Benzene	ND	20.0	"	"		11	"	"	
Bromodichloromethane	ND	20.0	"	"	"	"	"	"	
Bromoform	ND	20.0	"		"	"	"	"	
Bromomethane	ND	20.0		"	"	"	"	"	
2-Butanone	ND	100	"	**	"	"	**	"	
Carbon disulfide	ND	20.0	**	"	ec	"	.**	""	
Carbon tetrachloride	ND	20.0	"	"	"	22.	"		
Chlorobenzene	ND	20.0	"	"	"	"	"	"	
Chlorodibromomethane	ND	20.0	"	"	"	"	"	"	
Chloroethane	ND	20.0	"	**	100	**	**	"	
Chloroform	ND	20.0	**	"	"	**.	**	"	
Chloromethane	ND	20.0	"	"	".	77.	"		
1,1-Dichloroethane	ND	20.0	"	"	"	"	"	"	
1,2-Dichloroethane	ND	20.0	"			"	**	"	
1,1-Dichloroethene	ND	20.0		**	"	"	"	"	
cis-1,2-Dichloroethene	ND	20.0	"	"	115	90		w =	
trans-1,2-Dichloroethene	ND	20.0	**	"	100	11	.78.	""	
1,2-Dichloropropane	ND	20.0	"	"	"	"	"	"	
1,3-Dichloropropene (cis + trans)	ND	20.0			"	"	"	"	
Ethylbenzene	ND	20.0		W.		"	"	"	
2-Hexanone	ND	100	"	**		"	**	"	
Methylene chloride	ND	20.0	**	"			.11	"	
4-Methyl-2-pentanone	ND	100	**	"	"	11.	"		
Methyl tert-butyl ether	ND	20.0		"	"	"	"	"	
Styrene	ND	20.0	**	W.	"	"	**	"	
1.1.2.2-Tetrachloroethane	ND	20.0	**	**	100	**	**	"	
Tetrachloroethene	1290	20.0	**	**		110	**	"	
Toluene	ND	20.0	"	"				"	
1,1,1-Trichloroethane	ND	20.0				".	"		
1,1,2-Trichloroethane	ND	20.0		"	,,	"	,,	,,	
Trichloroethene	ND	20.0		w.		**	**	"	
Trichlorofluoromethane	ND	20.0		**		"	*	"	
Vinyl acetate	ND	100	**	".		10	"	<i>u</i> =	
Vinyl chloride	ND	20.0		"		**	,,		
Total Xylenes	ND	40.0		"	,,		"	"	
Surrogate: Dibromofluoromethane	TID.	103 %	70	5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		122 %		9-155	"	"	"	"	
Surrogate: Toluene-d8		100 %		5-131	"	"	"	"	
Surrogate: 1-btuene-as Surrogate: 4-Bromofluorobenzene		100 %		2-126	,,	"	"	"	



Grove, Illinois 60089 Fax: (847) 808-7772

Phone: (847) 808-7766

Thermal Remediation ServicesProject:GRE062325 Hudson St.Project Number:GRE06Lab ID:B607008Longview, WA 98632Project Manager:C. BlundyReported:07/17/06 18:26

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GRE06INF070506 (B607008-01) Air (Bag)	Sampled:	07/05/06 14:00	Rec	eived: 07/05	5/06 15:00				O15, QC
Acetone	ND	50.0	ug/l	5	6070232	07/17/06	07/17/06	8260 Mod.	
Benzene	ND	10.0	"	"	"	**	"	"	
Bromodichloromethane	ND	10.0	"	"	"	"	"	"	
Bromoform	ND	10.0	"	"	"	"	"	"	
Bromomethane	ND	10.0	"	**	"	"	"	"	
2-Butanone	ND	50.0	"	.11	"	**	"	115	
Carbon disulfide	ND	10.0	"	"	***	"	"	ec.	
Carbon tetrachloride	ND	10.0		"	"			"	
Chlorobenzene	ND	10.0	"	"	"	"	*	"	
Chlorodibromomethane	ND	10.0	"	"	"	"	"	"	
Chloroethane	ND	10.0	11	**	"	**		n:	
Chloroform	ND	10.0	11	"	"	**	**	96	
Chloromethane	ND	10.0	"	"	"			"	
1,1-Dichloroethane	ND	10.0	"	"	"	"	**	"	
1,2-Dichloroethane	ND	10.0	"	"	"	"	"	"	
1,1-Dichloroethene	ND	10.0		"	"	11	"	"	
cis-1,2-Dichloroethene	ND	10.0	w	.11	11	**	"	**5	
trans-1,2-Dichloroethene	ND	10.0		"	"	**		**	
1,2-Dichloropropane	ND	10.0	"	"	"	"	"	"	
1,3-Dichloropropene (cis + trans)	ND	10.0	"	"	"	"	"	"	
Ethylbenzene	ND	10.0	w	**	"	**	"	"	
2-Hexanone	ND	50.0	"	.11		11	"	#E	
Methylene chloride	ND	10.0	"	"	"	**		0.5	
4-Methyl-2-pentanone	ND	50.0	"	"	"			"	
Methyl tert-butyl ether	ND	10.0	"	"	"	"	"	"	
Styrene	ND	10.0	"	**	"	"	"	"	
1,1,2,2-Tetrachloroethane	ND	10.0	"	"	"	11.		11.5	
Tetrachloroethene	1050	10.0	w	**	11	**		100	
Toluene	ND	10.0		"		**		0.5	
1,1,1-Trichloroethane	ND	10.0	"	"	"			"	
1.1.2-Trichloroethane	ND	10.0	"	"	"	**	"	,,	
Trichloroethene	ND	10.0	,,	**	"	"		"	
Trichlorofluoromethane	ND	10.0	"	"	"	**	"	115	
Vinyl acetate	ND	50.0	**	"	"	**	"	**	
Vinyl chloride	ND	10.0	"	"	"			"	
Total Xylenes	ND	20.0	"	"	"	**	"	"	
Surrogate: Dibromofluoromethane	HENTYC	101 %	70	5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		111%		9-155	"	"	"	u	
Surrogate: Toluene-d8		101 %		6-131	"	"		"	
Surrogate: 4-Bromofluorobenzene		101 %		2-126	"	"	"	"	



Grove, Illinois 60089 Fax: (847) 808-7772

Phone: (847) 808-7766

Lab ID: B607157

Reported: 07/24/06 13:02

 Thermal Remediation Services
 Project
 GRE06

 2325 Hudson St.
 Project Number:
 GRE06

 Longview, WA 98632
 Project Manager:
 Paul Lansing

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06INF071806 (B607157-01) Air (Bag)	Sampled:	07/18/06 12:30	Reco	ived: 07/18	3/06 16:02	5			Q
Acetone	ND	50.0	ug/l	5	6070327	07/21/06	07/21/06	8260 Mod.	
Benzene	ND	10.0	. "	"	"	5.997	"		
Bromodichloromethane	ND	10.0	"	"	"	"	"	"	
Bromoform	ND	10.0	"	**	"	"	"	"	
Bromomethane	ND	10.0	.11	. 0	**	.11	**	"	
2-Butanone	ND	50.0	.0	"	**	11	**	"	
Carbon disulfide	ND	10.0	"	"	"	5.110	"		
Carbon tetrachloride	ND	10.0	11	"	"	"	"	"	
Chlorobenzene	ND	10.0	"	"	**	"	"	"	
Chlorodibromomethane	ND	10.0	**	11	**	"		"	
Chloroethane	ND	10.0	.0			11	**	"	
Chloroform	ND	10.0	.00	"		5,465	**	"	
Chloromethane	ND	10.0		"	"	"	"	"	
1,1-Dichloroethane	ND	10.0	"	"	"	"	"	"	
1,2-Dichloroethane	ND	10.0	"	"	**	"		"	
1,1-Dichloroethene	ND	10.0	.01	"	"	11	"	"	
cis-1,2-Dichloroethene	ND	10.0	.00	"	"	5.00	**	"	
trans-1,2-Dichloroethene	ND	10.0	. "	"	"	3.11	".		
1,2-Dichloropropane	ND	10.0	**	"	"	"	"	"	
1,3-Dichloropropene (cis + trans)	ND	10.0	"	**	"	"	**	"	
Ethylbenzene	ND	10.0	.11		**	.11	**	"	
2-Hexanone	ND	50.0	.0			11	**	"	
Methylene chloride	ND	10.0	. "	"		5.11	**		
4-Methyl-2-pentanone	ND	50.0		"	**	"	"	"	
Methyl tert-butyl ether	ND	10.0	**	"	**	"	"	"	
Styrene	ND	10.0	"		**	"	e.	"	
1,1,2,2-Tetrachloroethane	ND	10.0	0		"	110	**	"	
Tetrachloroethene	460	10.0			"	5.00	**	,,	
Toluene	ND	10.0	. 19	"	"		".		
1,1,1-Trichloroethane	ND	10.0	11	"		"	"	"	
1,1,2-Trichloroethane	ND	10.0	"	"	"	"	**	"	
Trichloroethene	11.2	10.0	.,	"	**	"		,,	
Trichlorofluoromethane	ND	10.0	"			"		"	
Vinyl acetate	ND	50.0					*	"	
Vinyl chloride	ND	10.0				5.865	"	"	
Total Xylenes	ND	20.0	.,	.,	"	"	,,	"	
Surrogate: Dibromofluoromethane	ND	113 %		5-119	"	"	"	"	
					"	"	,,	"	
Surrogate: 1,2-Dichloroethane-d4		118 %		0-155	"	"	"	"	
Surrogate: Toluene-d8 Surrogate: 4-Bromofluorobenzene		105 % 101 %		6-131 2-126	"	,,	,,	"	



2325 Hudson St.

Longview, WA 98632

1380 Busch Parkway Buffalo Grove, Illinois 60089

 Project:
 GRE06

 Project Number:
 GRE06

 Lab ID:
 B608016

 Project Manager:
 Paul Lansing

 Reported:
 08/09/06 16:00

Phone: (847) 808-7766

Fax: (847) 808-7772

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note:
GRE06INF080106 (B608016-01) Air (Bag)	Sampled: 0	Marie Landello XI	WHEN CONTRACTOR	2004-922-120000-0	122120473-A-12212073	Trepared	Thuryzeu	memod	QC
, , , ,						00.00	00.00.00		ŲĊ
Acetone	ND	50.0	ug/l "	5	6080099	08/07/06	08/08/06	8260 Mod.	
Benzene	ND	10.0	,,	,	,,	"	,,		
Bromodichloromethane	ND	10.0	,,						
Bromoform	ND	10.0	,,	,,		**		,,	
Bromomethane	ND	10.0	,,		,,		,	,,	
2-Butanone	ND	50.0	,,	,,	,,			,	
Carbon disulfide	ND	10.0	,,	,,		,,	,,	,,	
Carbon tetrachloride	ND	10.0	,,	,,	10	**	,,	,,	
Chlorobenzene	ND	10.0			ů.				
Chlorodibromomethane	ND	10.0			*		,	,	
Chloroethane	ND	10.0					,	,,	
Chloroform	ND	10.0	,,	,			,,		
Chloromethane	ND	10.0	,,		,,	,,	,,	,,	
1,1-Dichloroethane	ND	10.0	"		"	,,			
1,2-Dichloroethane	ND	10.0		,					
1,1-Dichloroethene	ND	10.0	"	,	"		,	"	
cis-1,2-Dichloroethene	ND	10.0	"			"		"	
trans-1,2-Dichloroethene	ND	10.0	"		11	**	"	"	
1,2-Dichloropropane	ND	10.0			11.	20.	311		
1,3-Dichloropropene (cis + trans)	ND	10.0	"	"	12.	"	"	SM3	
Ethylbenzene	ND	10.0	"	"	"	"	"	"	
2-Hexanone	ND	50.0	"	"	"	"	"	"	
Methylene chloride	ND	10.0	"	"	"	**	"	**	
4-Methyl-2-pentanone	ND	50.0	"	"	96	311	"		
Methyl tert-butyl ether	ND	10.0	".	"	95	"	"	585	
Styrene	ND	10.0	"	"	11	"	"	"	
1,1,2,2-Tetrachloroethane	ND	10.0	"	"	"	"	"	"	
Tetrachloroethene	399	10.0	"	"	**	"		"	
Toluene	ND	10.0	"	"	**	"	"	**	
1,1,1-Trichloroethane	ND	10.0	"	"	96	31.	"		
1,1,2-Trichloroethane	ND	10.0	".	"	22.		"	5.00	
Trichloroethene	ND	10.0	"	"	111	"	"	"	
Trichlorofluoromethane	ND	10.0	"	"	**		"	"	
Vinyl acetate	ND	50.0	"	**	11	"	"	"	
Vinyl chloride	ND	10.0	"	".	110	**	"		
Total Xylenes	ND	20.0		"	110	20.	211	"	
Surrogate: Dibromofluoromethane		90.2 %	79.3	5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		114 %		0-155	"	"	"	"	
Surrogate: Toluene-d8		94.6 %		5-131	"	**	"	"	
Surrogate: 4-Bromofluorobenzene		92.8 %		2-126	"	"	"	"	



2325 Hudson St.

Longview, WA 98632

1380 Busch Parkway Buffalo Grove, Illinois 60089

 Project:
 GREO6

 Project Number:
 GRE06

 Lab ID:
 B608174

 Project Manager:
 C. Blundy

 Reported:
 08/25/06 13:49

Phone: (847) 808-7766 Fax: (847) 808-7772

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06 INF 081606 (B608174-01RE1) Ai	r (Bag) Sa	mpled: 08/16/0	06 15:00	Received:	08/16/06	16:15			O15, QC
Acetone	ND	10.0	ug/l	1	6080353	08/18/06	08/23/06	8260 Mod.	
Benzene	ND	2.00	"	"	"	"	"	"	
Bromodichloromethane	ND	2.00	"	**	W.	"	**	**	
Bromoform	ND	2.00	"	"	*	16	**	"	
Bromomethane	ND	2.00	"	"	"	".		"	
2-Butanone	ND	10.0	"	"	"	"	"	"	
Carbon disulfide	ND	2.00	"	*	"	**	**	"	
Carbon tetrachloride	ND	2.00		**	"	"	**	"	
Chlorobenzene	ND	2.00	**	**	**	40	**	# S	
Chlorodibromomethane	ND	2.00	"	"		**	**	**	
Chloroethane	ND	2.00	"		"	"	"	"	
Chloroform	ND	2.00	"		"	"	"	"	
Chloromethane	ND	2.00		"	"	**	"	"	
1,1-Dichloroethane	ND	2.00	"	*	"	"	**	"	
1,2-Dichloroethane	ND	2.00	11		100	11	**		
1,1-Dichloroethene	ND	2.00	"	,,	"	11.			
cis-1,2-Dichloroethene	ND	2.00	.,		,,	"	"	,,	
trans-1,2-Dichloroethene	ND	2.00	,,		,,	n	11	"	
1,2-Dichloropropane	ND	2.00	"	w:		"	"	"	
1,3-Dichloropropene (cis + trans)	ND	2.00	"			11.	"	"	
Ethylbenzene	ND	2.00	,,	,,	,,	"	"		
2-Hexanone	ND ND	10.0	,,				,,	"	
		2.00	,,			iii	"		
Methylene chloride	2.34						,,	,,	
4-Methyl-2-pentanone	ND	10.0							
Methyl tert-butyl ether	ND	2.00	,,	,	,,	"		,,	
Styrene	ND	2.00	,,		,,			,,	
1,1,2,2-Tetrachloroethane	ND	2.00	,,			,,		,,	
Tetrachloroethene	40.3	2.00		,					
Toluene	ND	2.00	"		"	"	"	"	
1,1,1-Trichloroethane	ND	2.00	"		"	"	"	"	
1,1,2-Trichloroethane	ND	2.00		**	"	"	"	"	
Trichloroethene	ND	2.00	"	"	**	10	"	"	
Trichlorofluoromethane	ND	2.00	"	"				"	
Vinyl acetate	ND	10.0	"	"	"	"	"	"	
Vinyl chloride	ND	2.00	"		"	"	"	"	
Total Xylenes	ND	4.00	0	**	"	"	"	"	
Surrogate: Dibromofluoromethane		126 %	79.3	5-119	"		"	"	Н
Surrogate: 1,2-Dichloroethane-d4		128 %		0-155	"	14	"	"	
Surrogate: Toluene-d8		102 %		5-131	"	**	"	"	
Surrogate: 4-Bromofluorobenzene		99.4 %		2-126	"	"	"	"	



2325 Hudson St.

Longview, WA 98632

1380 Busch Parkway Buffalo Grove, Illinois 60089

 Project:
 GREO6

 Project Number:
 GRE06

 Lab ID:
 B608324

 Project Manager:
 C. Blundy

 Reported:
 09/07/06 16:58

Phone: (847) 808-7766 Fax: (847) 808-7772

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06INF083006 (B608324-01) Air (Bag)	Sampled:	08/30/06 10:10) Rece	eived: 08/30	/06 13:20				QC
Acetone	ND	10.0	ug/l	1	6090005	09/01/06	09/07/06	8260 Mod.	
Benzene	ND	2.00	*	.11	11	**	**	"	
Bromodichloromethane	ND	2.00	.11		#	.11	**	"	
Bromoform	ND	2.00		"	22		"	"	
Bromomethane	ND	2.00	"	"	**	"	"	"	
2-Butanone	ND	10.0	"	**	"	"	"	"	
Carbon disulfide	ND	2.00	**	"	11	**	**	"	
Carbon tetrachloride	ND	2.00			**	"	**	"	
Chlorobenzene	ND	2.00		"	25				
Chlorodibromomethane	ND	2.00	"	**	71	"	"		
Chloroethane	ND	2.00	"	"		"	"	**	
Chloroform	ND	2.00		"	"	"	"		
Chloromethane	ND	2.00	*	.11	**	"	**	"	
1.1-Dichloroethane	ND	2.00	.11	"	#	.11			
1,2-Dichloroethane	ND	2.00	"	"	11	"	"	,,	
1,1-Dichloroethene	ND	2.00	"	"	**	"	"	"	
cis-1,2-Dichloroethene	ND	2.00		**	"	**			
trans-1,2-Dichloroethene	ND	2.00	**		ii.	**	**	"	
1,2-Dichloropropane	ND	2.00	.11		#	.11		"	
1,3-Dichloropropene (cis + trans)	ND	2.00		"				"	
Ethylbenzene	2.10	2.00		"	**	**	"	"	
2-Hexanone	ND	10.0		"	**	"		,,	
4-Methyl-2-pentanone	ND	10.0		"	"	"			
Methyl tert-butyl ether	ND	2.00	**		**	"	**		
Styrene	ND	2.00			#	.11			
1,1,2,2-Tetrachloroethane	ND	2.00		"	,,	,,	**		
Tetrachloroethene	67.1	2.00	.,	,,	**	**	"	"	
1,1,1-Trichloroethane	07.1 ND	2.00			"	"	.,	,,	
1,1,2-Trichloroethane	ND ND	2.00		**		"	,,	,,	
Trichloroethene		2.00			,,	"	,,	,,	
	3.62		,	"	**	"	,,		
Trichlorofluoromethane	ND	2.00	,	,,		,,	,	,,	
Vinyl acetate	ND	10.0			,,				
Vinyl chloride	ND	2.00				,,		,	
Total Xylenes	9.15	4.00				011	377	9000	
Surrogate: Dibromofluoromethane		82.6 %		5-119	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		74.6 %		9-155	"	"	"	"	
Surrogate: Toluene-d8		96.4 %		6-131	"	"	311	и.	
Surrogate: 4-Bromofluorobenzene		107 %	64.2	2-126	"	"	"	n	


Attachment B



Phone: (847) 808-7766 Fax: (847) 808-7772

Project: GRE06 Thermal Remediation Services Project Number: GRE06 1755 Afton Ave. Lab ID: B605434 Project Manager: Paul Lansing Reported: 06/06/06 15:06 Charleston, SC 29407

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GRE06CT053106 (B605434-02RE1) Water	Sampled:	05/31/06 10:05	Rec	E					
Acetone	ND	10.0	ug/l	1	6060012	06/02/06	06/02/06	EPA 8260B	
Benzene	ND	2.00	"		"	31		(0)	
Bromodichloromethane	ND	2.00	"	"	"		"	"	
Bromoform	ND	1.00	"	"	"	"	"	"	
Bromomethane	ND	2.00	"	**	"	"	"	"	
2-Butanone	ND	10.0	**	**	"	**	"	"	
Carbon disulfide	ND	2.00	*	"	"	**	"	#6	
Carbon tetrachloride	ND	2.00		"	"	.00.5		10	
Chlorobenzene	ND	2.00	"	"	**	"	"	"	
Chlorodibromomethane	ND	2.00	"	"	"	"	"	"	
Chloroethane	ND	2.00	"	**	"	11	"	"	
Chloroform	ND	2.00	**		11		"	**	
Chloromethane	ND	2.00	**	"	"	**		ec	
1,1-Dichloroethane	ND	2.00	"	"	**	"	"	"	
1,2-Dichloroethane	ND	2.00	"	"	"	"	**		
1,1-Dichloroethene	ND	2.00	"	**	"	**	"	"	
cis-1,2-Dichloroethene	ND	2.00	**		"	**	***	"	
trans-1,2-Dichloroethene	ND	2.00	**	"	"			m;	
1,2-Dichloropropane	ND	2.00	"	"	"		**	**	
1,3-Dichloropropene (cis + trans)	ND	2.00	"	*	"	"	**	"	
Ethylbenzene	ND	2.00			"	"	"	"	
2-Hexanone	ND	10.0	**	w	**	**	"		
Methylene chloride	ND	2.00	**		91	**		"	
4-Methyl-2-pentanone	ND	10.0	"	"	"			"	
Methyl tert-butyl ether	ND	2.00	"	*	**	"	"	"	
Styrene	ND	2.00	"		"	"	"	e e	
1,1,2,2-Tetrachloroethane	ND	2.00	"	**	"	**		"	
Tetrachloroethene	ND	2.00	*	*	"	**	"	**	
Toluene	ND	2.00	**	**	"	310	,,	**	
1,1,1-Trichloroethane	ND	2.00	"	**	"	"	**	**	
1.1.2-Trichloroethane	ND	2.00		"	,,	"	"	"	
Trichloroethene	ND	2.00	,,	**	,,	**	,,		
Trichlorofluoromethane	ND	2.00	**		"			115	
Vinyl acetate	ND	10.0		"	"	310	"	"	
Vinyl chloride	ND ND	2.00	"	**	**	"	"		
Total Xylenes	ND ND	4.00		"	,,	**	"	,,	
9 (00 1 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	ND	4343	27.0	0.122	"	"	"	"	
Surrogate: Dibromofluoromethane		106 %		8-133	"	"	"	"	
Surrogate: 1,2-Dichloroethane-d4		99.6 %		2-141					
Surrogate: Toluene-d8		98.4 %		8-118	"	"	"	"	
Surrogate: 4-Bromofluorobenzene		87.8 %	68.	9-123	"	"	"	"	



ILLINOIS DEPARTMENT OF PUBLIC HEALTH DIVISION OF ENVIRONMENTAL HEALTH 525 WEST JEFFERSON STREET SPRINGFIELD, ILLINOIS 62761

RETURN ALL COPIES TO IDPH OR LOCAL HEALTH DEPARTMENT

TYPE OR PRESS FIRMLY 22 MW 055

3 J 12					
1. N7 2.	Ownership (Name of Controlling Party) UN ITED IC CREAT LAKES NW CORNEL Well Location: FORMER BLDG 105 SAMPSON Address - Lot Number	STATES N R of ST: C PATER	AVENUE GE	EAT LA County	KE
	General Description: Township 44 (N)(S)	Range 1	2. (E) (W)	Section_	4
	Quarter of theQu	erter of the	Q	uarter	ELEVAT
3.	Year Drilled 2003	_		57, 358.2	649.0
4.	Drilling Permit Number (and date, if known)	EAS	TING 1,1	17, 718.39	
5.	Type of Well: Bored Drilled (Other			-
6.	Total Depth 24 FEET Diameter	inches) 81/4	"BOREHO	LE -2 INC	H PYC
7.	Formation clear of obstruction Yes	No	τ.		•
8.	DETAILS OF PLUGGING				
	Filled with CEMENT - BENTON ITE SLIFE (cement or other materials)	from 24	.0 6 CROV	ind fkct	
	Kind of plug	from	to	ñ.	
	Filled with	from	to	ñ.	
	Kind of plug	from	to	ft.	
	Filled with	from	to	ft.	
	Kind of plug	from	to	ñ.	
9.	CASING RECORD: Upper 3 feet of casing removed	Yes	No		
10.	Date well was sealed: Month APRIL Day	<u>25</u> 1	ear 2006	_•	
11.	Licensed water well driller or other person approved by NEIL WIKTOR TIL ASSOCIATES Name	NA.	t performing w		
	1915 N. 12TH STREET	TOLE DO		OH 43 State/Zip	5624

ILLINOIS DEPARTMENT OF PUBLIC HEALTH DIVISION OF ENVIRONMENTAL HEALTH **525 WEST JEFFERSON STREET**

SPRINGFIELD, ILLINOIS 62761

RETURN ALL COPIES TO IDPH OR LOCAL HEALTH DEPARTMENT

TYPE OR PRESS FIRMLY

22 MW0110 D

1.	HTC GRENT LAKES NW COPHER OF	· · · · · · · · · · · · · · · · · · ·
	General Description: Township 44 (NS) Range 12 (W) Section 4	
3.	Quarter of theQuarter of theQuarter Vear Drilled 2003 NoFM ING 2,057,375.57 El	OJTAV3
4.	Drilling Permit Number (and date, if known) N EASTING 1,117,751.88	49.5
5,	. Type of Well: Bored Drilled Other	
6.	Total Depth 40 FEET Diameter (inches) 8'4 BOREHOLE - 2'IN NC	
7.	. Formation clear of obstructionYesNo	
8.		
	Filled with CEMENT. DENTONITE SWEET from 40 FT. to SUPERCE. (cement or other materials)	
	Kind of plugft.	
	Filled withtott.	
	Kind of plug from to ft.	
	Filled with from to fit.	
	Kind of plug from to ft.	
9.	CASING RECORD: Upper 3 feet of casing removed	
10.	Date well was sealed: Month APPIL Day 27 Year 2006.	
11.	Licensed water well driller or other person approved by the Department performing well sealing.	
	NEIL WILTOR TILASSOCIATES, INC. Onlylete License Number	
	1915 N.12 TH ST. JOLEDO OH 43624 Address City State Zip 1	

ILLINOIS DEPARTMENT OF PUBLIC HEALTH DIVISION OF ENVIRONMENTAL HEALTH 525 WEST JEFFERSON STREET SPRINGFIELD, ILLINOIS 62761

RETURN ALL COPIES TO IDPH OR LOCAL HEALTH DEPARTMENT

TYPE OR PRESS FIRMLY

22 MW 010S

1. NTC 2.	Ownership (Name of Controlling Party) UNITED GRENT LAKES NW COENER Well Location: FRIER BLDG 105 SAN PSON Address - Lot Number	FORTER C	1 .	County
	General Description: Township 44 (S)	Range 12		Section 4
3.	Year Drilled 2003	HOFTHING. EASTING	Qua 2,057,36 1,117,75	19.8°
4. 5.		ther		
6.	Total Depth 35 FEET Diameter(i	nches) 8/4 * \$	OFEHOLE -	21 war PMC
7.	Formation clear of obstructionYes	_No		
8.	DETAILS OF PLUGGING		4 -	
	Filled with CENCUT. PENTOPITE SWEY (cement or other materials)	from_ <u>35.0</u>	to <u>SuPfM</u>	<u>Ca.</u>
	Kind of plug	from	to	ft.
	Filled with	from	to	ft.
	Kind of plug	_from	to	ft.
	Filled with	from	to	ñ.
	Kind of plug	from	_to	_n.
9.	CASING RECORD: Upper 3 feet of casing removed	Yes	No	
10.	Date well was sealed: Month APPIL Day 2	27' Year	2006_	
11,	Licensed water well driller or other person approved by NEIL WIKTOR TIL ASSOCIATES Name	the Department p		sealing.
	1915 N.12TH ST.	City	<u></u>	of 43624 State/Zip

ILLINOIS DEPARTMENT OF PUBLIC HEALTH DIVISION OF ENVIRONMENTAL HEALTH 525 WEST JEFFERSON STREET

SPRINGFIELD, ILLINOIS 62761

RETURN ALL COPIES TO IDPH OR LOCAL HEALTH DEPARTMENT

TYPE OR PRESS FIRMLY

22 MW 065

3	
1. 2.	Ownership (Name of Controlling Party) UNITED STATES NAVY NTC GREAT LAKES Well Location: FRMER BLOG 105 SAMPSON ST. & PORTER GREAT LAKES Address - Lot Number Ave. City County
	General Description: Township 44 (NS) Range 12 (W) Section 4
	Quarter of the Quarter of the Quarter ELEVATION
3.	Year Drilled 2003 NoRTHING 2,057, 364.69 649.5
4.	Drilling Permit Number (and date, if known) NA EASTING 1, 117, 751.78
5 .	Type of Well: Bored Drilled Other
6.	Total Depth 24 FEET Diameter (inches) 814 PORCHOLE 21NCH TYC
7.	Formation clear of obstruction Yes No
8.	DETAILS OF PLUGGING
	Filled with CEMENT. BENTON THE SUPPLY from 24.0 to SWEENCE (cement or other materials)
	Kind of plugtotott.
	Filled withtott.
	Kind of plug to tt.
	Filled withtott.
	Kind of plug from to ft.
9.	CASING RECORD: Upper 3 feet of casing removedYesNo
10.	Date well was sealed: Month ATRIL Day 27 Year 2006.
l£.	Licensed water well driller or other person approved by the Department performing well sealing. NEIL WIFTOR TIL ASSOCIATES, INC. Name Complete License Number
	The state of the s
	Address City State/Zip

APPENDIX C

WASTE DISPOSAL DOCUMENTATION

P.O. BOX 19276

SPRINGFIELD, ILLINOIS 62794-9276 (217) 782-6761 LPC 62 8/81

IL532-0610

3542441935423 DR SHIPMENT OF HAZARDOUS AND SPECIAL WASTE

PLEASE TYPE (Form designed for use on elite (12-pitch) typewriter.) EPA Form 8700-22 (Rev. 6-89) Form Approved. OMB No. 2050-0039 UNIFORM HAZARDOUS 1. Generator's US EPA ID No. Manifesi Information in the shaded areas is not required by Federal law, but is required by Illinois law. WASTE MANIFEST IL7170024577 3. Generator's Name and Mailing Address Location If Different A. Illinois Manifest Document Number 11486 ACOS INSTALLATION AND ENVIRONMENT IL10823272 201 DECATUR AVE IF APPLICABLE GREAT LAKES, IL 60088
4. 24 HOUR EMERGENCY AND SPILL ASSISTANCE NUMBERS B. Generator's IL ID Number 10 (847) 688 -4820 5. Transporter 1 Company Name Transporter's ID Number UPW-0446276-OH US EPA ID Number POLLUTION CONTROL INDUSTRIES IND000646943 Transporter's Phone Q19)397-3951 7. Transporter 2 Company Name 8 US EPA ID Number Transporter's ID Number 9. Designated Facility Name and Site Address 10. US EPA ID Number F. Transporter's Phone (POLLUTION CONTROL INDUSTRIES 4343 KENNEDY AVE G. Facility's IL ID Number EAST CHICAGO, IN 46312 IND000646943 H. Facility's Phone (219) 11. US DOT Description (Including Proper Shipping Name, Hazard Class, and ID Number) 397-3951 Ç, 12. Containers 14. Unit źn•ie6ieur, Waste No Quantity Type WIMA WASTE, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, EPA HW Numbi N.O.S., 9, UN3082, PGIII (LABPACK) ERG#171 Ε 0.0.1 D.M 0,0,1,2,0 F 0 0 2 h N esuponse EPA HW Number Ε R C. A EPA HW Number at 217 / 782-7860 0 ď. R EPA HW Number J. Additional Description for Materials Listed Above K. Handling Codes for Wastes Listed Above in Item #14 9: Kd a) ZF the S01 National Hesponse C# E06/01 15. Special Handling Instructions and Additional Information a) E06101-1 (1x55DM) P.O.C. Mr. Mark S. Hoyeer COD Due to Mark S. Hoyeer within 45 days Transporter Offered Placards (Driver's Int 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator. I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford. Center 2: Printed /Typed Name 800 Day DRF 021006 17. Transporter 1 Acknowledgement of Receipt of Materials Printed /Typed Name Date Signature Day Year nathley nodge 18. Transporter 2 Acknowledgement of Receipt of Materials 021006 Printed /Typed Name Date Q Signature Month Day 202 19. Discrepancy Indication Space 20. Facility Owner or Operator: Certification of receipt of hazardous materials covered by this manifest except as noted in item 19. Printed /Typed Name This Agency is authorized to require, pursuant to Illinois Revised Statute, 1989. Chapter 11: 1/2, Section 1091 and 1021, that this information be submitted to the Agency. Faith in a civil penalty against the owner or operator not to exceed \$25,000 per day of violation. Falsification of this information may result in a fine upper day of violation und imprisonment up to 5 years. This form has been approved by the Forms Management Center. 100



Certificate

This certificate is to verify that the waste specified will be handled in accordance with all local, state, and federal regulations

Manifest:

IL10823272

Generator:

ACOS INSTALLATION AND ENVIRONMENT

Page/Line

Waste Stream

PCI H CODE

1 A

ZF

H061

Facility Name:

Pollution Control Industries

Facility Address:

4343 Kennedy Avenue

1

East Chicago, IN 46312

Facility EPA ID:

IND000646943

Signature:

Typed:

Tita LaGrimas

Title:

Executive Vice President of Regulatory Affairs

Date:

3/8/2006

Invoice #:

10071134

4343 Kennedy Avenue, East Chicago, IN 46312 (219) 397-3951 FAX: (219) 397-6411 www.pollutioncontrol.com RESPONSIBLES

RECYCLING

A commitment to our generators, our confirment, and our committee.



IL532-0610

<u>-</u>

THE CO

State Form LPC 62 8/81

PLEASE TYPE (Form designed for use on elite (12-pitch) typewriter.) EPA Form 8700-22 (Rev. 6-89) Form Approved, OMB No. 2050-0039 UNIFORM HAZARDOUS 1. Generator's US EPA ID No. Manifest Document No. Information in the shaded areas is not required by Federal law, but is required by Illinois law. **WASTE MANIFEST** IL7170024577 of 1 3. Generator's Name and Mailing Address Location if Different A. Illinois Ma Acos Installation and Environment IL11856884 FEE PAID 201 Decatur Ave. B. Generator's IL 4. *24 Gourather Total Korsind John Robers Numbers . ID Number | 0 | 9 | 71 | 21 55 | 00 5 847-688-4820 Transporter's ID Number 5. Transporter 1 Company Name US EPA ID Number UPW-0446276-OH D. Transporter's Phone (219) 397-IND000646943 Pollution Control Industries
7. Transporter 2 Company Name 8. US EPA ID Number E. Transporter's ID Number 9. Designated Facility Name and Site Address F. Transporter's Phone (US EPA ID Number Pollution Control Industries G. Facility's IL ID Number CIIICA 4343 Kennedy Ave East Chicago, IN 46312 H. Facility's Phone (IND000646943 219 397-3951 \mathbf{c} 11. US DOT Description (Including Proper Shipping Name, Hazard Class, and ID Number) 12. Containers 13 14. Unit Enleigency response Total Waste No. No. Туре Quantity Wt/Vo RQ(F002), Hazardous Waste, Solid, n.o.s. EPAHW Number E (Tetrachloroethylene, Trichloroethane), 9, NA3077, PGII F002 h. EPA HW Number R Α т o C. EPA HW Number ਕਾ 21777850 and the National Response P d. EPA HW Number Sec. 19. 1 J. Additional Description for Materials Listed Above K. Handling Codes for Wastes Listed Above in Item #14 Asia en bioxida A. 307200, contaminated soil, ERG 171 A) SO2. State of all sylve 15. Special Handling Instructions and Additional Information 24 Hour Emergency P.O.C Mr. Mark S. Hoyer Response: 847-688-4820 C.O.D. Due to Mr. Mark S. Hoyer within 45 days Transporter Offered Placards(Drivers Initials, 16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations.) Center If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford.

Date Date 앒 Printed/Typed Name Year Month Day Signature 800/424-8802 <u>Abbate</u> 050906 17. Transporter 1 Acknowledgement of Receipt of Materials Date Printed/Typed Name Day Sionature Dalle 155090F 18. Transporter 2 Acknowledgement of Receipt of Materials Date Q Printed/Typed Name Signature Month Day 202 19. Discrepancy Indication Space 426-2675 20. Facility Owner or Operator: Certification of receipt of hazardous materials covered by this manifest except as noted in item 19. Date Printed/Typed Name

be submitted to the A

This Agency is authorized to require, pursuant to litinois Revised Statute, 1989. Chacter 111 1/2, Section this information may result in a civil penalty against the owner or operator not to exceed \$25,000 per per day of violation and imprisonment up to 5 years. This form has been approved by the Forms Management Center.

8364244/8364234

Please print or type. (Form designed for use on elite (12-pitch) typewriter.) Form Approved. OMB No. 2050-0039 UNIFORM HAZARDOUS 1. Generator ID Number. 4. Manifest Tracking Number 2. Page 1 of 3. Emergency Response Phone 000602005 **JJK** WASTE MANIFEST 1 847-688-4820 IL7170024577 5. Generator's Name and Mailing Address Generator's Site Address (if different than mailing address) ACOS Installation and Environment 201 Decatur Ave. Generat: Lakes, IL 60038 ILS EPAID Number 6. Transporter 1 Company Name IND000646943 Pollution Control Industries U.S. EPA ID Number 7. Transporter 2 Company Name U.S. EPA ID Number 8. Designated Facility Name and Site Address Pollution Control Industries 4343 Kennedy Ave. IND000646943 Facility anside: Chicago, IN 46312 (800 - 388 - 7242)10. Containers 9b. U.S. DOT Description (including Proper Shipping Name, Hazard Class, ID Number, 11. Total 13. Waste Codes and Packing Group (if any)) Quantity Wt./Vol. No. Type RQ, (F002), Hazardous Waste Solid, N.O.S F002 GENERATOR (Tetrachloroethylene, Trichloroethane), D)M 10 9,NA3077, PGII none Non-RCRA, Non-DOT Regulated (Cooling Tower Water) 14. Special Handling Instructions and Additional Information
1.) 307200, Contaminated Soil, ERG. 171
2.) 289456, Cooling Tower Water P.O.C. Mr. Mark S. Hoyer C.O.D. due to Mr. Mark Transporter offered Placards (Driver Initials___) Hoyer within 45 days

15. GENERATOR'S/OFFEROR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by the proper shipping name, and are classified, packaged, marked and labeled/blacarded and are in all properts in proper shipping name, and are classified, packaged, marked and labeled/placarded, and are in all respects in proper condition for transport according to applicable international and national governmental regulations. If export shipment and Exporter, I certify that the contents of this consignment conform to the terms of the attached EPA Acknowledgment of Consent I certify that the waste minimization statement identified in 40 CFR 262.27(a) (if I am a large quantity generator) or (b) (if I am a small quantity generator) is true. Generator's/Offeror's Printed/Typed Name MAP Port of entry/exit Import to U.S. Date leaving U.S. Transporter signature (for exports only): 17. Transporter Acknowledgment of Receipt of Materials Transporter 1 Printed Typed Name 07 03 asili Transporter 2 Printed/Typed Name 18. Discrepancy 18a. Discrepancy Indication Space Туре ___ Residue Partial Rejection Full Rejection Quantity Manifest Reference Number: U.S. EPA ID Number 18b. Alternate Facility (or Generator) Facility's Phone: Year 18c. Signature of Alternate Facility (or Generator) 19, Hazardous Waste Report Management Method Codes (i.e., codes for hazardous waste treatment, disposal, and recycling systems) 20. Designated Facility Owner or Operator: Certification of receipt of hazardous materials covered by the manifest except as noted in Item 18a Printed/Typed Name EPA Form 8700-22 (Rev. 3-05) Previous editions are obsolete.



Certificate

This certificate is to verify that the waste specified will be handled in accordance with all local, state, and federal regulations

Manifest:

000602005JJK

Generator:

ACOS INSTALLATION AND ENVIRONMENT

Page/Line Waste Stream PCI H CODE 1 1 307200 H141

1 2 289456

NA

Facility Name:

Pollution Control Industries

Facility Address: 4343 Kennedy Avenue

East Chicago, IN 46312

Facility EPA ID:

IND000646943

Signature:

Tita LaGrimas

Typed: Title:

Executive Vice President of Regulatory Affairs

Date:

3/22/2007

Invoice #:

10081877



APPENDIX D

FIELD LOG SHEETS

NOVEMBER 2005



Tetra Tech NUS, Inc.

GROUNDWATER LEVEL MEASUREMENT SHEET

Project Name: Location: Weather Condition	3	GREAT	177		Project No.: Personnel: Measuring Dev	00202 CTO 0000 Teff Service: M-Scope	
Well or Piezometer Number	Date :	Time	Elevation of Reference Point (feet)*	(feet)*	Water Level Indicator Reading (feet)*	Groundwater Elevation (feet)*	Comments
NTC92MW01S	11-20-0	18:18		Not A.	ccessible (water filling	the well
NTC MW02S	M-21-0	12:00)		7,20	out)
NTCXMW03S	11-20-6	5 7:3	7		6.42	PID=	0.0 ppm
NTCOMMW04S	11-20-0	5 (7:	48		2.17	plug of	of riser
NTC92MW05S	11-20-0	510:1	5		6.08	PID=	0.0 pm
NTCDAMW06S	11-20-0	PS 15	-22		5.53	PID:	68.7 pp
ZZ NTCXMW07S	11-21-6	5 11:	45		7.07	PID=	0,0
NTCX/MW07D		Not	,	la (sa	e below)	
NTC MW08S	11-20-0	5 18:0	2		5.13	PID:	0,0 ppm
NTC) MW09S			Accessi	ble (se	e below		(/
NTCXXWW10S	11-20-0	5 138	55		5.13	PIS) = 0,0 pm
NTCDAMW10D	11-20-0	5 1281			5.15	PI	D = 0,0 pp
							0
NTC22MWO	5 11-2	11:15			4,44	of well	box with
						peristal t	ic pump
						cleaned	
						paper to	J-plue
						wdo re	moved
MW095	£11	ed w	the mend	and	coment i	pto sic	6 01
	Tolug				n it out		
	to 5	afel			plug. N		e cleaned
	out.	more	thoron	phys			
MW07	well	box i	s filled u	rith u	et stick	y benton	ite clay.
0	lay p			1	xpanded	and pur	shed up
	into o	vell			be thor	oughly	cleaned
* All measurements to the neare All wells	est 0.01 foot 6 need	new-	J-plugs	-plug	tocks.	red Pag	e of

1	71	<u> </u>	·	Tash	MHC	1
	Tt	5)'	etra	i ecn	NUS,	inc.

LOW FLOW PURGE DATA SHEET

PROJECT SITE NAME: PROJECT NUMBER:

NAVAL STATION GREAT LAKES

00202 CTO 0009 (CLEAN IV)

WELL ID.:

NTC 22 MW 055

DATE: 11/20/05

Time	Water Level	Volume	Flowrate	рН	Cond.	Turb,	DO	Temp.	ORP	_
(Hrs.)	(Ft. below TOC)	710-5		-				•		Comments
		(gal/L)	(mL/min)	(S.U.)	(mS/cm)	(NTU)	(mg/L)	(Celsius)	(mV)	
10:35	6,20									PID=0.0
10:44	5turted p	unpor	2	1.6/1	0.000	// -	-			when well
	1.14	10	200 1	6077	2.829		0.53	17.83	+32.3	opened
10:55	· .		230 m4	win 6.98	7.811	21	0.46	17.69	-22.5	turned down
11.01			1//0	- ,						purping rate
11:01			140 m	min				19.00	14.5	
11:07	- 70		150	7,01	2.811]3	0.53	17.37	-42.6	*
11:15	7.79			7.04	2.800		0.52	17.26	-49.3	
11:20	4		150	7.04	2.795	#_	0.52	17.29	-54,2	water
11:24	7.91			7.04	7.791		0.53		-56,4	has
11:30	0 00		/500	7.06	2.791		0.53		-56.4	Some
11:33	<u>ૄૄ</u> જુ		120	7.06	2.789	- 60 -	0,52	17.34	-54,8	orange
11.38	8,20		150	7.07	2.785	9.0	0.46	17,27		iron
11:40				7.07	2.782		0.47	17,27	-59.5	floc in
11:45						`				<i>i</i> ×
41.43	pump o			-						
			- 1	1						
			mped					<u> </u>		
		≈ 3 Ug	allons		-					
					,	_				
							Į l			

SIGNATURE(S): Jeff Schubert

19 feet of Jubing in well

PAGE_/OF/



GROUNDWATER SAMPLE LOG SHEET

Page___of__l

Project Site Name: Project No.: [] Domestic Well Data [x] Monitoring Well Data [] Other Well Type: [] QA Sample Type:				REAT LAKES	Sample ID No.: NTC 22 MW Sample Location: NTC 22 MW Sampled By: Teff Sc C.O.C. No.: 245 25 Type of Sample: [x] Low Concentration [] High Concentration			MW05S Schubert
SAMPLING DATA:								
Date: 11-20-05	Color	рН	s.c.	Temp.	Turbidity	DO	ORP	ODOR
Time: 11:40	Visual	Standard		°C .	NTU	mg/l		
Method: Low flow	Small Of Ivou f	7.07	2.782	17.27	9.0	0.47	-59,5	none.
			1		r			
Date: 11-20-05	Volume	pН	S.C.	Temp. (C)	Turbidity	DO	ORP_	Flow Rate
Method: Low Flow Per	istaltic	pur	P					
Monitor Reading (ppm): 0.0		<u> </u>	V					
Well Casing Diameter & Material								
Type: 2" PVC						l		
Total Well Depth (TD): 24.0								-
Static Water Level (WL): 6.20								
One Casing Volume(gal/L):			7					
Start Purge (hrs): 10544								-
End Purge (hrs): 1:45								
Total Purge Time (min): 61								
Total Vol. Purged (Ga)/L): ~3								
SAMPLE COLLEGION INFORMA	TON:							
Analysis		Preser	vative		Container Re	quirements		Collected
VOCS 8260 B		1	ICI	3 1		vials	V	29P
· · · · · · · · · · · · · · · · · · ·								
								·
				·				
				<u></u>				
			-					
		-						
		-						
OBSERVATIONS/NOTES:								
Bron flor in a started to class	ground ar uj	water	du	ping	purging	g and	samy	pling;
7 TORRO 1000 C 100	200000000000000000000000000000000000000	Incompany and						
Circle (f Applicable:					Signature(s)			
MS/MSD Duplicate ID No.:			•		Jef	Juny 8	. Sch	best



LOW FLOW PURGE DATA SHEET

PROJECT SITE NAME: PROJECT NUMBER:

NAVAL STATION GREAT LAKES

00202 CTO 0009 (CLEAN IV)

WELL ID .: NTC 22 MW 065

DATE:

Time	Water Level	Volume	Flowrate	рН	Cond.	Turb.	DO	Temp.	ORP	Comments	
(Hrs.)	(Ft. below TOC)	(gal/L)	(mL/min)	(S,U.)	(mS/cm)	(NTU)	(mg/L)	(Celsius)	(mV)		
15118										opened well	
15:22	5.53									1PID=68.7	m
15:25	p	rup 54	auted							1	V''
15:28	<u> </u>	V		7.20	2716	3.7	1.38	16,61	116,8		1
15:31	·	<u> </u>	220							two ned down!	Jun
15:33	7.52		140						1	V	rat
15:35	8 98	<u> </u>		7.21	2.870		0.65	17.46	34,3		1 '
15.36	8.08	<u> </u>									1
15:39		<u> </u>	135			3.7]
15:41			,	7,21	2.850		0.61	17.36	3.4	·	1
15:43	9.04										1
15:49	· · · · · · · · · · · · · · · · · · ·							-			1
15:51			140			2.3					1
15:55	<u> </u>			7.20	2.83		0.55	17,34	-31.8		1
15.57	11,05 12.84						•				1
16:06	12.84			7,20	2,650		0.49	17.15	-50,4		1
16:12	13.76		35			3.8					1
16:15				7,21	2.724		0,50	17100	-54.3		1
16.20				7,22	2,097		0.50	16,82	-53.6		1
16:22	₩,32										1
16126	· · · · · · · · · · · · · · · · · · ·		145	7,22	1.997	6.7	0.48	17.12	-49,5		1
16:30	14.64			7,22	2,058	. /	0,50	17.04	-48.0		1
16:33	• - • -			7,22	21155	6.7	0.53	16,97	-46.8		1
16:37			135	7,20	2,347	5.4	0,60	16.84	-43.6		1
16842	15.10			7/19	2.422		0.60	16.67	-39,0		1
16,47	15.27			7,19	2,444		0.65	16,98	-38.7		1
OOSFI	15,88		140	7.19	2.722	5.3	0.62	17,16	-34.8		1

Tubing placed down to bottom of well at 15:25 to check for DNAPLS. None were defected using small sample and Oil Rad. Tubing was lifted up 5 feet during purging (9'e. intake@19ft bgs).



GROUNDWATER SAMPLE LOG SHEET

Page of Sample ID No.: NTC22MW06902 Project Site Name: NAVAL STATION GREAT LAKES Project No.: 00202 CTO 00009 (CLEAN IV) Sample Location: NTC 22 MW 06 S Sampled By: [] Domestic Well Data C.O.C. No.: [x] Monitoring Well Data Type of Sample: [] Other Well Type: [x] Low Concentration [] QA Sample Type: [] High Concentration SAMPLING DATA: Date: 11-20-05 рΗ Color S.C. **Turbidity** DO ORP ODOR Temp. 17:00 6C Time: Visual Standard mS/cm NTU mg/l Method: Low - Flow clear 7.19 2.725 5,3 0.62 PURGE DATA: 11-20-05 Volume На S.C. Temp. (C) Turbidity ORP Flow Rate Pump Method: Low Flow -19-05 Monitor Reading (ppm): 💪 Well Casing Diameter & Material Туре: 2" PVC Total Well Depth (TD): 24.0 Static Water Level (WL): 5.5 One Casing Volume(gal/L): Start Purge (hrs): 7;00 End Purge (hrs): Total Purge Time (min): Total Vol. Purged (gal/L): ~ 4 gallows SAMPLE COLLECTION INFORMATION Analysis **Preservative Container Requirements** Collected 8260 B Hei 40-mL is sample was checked Signature(s): Circle if Applicable: MS/MSD Duplicate ID No.: NTC 22 FD03



LOW FLOW PURGE DATA SHEET

PROJECT SITE NAME: PROJECT NUMBER:

NAVAL STATION GREAT LAKES

00202 CTO 0009 (CLEAN IV)

WELL ID.: NTC 22 MW 10S DATE: 11-20-05

						1.0		<u> </u>		
Time	Water Level	Volume	Flowrate	рН	Cond.	Turb.	DO	Temp.	ORP	Comments
(Hrs.)	(Ft. below TOC)	(gal/L)	(mL/min)	(3.03)	(mS/cm)	(NTU)	(mg/L)	(Celsius)	(mV)	
13:55	5.13								6000 2000 0000 0000 0000 0000 0000 0000	
14:05	Started	Quan	فيلد							
14:10			140							
14112				7.58	1355	0.60	0.81	16.80	-122.7	
14:15	5.21			7.59	1.353	0,20	0.68	6.83	-129.3	
14:28	5,21		150	7.60	1.353 1.348	0.00	0,52	16.81	-136.7	
14:40	.,			7.59	1342	0.00	0.51		-136,4	
14:43	5.21		140	121	1333		0.5	16.47	136卫	
14846				7,59	1.338		0.5	16,48	-136,4	
W4554	* *			7,59	1.340		0.52	16.59	-136.7	
14:57	5.21		140	7-53	李中	0.00	0.52	16.HS	-136.6	
15:00				7,59	1.340	0,00	0.57	1645	-136,6	
		gallons					,	<u> </u>		
I	· · · · · · · · · · · · · · · · · · ·	total								
			:							·
		·								
		·								
						·	<u> </u>			
		ļ <u> </u>			. ,					
<u> </u>										
<u></u>									<u> </u>	
<u></u>										
			·							
L		·								

PAGE__OF__



GROUNDWATER SAMPLE LOG SHEET

Page___ of ___

Project Site Name: Project No.:				REAT LAKES CLEAN IV)		Location:	NTCZ	22MW 1050 22MW 105 Schubert	
[] Domestic Well Data [x] Monitoring Well Data [] Other Well Type: [] QA Sample Type:					C.O.C. No.: 245252 Type of Sample: [x] Low Concentration [] High Concentration				
SAMPLING DATA:									
Date: 11-20-05	Color	рН	S.C.	Temp.	Turbidity	DO	ORP	ODOR	
Time: 15:00	Visual	Standard		°C	NTU	mg/l	100		
Method: Low Flow	clear	7.59	1.340	16.45	0,00	0.52	-136.6	hone,	
PURGE DATA:							I		
Date: 11-20-05	Volume	pН	s.c.	Temp. (C)	Turbidity	DO	ORP	Flow Rate	
Method: Low Flow f	evista	ltre	rung	<u>, </u>	-				
Monitor Reading (ppm): 0,0			U			·			
Well Casing Diameter & Material									
Type: 2" PVC									
Total Well Depth (TD): 35,0									
Static Water Level (WL): 5.1	3								
One Casing Volume(gal/L):	:			1					
Start Purge (hrs): 4:05									
End Purge (hrs): 15,00									
Total Purge Time (min): 0:55									
	1/2 gal	lores		· · · · · · · · · · · · · · · · · · ·					
SAMPLE GOLLECTION INFORMA									
Analysis		Preserv	vative		Container Re	equirements		Collected	
			vative -{C l	3	Container Ro 40-m L	equirements Llaw	S\	Collected / PS	
Analysis				3		equirements	S		
Analysis				3		equirements	S		
Analysis				3		equirements	S		
Analysis				3		equirements	S		
Analysis				3		equirements	S \ \		
Analysis				3		equirements	S		
Analysis				3		equirements	S		
Analysis			HCI	3		equirements	S \ \		
Analysis			HCI	3		equirements	S		
Analysis VOCs 8260B			HCI	3		equirements	S		
Analysis			HCI	3		equirements	S \		
Analysis VOCs 8260B			HCI	3		equirements	S		
Analysis VOCs 8260B			HCI	3		equirements	S		
Analysis VOCs 8260B			HCI	3		equirements	S \		
Analysis VOCs 8260B			HCI	3		equirements	S		
Analysis VOCs 8260B			HCI	3		equirements	S\		
Analysis VOCs 8260B			HCI	3		equirements	S		
Analysis VOCs 8260B			HCI	3			S		
Analysis VOCS 8260B			HCI	3	40~m L Signature(s));	P. S.d.	J YPS	



LOW FLOW PURGE DATA SHEET

PROJECT SITE NAME: PROJECT NUMBER:

NAVAL STATION GREAT LAKES 00202 CTO 0009 (CLEAN IV)

WELL ID.: NTC 22 MW 10D
DATE: 11-20-05

Time	Water Level	Volume	Flowrate	рН	Cond.	Turb.	DO	Temp.	ORP	Comments
(Hrs.)	(Ftsbelow TOC)	(gal/L)	(mL/min)	(S:U.)	(mS/cm)	(NTU)	(mg/L)	(Celsius)	(mV)	
10.00										
12:08	Z-1,									well opened
12:11	5.15									PID = 0.0
12:26	started p									1310_ 40000
12730	soan a	ungi		7.63	1.326		1.82	16.57	-0.4	
12:32	5.20		150	1100	10000	2.9	1,02	,		
12:36				7.70	1.309	, ,	1.50	16.90	-91.3	Clear
12:40			150	7.67	1,307	1.9	1.09		-105.7	
12:45	5.20									
12:50	5.23		150	7,65	1.304	2.1	0.86	16.87	-116.7	clean
13:04	5,23		150	7.64	1,305	201	0.66	16,97	-122.5	
13:11			150	7.64	1.302	1.8	0.61	17.04	-125,6	
13:16	5.24		1	7.64	1.298		0.57	16.97	-126,9	clear
13:22			150	144	1 39 4	7.8	G-51	16.00	-129	
13:30	5.25	1 2	150	7.64	1,299	1	0,51	16.88	-129-6	
15.31	pung	011								
	, , , , , , , , , , , , , , , , , , ,	<i></i>								
		· · · · · · · · · · · · · · · · · · ·								
	<u> </u>						_	,	-	
							<u> </u>			
							<u> </u>			
							1		<u>l</u>	

PAGE / OF /

38 of turing placed down well search



GROUNDWATER SAMPLE LOG SHEET

Page ___ of ___

[x] Monit [] Other					REAT LAKES	Sample Sample C.O.C. I Type of [x] Lov	Location: d By:	NTC 2: Teff S 245 2! ration	MWIODO 2MW 101 dubert 52
SMEINEDA	TA:								
	0-05	Color	рН	s.c.	Temp. ⁰C	Turbidity	DO	ORP	ODOR
	-flow	Visual Clear	Standard	mS/cm	16.88	NTU /	mg/l 0.51	-129.6	none
PURGE DATA	7-4 10-W	COLOR-	1.67	11.47/	10.00		<i>U</i> , 3	1 ~100	1 10010
	20-05	Volume	рН	s.c.	Temp. (C)	Turbidity	DO	ORP	Flow Rate
		eristal		240	тотпр: (С)	ransiany			
Monitor Reading		31372		T					
	ameter & Material							† · · · · · · · · · · · · · · · · · · ·	
Type: 2" PV0						N .			
Total Well Depti	44								
	vel (WL): 5,15								
One Casing Vol	,								
Start Purge (hrs					•				
End Purge (hrs)							* * * * * * * * * * * * * * * * * * * *		
Total Purge Tim								<u> </u>	
	ed @/L):~3/2								
	ECTION INFORMA	TION:							
	Analysis		Preserv	vative		Container Re	quirements		Collected
VOC	s 8260	B	}	101	3 4	0-mL	vials		/ JPS
									
		, .		*****		-	<u>.</u>	<u></u>	•
					· · · · · · · · · · · · · · · · · · ·				
							 		
							· · · · · · · · · · · · · · · · · · ·		<u> </u>
Ningeria	S/NOTES:								
									•
							•		
٠.									
			•						
Girele III A GGIR	able:					Signature(s)	:		
Circle If Applica MS/MSD	sble: Duplicate ID No.:					Signature(s)	: P	Schul	2 of

Page ____ of ___

		T NAM		NAVAL	STATION C	REA	TLAKES		IBEI	R: NTC22SE		۷ ر	>_	
					TO 0009 (0		NIV)	DATE: GEOLOGIST:		11-17-05			<u> </u>	
		RIG:		Geor	notes / E	-5		DRILLER:		Jeff Sch Josh Du	411	ev	7	
		<u> </u>	1	==			RIAL DESCRIP		7	Jose Da	PID/F	D Pee	dina	(222)
Sample No. and Type or RQD	(Ft.) or	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	Color		assification	U & C & *	Remarks	Sample	Sampler BZ		Driller BZ**
						0	trove de	we point	4-		Π			
	1]		p		halt, gran			1	П		
							nd very	1		<u> </u>	厂	П		
	2			1		20	aterial	<u> </u>	2		\vdash			H
						In	o core	no vecove			_	Н		\vdash
	3					S		vectore	7					
Λ			1				sand, bl	ack cindo	-3		0		-	
	4			4/	· · · · · · · · · · · · · · · · · · ·		sand, bl	aterial			Ĭ			
y			41"/								H	H		
3	5		///		·		soft to	med			lt	H		
1			48"					Tty clay				H		ㅓ
8	6						greenish	my cury		soil sample		\Box		\dashv
1				,			some H.	Jag ,	-	NTC225B20	0		0	
V	7		V				mottle	no brown		-0203	Ĭ	Ĭ	Ť	\dashv
小			Λ					7						
	8						(same	as						コ
رة			#24/	1		×)			П			
199	9		48"					/			V			
3										NTC 225820 -	0	a	0	0
7	10									0506	1			٦
							V							
>	11		V								V			
							11 At bo	Hom of 1	2	-120				ヿ
										0				
	e monit	or reading	leofed	ervals @ bore	Samples		frequency if elevated re	0203 am	1	Drillin Background			C	_ []
Conve	z nted	to Wel	dovs		511 mo	ye	No /	Well I.D		-unes sever	_		,	<u> </u>



PRO	JEC1	T NAMI T NUMI G COMI		00202 C	STATION O TO 0009 (C	CLEA	N IV)	BORING DATE: GEOLO			11-17 Jeff			~ 4		
				Geopro	be/F55	04	nek	DRILLE		,		ua Dr				
Sample No. and Type or RQD	Depth (Ft.) or Run No.	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	Color	ERIAL DESCI	RIPTION al Classification		U s c s +	Rema		PID/FIC	Sampler BZ	Borehole** Buip	Öriller BZ** d
						di	The po	int ar	iven		throng	h	0			
	1				-	2 4	L V	hand a	1	1	. 0	1				
						gr	avel b	sase,	the	<u>.</u>	thron	ngh				
	2	\angle				2	ft of	50ft	- 1		4 .	se)				
		//			-											
	3	\angle				(,	io core	/no						_		╝
							neco	very)							_	
	4							· · · · · · · · · · · · · · · · · · ·							_	_
	14			ļ			almo:	st no	-	_					\dashv	
له	5		1"/				vecor									
8		\angle	36"				cind	ens, ve	ery		· · · · · · · · · · · · · · · · · · ·				_	_
1	6						soft.	nateria	!					_	_	_
\$ /										_				_	_	4
*	7			7'												4
1			1				50ft	to me	بار.	•		<u></u>	0			_
لو	8			,			stiff	clay, 51	/ /y							_
5			37"/				take a	ud gre	onish							
	9		48"			·	gray	")			soil san		Y			
3							wet	<u>-</u>			NTC 22 SE	21020	3	0	의	의
7	10												Ц			_
													\downarrow	_	_	_
V	11		V										الر	\downarrow		_]
	A								A		\setminus /		<u> </u>	\angle		4
	X.		X			\searrow	$\langle \rangle$	/-	X_{\perp}		_X_	X			久	$ \sqrt{} $
								\angle					<u> </u>	Δ		
** Includ	le moni arks:	tor reading	mple -3 for	tervals @ bor	225B21	020 ~a	frequency if elevated 23 colors and No	Coff.	Vell I.D.	<u>ma</u> #:_	Bac terials	Drilling kground			C	<u> </u>



Soft to mad. Stiff NTC225B2104 IT Si thy clan greentsh and stiff NTC225B2104 IT Si thy clan greentsh and stiff NTC225B2104 IT STANDER NTC			NAMI			STATION C			S		NUME	BEF		22.58				
DRILLING RIG: DI Geografia (Control of Control of Contr									-		NOT.		<u> 11-</u>	<u>17-05</u>				
Semple Complete Compl				_				2 V-V	ces									—
Sample No. (Pt.) (DHIL	LING	RIG:	ויוע	<u>Georg</u>						<u>:</u>			Dutto	<u> </u>			
No. (c)				٠,	'		MATE	RIAL D	ESCRIF	PTION					PID/FI	D Rea	ding (ppm)
When rock coring, enter rock brokeness. Brilling Area Brokeness of Coring and Coring a	No. and Type or	(Ft.) or Run	6" or ROD	Recovery / Sample	Change (Depth /Ft.) or Screened	Consistency or			Material C	lassification		s C			Sample	Sampler 82	Borehole**	Driller BZ**
S 38/ Si lty clay greenth and BECASE gray with some NTC22FDOI O M 14 Wet Wet Wet WET Same as IT 48" Son't sample o o o WTC22SB21- O O WTC													colles	fed las				
S 38/ Si lty clay greenth and BECASE gray with some NTC22FDOI O M 14 Wet Wet Wet WET Same as IT 48" Son't sample o o o WTC22SB21- O O WTC	J.	12					50	f4 4	to n	ed, 5th	*		NTC2Z	SB2104				
When rock coting, enter rock brokeness. "When rock coting, enter rock brokeness. "Include monitor reading to Bloot intervals @ borehole. Increase reading frequency if elevated reponse read. Bemarks: 13				384/			51	Hy c	lay		_ 1		and	-05.	40	PP	P	ч
When rock cofing, enter rock tokeness. *When rock cofing, enter rock tokeness. Include monitor reading in 6 foot increase reading frequency if elevated reponse read. Bernarks: PID readings in upper portrism of core 3 Background (ppm): (11-15 th logge were flust-beam 17-40 grams core when	`	13		48'"			gra	4 , u	~ Ath	' /			NTCZ					
When rock coring, enter rock brokeness. *When rock coring, enter rock brokeness. *Include monitor reading in 6 foot intervals @ borshole. Increase reading frequency if elevated reponse read. *Remarks: *PlD reading in foot intervals @ borshole. Increase reading frequency if elevated reponse read. *Beackground (ppm): **Coring a first brokeness. **Coring a first brokeness. **Coring a first rock brokeness.							to	In	mor	Hlvng			, , , ,		0	Ш	_	
When rock coing, enter rock brokeness. Include monitor reading in 6 tool intervals & borehole. Increase reading frequency if elevated reponse read. Remarks: PID cading in graph of core 3 Background (ppm): [III-13 the page) were Heathern 17-40 page in care when	10,5	14	\angle		·			wex							Ц	Ц	_	_
When rock coing, enter rock brokeness. Include monitor reading in 6 tool intervals & borehole. Increase reading frequency if elevated reponse read. Remarks: PID cading in graph of core 3 Background (ppm): [III-13 the page) were Heathern 17-40 page in care when												4			\coprod	\sqcup	_	_
*When rock coring, enter rock brokeness. *Include monitor reading in 6 tool intervals @ borehole. Increase reading frequency if elevated reponse read. *Remarks: PID cading in a paper portion of core 3 Background (ppm): [The 13 the appear portion of core 3 Background (ppm): [The 15 th	Y	15			_							4				Ц	\dashv	_
*When rock coing, enter rock brokeness. *Include monitor reading in 6 tool intervals @ borehole. Increase reading frequency if elevated reponse read. *Remarks: PID cading in graphy and proper portion of core 3 Background (ppm): [The 13 th again were the those in 17 40 ppm. Increase reading frequency if elevated and society and in the proper portion of core 3 Background (ppm): [The 15 th again were the those in 17 40 ppm. Increase reading frequency if elevated and society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and in the proper portion of core when a society and the proper portion of core when a society and the proper portion of core when a society and the proper portion of core when a society and the proper portion of core when a society and the proper portion of core when a society and the proper portion of core	7									_		-			H	\square	\dashv	_
*When rock coring, enter rock brokeness. *Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. *Remarks: PlD reading in mapper portion of core 3 Background (ppm): The standard were place through the standard for some when	\$	16			/			V	A C				·		$oxed{+}$	Н	_	_
*When rock coring, enter rock brokeness. Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Remarks: PD earling in under portion of core 3 Background (ppm): The page were blackfrown in 17-40 pm in core when a great and contains a second contains and contains and contains a second contains and co	2						7	abo	~ >	· · · · · · · · · · · · · · · · · · ·	·				-		\dashv	-
*When rock coring, enter rock brokeness. Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Remarks: PD earling in under portion of core 3 Background (ppm): The page were blackfrown in 17-40 pm in core when a great and contains a second contains and contains and contains a second contains and co	7	1/		48								-			-	Н	\dashv	\dashv
*When rock coring, enter rock brokeness. *Include monitor reading in 8 root intervals @ borehole. Increase reading frequency if elevated reponse read. *Remarks: P D reading in upper portion of core 3 Background (ppm): 11-13 ft again were black from 17-40 spon in care when	7					N		- 	· · · ·			-	·	· ·	1,	H	\dashv	
*When rock coring, enter rock brokeness. *Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. *Remarks: PD reading in a post portion of core 3 Background (ppm): The page of th	\mathbb{H}	18						+				┥	3001 50	ample	V	0	0	d
*When rock coring, enter rock brokeness. *Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. *Remarks: PD reading in appear portron of core 3 Background (ppm): C	V	19						W				\dashv	NTCZ		L	\vdash	\dashv	1
*When rock coring, enter rock brokeness. *Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. *PlD yeading in many portion of core 3 Background (ppm): **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. **Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency in factor							19	Ct 1	41	-11	L	\dashv	•	77.7	Y		\dashv	\dashv
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID reading in upper portion of core 3 Background (ppm): C [11-13 ft bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply collected lat same location as		\dashv				- 5	<i>V</i> /	TV D	0170	//	our	\dashv		,		\Box	十	-
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID reading in upper portion of core 3 Background (ppm): C [11-13 ft bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply collected lat same location as																	寸	\dashv
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID reading in upper portion of core 3 Background (ppm): C [11-13 ft bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply collected lat same location as																	一	7
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID reading in upper portion of core 3 Background (ppm): C [11-13 ft bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply collected lat same location as													:					
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID readings in upper portion of core 3 Background (ppm): C [11-13 ++ bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply colleged lat same location as																	T	
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID reading in upper portion of core 3 Background (ppm): C [11-13 ft bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply collected lat same location as						<i>u</i>												
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID readings in upper portion of core 3 Background (ppm): C [11-13 ++ bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply colleged lat same location as																		
"Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area Remarks: PID reading in upper portion of core 3 Background (ppm): C [11-13 ft bas) were between 17-40 ppm in core when broken 10 pen 3 Field duply collected lat same location as														. 1				
Converted to Well: Yes / No Well I.D. #: WTC 225B 2104	** Includ Rema	le monit arks:	P I	g in 6 foot into D ye 3 H			Pla	er p		7-40 Planted	cor Port ell I.D.	e	x cor	ackground <u>whe</u>	(ppr	m):[10	



_		•				=	50111110	<u> </u>							
		NAM			STATION C					3ER	: NTC ZZSB		<u>'_</u>		
		NUM			TO 0009 (C			DATE			11-17-05				
			PANY:		Field				LOGIST:		J. Schul	سع	4	-	
DHI	LING	HIG:	DPT	Geor	robe/F	-55	0 truck	DRILI	_EK:		J. Duty	77 ×	<u>1</u>		
		l				MATE	RIAL DESC	RIPTION				PID/FI	D Read	ding (ppm)
Sample No. and Type o	(Ft.) or	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	Color	Materi	al Classificati	on	N 0 0 0 +	Remarks	Sample	Sampler BZ	Borehole**	Driller BZ**
-				<u> </u>							· · · · · · · · · · · · · · · · · · ·				
<u> </u>		$\overline{}$						· · · · · · · · · · · · · · · · · · ·				╁	H	\dashv	
							drive	posh	<u>t </u>			┼	╁┼┤	\dashv	
					·		drive	i the	rongh		·	↓_	Ш		<u> </u>
	2	/_					about	3 H	- 0				Ш		
							of har	d asb	halt					.]	
	3						gravel	and	1 /					\Box	
							possible	y conc	refe			Т	П		
	4													コ	
			· , · · · · · · · · · · · · · · · · · ·				then	sush	ed				П		
	5						down	thro	ngh				П	コ	
							4 Lee	+ 2	soft						
	6						fill m	aterto	el		· · · · · · · · · · · · · · · · · · ·				
							no core	100							
4	7			>			Lac	overy	′)				П	\Box	
不												0	П		
\sqcap	8						50ft ,	to me	d	٠,		1			
الح							SHA	silty				П		\Box	
Co	9						clay,	green	rish		soil sample	П			
7:							gray	with	some	-	UTC225B22-	П		丁	
1	10						tan "	nottl	ling		0203	П		П	
1					·		near	400	0			П		T	
V	11				•		w	+ p	lastic			J			
1			^							1				7	
						X						\Box	V		
										コ			7	J	
			r rock broker									-			
		tor reading	g in 6 foot int	ervals @ bor	ehole. Increase	reading SB	frequency if elevated 22023	colle	eted f	100	Drillir Background			C	\sum_{i}
Conv	erted	to Wel		Yes			No	/	Well I D	#					<u> </u>



		NAM			STATION C				MBEF	R: NTC2ZSB		•	
		NUM		00202 C	TO 0009 (C	CLEA	N IV)	DATE:		11-17-05			
DBII	LING	i COM	PANY: (Env.	tield	Sev 10	rvices	GEOLOGIST	:	J Schule			
טאונ	LING	HIG:	Dry	Geor	nobe/		550 truck			Joshua			
Sample No. and Type or RQD	(Ft.) or	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	Galor	ERIAL DESCRIF	PTION assification	U S C S *	Remarks		Sampler BZ Borehole**	
1										·	0		1 1
	12						soft to	med stit	4				
1							0-11 0	y green			HH	\top	+1
6	13						SITY da	y, green	1Xh	· · · · · · · · · · · · · · · · · · ·	+++	+	+
	13						gray u	with some	牛_		╂╂		+
1							tax mo	Afling		soil sample	杯		$oldsymbol{\sqcup}$
X	14		-	<i>;</i>			wet	m		UTC 22 5 B22-	0	0 0	pk
13							nlaco	_		0708	1		
1	15						6				H		\Box
*			_		<u> </u>		prastri		+		H	+	+
H	1,	-							-		╁╂┼		++
	16										14	-	+
<u> </u>		\angle					<u> </u>				0		
8	17									·			1 1
											17	_	П
8	18								1	NTC225B22 -	26	b .c	
m	/ 0									7/12		45	
H									+	and			++
V	19									NTC 22 FD02	19		
								1 1					ألل
						//	TT DOV	tom of					
						-	hole						
			. *								$\vdash \vdash$	+	H
\vdash									+		┝	- 	1
ļI								· · ·	1		-		
					· .			<u> </u>					
	l												
					, .		- <u>- 1,127</u>				\Box	1	
				• •				•	+		\vdash	+	$\dagger \dagger$
*When	rock co	ring, ente	r rock broken	ess.					لــــــــــــــــــــــــــــــــــــــ		Щ		۳
** Includ	le moni	tor reading	g in 6 foot inte	ervals @ bor			frequency if elevated re			Drillin			
Rema	arks: _	fie	ed du	plica		_	2FD02)	collect	<u>ed</u>	Background	* .): <u>[</u>	2
	-	me	asure	A who		322 doe	of 3rd c	PID rea	La.	go of 17-7	=14	15	T+
Conv	erted	to We	ll:	Yes			No	Well I.	D. #:			Las	4

Page ___ of ___

		r nam: r num			STATION C				BEF	1: 7VTC 22 SB	23			
					TO 0009 (C Field Se			DATE: GEOLOGIST:		11-17-05 Jeff Schu	<u></u>	<u></u>		
		RIG:	_,	TGeor	probe/F	-55	O truck	DRILLER:		Joshua D	wt	<u>√</u>		
	T						RIAL DESCRIP		I		_	D Read		ppm)
Samp No. and Type o	(Ft.) or Run	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	Color			U S C S *	Remarks	Sample			Driller 82**
						n	cove d	rove driv	و		0	П		
	1					100	nt down	18 malas	7		1	Ħ	寸	
						10		10 1120			╫╌	\vdash	\dashv	
不	2		1				onel ca	4 1 1 L			╫		7	\exists
			22"/	/		T	orders of	a la uma			╫╴	H	\dashv	
3	3		30"			٠.	Lund b	420					寸	
15						n	aterial a	ase and fill					寸	
T	4		V	4'									\exists	
1			1										丁	
	5						soft to n	edium		Collected Soil samples			\exists	
र			384/					Ly clay			V		T	
3	6		48"				greenish	gray		NTC225B 23016	12	0	0	O
8							plastic				\downarrow			
N	7						σ			NTC225B230	203		0	0
V	8		V					•		·	V			
						8	A potto	m of bor	n c		季			
							,	· · · ·	0					
					·									╝
								, c						
												\perp		
													_	
										-1		\perp	\perp	
L					·		· · · · · · · · · · · · · · · · · · ·						丄	
			r rock broken a in 6 foot inte		hole. Increase	reading	frequency if elevated re	nonse read	i i	Drillin	a Ar	ea.		
Rem	arks:	Sam	ples	NTC	225B29	301	02 and 1	TC225B2	302	203 Background			ح	\sum
50	-	SAK			ill mai	22'		0-32" re		extively, bel	-07	_		
Conv	/erted	to Wel	l:	Yes			No 🚺	Well I.D	. #:					



		NAMI NUM			STATION (BORING NUM DATE:	BEF	11-17-05		4		
		COM		ENT.			rvices	GEOLOGIST:		Jeff Sch	_	se 1	<u>~</u>	
DRIL	LING	RIG:			oprobe		550 truck	DRILLER:		J. Dutto				
Sample No. and Type or RQD	Depth (Ft.) or Run No.	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval		Color	ERIAL DESCRIP Material Cl		U S C S			Sampler BZ Bea	Borehole** bu	Driller BZ*** 3
					no .	con	e, drove d	lrive pool	+		0			
stare >	2		1 18"/		thr gr	ongl nbe	asphalt l base grave black o	and (1/2 ft) , sand						•
8/		\angle					bottom	15 f+						
Y	4		V	44			very sor	t no						
1		\angle	1											
	5							med, stiff		collectedsoil	V			
V			384				silty d	lay,		NTC 22 5 B24 - 0102	0	0	0	<u>o</u>
3	6		48/11				greeni	sk gray,		-0102				
8						·	plasti	_ //			1			
3	7									NTC225B24	0	0	0	0
7			``							0203			-	╝
V	8		Y _							*	1			
						81	bottom	of hole			98			
									·					
	•													
										<u> </u>				
							.						1	
												П	T	1
** Includ	le monit arks: 1	or reading	sles / sted s	tervals @ bore		102	frequency if elevated re AUTC 30-32" No		140	Drillin Background			<u> </u>	
									•					



		NAM			STATION C				BEF	R. NTCZZSE	<u>} </u>	<u>5</u>		
		NUM		00202 C	TO 0009 (C	CLEA	V IV)	DATE:		11-17-05				
			PANY:	Envi	ronnend	al 1	jeld Service	GEOLOGIST:		Jeff Sch	<u>بداهد</u>	<u>* *</u>		
DKIL	LING	RIG:		_ ארי			/F-550 tr			Joshua I	<u> </u>	Ho	7	
Sample No. and Type or RQD	Depth (Ft.) or Run No.	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth /Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	MATE Color	ERIAL DESCRIP	TION .	ມ	Remarks	Sample Sample	Sampler BZ		Driller BZ** 3
3.							pounded	down		used	0			
		/						asphalt		drive		П		
160			1	1-'	1		, 0	ravel/no	1	covery	П	П		
Ø	2		1/2 ft	1 -			aravel	eand			П		\exists	
x			3 H	-	1		black	cinders			Ш		\Box	
7	3		ĺ	1	~	ert	vsoft.	~			П			
						1	recove	ry			П		\exists	
V	4		V	4 ft				1			П			
不			1	XXX			soft to	med.		. 00- 1-1				
	5			**			stiff s	ity clay		soil sample	\mathbf{V}			
[2]			32"/	?			greenish	-grav		NTC225825-	0	0	0	0
उ	6		48"				greenish plastic	0 1		0/02				
3			1								V			
K	7									NTC 225B25	d	0	0	0
V	8		V								V			
		1				R	ft bott	om of						
							hole	U						
										• :				
												┙		
										·				
														·
			r rock broke							5.40				
							frequency if elevated re	<u> </u>		Drillin				$\overline{}$
Rema	ırks:_	<u>δ</u>	ampl		702251	5 6 5	0102 au	18 and 3	0 2	Background Acheo, reso			7	<u>.</u>
		<u>he</u>	low	asphal	t, gras		and fill	material						=
Conv	erted	to We	II:	Yes	-		No /	Well I.D	.#:	•				



Page / of / Sample ID No.: NTC 22 SB 20 02 03 Project Site Name: **NAVAL STATION GREAT LAKES** Sample Location: NTC 22 58 20 Project No.: 00202 CTO 0009 (CLEAN IV) Sampled By: Jeff Schuleer [] Surface Soil C.O.C. No.: 245250 Subsurface Soil [] Sediment Type of Sample: Other: [X] Low Concentration [] QA Sample Type: I High Concentration CHAR SAMPLE DATAS Date: 11-17-05 Depth Color Description (Sand, Silt, Clay, Moisture, etc.) moist -Time: 3 feet bottom of fill soft to med stiff Method: DPT Monitor Reading (ppm): COMPOSITE SAMPLEDATA: Time Depth Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE GOLLECTION INFORMATION: Analysis **Container Requirements** Collected Other &n Core mossture OBSERVATIONS / NOTES: MAP: Circle (Applicable: Signature(s): Jeffrey P. Schubert MS/MSD **Duplicate ID No.:**



Page___ of __

Sampled By: C.O.C. No.: 745250 Sampled By: C.O.C. No.: 745250 Sediment Type of Sample: [X] Low Concentration [High Concentration] Grads Sample Type: [X] Low Concentration [High Concentration] Grads Sampled Data: [High Concentration] Grads Sampled Data: [High Concentration] Grads Sample Type: [X] Low Concentration [High Concentration] Grads Sample Type: [X] Low Concentration [High Concentration] Grads Sample Type: [X] Low Concentration [High Concentration] [High Concen	Project Site Nar		L STATION GREAT L		Sample ID No	.: NTC2	SB20057
Subsurface Soil Sediment Other: Oth	Project No.:	-	02 C1O 0009 (CLEAN	IV)	Sampled By:		
Date: 11-17-05 Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 14:40 5-6 feat below Sthat for wead. Sharp for your Sthat for your state of your state of your state. Monitor Readings (Range in ppm): BRAINFLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B 3 Encore samples TPS Soil moisture. 1 jan TPS OBSERVATIONS / NOTES: Brook for borring location. Signature(s):	Subsurface [] Sediment [] Other:	e Soil			Type of Samp [X] Low Cond	entration	50
Time: 14540 Method: DPT Style Clay mosts to well style to med. Style great to med. St	GEWEENWEEN	A:					
Method: DPT Monitor Reading (ppm): O=O COMPOSITE SAMPLE DATA: Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B 3 Encore Samples / TPS Soil moisture 1 jar / PS Description (Sand, Silt, Clay, Moisture, etc.) MAP: See Field Log Book for borning Location Signature(e):	Date: 11-17-0	5	Depth	Color	Description (Sar	nd, Silt, Clay, Mois	sture, etc.)
Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B SEncore Samples JPS Soft matisture Apple See Field Log Book for borning Location Signature(e):				elow	Silty de	y moi	st to
Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS R260 B 3 Encore Samples TPS Soft unsisture 1 jan JPS See Field Log Book for borning Loration Container Requirements See Field Log Book for borning Loration Signature(s):	Method: DPT		FM (9-10 A	eet bgs)	week so	0 74 to	mag.
Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B 3 Encore Samples / TBS Soil moisture 1 jar / TBS COBSERVATIONS / NOTES: MAP: See Field Log Book for borning Lorarism Signeture(s):					37 H-, 9	remish	gray
Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B 3 Encore Samples JTS Soft moisture 1 jan JPS OBSERVATIONS / NOTES: MAP: See Field Log Book for borning Location Signature(s):	Negopoge as a second a passure a second public		Dth	Colon	Description (Sec	od Silt Clay Mai	eture etc.)
Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B SEncore Samples JPS Soft moisture J jar MAP: See Field Log Book for borring Location Circle 11 Applicable: Signature(s):	Date:	I ime	Deptn	Color	Description (Sar	id, Siit, Clay, Mois	sture, etc.)
SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 82608 SEncore Samples TPS Soil moistme 1 jar TPS OBSERVATIONS! NOTES: MAP: See Field Log Book for borning Location Circle If Applicable: Signature(e):	Method:						
SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B Soil moisture 1 jar VPS OBSERVATIONS / NOTES: MAP: See Field Log Book for borning Location Circle If Applicable: Signature(s):	Monitor Readings						
SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other VOCS 8260 B Soil moisture 1 jar VPS OBSERVATIONS / NOTES: MAP: See Field Log Book for borning Location Circle If Applicable: Signature(s):	i .						
Analysis Container Requirements Collected Other VOCS R260 B SEncore Samples TPS 2011 moristure Location Circle If Applicable: Signature(s):		•		* 1			
Analysis Container Requirements Collected Other VOCS R260 B SEncore Samples TPS 2011 moristure Location Circle If Applicable: Signature(s):						,	
Analysis Container Requirements Collected Other VOCS R260 B SEncore Samples TPS 2011 moristure Location Circle If Applicable: Signature(s):							
VOCS 8260 B Soil moisture 1 jan OBSERVATIONS/NOTES: MAP: See Field Log Book for borning Location Circle If Applicable: Signature(s):	JOHN BEST SAME	ON INFORMAT	ION:				
Soit moisture 1 jan OPS OBSERVATIONS/NOTES: MAP: See Field Log Book for borning Location Circle It Applicable: Signature(s):	B0000000000000000000000000000000000000	Analysis		Container Requ	irements	Collected	Other
Soit moisture 1 jan OPS OBSERVATIONS/NOTES: MAP: See Field Log Book for borning Location Circle It Applicable: Signature(s):						1000	
OBSERVATIONS/NOTES: MAP: See Field Log Book for borning Location Circle If Applicable: Signature(s):	VOCS	8260 B	S :	3 Encore	Samplos	V 1 PS	
See Field Log Book for borning Location Circle If Applicable: Signature(s):	Soil me	nstue.		7 jar		V 1/-3	
See Field Log Book for borning Location Circle If Applicable: Signature(s):					-		
See Field Log Book for borning Location Circle If Applicable: Signature(s):							
See Field Log Book for borning Location Circle If Applicable: Signature(s):	11						
See Field Log Book for borning Location Circle If Applicable: Signature(s):				•			
See Field Log Book for borning Location Circle If Applicable: Signature(s):						·	
See Field Log Book for borning Location Circle If Applicable: Signature(s):		· .					
See Field Log Book for borning Location Circle If Applicable: Signature(s):			<u> </u>	<u> </u>			
See Field Log Book for borning Location Circle If Applicable: Signature(s):					TYTATE:		
Circle If Applicable: Signature(s):					WAL.		
Circle If Applicable: Signature(s):						00 1	
Circle If Applicable: Signature(s):					See 1	field L	-og
Circle If Applicable: Signature(s):					2-1.	La bo	
Circle If Applicable: Signature(s):				4	DOOK	107	
Circle If Applicable: Signature(s):					Vocas	nect	
			•			•	
		**.					
MS/MSD Duplicate ID No.:					_		
	MS/MSD	Duplicate ID	No.:		Jethres	P. Solu	best



Page__/ of __/

Project Site Nai Project No.: [] Surface So Subsurface [] Sediment [] Other: [] QA Sample	ooz oil e Soil	L STATION GREAT L 02 CTO 0009 (CLEAN		Sampled B C.O.C. No. Type of Sa [X] Low C	cation: <u>NTC 2</u> y: <u>Teff 3</u> : <u>245 2</u>	25B210203 25B21 Schuber V.
GMIGMEIM						
Date: 11-17-C	25	Depth C 5	Color	1 / 1	Sand, Silt, Clay, Moi	
Time: 15:15	_	2-3 test	"Il material	Sity	day, mo	ist to
Method: D P S Monitor Reading (ppr	m): <i>O.O</i>	(4-10 fee	t bas)	stiff a	reenish a	rav
COMPOSITE SAMP				1 7 7		
	000000000000000000000000000000000000000	D4h	0-1	l Basariatian	Sand Silt Clay Mai	eture ete \
Date:	Time	Depth	Color	Description	Sand, Silt, Clay, Moi	sture, etc.)
	<u> </u>		<u> </u>	<u> </u>	· · · · · · · · · · · · · · · · · · ·	
Method:						
					· · · · · · · · · · · · · · · · · · ·	
Monitor Readings						
(Range in ppm):			·		·	
,	* .					
Saureelleei	en inizezma	jen:				
	Analysis		Container Req	uirements	Collected	Other
					- A Car	``
VOCS	8260		3 Encor	e samples	VYIS	
5011 V	noistur	۰.	1 jar	0	13/25	
	<u> </u>		U			
1.17 11.1.1						
		 			1111	
Meneral Maren	IOTES:		•	MAP:		
•						
					Field L for bo	~
				See.	Field C	7
1				Book	c for bo	nng
					Loren	
•				1000	A wh	
4 - N					•	
មាក្រខ (Aរបាក្រាប់				Signature(s):		
MS/MSD	Duplicate IE) No ·		1	0 0	
MOIMGU	- Pahiioare Ir			Alhe	y P. Solul	Dent
	· .				/ 1	· - •



Page 1 of 1

Project Site Nam Project No.:	_	STATION GREAT L 2 CTO 0009 (CLEAN		· · · · · · · · · · · · · · · · · · ·	Sample Sample	ID No.:	97C 27	SB2104	05
[] Surface So	 iI		<u> </u>		Sampled C.O.C.	d By: 💃		chuber 50	-
Sediment Other: QA Sample	Type: _					Sample: / Concentra Concentra			
GRAE SAMPLE DAT		Depth	1 (Color	Description	on (Sand, Si	t, Clay, Mois	sture, etc.)	
Time: 15:45 Method: DP 7 Monitor Reading (ppm): 17-40 0	4-5 ft bel	out after	ial p	silty	clay sof	to to	med.	4
COMPOSITE SAMPL		Pm	1		1 V V	2 3471	Y		
Date:	Time	Depth		Color	Description	on (Sand, Si	t, Clay, Mois	sture, etc.)	
Method:									
Monitor Readings									
(Range in ppm):									
SAMPRECORRECTION	NINEORMAU	ēN:							
	Analysis		Co	ntainer Requ	irements	Coll	ected	Other	
VOCS	826	OR	3	Ence	re san	noles	JJP	 	
soil	moiste	ne	1	jar		9	JJP	5	
				<i>Ø</i>			· · · · · · · · · · · · · · · · · · ·		
	·	· · · · · · · · · · · · · · · · · · ·		 			· · · · · · · · ·		
		· · · · ·					· · · · · · · · · · · · · · · · · · ·		
OESERVATIONS/INC)TES)	<u> </u>			MAP:				
						•			
					see	tiel	d Log	Book	
						Ba	1	Book	
	•				401	1307	J	o zamili	
							-		
Circle (f Applicable)					Signature(s)	:			
MS/MSD	Duplicate ID	No.:					<i>Q</i> ,	0	
No	NTO	22 FD	01		YTT	ray r.	الهند	mbert	



Page____ of ___

Project Site Nam Project No.: [] Surface Soi	0020	STATION GREAT LA 2 CTO 0009 (CLEAN		Sample ID N Sample Loca Sampled By: C.O.C. No.:	o.: NTC 22 S tion: NTC 22 Jeff Sc 245 25	SBZL,
Subsurface [] Sediment [] Other: [] QA Sample	Type: _			Type of Sam [X] Low Cor [] High Con	ncentration	
(egas gamenabar	3888888888888888888888888888					<u>.</u>
	25	Depth	Color	Description (Sa	and, Silt, Clay, Moist	
Time: 16:00	2 '	11-12 teat	below	51/4	y clay s	off to
Method: DFY		18 19 6	1-00)	med	, 5000	4 some
Monitor Reading (ppm COMPOSITE SAMPL)		18-17 Feex	694-)	greenism	Will war	30 100
808080800000000000000000000000000000000			.	Description (S	and Silt Clay Mais	(Iro. etc.)
Date:	Time	Depth	Color	Description (S	and, Silt, Clay, Moist	ure, etc.)
Method:				· .		
						·
Monitor Readings						
(Range in ppm):						
(g · pp ·)						
					 	
					<u> </u>	
SAMBLEGOLUEGIG		277				
	199000111000000000000000000000000000000		Container Requ	iromonte	Collected	Other
	Analysis		Container negu	mements	- Compositua	
MOGS	8260 1	3	3 Enlave	· samples	VOPS	
Soil m	275 L.		lian		V JPS	
	<u> </u>					
		*				
			0			
			0			
			0			
			0			
			0			
OBSERVATIONS/INC	DTES:			MAP;		
OBSERVATIONS / NO	DIES:			888388888888888888888888888888888888888	2	
OBSERVATIONS//NO	OTES:			888388888888888888888888888888888888888	Field Log	Book
OBSERVATIONS / NO)II=S:			888388888888888888888888888888888888888	Field Log	Book
OBSERVATIONS / NO	DTES:			888388888888888888888888888888888888888	Field Log	Book con .
OBSERVATIONS/INC	DITES:			888388888888888888888888888888888888888	Field Log oring lo	Book - Estion .
OBSERVATIONS/ NO	DITES:			888388888888888888888888888888888888888	Field Log	Book - zeton .
OBSERVATIONS / NO	DITES:			888388888888888888888888888888888888888	Field Log oning lo	Book - cation .
OBSERVATIONS / NO	DTES:			888388888888888888888888888888888888888	Field Log oring lo	Book - extron.
	DIES:			see f	Field Log oning lo	Book extron.
Circle If Applicable:				See F for b		
	Duplicate ID	No.:		See F for b	Fredd Log oning lo	



Page____ of _____

Project Site Nan	ne: NAV	AL STATION GREAT L		No.: NTC22		203	
Project No.:	00:	202 CTO 0009 (CLEAN	IV)		cation: NTC 27	25B22	
50 (0	••			Sampled B		Schuber	4
[] Surface So	 Cail			C.O.C. No.	2452	50	
Subsurface	2011			Type of Sa	molo:		
Other:				Type of Sal	oncentration		
[] QA Sample	Type		, and the second		oncentration		
l ar cample	турс.			Li riigir o	on contration		
GIFAE SAMPLE DAT	Ą:						
Date: 11-17-05	7	Depth	Color	Description	Sand, Silt, Clay, Moi	sture, etc.)	
Time: 17:00		2-3 ft bel	ow fill and	greeni		try clay	
Method: DPT		cap materio	1 (9-10 ft	with so	me l'ordange	. motory	رُكُ
Monitor Reading (ppm):	10ga_)		soft to m	ed. Stiff U	ver	0
COMPOSITE SAMPL	E DATA:						
Date:	Time	Depth	Color	Description	Sand, Silt, Clay, Moi	sture, etc.)	
					, , <u>, ,</u>	, , , , , ,	
N 4 - 41 - 1 - 1 - 1							
Method:							
Monitor Readings							
(Range in ppm):				l	· · · · · · · · · · · · · · · · · · ·		
SAMPLECOLLECTIO	M INEORMA	TION:					
usidiooddollaacoelladhalaabalaadaaladhala	Analysis		Container Requ	irements T	Collected	Other	
	Allalysis		Container nequ	in enterits	Collected	- Outer	
VACS 9	2260B		3 En Con	e cample	rs UNPS		
Soil m	on3tu	<u>م</u>	1 cmall	screw to	se jar VJJI	PS	
				-			
		-					
OBSERVATIONS / NO	ĴŢĒŚ!			MAP:			
•						· · · · · · · · · · · · · · · · · · ·	
				See	tield L	09	
				R	Field L k for bo		
				Pool	r for bo	7	
				1000	ANON		
		•					
					•		
						.1	
Circle if Applicable:				Signature(s):			
MS/MSD	Duplicate II	D Na.:		0.11	y P. Sche	0 -	
	F			VIn	y 1. orne	voer -	
					7		



Page of

Sample ID No.: NTC22 5B22 0708 Project Site Name: **NAVAL STATION GREAT LAKES** Sample Location: UTC 22 SB 22 Project No.: 00202 CTO 0009 (CLEAN IV) Sampled By: C.O.C. No.: Surface Soil Subsurface Soil [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAS SAMPLE DATAL Description (Sand, Silt, Clay, Moisture, etc.) Color Date: Depth soft to med stiff Time: greenish gray? Method: Monitor Reading (ppm): (elembes ii = s/am: le e/a /au Description (Sand, Silt, Clay, Moisture, etc.) Date: Time Depth Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Analysis Container Requirements** Collected Other 8260 B Vocs En Core samplar moisture OBSERVATIONS / NOTES: MAP: See Field Lo Book for boil Signature(s): eirele il Arrolicable Spry P. Schubert MS/MSD **Duplicate ID No.:**



Page 1 of 1

	AVAL STATION GREAT LAKE 002 <u>02 CTO 0009 (CLEAN IV)</u>	S S	ample ID No.: A ample Location: ampled By: .O.C. No.:	NTC 22 5 B 7 NTC 22 5 I Telf Sele 27 5 2 5	
Subsurface Soil [] Sediment [] Other: [] QA Sample Type:		T	ype of Sample: X] Low Concentr] High Concentr		
GRAB SAMPLE DATA:					
Date: 11-17-05	Depth H-12 Gest la	Color De		ilt, Clay, Moisture, و الم سعول الاستار	
Time: 17:30 Method: DPT	cap and A.V.	materios;	SOFT Si	Ity slay.	
	26 18-19 AT 1	bgs.	vet in los	Alized Fir	tervals,
GOMPOSTESAMBLE OVIAL					
Date: Time	Depth	Color Do	escription (Sand, S	ilt, Clay, Moisture, €	tc.)
Method:			3		
Monitor Readings					
(Range in ppm):					
SVINGREGOUS OF CONTROL	MATIENE				
Analysis		Container Requireme	nts Col	lected Ot	her
100 - 0 - 1			0	000	
VOCS 826	0 13	Encore sa	jar 12	JE (PC)	
3011 1000131		# parice			
		3	plicate a	ntarners	
		~~	2000 -		
		n X	Vested L	- dualiza	Lo
		<u>col</u> Sa	uple NT	- duplice	te 2.
		5a - 6	lected to uple NT add Home		1/e 2. e_
			uples co	el Encor	te 2. For
ODEED/ATIONS / NOTES		M≤	MAISD	el Encor	te 2. For
OBSERVATIONS / NOTES:			MAISD	el Encor	Je 2. Por
		M≤ MAP:	MAISD	el Encor	de 2. Cor
	MSD, and a	M≤ MAP:	AISD	el Encor lla.ted	Je 2. For
MS,	MSD, and a	M≤ MAP: 	cho	el Encor lle ted	te 2. For
MS,	MSD, and a hed from the	M≤ MAP: 	cho	el Encor lle ted	Je 2. For
MS,	MSD, and of ted from the	M≤ MAP: 	cho	el Encor lle ted	te 2. For tron
MS,	MSD, and a hed from the	M≤ MAP: 	cho	el Encor lla.ted	te 2. For ton
MS,	MSD, and a ted from the	MS MAP: Luplicate is soil	cho	el Encor lle ted	Lon Con
MS, colley interv	MSD, and of the form the al	MS MAP: Luplicate is soil	ske Log bonic	el Encor lle ted	



Page__i of __i

Project Site Nam Project No.:		AL STATION GREAT L		Sample Loc	ation: VTC 2	S B 23 0102 25 B 23
Surface Soi Subsurface Sediment Other: QA Sample	Soil		- in _ new _			- Luber V
GENERAMETE DAT	l l					
Date: 11-17-6	5	Depth	Color		Sand, Silt, Clay, Mois	
Time: 13:10	7	0- Feet	11 and cas	soft	To man st	-aray
Method: DPT	١. ٥ ٥	material 1	4-5 ft La	day	Mc mos	1-8
Monitor Reading (ppm COMPOSITE SAMPL		mas - v · · · ·) Jacob	,	
		Domah	Color	Description (Sand, Silt, Clay, Mois	ture etc.)
Date:	Time	Depth	Color	Description	Sand, Sitt, Clay, Mois	ture, etc./
Method:						
Monitor Readings						
(Range in ppm):						
(Hange III ppin).			-		 	
				1		
·	1					
EVW512 COLLECTION	Wikizabila				· · · · · · · · · · · · · · · · · · ·	
	Analysis		Container Req	uirements	Collected	Other
-	Allarysis		Container rioq			
VOCS	826	0 B	3 EXCON	Samples	V3 18.	5
501	moist	me_	1 slast	ic jah	VIYES	
				0		
	·				·	
				-		
			-			
	:					
oreanationem	DIES.			MAlex	_	
					C	ارج
				See	Field Lo	g Wook
					$h = \dots \theta_{\alpha}^{\alpha}$	
				Tor	T KO	
Gircle (Acolicatio				Signature(s):		
MS/MSD	Duplicate I	D No.:		1 000	rey P. Sel	0 0
				1 797	uy 1. Ner	moery



Sample ID No.: NTC 22 SB23 0203 Project Site Name: **NAVAL STATION GREAT LAKES** Sample Location: NTC 22 5 B 23 Project No.: 00202 CTO 0009 (CLEAN IV) Sampled By: C.O.C. No.: [] Surface Soil Subsurface Soil Sediment
 Sediment Type of Sample: [] Other: [X] Low Concentration [] High Concentration [] QA Sample Type: CIFAG SAMPLE DATA: Date: Depth Color Time: Method: Monitor Reading (ppm): O. C COMPOSITE SAMPLE DATA: Date: Time Depth Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Other Collected **Container Requirements** VOCS 8260B moisture OBSERVATIONS/NOTES: MAP: See Field Log Book for boring locations Hoge P. Schubert errole in Associations. Signature(s): MS/MSD **Duplicate ID No.:**



		· · · · · · · · · · · · · · · · · · ·			Page	of	_
Project Site Nar Project No.: [] Surface So	002	AL STATION GREAT 202 CTO 0009 (CLEA		Sample ID Sample Lo Sampled B C.O.C. No.	cation: NTC2 y: Jeff	2 SB 24 C 2 SB 24 5 Schulse	10.
Subsurface Sediment Other: QA Sample	e Soil			Type of Sa [X] Low C			-
GRAG SAMPLE DAT							
	25	Depth	Color	Description	(Sand, Silt, Clay, Mois	ture, etc.)	
Time: 12:30 Method: DPT Monitor Reading (ppn	n): 0, 0	1-2 feet b	alow cap naterials	greenist Soft to	gray Sit	2 Half	
eempesie zwii		U J - P - M	990	1 1 1	per 1		
Date:	Time	Depth	Color	Description	(Sand, Silt, Clay, Mois	ture, etc.)	
Method:							
Monitor Readings (Range in ppm):							: "
(ricange in ppin).							
		1014				-	
	Analysis		Container Requ	irements	Collected	Other	
Vocs	(826 moisfu	oB)	3 Encores	amplers	13 OPS	S	
							
OBSERVATIONS//N	jies -			MAP:			
				See F	held Log	Book	
				Signature(s):	<u> </u>		
MS/MSD	Duplicate ID	No.:		Vff	ey P. Idu	ted	_



Page ___ of ___

Project Site Nam	e: NAVAL	. STATION GREAT L	AKES	Sample ID	No.: NTC 22	25B2402	03
Project No.:	_	02 CTO 0009 (CLEAN		Sample Lo Sampled B	cation: N	chuber	
[] Surface Soil Subsurface				C.O.C. No.	2452	50	
Sediment Other:				Type of Sa	mple: oncentration		
[] QA Sample	Type:			[] High Co	oncentration		
GRAE SAMPLE DATA Date: //- (7-0)	900000000000000000000000000000000000000	Depth	Color	Description	(Sand, Silt, Clay, Moi	eturo eta)	
Time: 12:30		2-3 feet	below fill	green	ish gray	sture, etc.)	
Method: DPT Monitor Reading (ppm)		(6-8 fee	t bas)	med 2	tiff pla	estre	
COMPOSITE SAMPLE Date:	DATA:	Depth	Color	Description (Sand, Silt, Clay, Moi	sture etc.)	
		- John	00101	Description	Cana, Ont, Olay, Mor	stare, etc.)	
Method:							
Monitor Readings							
(Range in ppm):					**************************************		
			:				
SAMPREDORISMO	I VANCESTATE	0)()					
***************************************	Analysis	318000000000000000000000000000000000000	Container Requ	irements	Collected	Other	• •
Vocs	82.60	B	3 Encor	e sampl	ers 3VD	25	
Soil	moist	me	- plast	re jalv		PS	
				·	······································		
					·		
· · · · · · · · · · · · · · · · · · ·							
DESERVATIONS/MO				MAE:			
				000000000000000000000000000000000000000			
				See F	ield Log	Book	
				for b	oning lo	ation	
	·						
ercie (l'Applicable:				Signature(s):	· · · · · · · · · · · · · · · · · · ·		
MS/MSD	Duplicate ID I	No.:			ffrey P. Se	lubert	



NTC225B250102 Project Site Name: Sample ID No.: **NAVAL STATION GREAT LAKES** Sample Location: NTC 22 5 B2 9 Project No.: 00202 CTO 0009 (CLEAN IV) Sampled By: [] Surface Soil C.O.C. No.: Subsurface Soil [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 11-17-05 Depth Description (Sand, Silt, Clay, Moisture, etc.) 11:30 Time: 1-2 feet Method: Monitor Reading (ppm): O, O 5-6 ft COMPOSITE SAMPLE DATA: Date: Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION Analysis **Container Requirements** Collected Other 8260 B En Core Sam lastic OBSERVATIONS/NOTES MAP: See Field Log Book for boring location Circle If Applicable: Signature(s): offrey P. Seluber MS/MSD **Duplicate ID No.:**



NTC225B250203 Project Site Name: Sample ID No .: **NAVAL STATION GREAT LAKES** Project No.: Sample Location: NTC 225B 00202 CTO 0009 (CLEAN IV) Sampled By: [] Surface Soil C.O.C. No.: Subsurface Soil ∏ Sediment Type of Sample: Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 11-17-05 Depth Description (Sand, Silt, Clay, Moisture, etc.) Color 11:40 2-3 feet 1 Time: DPT Method: Monitor Reading (ppm): 0,0 COMPOSITE SAMPLE DATA: Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Other **Analysis Container Requirements** Collected 8260 B ncore OBSERVATIONS / NOTES: Sea Field Log Book for borning location Signature(s): Circle if Applicable: effrey P. Schulet MS/MSD **Duplicate ID No.:**



EQUIPMENT CALIBRATION LOG

PROJECT NAME:	NAVAL	STATION	GREAT	LAKES

INSTRUMENT NAME/MODEL:

Photovac 2020 PD

SITE NAME:

GREAT LAKES

MANUFACTURER:

PhotoVac

PROJECT No.:

00202 CTO 0009 (CLEAN IV)

SERIAL NUMBER:

ED GR 301

Date	Instrument	Person	Instrument Settings	Instrumen	t Readings	Calibration	Remarks
of Calibration	I.D. Number	Performing Calibration	Pre Post- calibration calibratio	Pfe	. Post-	Standard (Lot No.)	and Comments
######################################		Pedalogue para merebera					
11-17-09	EDGR	SOI JPS		99.3	100.0	100 00	m (Lot No. 3695.
8819	Sam				10010	100 pg	isobutylene gas)
							Spec/AN Gases
11-19-05	EDGR:	301 JPS		98.7	100.0	11	& Technologies.
11 20-0	DO am	301 JPS		99.5	100 0	44	Auburn ME
810	20 am	301 413		177.5	100.0	H	
*							
11-21-0	5 9:300 ED GR	am JPS		98.8	100.0	11	
	ED GR	301					
					·		
							
	•						
	h						

	TŁ.	Tetra Tech NUS, Inc.	
1			

DOCUMENTATION OF FIELD CALIBRATION

PROJECT NAME: NAVAL STATION GREAT LAKES

YSI 650 MDS water Quality Meter

SITE NAME:

GREAT LAKES

MANUFACTURER:

PROJECT No.:

00202 CTO 00009 (CLEAN IV)

SERIAL NUMBER:

YSI Soude 0100979 AA Meler 03D0903 AB

Date	Person			L READ					FINA	AL READI	NGS	1		Calibration	Remarks
of Calibration	Performing Calibration	PH	COND	TURB	DO	TEMP	SAL	PH	COND	TURB	DO	TEMP	SAL	Standard (Lot No.)	and Comments
11-20-05	TJB	7.15	1.040	þ	101.1	%		7,00	0.999	P	100%	6/9,2	7 mg	/L D.O.	as estata da a compresenta esta antenda pendenta tras emido establida.
9:00 an	1	3.91						4,00			-		0		
														K	
a Motte															
urbidit Meter	JPS														
				0.0						0.0				Sp. Con	Cal Standard
9530a	n			10.0						10,0				Lot 49	Sal Standard SB Exp. 6-23-0 buffer cal Co.
	<u> </u>													PH 7.0	buffer
		:												Auri	cal Co.
i														LotA	0,5014
					·									-xf.	6. 5014 8-12-2007
														PH 4.0	buffer
					ř									Auric	buffer al Co. Jo. 4804 01-25-2007
														Lot, A	10. 4804
	÷													Exp.	01-25-2007

JULY 2006



Page Project Site Name: NAVAL STATION GREAT LAKES Sample ID No.: N7c225BZ00203R Project No.: Sample Location: NTC22 5B20 112G00202 CTO 0009 Sampled By: MLM [] Surface Soil C.O.C. No.: 3794 [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRIAG SAMELE DATA Date: 7/11/06 Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 0830 SILTY CLAY And SOME 2-31 Method: ENCORE SANd. Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): Sample collection information: Analysis **Container Requirements** Collected Other CVOCS 3 SAMMERCORL MOISTURE 202 PLASTIC OBSERVATIONS / NOTES: MAP: Circle il Applicable: Signature(s): MS/MSD **Duplicate ID No.:** Mark f. Mengel



Page Project Site Name: NAVAL STATION GREAT LAKES Sample ID No.: NTC 225B200607 R Project No.: 112G00202 CTO 0009 Sample Location: NTC22 5820 Sampled By: MLM [] Surface Soil C.O.C. No.: 3794 [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 7-11-06 Description (Sand, Silt, Clay, Moisture, etc.) Depth Color 0835 Time: SILTY CLAY, GREENISH GREY 1-21 Method: ENCORC soft Monitor Reading (ppm): GOMPOSITE SAMPLE DATA: Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other CUOCS 3 5-9RAM ENCORE MOISTURE Z 02 PLASTIC OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s): Markt Mingl MS/MSD **Duplicate ID No.:**



				Pag	e of
Project Site Name: Project No.: [] Surface Soil Subsurface Site Name:	112G00202 (TION GREAT LAKES CTO 0009	Sample ID Sample Lo Sampled E C.O.C. No	379	1W 05 \$
[] Other: [] QA Sample T	ype:		[X] Low C	Concentration oncentration	
CHARSAMPLE PAIA					
Date: 7-11-06	Depth	Color	Description	(Sand, Silt, Clay, Mo	isture, etc.)
Time: 0900 Method: Encore Monitor Reading (ppm):	0-1		SILTY	CLAY, Sof	+
Gombosherawise	PATA				
Date:	Time Depth	Color	Description	(Sand, Silt, Clay, Mo	sture, etc.)
Method:					
Monitor Readings					
(Range in ppm):				·	
SAMPLE (POLLET PION	INFORMATION:				
	nalysis	Container Requ		Collected	Other
CUOCS	· · · · · · · · · · · · · · · · · · ·	3 5-9RAM		<u> </u>	
MOISTULE		Zoz PIAST	FIC	<u> </u>	
	 				1
				· ·	
OBSERVATIONS//NOTE			MAP:		
***************************************	000000000000000000000000000000000000000				
				•	
	•				
			*	9 .	
Circle II Applicable:					
			Signature(s):		



			and the second second		Pa	ge of
Project Site Nam Project No.: [] Surface So [] Subsurface [] Sediment [] Other: [] QA Sample	il Soil	NAVAL STATION 112G00202 CTO		Sampled E C.O.C. No Type of Sa [X] Low 0	Docation: 6493 By: 713 373	LM
CEPAS SAMPLE DATE	SKENED EDGESSE SE ERREIGE SKENED FOR FOR FOR					
Date: 7-//- 0		Depth	Color	Description	(Sand, Silt, Clay, M	loisture, etc.)
Time: 093 Method: ENCOR		0-1		SANDY	51LF ,50	MC
Monitor Reading (ppm		0-1		CIAY		
GOMPOSITE SAMPL						
Date:	Time	Depth	Color	Description	(Sand, Silt, Clay, M	loisture, etc.)
Method:						
Monitor Readings						
(Range in ppm):						
(riange in ppin).						
						·
+						
· ·		1 200 1 200			•	
SAM: DE COURSON	i Ningo:ma	ΠON:				
SAMPLE COLLEGIO	000000000000000000000000000000000000000	TION:	Container Regu	irements	Collected	Other
SAMPLE COLLECTION	ON INFORMA Analysis	TION:	Container Requ		Collected	Other
	Analysis	TION:		NLORE		Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
Cuocs	Analysis	TION:	3 SqRAM EI	NLORE	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. Plasti	NLORE 'C	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. Plasti	NLORE	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. Plasti	NLORE 'C	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. Plasti	NLORE 'C	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. Plasti	NLORE 'C	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. PIASTI	NLORE 'C	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. PIASTI	NLORE 'C	<u> </u>	Other
Cuocs	Analysis	TION:	3 Sqram Ex 202. PIASTI	NLORE 'C	<u> </u>	Other
CUOCS	Analysis	TION:	3 Sqram Ex 202. PIASTI	NLORE 'C	<u> </u>	Other
CUOCS MOISTURE	Analysis	TION:	3 Sqram Ex 202. Plasti	MAP:	<u> </u>	Other
CUOCS	Analysis		3 Sqram Ex 202. Plasti	MAP:	<u> </u>	



Page___ of Project Site Name: Sample ID No.: 6195/05\$120203R NAVAL STATION GREAT LAKES Project No.: 112G00202 CTO 0009 Sample Location: 6495/05\$12 Sampled By: MLM [] Surface Soil C.O.C. No.: 3794 ∏ Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAG SAMPLE DATA: Date: 7-11-06 Description (Sand, Silt, Clay, Moisture, etc.) Depth Color 0935 Time: SILTY CLAY, grey in Method: ENCORE 2-3 color, stiff Monitor Reading (ppm): GOMPOSITE SAMPLE DATA: Date: Time Color Description (Sand, Silt, Clay, Moisture, etc.) Depth Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION IN SERVICES BY AMERICAN Analysis Container Requirements Collected Other CUOLS 5-9RAM ENCORE 4 MOISTURE 2 02 PLASTIC OBSERVATIONS/NOTES: MAP: Gice (Avvilcable: Signature(s): MS/MSD **Duplicate ID No.:**



Project Site Name: Project No.: 112G00202 CTO 0009 Surface Soil Surface Soil						га	ge oi
Surface Soil Sediment Type of Sample:		me:			Sample Lo	ocation: NTCZ	25815
State Stat	II Surface S	oil		•			
Sediment Type of Sample:					C.O.C. NO).: <i>37</i>	94
Cother: (X) Low Concentration High Concentration Starty ccar, gazensh que; Soft Soft Concentration Starty ccar, gazensh que; Soft Soft Concentration High Concentration Soft High Concentration High Concentration High Concentration High Concentration Soft High Concentration High Concentrat		e Son			Turno of Sa	-mala:	
GRAS SAMPLE DATA: Date: 7-1/-04 Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: ENCORE DATA: Date: 1 Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Monitor Reading (ppm): Date: 1 Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Mothod:							
GRAB SAMPLE DATA Date: 7-1-6C Depth Color Description (Sand, Silt, Clay, Moisture, etc.) SILTY CCAY, 9 Recensh 9 Rey Monitor Readings (Range in ppm): COMPOSITE SAMPLE COLLECTION INFORMATION: Analysis Container Requirements CVOCS 3 5 9 1 9 1		e Type					
Date: 7-1/-64 Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 1010 SILTY CLAY , GREEN'S GREY Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Description (Sand, Silt, Clay, Moisture, etc.) Monitor Readings (Range in ppm): Analysis Container Requirements Collected Other CVOLS 3 5-914m ENCORES L. MOSSTULC 2 02 Plastic L. DESERVATIONS / NOTES: MAP:	l Li wax oump	о туро.			_ u ingire	Oncentration	
Time: /O/O Method: ENCORES Date: Time Dopth Color Description (Sand, Sit, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other C VOCS 3 5-9LAM ENCORES MOSSTULC Collected Other C VOCS 1 5-9LAM ENCORES MAP: DESCRIPTIONS/NOTES: MAP: Signaturs(a): Signaturs(a):	GERAGESAMELE DA	TA:					
Time: /O/O Method: ENCORES Date: Time Dopth Color Description (Sand, Sit, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other C VOCS 3 5-9LAM ENCORES MOSSTULC Collected Other C VOCS 1 5-9LAM ENCORES MAP: DESCRIPTIONS/NOTES: MAP: Signaturs(a): Signaturs(a):	Date: 7-//-0	6	Depth	Color	Description	(Sand, Silt, Clay, M	oisture, etc.)
Method: ENCOR E Monitor Reading (ppm): Dete: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other CVOCS 3 5-9LAM ENCORES MAP: Description (Sand, Silt, Clay, Moisture, etc.) Monitor Readings (Container Requirements Collected Other CVOCS 3 5-9LAM ENCORES MAP: Description (Sand, Silt, Clay, Moisture, etc.) Monitor Readings (Container Requirements Collected Other CVOCS 3 5-9LAM ENCORES MAP: Description (Sand, Silt, Clay, Moisture, etc.)							
Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis C 2 2 Plastic C 3 5- \$LAM Excoll 5 MOP STULE C 3 5- \$LAM Excoll 5 MAP: Color Description (Sand, Silt, Clay, Moisture, etc.) Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements C Collected Other C VOC 5 3 5- \$LAM Excoll 5 MAP: Description (Sand, Silt, Clay, Moisture, etc.)		RE	0-1		SILTY	CLAY, GRO	enish grey
Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): Color Description (Sand, Silt, Clay, Moisture, etc.) SAMPLE COLLECTION INFORMATION: Collected Other CUOCS 3.5-1/Am Encontes MAP: DESCRIPTIONS/NOTES: Signature(s):	Monitor Reading (pp	m):	1		Soft		
Date: Time Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Method:	OOMPOSITE SAMP	LE DATA:					
Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other CVOCS 3 5-9LAM ENCARES MAP: DBSERVATIONS / NOTES: MAP: Signature(s):			B	l .	Ι		
Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other C VOC \$ 3 5-9LAM ENCORE \$ MOSSTULC COSSERVATIONS / NOTES: MAP: Signature(s):	Date.	Time	Depth	Color	Description	(Sand, Silt, Clay, Mo	oisture, etc.)
Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other C VOC \$ 3 5-9LAM ENCORE \$ MOSSTULC COSSERVATIONS / NOTES: MAP: Signature(s):							
Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis CUCS Analysis Container Requirements Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other Collected Other CUCS Analysis Collected Other Co	Method:						
Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis CUCS Analysis Container Requirements Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other Collected Other CUCS Analysis Collected Other Co				, , ===			
Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis CUCS Analysis Container Requirements Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other CUCS Analysis Collected Other Collected Other CUCS Analysis Collected Other Co	Monitor Readings						
SAMPLE COLLECTION INFORMATION: Analysis Container Requirements Collected Other CUOCS 3 5-9LAM ENCORES MAP: OBSERVATIONS / NOTES: MAP: Signature(s):	•	l		 			
Analysis Container Requirements Collected Other CUOCS 3 5-9LAM ENCORES L MOSSTULC 2 02 Plastic L OBSERVATIONS / NOTES: MAP: Signature(s):	(Hange in ppm):						
Analysis Container Requirements Collected Other CUOCS 3 5-9LAM ENCORES L MOSSTULC 2 02 Plastic L OBSERVATIONS / NOTES: MAP: Signature(s):							
Analysis Container Requirements Collected Other CUOCS 3 5-9LAM ENCORES L MOSSTULC 2 02 Plastic L OBSERVATIONS / NOTES: MAP: Signature(s):							
Analysis Container Requirements Collected Other CUOCS 3 5-9LAM ENCORES L MOSSTULC 2 02 Plastic L OBSERVATIONS / NOTES: MAP: Signature(s):		-					
Analysis Container Requirements Collected Other CUOCS 3 5-9LAM ENCORES L MOSSTULC 2 02 Plastic L OBSERVATIONS / NOTES: MAP: Signature(s):	SAMPLE COLLEGI	ON INFORMA	ATION:				
Circle If Applicable: Signature(s):		Analysis		Container Regu	irements	Collected	Other
MAP: Circle If Applicable: Signature(s):	CU						
OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s):							
OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s):				2 02 7.43	,,,,	,	
OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s):							-
OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s):						······································	
Circle If Applicable: Signature(s):							
Circle If Applicable: Signature(s):							
Circle If Applicable: Signature(s):							
Circle If Applicable: Signature(s):							
Circle If Applicable: Signature(s):							<u> </u>
Circle If Applicable: Signature(s):	·						
Circle If Applicable: Signature(s):		<u></u>					-
Circle If Applicable: Signature(s):					l l		
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark J. Mury	individual de la				MAP:		
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1. Mury	A Company				100		
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury							
Circle if Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury							
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury				·	-		*
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mary 2							
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury							
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury							
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury					•		
Circle If Applicable: MS/MSD Duplicate ID No.: Signature(s): Mark 1: Mury			<u> </u>	· .			. [
MS/MSD Duplicate ID No.: Mark 1: Mung	eircle if Applicable:				Signature(s):		
Mark 2: Mings	MS/MSD	Duplicate I	D No.:		200	Im 6	ン .
					/ lork	1. I rings	-



						Page c	of
Project Site Nar Project No.: [] Surface So Sufface So Suff	oil	NAVAL STATION 112G00202 CTO		Sample Lo Sampled I C.O.C. No Type of Sample	o.:	TC22 SB1. MLM 3794	12 R
[] QA Sample	e Type:			[] High C	Concentration		
GIJAE SAMPLE DAI	TA:						
Date: フ-//-	06	Depth	Color	Description	(Sand, Silt, Cla		
Time: JoZ Method: ENG Monitor Reading (ppn	CORE	11-12		CIAY,	some sin	E And	
Gentesuazmi					, , , , , , , , , , , , , , , , , , ,		
Date:	Time	Depth	Color	Description	(Sand, Silt, Cla	ıy, Moisture, e	itc.)
A - A4						·	
Method:	<u> </u>						· · · · · · · · · · · · · · · · · · ·
Monitor Readings						· · · · · · · · · · · · · · · · · · ·	
(Range in ppm):					1		
						<u> </u>	
		l t	•				
S/AMBLE (O) LEGIT	ON INFORMA	TION:					
	Analysis	TON	Container Requ	irements	Collected	Oti	ner
CUO	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
	Analysis	TION:		ENCORCS		Oti	ner
	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
CUO	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
CUO	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
CUO	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
CUO	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
CUO	Analysis	TION:	3 5-6RAM 1	ENCORCS	レ	Oti	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Oti	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Oti	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Ott	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Oti	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Oti	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Ott	her
CUO	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Oti	her
C UO MOIST	Analysis C.s V/L C	TION:	3 5-61AM) 2 02 PIAST	ENCORCS	レ	Oti	her
CUO MOIST	Analysis C.S. U.R. C. DTES:		3 5-61AM) 2 02 PIAST	ENCORCS VC MAP: Signature(s):			her
MOIST	Analysis C.s V/L C		3 5-61AM) 2 02 PIAST	ENCORCS VC MAP: Signature(s):	レ		her



						Page	_ of
Project Site Name: Project No.: [] Surface Soil [] Sediment [] Other: [] QA Sample Type:		NAVAL STATION 112G00202 CTO		Sample ID N Sample Loca Sampled By: C.O.C. No.: Type of Sam [X] Low Cor	ation: NTC 22 at	5 B 2 MW/01	00708R
GRAB SAMPLE DA							
Date: 7-//-		Depth	Color	Description (S	and Silt. Cla	· Moistur	e etc.)
Time: /050 Method: ENCOR Monitor Reading (ppm	0 (E 1):	7-8	00.0.	SILTY CL trace pe	AY, 920		6, 6tv.,
COMPOSITE SAMPL		<u>.</u>	-				
Date:	Time	Depth	Color	Description (S	and, Silt, Clay	, Moistur	e, etc.)
Method:							
Monitor Readings (Range in ppm):							
awine confedit		TION:					
	A	and the second s			•	_	Other
CVC	Analysis		Container Requi	 	Collected		Otner
CVC			3 5-9KAM 1	ENCORC	Collected		Other
	065		3 5-9KAM	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
	065		3 5-9KAM 1	ENCORC	レ		Other
Mois	TURE		3 S-GKAM 1 2 OZ PIAS	ENCORC	レ		Other
MOIS!	OCS TURE		3 5-9KAM 1	ENCORE	レ		Other
MOIS!	OCS TURE	ICATE (NTC	3 5-9KAM 1	ENCORE	レ		Other
MOIS!	OCS TURE	ICATE (NTC	3 5-9KAM 1	ENCORE	レ		Other
MOIS!	OCS TURE	ICATE (NTC	3 5-9KAM 1	ENCORE	レ		Other
MOIS!	OCS TURE	ICATE (NTC	3 5-9KAM 1	ENCORE	レ		
MOIS!	OCS TURE	ICATE (NTC	3 5-9KAM 1	ENCORE	レ		Other
MOIS!	OCS TURE	ICATE (NTC:	3 5-9KAM 2 02 P/A.	ENCORE			



					Г (age 01	
Project Site Name: Project No.:		NAVAL STATIO	N GREAT LAKES	Sample ID I	No.: NTC22/	SB NW1001112 R	
[] Surface Soil M. Subsurface Soil		112000202 010 0009		Sampled By C.O.C. No.:	/: <u>/</u> /	NTL22 MW 10 D MLM 3794	
[] Sediment [] Other:	9 2011			Type of San	nple: oncentration		
[] QA Sample					ncentration		
GRAB SAMPLE DAT Date: 7-//- C		Danah.		I			
Time: //00		Depth	Color		Sand, Silt, Clay, I	· · · · · · · · · · · · · · · · · · ·	
Method: ENCO		11-12		SILTY C	LAY , 91.	4	
Monitor Reading (ppn		201000000000000000000000000000000000000		tight Si	-,	intiffbrinffnikenneoloogoocoocoocoocoo	
COMPOSITE SAMP			1 .	I			
Date:	Time	Depth	Color	Description (S	Sand, Silt, Clay, I	Moisture, etc.)	
Method:							
Monitor Readings				·			
(Range in ppm):		,					
(Hango III ppin).							
				/ 			
SAM: JEE POLLEGIJ		ΠON:					
	Analysis VOC 5		Container Requ		Collected	Other	
	NSTURC		3 5-LLAM ZOZ PIASTIC		<u></u>		
			<u> </u>		*		
	- 						
					<u> </u>		
ORSERVATIONS/AN) (ES			MAP:			
			1.	•			
		18888888188888888888888888888888					
Sircle il Applicable: MS/MSD	Dunlinete !!	D.No.		Signature(s):			
M3/M3D	Duplicate II	J 140.:		Mark	L. Minge		



						age 0i
Project Site Nam Project No.: [] Surface So [] Subsurface [] Sediment [] Other: [] QA Sample	il e Soil	NAVAL STATION 112G00202 CTO		Sample Lo Sampled E C.O.C. No Type of Sa [X] Low C	cation: NTC	5B 2MW0600708R 2ZMW060 MLM 3794
GRAB SAMPLE DAT	A:					
Date: 7-//- 0		Depth	Color	Description	(Sand, Silt, Clay	Moisture, etc.)
Time: //30)					
Method: ENC		7-8	·			enish grey
Monitor Reading (ppm COMPOSITE SAMPL				571	FF	
				I		
Date:	Time	Depth	Color	Description	(Sand, Silt, Clay,	Moisture, etc.)
Method:						· · · · · · · · · · · · · · · · · · ·
Metriod.		 				
Monitor Readings					·	
(Range in ppm):						
(ricange in ppin).						
						
SAMPLE COLLECTIO) N INFORM	TION	<u></u>			
	Analysis		Container Requ	irements	Collected	Other
	OCS		3 5-GRAM		4	
moi	STURE		2 or PIAS	TIC		
	·					
· · · · · · · · · · · · · · · · · · ·					·	
OBSERVATIONS/NO	OTES:			MAP;		
			•	· .		
					÷.	
					٠.	
	•					
Sirce (f Applicable:				Signature(s):		
MS/MSD	Duplicate I	D No.:		m /	1 Mong	
	• 13.33			1 com	n , Jong	



		· · · · · · · · · · · · · · · · · · ·	-			Page	_ of
Project Site Nar Project No.: [] Surface So [] Subsurface [] Sediment [] Other: [] QA Sample	il e Soil	NAVAL STATION 112G00202 CTO		Sample Lo Sampled E C.O.C. No Type of Sa [X] Low O	.:	25B2 225B2 MLM 3794	2 0708 R 22
CHARSAMPUE DAT							
Date: 7-//-		Depth	Color	Description	(Sand, Silt, Cla	y, Moistur	e, etc.)
Time: /2/5 Method: ENCO Monitor Reading (ppm	LE	7-8		SILTY	CLAY 1	wer,	
COMPOSITE SAMPL	E DATIA:						
Date:	Time	Depth	Color	Description	(Sand, Silt, Clay	, Moistur	e, etc.)
Method:							
					<u> </u>		
Monitor Readings (Range in ppm):							
SAMPLE CELLECTION		11(6));	Container Regu	irements	Collected		Other
SAMPLE COLLECTIO	Analysis	TION:	Container Requ		Collected		Other
	Analysis	TION:		ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
CVO	Analysis	TION:	3 SGLAM A	ENCORE	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCOR C	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCORE	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCOR C	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCOR C	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCOR C	Collected		Other
CVO	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCOR C	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A ZOL PIASTI	ENCOR C	Collected		Other
Mois	Analysis OCS TURE	TION:	3 SYLAM A	ENCOR C	Collected		Other



Page_ Project Site Name: NAVAL STATION GREAT LAKES Sample ID No.: NT<22 SB22 1819 R Project No.: 112G00202 CTO 0009 Sample Location: NTC22 5B2Z Sampled By: MLM [] Surface Soil C.O.C. No.: 3794 X Subsurface Soil [] Sediment Type of Sample: ○ Other: [X] Low Concentration [] High Concentration [] QA Sample Type: GRAB SAMPLE DATA: 7-11-04 Date: Depth Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 1300 SILTY CLAY , STIFF 18-19 Method: ENCOLE Monitor Reading (ppm): 9164 COMPOSITE SAMPLE DATA: Date: Time Description (Sand, Silt, Clay, Moisture, etc.) Depth Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other C VOCS 5- GRAM ENCOLL L MOISTURE 2 02 PLASTIC OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s): Mark& rungl MS/MSD **Duplicate ID No.:**



					Pag	je of
Project Site Nan Project No.: [] Surface So Subsurface [] Sediment [] Other: [] QA Sample	il e Soil	NAVAL STATION 112G00202 CTO		Sample ID N Sample Loca Sampled By: C.O.C. No.: Type of Sam [X] Low Cor [] High Cor	ple:	25821
GRAB SAMPLE DAT						
Date: 7//2/6 Time: 08/		Depth	Color		and, Silt, Clay, Mo	
Method: ENCOR		9-10		SILTY CLA	Y, GREYISA	h green,
Monitor Reading (ppm		, ,,	·	STIFF		
GOMPOSITE SAMPL						
Date:	Time	Depth	Color	Description (Sa	and, Silt, Clay, Mo	isture. etc.)
				(, , , , , , , , , , , , , , , , , , ,	
Method:						
Monitor Readings						
(Range in ppm):			**		· .	
(nange in ppin).	 					
					 	
					- <u> </u>	
			· · · · · · · · · · · · · · · · · · ·	i .		*
CV. U.O. E. Dalle Parille	NI NEGOLA	TION:				
		1(e));	Container Regu	irements	Collected	Other
	Analysis	TION:	Container Requ		Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
CV	Analysis	TION:	3 5-gram	ENCOLE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCOLE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
CV	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
Cve	Analysis 2C.5 2STULE	TION:	3 5-GRAM 202 PLAS	ENCORE	Collected	Other
OBSERVATIONS / NO	Analysis 2C.5 2STULE	TION:	3 5-9RAM 202 PLAS	ENCORE TIC	Collected	Other
Cve	Analysis 2C.5 2STULE		3 5-9RAM 202 PLAS	ENCORE TIC MAP: Signature(s):	Collected	



Tetra Tech NUS, Inc. SOIL & SEDIMENT SAMPLE LOG SHEET

Page___ of __

Project Site Nan Project No.: [] Surface So Subsurface Sediment Other: QA Sample	il e Soil	NAVAL STATION 112G00202 CTO		Sample ID No Sample Locat Sampled By: C.O.C. No.: Type of Samp [X] Low Cond	centration	25821
gaesmpe pai	A:					
Date: 7-/2		Depth	Color	Description (Sai	nd, Silt, Clay, Moi	sture, etc.)
Time: 0820 Method: ENCOR		12 111		SILTY CLA	y, greyis.	h green
Method: ENCOR Monitor Reading (ppm		13-14		STIFF		
COMPOSITE SAMPL						
Date:	Time	Depth	Color	Description (Sec	ad Silt Clay Mai	oturo oto \
Date.	111116	Deptit	Color	Description (Sai	nd, Silt, Clay, Moi	stare, etc.)
Method:						
Metriod.						
Monitor Readings	<u> </u>					· · · · · · · · · · · · · · · · · · ·
(Range in ppm):						
						•
					·	
SAMPLE COLLECTION	L Winesella	l Statt				
						I au
	MUSINGIE	· ·	Container Beauti	romente i	Callected	
Cv	Analysis		Container Requi		Collected	Other
	VOC S VSTURC		3 J-9RAM	ENCOLE	 	Otner
	ocs			ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
	ocs		3 J-9RAM	ENCOLE		Other
mo	OCS DISTURC		3 J-9RAM	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
mo	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE		Other
	OCS DISTURC		3 J-GRAM 202 PLA	ENCOLE STIL STIL Signature(s):		
OBSERVATIONS/NO	OCS DISTURC	D No.:	3 J-GRAM 202 PLA	ENCOLE STIL STIL Signature(s):		



Project Site Nar Project No.:	ne:	NAVAL STATION 112G00202 CTO			ocation: NTC 2	
[] Surface Soil ⅓ Subsurface Soil				Sampled B C.O.C. No.		nem
Sediment Other: QA Sample	e Tvpe:				imple: Concentration oncentration	
				_ Uə		
GRAB SAMPLE DAT						
Date: 7-/2- Time: //05		Depth	Color		(Sand, Silt, Clay, Mo	
Method: ENCOR		19-20		31474 (CLAY , bR	ex
Monitor Reading (ppn		d ''			, MOIST	
COMPOSITE SAMPL					<i>,</i>	
Date:	Time	Depth	Color	Description /	(Sand, Silt, Clay, Mo	isture, etc.)
					June, 2,	1000.0, 0,
Method:						
Midd iod.	<u> </u>		 			
Monitor Readings		+	 			
(Range in ppm):	<u> </u>		 	+		
					***************************************	- COOTEN TO THE COOTEN AND THE COOTE
SAMPLE COLLECTION		ATION:			·	
	Analysis		Container Requ		Collected	Other
	CVOCS		3 59 RAM 202 PLA	* ENCORE		
	0/3/42		EUL FEI	3772		-
				- +		
	·					
					· · · · · · · · · · · · · · · · · · ·	+
						1
				·		
ļ.						
ebservations/in		-	_	MAP:		
Collected	duplicat	TC (NTCZZ F	=002)			
PID Reading	gs in	bonehole > 40	20			
PID Reading	15 of 3 7-10 Pi	soil on Angens opm.	After many			
BREATHING.	Zone:	< 1 ppm			<u> </u>	
Pire i Applicable:				Signature(s):		- 1
MS/MSD	Duplicate I	ID No.:		1 7/	Park to Mine	
		NTCZZFL	002	1 / "	Will I I wone	yv -

AUGUST 2006



Page_ of NTC22SB200203R1 Project Site Name: **Naval Station Great Lakes** Sample ID No.: Sample Location: NTC22SB20 112G00202 CTO 0009 Project No.: MLM Sampled By: Il Surface Soil C.O.C. No.: [X] Subsurface Soil [] Sediment Type of Sample: [X] Low Concentration I Other: [] High Concentration [] QA Sample Type: GRAE SAMPLE DATA: Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Date: 8-7-06 Color Time: 1415 2.5-3.5 fine sandy Silty Clay, TRACE grey Method: **Encore®** sand. Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color 8/7/06 Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Collected **Container Requirements** Other **Analysis** Chlorinated VOCs 3 - 5 gram Encore® Moisture 2 oz. plastic OBSERVATIONS / NOTES: MAP: OFFSET APPROXIMATELY I'EAST of PRIOR LOCATION. Circle if Applicable: Signature(s): MS/MSD **Duplicate ID No.:**



Page_ of [NTC22SB151112R1 Sample ID No.: Project Site Name: **Naval Station Great Lakes** Sample Location: NTC22SB15 CTO 0009 Project No.: 112G00202 MLM Sampled By: [] Surface Soil C.O.C. No.: [X] Subsurface Soil [] Sediment Type of Sample: [X] Low Concentration [] Other: | High Concentration [] QA Sample Type: GRAB SAMPLE DATA: Description (Sand, Silt, Clay, Moisture, etc.) Date: 8-7-06 Depth Interval Color Time: 1505 SILTY CLAY gray 11-12 Encore® Method: Monitor Reading (ppm): GOMPOSITE SAMPLE DATA: Description (Sand, Silt, Clay, Moisture, etc.) Date: Time Depth Interval Color Method: **Monitor Readings** (Range in ppm): SAMPLE COLLECTION INFORMATION: **Container Requirements** Collected Other **Analysis** 3 - 5 gram Encore® Chlorinated VOCs 2 oz. plastic Moisture OBSERVATIONS / NOTES: MAP: OFFSET APPROXIMATELY I'WEST OF PRIOR LOCATION. GOT REFUSAL @ 3.51. OFFSET TO Southwat. Signature(s): Circle If Applicable: MS/MSD **Duplicate ID No.:**



of

Page_ NTC22SB210910R1 Project Site Name: **Naval Station Great Lakes** Sample ID No.: Sample Location: NTC22SB21 112G00202 Project No.: CTO 0009 MLM Sampled By: C.O.C. No.: [] Surface Soil [X] Subsurface Soil [] Sediment Type of Sample: [X] Low Concentration [] Other: [] High Concentration [] QA Sample Type: GRAB SAMPLE DATA: 8-7-06 Description (Sand, Silt, Clay, Moisture, etc.) Date: Depth Interval Color Time: 1620 SAND + SILT 9-10 brown Method: **Encore®** Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Description (Sand, Silt, Clay, Moisture, etc.) Date: Time Depth Interval Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Collected Other **Analysis Container Requirements** Chlorinated VOCs 3 - 5 gram Encore® Moisture 2 oz. plastic OBSERVATIONS / NOTES: MAP: MINIMAL RECOVERY. LOCATION WAS 21' WEST of PRIVE Location Circle If Applicable: Signature(s): MS/MSD **Duplicate ID No.:**



Page___ of _ Project Site Name: NTC22SB211314R1 **Naval Station Great Lakes** Sample ID No.: Project No.: Sample Location: NTC22SB21 112G00202 CTO 0009 Sampled By: MLM [] Surface Soil C.O.C. No.: [X] Subsurface Soil [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 8-7-06 Description (Sand, Silt, Clay, Moisture, etc.) Depth Interval Color Time: SICTY C/AY 13-14 grey Method: **Encore®** Monitor Reading (ppm): GOMEOSITE SAMETE DATA Time Description (Sand, Silt, Clay, Moisture, etc.) Date: **Depth Interval** Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Container Requirements** Collected Other Analysis Chlorinated VOCs 3 - 5 gram Encore® -Moisture 2 oz. plastic -OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s): **Duplicate ID No.:** MS/MSD



Page of Project Site Name: NTC22SB191920R1 **Naval Station Great Lakes** Sample ID No.: Sample Location: NTC22SB19 Project No.: 112G00202 CTO 0009 Sampled By: MLM □ Surface Soil C.O.C. No.: [X] Subsurface Soil [] Sediment Type of Sample: [X] Low Concentration [] Other: [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Description (Sand, Silt, Clay, Moisture, etc.) Date: 8-0-06 **Depth Interval** Color Time: 0850 SILTY CLAY, TRACE SAND GREY 19-20 Method: **Encore®** Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Description (Sand, Silt, Clay, Moisture, etc.) **Depth Interval** Date: Time Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other L Chlorinated VOCs 3 - 5 gram Encore® Moisture 2 oz. plastic OBSERVATIONS / NOTES: MAP: Collected deplicate Circle il Applicable: Signature(s): MS/MSD **Duplicate ID No.:** NTCZZ -FOOI



Page

of

Project Site Name: NTC22FD01 **Naval Station Great Lakes** Sample ID No.: Project No.: 112G00202 Sample Location: NTC22FD CTO 0009 Sampled By: MLM Surface Soil C.O.C. No.: [X] Subsurface Soil [] Sediment Type of Sample: Other: [X] Low Concentration [X] QA Sample Type: Field Duplicate [] High Concentration GRAB SAMPLE DATA: Date: 8-8-04 Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color 0000 Time: Method: **Encore®** Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Analysis Container Requirements** Collected Other Chlorinated VOCs 3 - 5 gram Encore® Moisture 2 oz. plastic OBSERVATIONS / NOTES: MAP: DUPLICATE of NTC2ZSB191920R1 Circle if Applicable Signature(s): MS/MSD **Duplicate ID No.:**

SEPTEMBER 2006



Page

of

NTC22SB151112R3 Project Site Name: **NAVAL STATION GREAT LAKES** Sample ID No.: Sample Location: NTC22SB15 112G00202 CTO 009 Project No.: Sampled By: MLM [] Surface Soil C.O.C. No.: Type of Sample: [] Sediment [X] Low Concentration [] Other: [] High Concentration QA Sample Type: GEAG SAMPLE DATAL Description (Sand, Silt, Clay, Moisture, etc.) Date: 9/28/2006 Depth Interval Color Time: 1325 **ENCORE** 11' - 12' Method: Monitor Reading (ppm): e(simijosijie samije bayas Description (Sand, Silt, Clay, Moisture, etc.) Date: Time Depth Interval Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Container Requirements** Collected Other **Analysis CVOCS** (3) 5-GRAM ENCORE 2 OZ. PLASTIC MOISTURE CONTENT OBSERVATIONS / NOTES: MAP Signature(s): Circle if Applicable: MS/MSD **Duplicate ID No.:**



		<u></u>				Page_	of
Project Site Nam Project No.: [] Surface So Subsurface [] Sediment [] Other:	oil e Soil	NAVAL STATION 112G00202 CT	N GREAT LAKES TO 009	Sample ID I Sample Loc Sampled By C.O.C. No.: Type of Sar [X] Low C	cation: 1 y: : : mple: Concentra		
[] QA Sample				[] High Co	ncentrat	ioù	
CIASEANII SIAN					. 211		
Date:	9/28/2006	Depth Interval	Color	Description	Sand, Sin	t, Clay, Moistu	re, etc.)
Time: Method:	1410 ENCORE	10' - 12'			•		. !
Monitor Reading (ppm	n):	i			- <u> </u>		·
COMPOSITE SAMPL							
Date:	Time	Depth Interval	Color	Description (Sand, Silt	t, Clay, Moistu	re, etc.)
		-			-		
Method:		†					7
INOUTION.			†				
Monitor Readings	 						
(Range in ppm):			+		<u></u>		
(hange in ppin).				 			
	 		 	 			
			1				
SAMPLE COLLEGI	L ANIMEGRAT	L STATE					
leab discarda belli se de collisió di collecte colored mello disc	Analysis		Container Requ	uirements	Colle	cted	Other
cvocs	ruin.y		(3) 5-GRAM EN		۷		
MOISTURE CON	TENT		2 OZ. PLASTIC				
							<u> </u>
		<u> </u>					
<u> </u>					<u> </u>		
			<u> </u>				
			-				
OESERVATIONS/N	OTES:			MAPE			
889998888888899999999	200000000000000000000000000000000000000	808088888888888888888888	88888884688846666666	Responses		Attours and a second	
				1			
			, e e e e e e e e e e e e e e e e e e e	1			
			- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1				
			:	1			
			•	1		•	
				l 37			
Gircle (f Acolicable)				Signature(s):			
MS/MSD	Duplicate I	mu.		oldinger -/-/-			
Makian	Dupiloato .	D No	: · · · · · · · · · · · · · · · · · · ·				
í .	1		· · · · · · · · · · · · · · · · · · ·	4			7.8



Page_ of _ Project Site Name: NTC22SB221819R3 NAVAL STATION GREAT LAKES Sample ID No.: Project No.: 112G00202 Sample Location: NTC22SB22 **CTO 009** Sampled By: MLM [] Surface Soil C.O.C. No.: X Subsurface Soil ∏ Sediment Type of Sample: Other: [X] Low Concentration [] High Concentration [] QA Sample Type: GRAB SAMPLE DATA: Date: 9/28/2006 Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Time: 1445 **ENCORE** Method: 18' - 19' Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: eree ranneade Signature(s): MS/MSD **Duplicate ID No.:**



Page NTC22SB200203R2 Project Site Name: NAVAL STATION GREAT LAKES Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: NTC22SB20 Sampled By: MLM Surface Soil C.O.C. No.: 308783 [X] Subsurface Soil Type of Sample: [X] Low Concentration Other: [] QA Sample Type: [] High Concentration GRAÐ SAMPLE DATA: 9-12-06 Description (Sand, Silt, Clay, Moisture, etc.) Date: Depth interval Color 0745 Time: **ENCORE** 2' - 3' Method: Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Time Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other cvocs (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: Signature(s): Circle if Applicable: mark to Mengel MS/MSD **Duplicate ID No.:**



Page Project Site Name: NAVAL STATION GREAT LAKES Sample ID No.: NTC22SB200607R2 Project No.: 112G00202 CTO 009 Sample Location: NTC22SB20 Sampled By: MLM [] Surface Soil C.O.C. No.: 308783 [X] Subsurface Soil [] Sediment Type of Sample: Other: [X] Low Concentration [] High Concentration [] QA Sample Type: GRAB SAMPLE DATA: Date: 9-12-06 Description (Sand, Silt, Clay, Moisture, etc.) Depth Interval Color Time: 0755 **ENCORE** Method: 6' - 7' Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): Pampi e edilection incommation: **Analysis Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE _ MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS/NOTES: MAP: Circle if Applicable: Signature(s): MS/MSD **Duplicate ID No.:** Mark & Mingel



Page of Project Site Name: NTCMW05S0001R2 NAVAL STATION GREAT LAKES Sample ID No .: Sample Location: NTCMW05S Project No.: 112G00202 CTO 009 Sampled By: MLM [] Surface Soil C.O.C. No.: 308783 [X] Subsurface Soil Sediment
 Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 9-12-06 Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) 0815 Time: Method: **ENCORE** 0' - 1' Monitor Reading (ppm): GOMPOSITE SAMPLE DATAS Date: Time Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Analysis Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s): Mark L. Mingel MS/MSD **Duplicate ID No.:**



Page_ of _ GL95105S120001R2 Project Site Name: NAVAL STATION GREAT LAKES Sample ID No.: 112G00202 CTO 009 GL95105S12 Project No.: Sample Location: MLM Sampled By: [] Surface Soil C.O.C. No.: 308783 [X] Subsurface Soil [] Sediment Type of Sample: Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 9-12-06 Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 0845 Method: **ENCORE** 0' - 1' Monitor Reading (ppm): (ete)MEOSTERSAMELER PATA Time Description (Sand, Silt, Clay, Moisture, etc.) Date: **Depth Interval** Color Method: Monitor Readings (Range in ppm): SAMBINE GOUNEGION NESEMATION Analysis **Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: Gircle if Applicable: Signature(s): Mark & Mangel MS/MSD **Duplicate ID No.:**



Project Site Name: NAVAL STATION GREAT LAKES GL95105S120203R2 Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: GL95105S12 MLM Sampled By: Surface Soil C.O.C. No.: 308783 [X] Subsurface Soil [] Sediment Type of Sample: Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 9-12-06 **Depth Interval** Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 6850 Method: **ENCORE** 2' - 3' Monitor Reading (ppm): COMPOSITE SAME E DAYA: Date: Time Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Analysis Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC ___ OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s): MS/MSD Mark L. Mengel **Duplicate ID No.:**



					Pag	je of
Project Site Nam Project No.: [] Surface So [X] Subsurface [] Sediment [] Other: [] QA Sample	il ce Soil	NAVAL STATION 112G00202 CT	I GREAT LAKES TO 009	Sample ID No Sample Loca Sampled By: C.O.C. No.: Type of Samp [X] Low Con [] High Con	ple:	8B150001R2 8B15 8783
GIF/AR SAMPLE DAT	A:					
	7-12-06	Depth Interval	Color	Description (Sa	and, Silt, Clay, Mo	oisture, etc.)
	0910					-
Method:	ENCORE	0' - 1'				
Monitor Reading (ppm						
155555555555555555555555555555555555555		I				
Date:	Time	Depth Interval	Color	Description (Sa	ınd, Silt, Clay, Mo	isture, etc.)
	ļ					
Method:						
	<u> </u>					
Monitor Readings					* v	
(Range in ppm):						
***************************************				010000000000000000000000000000000000000		999090009888999999999999999999
SAMPLEGALLEGIA	ON INFORMA	TON:				
en de santa de la companya de la com	ON INFORMA Analysis	TION:	Container Requi		Collected	Other
CVOCS	Analysis	ITION:	(3) 5-GRAM ENC	CORE	4	Other
en de santa de la companya de la com	Analysis	TION:		CORE		Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENC	CORE	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	C	4	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENC 2 OZ. PLASTI	MAP:	4	Other
CVOCS MOISTURE CON	Analysis		(3) 5-GRAM ENC 2 OZ. PLASTI	CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	4	



Page_ of Project Site Name: NTC22SB151112R2 NAVAL STATION GREAT LAKES Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: NTC22SB15 Sampled By: MLM [] Surface Soil C.O.C. No.: [X] Subsurface Soil Sediment
 Sediment Type of Sample: Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAG SAMPLE DATA: Date: 9-12-06 **Depth Interval** Description (Sand, Silt, Clay, Moisture, etc.) Color 0925 Time: **ENCORE** Method: 11' - 12' Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time **Depth Interval** Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION. Container Requirements Analysis Collected Other CVOCS (3) 5-GRAM ENCORE _ MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: DIO MS/MSD Signature(s): Girce II Atholicables MS/MSD **Duplicate ID No.:** Mark L. Mengel



						Page_	of
Project Site Nam Project No.: [] Surface So [X] Subsurfact [] Sediment [] Other: [] QA Sample	il ce Soil	NAVAL STATION 112G00202 C	I GREAT LAKES TO 009	Sample II Sample Lo Sampled I C.O.C. No Type of Sa [X] Low [] High C	ocation: By: o.: ample: Concent	NTC22MW MLM 308 2	
GEAS SAMPLE DAT	A						
Date: 9	7-12-06	Depth Interval	Color	Description	(Sand, Si	it, Clay, Moist	ıre, etc.)
Time: Method: Monitor Reading (ppm		7' - 8'					
eempesije same	EDATA						
Date:	Time	Depth Interval	Color	Description	(Sand, Si	lt, Clay, Moist	ıre, etc.)
Method:							
Monitor Readings (Range in ppm):							
Sample collection	N INFORMA	TION					,
	Analysis		Container Requ		Coll	ected	Other
cvocs			(3) 5-GRAM EN		۷		
MOISTURE CON	<u>TENT</u>		2 OZ. PLAST	IC	. 4		
							
		· · · · · · · · · · · · · · · · · · ·					:
	·						
	· ·						
ON VENIONTAVIARIZATO	DIES .			MAP:			
elide (Applicable:				Signature(s):			
MS/MSD	Duplicate II	D No.:			l1.7	Nenge (<i>'</i>
			•	, ,	•	7	



					ray	e or
Project Site Na Project No.:	me:		O GREAT LAKES	Sample ID No Sample Locat Sampled By:	o.: NTC22M NTC22M MLM	W10D1112R2 W10D
[] Surface So [X] Subsurfa [] Sediment				C.O.C. No.: Type of Samp	ole:	783
[] Other: [] QA Sampl	e Type:			[X] Low Cor High Cond		
etassani eta	A:					
	9-12-06	Depth Interval	Color	Description (Sa	nd, Silt, Clay, Mo	isture, etc.)
Time:	1145	441.40		ŀ		
Method: Monitor Reading (ppr	ENCORE	11' - 12'				
COMPOSITE SAMP						
Date:	Time	Depth Interval	Color	December (Se	nd Silt Olav Ma	
Date.	Tillie	Deptil Interval	Color	Description (Sa	nd, Silt, Clay, Mo	isture, etc.)
Method:						
Monitor Readings						
(Range in ppm):					· · · · · · · · · · · · · · · · · · ·	
(riango in ppin).						
			T. T.		**************************************	
SAM: LEGOLLEGI		L T/au:				
hoofdhaaddelliiseeund Neu Naatzaka Jacobadh (b)	Analysis	A46545555555555555555555555555555555555	Container Requ	uirements T	Collected	Other
CVOCS			(3) 5-GRAM EN		2-	J. J
MOISTURE CON	ITENT		2 OZ. PLAST		-	
	· · · · · · · · · · · · · · · · · · ·					
			<u> </u>			

					Ł	
OBSERVATIONS//N	OTES:			MAP:		
						· · · · ·
					*	
			÷			
	,		•	· ·		
ircie (l'Applicable)				Signature(s):		
MS/MSD	Duplicate II	D No.		_		
,	Dupiloate II	J 110	View Control	Mark	Mings	



Page_

Project Site Name: NTC22MW06D0708R2 NAVAL STATION GREAT LAKES Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: NTC22MW06D Sampled By: MLM Il Surface Soil C.O.C. No.: 308783 [X] Subsurface Soil Sediment
 Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: ∏ High Concentration CIPAG SAMPLE PATA Depth Interval Date: 9-12-06 Description (Sand, Silt, Clay, Moisture, etc.) Color Time: 1020 Method: **ENCORE** 7' - 8' Monitor Reading (ppm): COMPOSITE SAMPLE DATA Date: Time Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other <u>cvocs</u> 4 (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS/NOTES: MAP: Circle (Applicable: Signature(s): Mark & Mengel MS/MSD **Duplicate ID No.:** NTC 22 FD 001



					Page	of
Project Site Nar Project No.: [] Surface So [X] Subsurface [] Sediment [] Other: [] QA Sample	oil ce Soil	NAVAL STATION 112G00202 CT	I GREAT LAKES TO 009	Sample ID No.: Sample Location Sampled By: C.O.C. No.: Type of Sample [X] Low Concentration	n: NTC22FD MLM 308 e: eentration	
GETAGESAMELE DAT	A:					
	9-12-06	Depth Interval	Color	Description (Sand	d, Silt, Clay, Mois	ture, etc.)
Time:	0000	<u> </u>				
Method:	ENCORE]				
Monitor Reading (ppm						
eempesiiesamei		T				
Date:	Time	Depth Interval	Color	Description (Sand	d, Silt, Clay, Mois	ture, etc.)
	<u> </u>					· ·
Method:						
				4		
Monitor Readings						
(Range in ppm):						
(, m., 9						
			\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			· · · · · · · · · · · · · · · · · · ·
	<u> </u>					
SWISE HOUSE		TIEN:	Cantainer Regu	!	Callacted	Other
	Analysis	VI (ON):	Container Requi		Collected	Other
CVOCS	Analysis	(TION):	(3) 5-GRAM EN	ÇORE	Collected	Other
	Analysis	TION:		ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	ITION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	ÇORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	ÇORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	CORE	-	Other
CVOCS MOISTURE CON	Analysis	TION:	(3) 5-GRAM ENG 2 OZ. PLASTI	MAP	-	Other
CVOCS MOISTURE CON	Analysis		(3) 5-GRAM ENG 2 OZ. PLASTI	CORE		



Page_ of . Project Site Name: NAVAL STATION GREAT LAKES Sample ID No .: NTC22SB210910R2 Project No.: 112G00202 CTO 009 Sample Location: NTC22SB21 Sampled By: MLM f) Surface Soil C.O.C. No.: 307444 [X] Subsurface Soil [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration CITATE SAME DATA Date: Description (Sand, Silt, Clay, Moisture, etc.) 9-13-06 Depth Interval Color Time: 0740 **ENCORE** Method: 9' - 10' Monitor Reading (ppm): GOMPOSITESAMETE DATA: Date: Time **Depth Interval** Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION IN FORMATION I **Analysis Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE --MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: Circle if Applicable) Signature(s): Mark & Mingl MS/MSD **Duplicate ID No.:**



Page_

of

Project Site Name: NTC22SB211314R2 NAVAL STATION GREAT LAKES Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: NTC22SB21 Sampled By: MLM [] Surface Soil C.O.C. No.: 307444 [X] Subsurface Soil Sediment
 Sediment Type of Sample: [X] Low Concentration [] Other: [] High Concentration [] QA Sample Type: CIFAS SAMPLE DATA Date: 9-13-06 Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color 0750 Time: **ENCORE** 13' - 14' Method: Monitor Reading (ppm): GOMPOSITE SAME DATAS Date: **Depth Interval** Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMBLE GOLDEGO (ON INFORMATION) Analysis **Container Requirements** Collected Other CVOCS (3) 5-GRAM ENCORE 4 MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS/NOTES: MAP Circle if Applicable: Signature(s): Mark & Mengel MS/MSD **Duplicate ID No.:**



					Page	of
Project Site Nan Project No.: [] Surface So		NAVAL STATION 112G00202 C	I GREAT LAKES TO 009	Sample ID No.: Sample Location Sampled By: C.O.C. No.:	n: NTC22SB MLM	1191920R2 119
[X] Subsurfac				Type of Sample:		
[] Other:				[X] Low Conce	entration	
[] QA Sample	e Type:			[] High Concer	ntration	
GFAG SAMPLEDAT	A					
	7-13-06	Depth Interval	Color	Description (Sand,	Silt, Clay, Mois	sture, etc.)
Time:	//35 ENCORE	401 001	1		•	
Method: Monitor Reading (ppm	ENCORE	19' - 20'	,			
COMPOSITE SAMPL		.	I			
Date:	Time	Depth Interval	Color	Description (Sand,	Silt Clay Mois	ture. etc.)
				20001112111 (04114)	Only Oray, more	
Method:						
,						
Monitor Readings			<u> </u>		×	
(Range in ppm):						
					·····	
190000000000000000000000000000000000000	COSUDO DO DE LA COSTA DEL COSTA DE LA COSTA DE LA COSTA DEL COSTA DE LA COSTA DEL COSTA DELA COSTA DE LA COSTA DELA COSTA DE LA COSTA DE LA COSTA DE LA COSTA DE LA COSTA DE L					
Sameleeneene	Kinedima	TION:				
	ON INFORMA Analysis	TION:	Container Requ		ollected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	Collected	Other
	Analysis	TION:		CORE	collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	Collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	collected	Other
CVOCS	Analysis	TION:	(3) 5-GRAM EN	CORE	Collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	Collected	Other
CVOCS	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	Collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	CORE	collected	Other
CVOCS MOISTURE CON	Analysis TENT	TION:	(3) 5-GRAM EN 2 OZ. PLAST	MAP:	collected	Other
CVOCS MOISTURE CON	Analysis TENT		(3) 5-GRAM EN 2 OZ. PLAST	CORE		



Page_

of

Project Site Name: **NAVAL STATION GREAT LAKES** NTC22SB220708R2 Sample ID No .: Project No.: 112G00202 CTO 009 Sample Location: NTC22SB22 Sampled By: MLM [] Surface Soil C.O.C. No.: 307444 [X] Subsurface Soil ∏ Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration CEPAGESAMPLE PATA Date: 9-13-06 Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Time: 1000 **ENCORE** Method: 7' - 8' Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth Interval Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Container Requirements** Other **Analysis** Collected **CVOCS** (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC ___ OBSERVATIONS/INCITES MAP: Circle if Applicable: Signature(s): Mark 1. Mingel MS/MSD **Duplicate ID No.:**



Page_

of

Project Site Name: **NAVAL STATION GREAT LAKES** NTC22SB221819R2 Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: NTC22SB22 Sampled By: MLM Il Surface Soil C.O.C. No.: 307444 [X] Subsurface Soil Sediment Type of Sample: [] Other: [X] Low Concentration [] High Concentration [] QA Sample Type: GRAE SAMPLE DATA: Date: Description (Sand, Silt, Clay, Moisture, etc.) 9-13-06 Depth Interval Color Time: 1025 Method: **ENCORE** 18' - 19' Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time Depth interval Description (Sand, Silt, Clay, Moisture, etc.) Color Method: Monitor Readings (Range in ppm): SAMPLE DOLLEGION INFORMATION: Analysis **Container Requirements** Collected Other cvocs (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC -OBSERVATIONS/NOTES: MAP: Circle if Applicable: Signature(s): Markt Mengel MS/MSD **Duplicate ID No.:**



Page_

of

Project Site Name: Sample ID No.: NTC22FD002 NAVAL STATION GREAT LAKES Sample Location: NTC22FD Project No.: 112G00202 CTO 009 Sampled By: MLM [] Surface Soil C.O.C. No.: 307444 [X] Subsurface Soil Sediment
 Sediment Type of Sample: ○ Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAG SAMPLE DATA: 9-13-06 Date: Description (Sand, Silt, Clay, Moisture, etc.) Depth Interval Color 0000 Time: **ENCORE** Method: Monitor Reading (ppm): GOMEOSTE SAME E DATA. Color Date: Time **Depth Interval** Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMRUE COLUECTION INFORMATIONS Container Requirements Collected Other **Analysis** cvocs (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC _ OBSERVATIONS/NOTES: MAP Signature(s): Circle II Applicable: MS/MSD **Duplicate ID No.:** Mark & Mingl NTC22 58191920 RZ



Page_

of

Project Site Name: **NAVAL STATION GREAT LAKES** Sample ID No.: NTC22SB151112R3 NTC22SB15 Project No.: 112G00202 CTO 009 Sample Location: Sampled By: MLM [] Surface Soil C.O.C. No.: ¥ Subsurface Soil []. Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 9/28/2006 **Depth Interval** Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 1325 **ENCORE** 11' - 12' Method: Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time **Depth Interval** Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: **Analysis Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS / NOTES: MAP: Circle if Applicable: Signature(s): MS/MSD **Duplicate ID No.:**



of

Page_ Project Site Name: NAVAL STATION GREAT LAKES NTC22MW10D1012R3 Sample ID No.: Project No.: NTC22MW10D 112G00202 CTO 009 Sample Location: Sampled By: MLM [] Surface Soil C.O.C. No.: ★ Subsurface Soil [] Sediment Type of Sample: [] Other: [X] Low Concentration [] High Concentration [] QA Sample Type: GRAB SAMPLE DATA: Date: 9/28/2006 Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 1410 10' - 12' Method: **ENCORE** Monitor Reading (ppm): COMPOSITE SAMPLE DATA: and the second s Date: Time Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other **CVOCS** (3) 5-GRAM ENCORE -MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS/NOTES: MAP: Circle if Applicable: Signature(s): MS/MSD **Duplicate ID No.:**



Page_ of Project Site Name: **NAVAL STATION GREAT LAKES** NTC22SB221819R3 Sample ID No.: Project No.: 112G00202 CTO 009 Sample Location: NTC22SB22 Sampled By: MLM [] Surface Soil C.O.C. No.: X Subsurface Soil [] Sediment Type of Sample: [] Other: [X] Low Concentration [] QA Sample Type: [] High Concentration GRAB SAMPLE DATA: Date: 9/28/2006 Depth Interval Color Description (Sand, Silt, Clay, Moisture, etc.) Time: 1445 **ENCORE** Method: 18' - 19' Monitor Reading (ppm): COMPOSITE SAMPLE DATA: Date: Time **Depth Interval** Color Description (Sand, Silt, Clay, Moisture, etc.) Method: Monitor Readings (Range in ppm): SAMPLE COLLECTION INFORMATION: Analysis **Container Requirements** Collected Other cvocs (3) 5-GRAM ENCORE _ MOISTURE CONTENT 2 OZ. PLASTIC OBSERVATIONS/NOTES: MAP: Circle if Applicable: Signature(s): MS/MSD **Duplicate ID No.:**

MARCH 2007



Page 1 of 2

DRIL	LING	NUMI COMI RIG:	BER: PANY:	112G0	00202		REAT LAKES BORING N DATE: GEOLOGIS DRILLER:		NTC22SB 20 3-6-07 MLM CHRIS WHITE				
Sample No. and Type or RQD	(Ft.) or	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth/Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness		RIAL DESCRIPTION Material Classification	U	Remarks	Sample Sample	Sampler BZ		Driller BZ** 3
							8 /4 HSA 0-30' REFER TO BORING 101 FOR SB20 (10 121-22 103)						
	5					UR	for complete soil description CIRY @ 7			0		0	
	10					in	CLAY		CUTTINGS	/		0	
	15					હ િ	CLAY		CUTTINES	 		0	
				V	3 (1)	GR							
	20			∇	WET	_છ હ	WATER /CLAY		CUTTINUS	2		0	
	z s												
** Includ Rema	le moni arks:				borehole. In	ncrease	reading frequency if elevated reponse re		Drilling Background				



Page <u>2</u> of <u>2</u>

					N	ATE	RIAL DESCRIPTION			PID/FII	Read	Jing (ррп
Sample No. and Type or RQD	(Ft.) or	Blows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth/Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness	Color	Material Classification	U S C S *	Remarks	Sample	Sampler BZ	Borehole**	Driller BZ**
													L
			. 1										_
		/						_		_		_	L
								_					H
	30					GR	CLAY	_	81/4 HSA 0-30'			_	H
											_		_
							- And			-	\vdash		_
							SAND + SILT	<u></u>					_
								<u> </u>				_	-
	35					leis	FINE SAND						
			·								\exists		H
					. :								_
	40						FINC SAND		3 1/4" NSA 30-40				
							40' BOTTOM			-			
													Ŀ
													_
		\angle											
<u> </u>													
								_			\dashv		_
			:				7040						_
		oring, ente									لبا		Ĺ,



Page ___ of ___

		,					Jima Loa						
		Г NAM		NAVAL	STATIO	N GF	REAT LAKES BORIN	IG No.:	NTC22SB06 R				
		T NUM		112G0	00202		DATE:		NALKA				
		RIG:	PANY:	IIL			GEOLG DRILLI	OGIST:	CHRIS WHITE				
DAIL	LINC	i nia.			<u> </u>			En.	CHAIS WHITE				_
Sample	Depth	Blows /	Sample	Lithology	<u> </u>	/AIE	RIAL DESCRIPTION			PID/FI	D Res	iding ((ppm)
No.	(Ft.)	6" or	Recovery	Change				U					
and Type or	Or Run	RQD (%)	Sample	(Depth/Ft.) or	Soil Density/ Consistency			C	Remarks	9	r 82	ş	BZ.
RQD	No.		Length	Screened Interval	or Rock	Color	Material Classification	S	i temarke	Sample	Sampler BZ	Borehole**	Oriller BZ"
1	<u> </u>		}	Interval	Hardness					9	88	8	12
						1		il e		4		4.	
											,		
				1									
_	 	F_{\nearrow}	<u> </u>	1.		ļ				+-	-		\vdash
		/_			<u>. </u>					-	Ш		_
							SCO ORIGINAL BOAL	iha					
	5						see original box	Fan		0		٥	
							details.						
						6R	Clay @ 7'						
							<u> </u>			1			
										†	Н		
	10												
	10					UR.	CLAY / SILT			10	H		
								-			Н	•	\vdash
										+	H	\dashv	
										+	$\vdash \vdash$		
										+-	\mid	\dashv	
	15					6R	CLAY / SILT			0		4	
								_		+			
							· · · · · · · · · · · · · · · · · · ·						
		\angle											
	20					6R	CLAY / SILT					1	
										11	Ħ	一	
										11	П	一	
							7,11	_		†	十	\dashv	
	25						bottom @25	.,		+		ᅥ	
* When		ring, ente	r rock brol	keness.	1		WOIIOM OLS		1				
** Includ	de moni	tor readin	g in 6 foot		borehole. Ir	ncrease	reading frequency if elevated repo	nse read.		ng Ar			
Rema	arks:	4 1/	4"	HS A					Background	l (ppr	n):[_]
													_
Conv	erted	to We	ll:	Yes			No Wel	I I.D. #:					



MONITORING WELL SHEET FLUSH - MOUNT

OVERBURDEN

Tetra Tech NUS, Inc.

	PRO DAT FIEL	DJECT NTO GREAT LAKES DJECT NO. 112600202 E BEGUN 3-6-07 D GEOLOGIST MI	LOCATION STO 22 BORING SBOGR DATE COMPLETED 3-	DRILLER TTL (CARIS WANTE) DRILLING METHOD HSA DEVELOPMENT METHOD
) IN			ELEVATION TOP OF RISER	<u> </u>
67/26/99			TYPE OF SURFACE SEAL:	Cement
ACAD: FORM_MWFM.dwg		FLUSH MOUNT— SURFACE CASING	TYPE OF PROTECTIVE CAS	
FORM	-	WITH LOCK	I.D. OF PROTECTIVE CASI	NG:
ACAD			DIAMETER OF HOLE: 4	4 HSA
	÷		TYPE OF RISER PIPE:	Z" PVC
			RISER PIPE I.D.:	, 18
			TYPE OF BACKFILL/SEAL:	
4			COMENT GROW	
			ELEVATION/DEPTH TOP OF	F SEAL:
			TYPE OF SEAL: Bent	ONITG
				——————————————————————————————————————
			ELEVATION/DEPTH TOP OF	F SAND: / 13
			ELEVANORY DEFINITION OF	JANU.
			ELEVATION (DEDT), TOD OF	CODEEN.
	٠.		ELEVATION/DEPTH TOP OF TYPE OF SCREEN: 14	
			SLOT SIZE x LENGTH: 101	
			TYPE OF SAND PACK:	
			DIAMETER OF HOLE IN BE	DROCK:
			ELEVATION / DEPTH BOTT	OM OF SCREEN: 125
			ELEVATION / DEPTH BOTT	
			ELEVATION/DEPTH BOTTON	
			BACKFILL MATERIAL BELOV	W SANU:
Ĺ				



		Γ NAM		NAVAL	STATIO	N GF	REAT LAKES	BORING N	o.:	NTC22SB 1 € \$	R_			
			BER: PANY:	112GC	0202			DATE: GEOLOGIS	ξT·	3-7-07 MIM				
		RIG:		116				DRILLER:	<i>,</i>	CHRIS WHITE				
	г -		1		I N	/ATF	RIAL DESCRIPT				PID/FI	D Rea	dina	(ppm
Sample No. and Type or RQD	(Ft.) or	Biows / 6" or RQD (%)	Sample Recovery / Sample Length	Lithology Change (Depth/Ft.) or Screened Interval	Soil Density/ Consistency or Rock Hardness				U	Remarks	Sample	Sampler BZ		
		\angle		·			see origin	1						
		/					boring log 1	FOR 10\$		· ·		Ш		
		\angle					Sce original boring log for details				<u> </u>			
	.5	$\langle \cdot \rangle$									 	Ш		_
											+	Н		<u> </u>
							CLAY	SILT			+-			
							*	·						_
	10										1			\vdash
	10													
										∀ % 12'				
	15						CLAY .	SILT						
			-				<u> </u>							
											1			
				·					_		-			-
		<u> </u>	•								\blacksquare	_	_	
	20			ŀ			CLAY, SI	LT			+			
										<u> </u>	+	\dashv		
	$\overline{}$					-			_		+			
				4 1							H	\dashv	ᅦ	П
	25						CLAY, S	iLT						
* When	rock co	ring, ente	r rock bro	keness.		· .				Daini	I	·		
Rema	e moni arks:	tor readin	g in 6 foot #SA 1	intervals @	porehole. In	ncrease HSA	reading frequency if ele	evated reponse re	ad.	Drillii Background				
Conv	- -	to We	ii.	Vec			No	Well D	#.					



Page <u>2</u> of <u>2</u>

DRILLING RIG: Service Depth Blows / Service Color Material Classification Service Consistency Consisten	PRO	JEC ⁻	NAM NUM COM		112G0	STATIO 00202	 REAT LAKES				<u> </u>			
Sample Double Storm / Recovery of Recovery (Congress of Double Storm) (Cong	DRIL	LINC	RIG:				 	DRILLER:		CHRIS WHITE			<u> </u>	
*When rock coring, enter rock brokeness. *Include monitor reading in 6 foot intervals & borehole. Increase reading frequency if elevated reponse read. Drilling Area	No. and Type or	(Ft.) or Run	6" or RQD	Recovery / Sample	Change (Depth/Ft.) or Screened	Soil Density/ Consistency or Rock	12		s c s					Driller BZ** add
*When rock corling, enter rock brokeness. *Include monitor reading in 6 foot intervals © borehole. Increase reading frequency if elevated reponse read. Drilling Area										814 HSA-TO 30				
*When rock coring, enter rock brokeness. * include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area		30					SAND ,	SILT						
*When rock coring, enter rock brokeness. * include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area														
*When rock coring, enter rock brokeness. ** Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area		35					DOTTOM	Q 35'						
*When rock coring, enter rock brokeness. ** Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area									-					
*When rock coring, enter rock brokeness. ** Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area														
*When rock coring, enter rock brokeness. ** include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area							-							
*When rock coring, enter rock brokeness. ** Include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area						:								
** include monitor reading in 6 foot intervals @ borehole. Increase reading frequency if elevated reponse read. Drilling Area											(#	+	
Converted to Well: Yes No Well I.D. #:	** includ Rema	le monit arks: _ -	or reading	j in 6 foot	intervals @									

WELL NO .: MW 10\$ R



Tetra Tech NUS, Inc.

OVERBURDEN MONITORING WELL SHEET FLUSH - MOUNT

	PRO DA	DJECT NTC 22 DJECT NO. 112600202 TE BEGUN 3-7-07 LD GEOLOGIST MLM	LOCATION_BORING_DATE COMPLETED_3-7-07	DRILLER TTL DRILLING METHOD DEVELOPMENT		
	GRO	OUND ELEVATION	DATUM	METHOD		
B INL			ELEVATION TOP OF RISER:	•		
67/26/99			TYPE OF SURFACE SEAL:	'ement		
ACAD: FORM_MWFM.dwg		FLUSH MOUNT—SURFACE CASING	TYPE OF PROTECTIVE CASING:			
AD: FOR		WITH LOCK	I.D. OF PROTECTIVE CASING: DIAMETER OF HOLE: 81/41/74			
¥			TYPE OF RISER PIPE: 2"			
			RISER PIPE I.D.: 2"			
			TYPE OF BACKFILL/SEAL: _CC	nent / bentanite		
			ELEVATION/DEPTH TOP OF SEA	L:		
			TYPE OF SEAL: Bentonit	6		
			ELEVATION/DEPTH TOP OF SAN	D: / 30		
			ELEVATION/DEPTH TOP OF SCRI	TEN. , 27		
			TYPE OF SCREEN: 10 sl			
			SLOT SIZE x LENGTH: 10 X	(2)		
			TYPE OF SAND PACK:			
			DIAMETER OF HOLE IN BEDROCK	:		
			ELEVATION / DEPTH BOTTOM OF	F SCREEN: / 35		
	,		ELEVATION / DEPTH BOTTOM OF			
			ELEVATION/DEPTH BOTTOM OF H			
			BACKFILL MATERIAL BELOW SAN	D:		

WELL NO .: MWIDD R



OVERBURDEN MONITORING WELL SHEET FLUSH - MOUNT

Tetra Tech NUS, Inc.

	PRO DAT FIEL	DJECT NTC GREAT A DJECT NO. 1/260020 E BEGUN 3-6-0 LD GEOLOGIST ML DUND ELEVATION	2 BO 7 DA	CATION <u>NTC ZZ MW 100 R</u> RING <u>SB 20 R</u> TE COMPLETED	DRILLER
JNI 6				ELEVATION TOP OF RISER:	
67/26/99				TYPE OF SURFACE SEAL: COM	NENT
ACAD: FORM_MWFM.dwg		FLUSH MOUNT— SURFACE CASING		TYPE OF PROTECTIVE CASING:_	
AD: FORM		WITH LOCK		I.D. OF PROTECTIVE CASING: DIAMETER OF HOLE: 8 1/4 1/1 a.	
¥C				TYPE OF RISER PIPE: 2" P	
				RISER PIPE I.D.: 2"	
				TYPE OF BACKFILL/SEAL: CEMENT GROUT	
				ELEVATION/DEPTH TOP OF SEAL	
				TYPE OF SEAL; BCHTONITO	
			XXXX	ELEVATION/DEPTH TOP OF SAND): <u>/ 35</u>
			-	TYPE OF SCREEN: 10 5407 SLOT SIZE x LENGTH: 10 x	<u> </u>
				— TYPE OF SAND PACK:	
				DIAMETER OF HOLE IN BEDROCK	•
				- ELEVATION / DEPTH BOTTOM OF	
				ELEVATION / DEPTH BOTTOM OF HELEVATION/DEPTH BOTTOM OF H	
				BACKFILL MATERIAL BELOW SAN	D:

TŁ	Tetra Tech NUS, Inc.	
	,	

MONITORING WELL DEVELOPMENT RECORD

Page _/ of _/

Well:	Depth to Bottom (ft.):4/0 /	Responsible Personnel:
Site: ZZ	_ Static Water Level Before (ft.): _ <u></u> <u> </u>	Drilling Co.:
Date Installed: 3-6-07	_ Static Water Level After (ft.):	Project Name: SITE 22
Date Developed: 3-8-07	_ Screen Length (ft.): <i>ろ</i> ′	Project Number:
Dev. Method: cleater Pump	Specific Capacity:	_
Pump Type:	_ Casing ID (in.):	

Time	Estimated Sediment Thickness (Ft.)	Cumulative Water Volume (Gal.)	Water Level Readings (Ft. below TOC)	Temperature (Degrees C)	pН	Specific Conductance (Units)	Turbidity (NTU)	Remarks	color, etc.)	(odor,
1445	2.1		4.10	24-73	7.88	.647	. —			
1450			16.70	24.80	793	-452	_			
1455			16.20	31.22	7.57	.629				-
1500			1680	31.50	7.54	. 624	550			
1505			16.65	31.30	7.56	.627	550			
1510	1.		16.80	31.70	7.52	-628	550			
1515			16.70	29.35	7.54	1633	400			
		, , , , , , , , , , , , , , , , , , , ,				**************************************				
						1. 				
	·									
	<u>.</u>									

Tetra Tech NUS, Inc.

MONITORING WELL DEVELOPMENT RECORD

Page __/ of __/

Well: <u>سس دے R</u>	Depth to Bottom (ft.): Z4 6	_ Responsible Perso	onnel:		
Site: ZZ	Static Water Level Before (ft.): _5.20	_ Drilling Co.:		·	
Date Installed: 3-7-07		Project Name:	NIL	SAC ZZ	
Date Developed: 3-8-07	Screen Length (ft.): /o'	Project Number:		2600202	
Dev. Method: cleet RIC PUMP	Specific Capacity:				
Pump Type:	Casing ID (in.): 2 //	•			$N_{\rm c}$

Time	Estimated Sediment Thickness (Ft.)	Cumulative Water Volume (Gal.)	Water Level Readings (Ft. below TOC)	Témperature (Degrees C)	pН	Specific Conductance (Units)	Turbidity (NTU)	Remarks (odor, color, etc.)
1350			Punged day	37.0	フ・ハ	.670	228	
			18.00		777		_	Pueved dex +wice
								WATER
,								
		·						
			2					
1								
		į.						
					-			



MONITORING WELL DEVELOPMENT RECORD

Page __/ of __/

Well: <u>mw/o </u>	Depth to Bottom (ft.):35	Responsible Personn	el:
Site: <u>22</u>	Static Water Level Before (ft.): 5.47	Drilling Co.:	TTL
Date Installed: 3-7-07	Static Water Level After (ft.):	Project Name:	SITE 22
Date Developed:	Screen Length (ft.): 2'	Project Number:	112600202
Dev. Method: Claster Pump	Specific Capacity:		
Pump Type:	Casing ID (in.):		

Time	Estimated Sediment Thickness (Ft.)	Cumulative Water Volume (Gal.)	Water Level Readings (Ft. below TOC)	Temperature (Degrees C)	рН	Specific Conductance (Units)	Turbidity (NTU)	Remarks (odor, color, etc.)
1400			5.47	36.0	8.48	.596	154	
1410			14.30	37.3	7.94	.562	(
1415			1430	31.40	7.82	.590		
1420			1430	33.40	7-21	1585	900	
1425			1430	32.90	7:72	.590	550	
1420			14.30	32.93	7.78	1580	550	
		90 gal	punged					STOPPED
							<u> </u>	
	WL.		·					
								-
							l 	



* All measurements to the nearest 0.01 foot

GROUNDWATER LEVEL MEASUREMENT SHEET

Project Name:		NAVAL S	STATION GREAT	r lakes		0202 CTO 0009	
Location:		SITE 22			Personnel:		
Weather Condition		501	NN1 40°		Measuring Dev	rice: M-Scope	
Tidally Influence	_		No		Remarks:	73000-00000	
Well or Piezometer Number	Date	Time *	Elevation of Reference Point (feet)*	Total Well Depth (feet)*	Water Level Indicator Reading (feet)*	Groundwater Elevation (feet)*	Comments
NTC22MW01S	3-11-07	1458	·	<i>3</i> 2	2.51		
NTC22MW02S		1565		20	5.85		
NTC22MW03S		1457		24	5.24		
NTC22MW04S		1510		24	3.71		
NTC22MW05S	ABAND)				
NTC22MW06S	ABAND	DONE		25'	24.05		
NTC22MW07S		1452		20		Submerge	<u>d</u>
NTC22MW08S		1501		24	4.83		
NTC22MW09S				1		FROZER	
NTC22MW10S	ABANI			35	4.20		
		1453					
NTC22MW06D	ABANI	DONEL)				
NTC22MW07D		1503			4.85		
NTC22MW10D	ABANI	DONE		40	4.05		
		£1455					
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					
						Pag	de of



GROUNDWATER SAMPLE LOG SHEET

Page / of Z

		NAVAL ST 112G0020		GREAT L	AKES	Sampled C.O.C. I Type of [X] Lo	Location: d By:		
SAMELING DAT									
	- 10 -07	Color	рΗ	s.c.	Temp.	Turbidity	DO	Salinity	-Othor-
Time:	1315	(Visual)	(S.U.)	(mS/cm)	(⁰ C)	(NTU)	(mg/l)	(%)	ORP
	Low -Flow	56600000000000000000000000000000000000	802	1.30	41.90		0.81		-19
EUEGEPAYA									0.1
Date:		Volume	pН	S.C.	Temp.	Turbidity	DO	Salinity	Other
Method: P	eristaltic Pump			•					
Monitor Reading	(ppm):		_						
Well Casing Dian	neter & Material								
Type: 2-	inch PVC								
Total Well Depth	(TD):								
Static Water Leve	el (WL):								
One Casing Volu	me(gal/L):								
Start Purge (hrs):									
End Purge (hrs):									
Total Purge Time	(min):					·	L.		
Total Vol. Purgeo									
Sauguseuli	enonineima	11(0)(4							
	Analysis		Preser	vative		Container R			Collected
VOCs			HCL		3	40-mi VOA V	IALS		
	·					· · · · · · · · · · · · · · · · · · ·			
_									
						·			
									·
Mediavaterio	SAMOYES								
, , ,									
	<u> </u>	·		<u> </u>					
erzencenz						Signature(s):	•	1
MS/MSD	Duplicate ID No.	•				Ma	nd 1.1	Mingel	-
								. /	



LOW FLOW PURGE DATA SHEET

PROJECT SITE NAME: PROJECT NUMBER:

NAVAL STATION GREAT LAKES

112G00202

WELL ID.: DATE:

NTC22MW 06 \$ R

3-10-07

Time	Water Level	Flow	рН	S. Cond.	Turb.	DO	Temp.	ORP	Salinity	Comments
(Hrs.)	(Ft. below TOC)	(mL/Min.)	(\$.U.)	(mS/cm)	(NTU)	(mg/L)	(Celcius)	mV	% or ppt	
0800	22.20	250	7.94	1.37	50	000	41.42	61		
0810		250	8.18	1.48	700	0.35	42.90	38		
0820	<u> </u>	250	8.02	1.32	750	0-81	41.90	-19		well is day
			·							
	· · · · · · · · · · · · · · · · · · ·		,							
<u> </u>							· · · · · · · · · · · · · · · · · · ·			·
						<u></u>			<u> </u>	
									<u> </u>	
									<u> </u>	
									 	
	· · · · · · · · · · · · · · · · · · ·						<u> </u>		-	
				<u></u>	·					
			 							
			 			 				
Nores	· /// 45 ON	V 40000	MATEL	21 15	140711	en en d	/ /MAT	co mas		1 -
7,57,6	but fine	in be	TOM C	esated ?	ul bidy	Ate	nd of po	100	Will TRY	J to start to Pulge Additional
	laten.	Used	Pular	HZO to	send	10 60	0261A 7	Ce A		1-172 1-1211 102/61
										
									<u> </u>	
							 			
	··									
	:									

SIGNATURE(S): Mark A. Mengl

PAGE ZOF Z



GROUNDWATER SAMPLE LOG SHEET

Page__/ of _2

Project Site Name: Project No.: [] Domestic Well Data [X] Monitoring Well Data [] Other Well Type: [] QA Sample Type:	NAVAL ST 112G0020		GREAT	LAKES	Sample C.O.C. Type of [X] Lo	Location: d By:		
SAMPLING DATA:								
Date: 3-10-07	Color	pН	s.c.	Temp.	Turbidity	DO	Salinity	-Other-
Time: /000	(Visual)	(S.U.)	(mS/cm)	(°C)	(NTU)	(mg/l)	(%)	ORP
Method: Low -Flow -	Clear	7.39	.596	39.27	6.5	0.0		-172
PURGE DATA:					I		I	<u> </u>
Date: 3-10-07	Volume	рН	s.c.	Temp.	Turbidity	DO	Salinity	Other
Method: Peristaltic Pump								
Monitor Reading (ppm):			-	-				
Well Casing Diameter & Material								
Type: 2-inch PVC						_	ļ	
Total Well Depth (TD): 35'								
Static Water Level (WL): 4-22								
One Casing Volume(gal/L):								
Start Purge (hrs): 0845								
End Purge (hrs): 0955								
Total Purge Time (min): 70	·							<u> </u>
Total Vol. Purged (gal/L): 5 60/								
SAMBLE COLLECTION INFORMA	filosy:							
Analysis		Preser	vative		Container R			Collected
VOCs		HCL		3	40-ml VOA V	ALS		
		- *						
				· · · · · · · · · · · · · · · · · · ·				
<u> </u>						,		
observations/Notes:								
								· .*
						•		10 a
				•				
		-						
Circle il Applicable:					Signature(s):		1
MS/MSD Duplicate ID No.					m	111	Nengo	ℓ
				e.	1.00	W/ /	July.	



LOW FLOW PURGE DATA SHEET

PROJECT SITE NAME: PROJECT NUMBER:

NAVAL STATION GREAT LAKES

112G00202

WELL ID.: DATE: NTC22MWOID \$ R

3-10-07

Time (Hrs.)	Water Level (Ft. below TOC)	Flow	pH (S.U:)	S. Cond.	Turb.	DO	Temp.	ORP	Salinity	Comments
		(mL/Min.)		(mS/cm)	(NTU)	(mg/L)	(Celcius)	mV	% or ppt	
0845	4.22	280	7.55	.615	80	.89	38.41	-/03		· · · · · · · · · · · · · · · · · · ·
0855	4.50	280	7.64	.619	<i>55</i>	0.0	39.36	-/35		
0905	4.50	280	7:52	-617	65	0.0	38.68	-168		
0915	4.51	280	7.45	-616	19	8.0	38.36	-/7/		
0925	4.51	280	7.41	.610	9.4	0.0	38.40	-171		
0735	4:52	280	7.39	-603	5.6	0.0	38.61	-170		
0945	4.52	280	7.37	-602	5.2	6.0	38.94	-171	·	· · · · · · · · · · · · · · · · · · ·
0955	4.52	280	7.39	.596	6.5	0.0	39.27	-172		
										<u> </u>
			END	PULBC			-			-
	· · · · · · · · · · · · · · · · · · ·								· · · · · · · · · · · · · · · · · · ·	
								·		·
	· - ·· · · · · · ·		,							····
				<u></u>						
										<u> </u>
				**						-
					l —— —— —— —— —— —— —— —— —— —— —— —— ——					
9		,							VII	
										

SIGNATURE(S): Mark & Mongel



GROUNDWATER SAMPLE LOG SHEET

[X] Monit [] Other V		NAVAL ST 112G0020		GREAT I	AKES	Sample C.O.C. I Type of [X] Lo	Location: d By:	NTC22MW MLM	010 D R
	A:								
	-10-07	Color	рН	S.C.	Temp.	Turbidity	DO	Salinity	-Other-
	1245	(Visual)	(S.U.)	(mS/cm)	(°C)	(NTU)	(mg/l)	(%)	ORP
Method: PURGE DATA:	Low-Flow	CICAR	7.43	.656	38.02	7.4	0.32		-/82
	-10-07	Volume	рН	s.c.	Tomn	Turbidity	DO	Salinity	Other
		Volume	рп	3.0.	Temp.	ruibidity	<u> </u>	Camility	Calor
Method: F Monitor Reading	Peristaltic Pump								
Well Casing Diar									
· · ·	-inch PVC								
Total Well Depth									
Static Water Lev									
One Casing Volu									
Start Purge (hrs)									
End Purge (hrs):									
Total Purge Time	e (min): <i>40</i>								
Total Vol. Purge	d (gal/L): チャ								
Sample Colli	EGTION INFORMA	10)(1:							
	Analysis		Preserv	vative		Container R			Collected
VOCs	<u> </u>		HCL		3	40-ml VOA V	ALS		
		•	•	-	<u> </u>			. 1	
								- :	
oesenivation	S/NOTES:								
								·	
GITGE HADDIE	196:					Signature(s):		
MS/MSD	Duplicate ID No.:					me	rolf.	Mirgi	



LOW FLOW PURGE DATA SHEET

PROJECT NUMBER:

NAVAL STATION GREAT LAKES

112G00202

WELL ID.: DATE:

NTC22MWOIOD R

3-10-07

Time	Water Level	Flow	рН	S. Cond.	Turb.	DO	Temp.	ORP	Salinity	Comments
(Hrs.)	(Ft. below TOC)	(mL/Min.)	(S.U.)	(mS/cm)	(NTU)	(mg/L)	(Celcius)	mV	% or ppt	
1125	4.10	250	7.78	-689	3/	1-69	39.35	-146		
1135	4.50	250	7.73	.671	19	0.74	39.35	-182		
1145	4.50	250	7.55	.670	31	0.40	38.75	-185	,	
1155	4.50	250	7.55	.660	17	0.37	38.52	-185		
1205	4.50	250	7.46	.650	9.2	0.29	38.42	-186		
1215	4.50	250	7.44	-460	7.9	0.28	38.18	-/84		
1225	4.50	250	7.43	-656	7.4	6.32	38.02	-182		
	· · · · · · · · · · · · · · · · · · ·			END	PURBE					
		<u>. </u>								
					-					
								1.0	·	
		·								
								·		
·					1					
,				-						
				-						
·										
						 				
	<u> </u>						 			
******		<u> </u>						-		
		 								
									 	
		*				<u> </u>	<u> </u>		<u> </u>	

SIGNATURE(S): Mark & Mingel

PAGE 20F 2



PROJECT NAME:

NAVAL STATION GREAT LAKES

INSTRUMENT NAME/MODEL:

LAMOTTE 2020

SITE NAME:

NTC22

MANUFACTURER:

LAMOTTE

PROJECT No.:

112G00202

SERIAL NUMBER:

10420599

Date of Calibration	Person Perform Calibration		рН	s.c	Turbidity	D.O.	Temperature	Salinity	ORP	Calibration Standard	Remarks
(mn/di <i>Vsy</i> e) ::	(Name)		(5,04)	(S/cm)	(NTUs)	(mg/L)	10.00 pc \$ 1.	(%)	≟ (m¥)	Lot# & Expiration Date	
		Pre	15.1		11					Lot# /404402	
3-8-07	MLM	Post			10.79					Exp. Date:	
		Pre			9.10					Lot #	
3-10-07	MLM	Post			10.00					Exp. Date:	
		Pre								Lot #	
		Post								Exp. Date:	
		Pre								Lot#	
		Post						·		Exp. Date:	
	**	Pre		•						Lot#	
		Post								Exp. Date:	•
		Pre								Lot#	
		Post								Exp. Date:	•
·		Pre								Lot #	
		Post								Exp. Date:	
		Pre								Lot #	
		Post								Exp. Date:	
		Pre					<u> </u>	·		Lot #	•
		Post								Exp. Date:	
		Pre							<u> </u>	Lot#	
		Post								Exp. Date:	
		Pre					·		1	Lot#	,
	· · · · · · · · · · · · · · · · · · ·	Post					<u> </u>		<u> </u>	Exp. Date:	
		Pre					 		<u> </u>	Lot#	
		Post							<u></u>	Exp. Date:	



PROJECT NAME:

NAVAL STATION GREAT LAKES

INSTRUMENT NAME/MODEL:

Horiba U-22 Water Quality Meter

SITE NAME:

NTC22

MANUFACTURER:

Horiba

PROJECT No.:

112G00202

SERIAL NUMBER:

00000003

LOT# 2604301

Date of Calibration	Person Performi Calibration	ng	рН	s.c	Turbidity	D.O.	Temperature	Salinity	ORP	Calibration Standard	Remarks
(mg/skyyy)	[[] (Name)] [(SU)	(ES/cii)	(Krius)	(mg/L)	C M	(%)	. (mV)	Col#& Expiration Date	
		Pre	3.95	99.9	0	8113	18.63		237	Lot# 5350	
3/8/07	MLM	Post	400	4.59	0	9.18	17.70			Exp. Date: 7-67	
		Pre	4.05			10.75	6.92			Lot#	
3/10/07	mem	Post	4.00	4.59		11.17	6.91			Exp. Date:	
		Pre								Lot#	
*		Post								Exp. Date:	1
		Pre								Lot#	
		Post								Exp. Date:	
		Pre								Lot#	
		Post								Exp. Date:	1.
		Pre								Lot#	
		Post								Exp. Date:	
	, , , , , , , , , , , , , , , , , , , ,	Pre								Lot #	
	·	Post								Exp. Date:	
		Pre					<u> </u>			Lot #	
		Post								Exp. Date:	
		Pre								Lot #	1
		Post	ļ					ļ <u>.</u>	<u> </u>	Exp. Date:	
		Pre				<u></u>				Lot #	
		Post				<u> </u>		·	ļ	Exp. Date:	
		Pre							-	Lot#	4
 		Post							 	Exp. Date:	
		Pre							-	Lot#	4
	I	Post	İ		<u> </u>		<u> </u>	L		Exp. Date:	<u> </u>



PROJECT NAME:	NAVAL STATION GREAT LAKES	INSTRUMENT NAME/MODEL:	
SITE NAME:	NTC22	MANUFACTURER:	
PROJECT No.:	112G00202	SERIAL NUMBER:	

Date of Calibration	Person Performir Calibration	ıg	рН	sc PPM	Turbidity	D.O.	Temperature	Salinity	ORP	Calibration Standard	Remarks
(middy/yr)	(Name)		(8.0.)	(ˈJs/cm)	(NTUS)	(mg/L)	Par September	星(%)署	a (ny)	Lot # & Expiration Date	
		Pre		98						Lot#	
3/6/07	MINI-RAY 2000	Post		100						Exp. Date:	100PPM CAL GAS
		Pre						٠ .		Lot#	
		Post								Exp. Date:	<u> </u>
		Pre								Lot #	
	$\rho = 1 + 2 \epsilon \epsilon_{\rm p} = 1 + \epsilon_{\rm p} = 1$	Post								Exp. Date:	
		Pre								Lot #	·
		Post								Exp. Date:	
		Pre								Lot #	
		Post								Exp. Date:	l
· · · · · · · · · · · · · · · · · · ·		Pre								Lot#	
	,	Post								Exp. Date:	
		Pre								Lot#	
		Post								Exp. Date:	
		Pre								Lot#	
		Post								Exp. Date:	
÷		Pre							<u> </u>	Lot#	_
		Post								Exp. Date:	
		Pre								Lot #	
		Post							<u> </u>	Exp. Date:	
		Pre							1	Lot#	
		Post							-	Exp. Date:	
		Pre						ļ		Lot #	4
		Post		l				<u> </u>		Exp. Date:	

APPENDIX E

SURVEY DATA

James Anderson Company Point No.	Monitoring well ID and/or Description	Northing (NAD 83 US feet)	Easting (NAD 83 US feet)	Elevation of top of well casing (NAVD 88 US feet)	Existing ground or concrete elevation adjacent to well (NAVD 88 US feet)
204	22MW01 NEW	2057372.29	1117751.21	648.93	649.30
205	22MW02 NEW	2057366.52	1117751.74	649.06	649.31
206	22MW03 NEW	2057360.98	1117752.51	649.03	649.30
203	NTC22MW03S	2057409.39	1117732.22	648.74	649.00
201	NTC22MW04S	2057379.50	1117673.21	648.36	648.82
202	NTC22MW08S	2057340.25	1117661.96	648.46	648.84
Note: Eleva	ations shown hereon were obta	ined using a level.			

James Anderson Company Point No.	Monitoring well ID and/or Description	Northing (NAD 83 US feet)	Easting (NAD 83 US feet)	Elevation of top of well lid (NAVD 88 US feet)	Existing pavement or concrete elevation at abandoned well location (NAVD 88 US feet)
285	NTC22MW01S	2057514.92	1117634.75	648.43	
286	NTC22MW02S	2057458.78	1117831.93	650.08	
287	NTC22MW05S ABANDONED	2057358.40	1117718.49	030.00	649.13
288	NTC22MW07D	2057342.19	1117811.69	649.89	049.13
289	NTC22MW07S	2057353.76	1117811.91	649.58	
	NTC22MW09S	2057304.18	1117751.45	649.29	
290	NTC22MW10D ABANDONED	2057375.64	1117751.43	049.29	649.28
291	NTC22MW10S ABANDONED	2057369.04	1117751.78	 	649.43
	INTOZZIWW TOS ABANDONED	2037309.04	1111/31.76		049.43
207	MW ABANDONED	2057346.74	1117762.75		649.83
208	MW ABANDONED	2057358.90	1117762.54		649.76
209	MW ABANDONED	2057365.25	1117762.53	-	649.76
210	MW ABANDONED	2057371.69	1117762.19		649.75
211	MW ABANDONED	2057379.97	1117763.45		649.73
212	MW ABANDONED	2057387.13	1117763.85		649.62
213	MW ABANDONED	2057380.70	1117778.41		649.09
214	MW ABANDONED	2057372.38	1117774.93		649.33
215	MW ABANDONED	2057364.52	1117778.46		649.15
216	MW ABANDONED	2057353.06	1117747.48		649.45
217	MW ABANDONED	2057366.05	1117747.45	 	649.44
218	MW ABANDONED	2057373.42	1117745.82		649.35
219	MW ABANDONED	2057377.18	1117745.09		649.26
220	MW ABANDONED	2057373.30	1117735.24		649.24
221	MW ABANDONED	2057366.92	1117739.44	<u> </u>	649.29
	MW ABANDONED	2057359.95	1117734.96		649.37
223	MW ABANDONED	2057346.25	1117734.92		649.40
224	MW ABANDONED	2057352.79	1117721.32		649.26
225	MW ABANDONED	2057366.91	1117720.90		649.15
226	MW ABANDONED	2057359.65	1117713.81	 	649.15
227	MW ABANDONED	2057359.27	1117707.00		649.09
228	MW ABANDONED	2057356.94	1117700.53		649.09
229	MW ABANDONED	2057353.04	1117695.27		649.07


		.	1		
STA	+			EL	
BM-2	3.835	652.685		648.85	
	6.24	654.445	4.48	648.2051	- Company - Comp
GRD MW04S			5.625	648.82	
22MW04S	5.58	653. 935	6.09	648.355	
GRD MW 085			5.10	648.8351	
22 MW085	5-405	653.8651	5.475	648.46	
GRDMW 035			4. 87	648.995	
22.MW03S	5.45	654.185	5./3	648. 735	
GRD MWOI	VEW		4-88	649.3051	
22MW OI NEW	5.4/5	654.34	5.26	648.925	
GRD MWOZ	NEW		5.03	649.31 /	ad an emission and the second
22 MW021	VEW 5.195	654.255	5.28	649.06	
GRD MWO	3 NEW		4.95	649.305	
22 MW 03 M	1	654.085	5.23	649, 025	
	4.535	652.74	5.88	648.205	
					ļ
BM-2			3.895	648.845	(-0.005)
MIN					1

Ma		6	12	21	יר <i>ח</i> ב	,					, ,	·VA	-	2 <i>8</i>
77,0	161		14,		U/	!		}	· · · · · ·			T. M	7	T
	X	@	АЛ	28	76						†	. HT=		ļ
		1	CHK				1	1	:		/			
	200	9 <i>-</i> _	337	(CHK	A	J 26	8/3	H	'D=	0.	0/	-).	
A	lai	ch	, 7 /	3, 2	200	7			ļ	1.	7:	VAN	ЖO	v
										- 4	2.;	7- M	ILL	EA
ST		ES	+ "	70 P	CON	/	EVE	:	EL					
ROI			1. 92 1. 92	-					3.6	30				
BM.			4.//3			5.5. 0.4		<i>*</i>	3.6	-				
								J						
S	7A		+			$\overline{\lambda}$			_			EL		
BI EE E			4.1 16R		6	93.	66 1					689.	49	/
MV	V 05		2-	335	- 6	:91-	70 1	·	4.	295		689	, 3 <i>6</i>	51
BM E M S	-10		<i>3.</i>	02	6	88.	775	-/	5.	945		68	<i>5.</i> 7.	55
-	w o		 	645	e.	5 8 5.	36		<u>5</u>	06		68.	3. 71	·5

field sketch

for


location of 3 monitoring wells at Site 22 at Great Lakes Naval Training Station



All dimensions hereon shown unless it is otherwise noted are given in feet and decimal parts thereof.

Copyright 2007 James Anderson Company, all rights reserved.

scale: 1 inch = 20 feet



or

Tetra Tech NUS, Inc. 661 Andersen Drive Pittsburgh, Pennsylvania 15220 FROM THE OFFICE OF

JAMES ANDERSON COMPANY

ENGINEERS, PLANNERS, AND SURVEYORS

920 WEST NORTH SHORE DRIVE

LAKE BLUFF, ILLINOIS, 60044

847 - 295-3322

APPENDIX F

LABORATORY ANALYTICAL DATA, CHAIN OF CUSTODY RECORDS, AND VALIDATION INFORMATION

NOVEMBER 2005



Tetra Tech NUS

INTERNAL CORRESPONDENCE

TO:

B. DAVIS

DATE:

JANUARY 20, 2006

FROM:

EDWARD SEDLMYER

COPIES:

DV FILE

SUBJECT:

ORGANIC DATA VALIDATION- VOA

CTO 0009, NTC GREAT LAKES

SDG 5K18318

SAMPLES:

7/Aqueous

NTC22FD03 NTC22MW10D02 NTC22MW05S02

NTC22MW06S02

NTC22TB02

NTC22MW10S02

NTC22TB01

16/Solid

NTC22SB200203 NTC22SB210405 NTC22SB220708 NTC22SB230203

NTC22SB211112 NTC22SB221112 NTC22SB240102

NTC22SB250203

NTC22SB200506

NTC22SB220203 NTC22SB230102 NTC22SB240203

NTC22FD01

NTC22SB210203

NTC22SB250102

NTC22FD02

OVERVIEW

The sample set for CTO 0009 NTC Great Lakes, SDG 5K18318 consists of two (2) trip blanks, five (5) aqueous environmental samples, and sixteen (16) solid environmental samples. The samples were analyzed for select chlorinated volatile organic compounds (VOCs). Three field duplicate pairs were included in this SDG: NTC22SB210405/NTC22FD01, NTC22SB221112/NTC22FD02, and NTC22MW06S02/NTC22FD03.

The samples were collected by TetraTech NUS on November 17 and 20, 2005 and analyzed by STL Laboratories Laboratories. All analyses were conducted in accordance with Naval Facilities Engineering Service Center (NFESC) Quality Assurance/Quality Control (QA/QC) criteria. All analyses were conducted using USEPA SW- 846 Method 8260B analytical and reporting protocol. The data contained in this SDG were validated with regard to the following parameters:

- Data completeness
- Holding times
- Initial/continuing calibrations
- Laboratory method blank results
- Field Duplicate Results
- **Detection Limits**

In addition, samples NTC22SB210405 and NTC22MW06S02 was also validated with regard to the following parameters:

- Surrogate Recoveries
 - Blank Spike/Blank Spike Duplicate Results
- Matrix Spike/Matrix Spike Duplicate Results
 - Internal Standard Recoveries
 - Compound Quantitation

TO: B. DAVIS

DATE: JANUARY 20, 2006 - PAGE 2

Compound Identification

The symbol (*) indicates that quality control criteria were met for this parameter. Problems affecting data quality are discussed below; documentation supporting these findings is presented in Appendix C. Qualified Analytical results are presented in Appendix A. Results as reported by the laboratory are presented in Appendix B.

Volatile

The following compound was detected in the method blank associated with the diluted aqueous samples:

CompoundMaximumBlankConcentrationAction LevelTetrachloroethene(1)0.64 ug/L6.4 μg/L

- Value < Reporting Limit (RL); report RL followed by a U.
- Value > RL and < Action level; report value followed by a U.
- Value > RL and > Action level; report value followed by a BJ.
- 1- Concentration detected in a method blank analyzed on 12/1/05 on instrument UX15. Only diluted samples analyzed on this date were evaluated relative to this blank.

No action was taken for blank contamination because the tetrachloroethene concentrations in samples NTC22MW06S02 and NTC22FD03 were greater than 10X the blank action level. Sample NTC22MW10S02 had a tetrachloroethene concentration of 3.5 ug/L, which is less than the adjusted blank action level, but because tetrachloroethene is a compound that may be present in the sample the data validator used professional judgment to qualify the result as estimated, J, instead of negating the result because of the method blank contamination.

A continuing calibration had a %D outside the 25% quality control limit on 11/29/05 at 10:27 for chloroethane. The non-detected result for chloroethane was qualified as estimated, UJ, for sample NTC22SB210405.

Field duplicate imprecision was noted for tetrachloroethene for the field duplicate pairs NTC22SB210405/NTC22FD01 and NTC22SB221112/NTC22FD02. The results for tetrachloroethene have been qualified as estimated in the field duplicate pairs NTC22SB210405/NTC22FD01 and NTC22SB221112/NTC22FD02.

Samples NTC22SB200203, NTC22SB210203, NTC22SB210405, NTC22SB220203, NTC22SB221112, NTC22SB230203, NTC22SB230102, NTC22SB240102, NTC22SB240203, NTCSB250102, NTC22FD01, NTCFD02, NTC22MW10S02, NTC22MW06S02, and NTC22FD03 were analyzed at dilutions due to high concentrations of target analytes. No action was taken based on the dilutions.

Additional Comments:

Positive results less than the reporting limit (RL) were qualified as estimated, J, due to uncertainty near the detection limit.

The laboratory incorrectly transposed a sample ID on the VOA Form I. The sample ID NTC22SB2102 has been corrected in the database to NTC22SB210203.

TO: B. DAVIS

DATE: JANUARY 20, 2006 - PAGE 3

The original EDD provided by the laboratory did not have data reported for all soil samples. The laboratory was contacted and a new EDD was submitted.

Form Is for all soil samples did not display positive results reported at concentrations below the reporting limit. The laboratory was contacted and re-submitted Form Is were provided. The database was unaffected by this issue.

EXECUTIVE SUMMARY

Laboratory Performance Issues: Chloroethane exceeded the continuing calibration %D criteria. Tetrachloroethene was detected in an aqueous laboratory preparation blank. Several compounds exceeded the linear calibration range of the instrument.

Other factors affecting data quality: Field duplicate imprecision was noted in two field duplicate pairs. Tetrachloroethene was detected in an aqueous laboratory preparation blank.

The data for these analyses were reviewed with reference to the EPA Functional Guidelines for Organic Data Validation (10/99), EPA Region V Validation Guidelines (08/93), and the NFESC guidelines IRCDQM (Sept., 1999). The text of this report has been formulated to address only those problem areas affecting data quality.

"I attest that the data referenced herein were validated according to the agreed upon validation criteria as specified in the NFESC guidelines and the Quality Assurance Project Plan (QAPP)."

Tetra Tech NUS

Edward Sedlmyer Chemist/Data Validator

Joseph A. Samchuck

etraTech NUS

Data Validation Quality Assurance Officer

Attachments:

Appendix A - Qualified Analytical Results

Appendix B - Results as Reported by the Laboratory

Appendix C - Support Documentation

APPENDIX A

QUALIFIED ANALYTICAL RESULTS

Data Validation Qualifier Codes:

A = Lab Blank Contamination

B = Field Blank Contamination

C = Calibration Noncompliance (e.g. % RSDs, %Ds, ICVs, CCVs, RRFs, etc.)

C01 = GC/MS Tuning Noncompliance

D = MS/MSD Recovery Noncompliance

E = LCS/LCSD Recovery Noncompliance

F = Lab Duplicate Imprecision

G = Field Duplicate Imprecision

H = Holding Time Exceedance

= ICP Serial Dilution Noncompliance

J = GFAA PDS - GFAA MSA's r < 0.995

K = ICP Interference - includes ICS % R Noncompliance

L = Instrument Calibration Range Exceedance

M = Sample Preservation Noncompliance

N = Internal Standard Noncompliance

N01 = Internal Standard Recovery Noncompliance Dioxins

N02 = Recovery Standard Noncompliance Dioxins

N03 = Clean-up Standard Noncompliance Dioxins

O = Poor Instrument Performance (e.g. base-line drifting)

P = Uncertainty near detection limit (< 2 x IDL for inorganics and <CRQL for organics)

Q = Other problems (can encompass a number of issues; e.g. chromatography,interferences, etc.)

R = Surrogates Recovery Noncompliance

S = Pesticide/PCB Resolution

T = % Breakdown Noncompliance for DDT and Endrin

U = % Difference between columns/detectors >25% for positive results determined via GC/HPLC

V = Non-linear calibrations; correlation coefficient r < 0.995

W = EMPC result

X = Signal to noise response drop

Y = Percent solids <30%

Z = Uncertainty at 2 sigma deviation is greater than sample activity

APPENDIX A

QUALIFIED ANALYTICAL RESULTS

SDG: 5K18318 MEDIA: SOIL DATA FRACTION: OV

NTC22FD01 nsample NTC22FD02 nsample nsample NTC22SB200203 samp_date samp_date 11/17/2005 11/17/2005 samp_date 11/17/2005 lab_id lab_id lab_id A5K180318015 A5K180318016 A5K180318001 qc_type NM NM NM qc_type qc_type UG/KG UG/KG UG/KG units units units Pct_Solids Pct_Solids Pct_Solids 85.0 83.0 82.0 DUP_OF: DUP_OF: DUP_OF: NTC22SB210405 NTC22SB221112

	1		
Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	2300	U	
1,1,1-TRICHLOROETHANE	160	J	Р
1,1,2,2-TETRACHLOROETHANE	2300	U	
1,1,2-TRICHLOROETHANE	2300	U	
1,1-DICHLOROETHANE	2300	U	
1,1-DICHLOROETHENE	2300	U	
1,2-DICHLOROETHANE	2300	U	-
CARBON TETRACHLORIDE	2300	U	
CHLOROETHANE	2300	U	
CHLOROMETHANE	2300	U	
CIS-1,2-DICHLOROETHENE	11000		
TETRACHLOROETHENE	74000	J	G
TRANS-1,2-DICHLOROETHENE	2300	U	
TRICHLOROETHENE	7900		
VINYL CHLORIDE	2300	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	3200	U	
1,1,1-TRICHLOROETHANE	3200	U	
1,1,2,2-TETRACHLOROETHANE	3200	U	
1,1,2-TRICHLOROETHANE	3200	U	
1,1-DICHLOROETHANE	3200	U	
1,1-DICHLOROETHENE	3200	U.	
1,2-DICHLOROETHANE	3200	U.	
CARBON TETRACHLORIDE	3200	Ü	
CHLOROETHANE	3200	U	
CHLOROMETHANE	3200	Ū	
CIS-1,2-DICHLOROETHENE	3200	U.	
TETRACHLOROETHENE	100000	J	G
TRANS-1,2-DICHLOROETHENE	3200	Ų	
TRICHLOROETHENE	620	J	Р
VINYL CHLORIDE	3200	Ü	

Result	Val Qual	Qual Code
850	U	
850	U	
850	U	
850	U	Ī
850	U	
850	U	
850	υ	
850	U	
26000		
850	U	
850	U	
850	U	
	850 850 850 850 850 850 850 850 850 850	Result Qual 850 U

SDG: 5K18318 MEDIA: SOIL DATA FRACTION: OV

NTC22SB210405 NTC22SB210203 nsample nsample nsample NTC22SB200506 11/17/2005 11/17/2005 samp_date samp_date 11/17/2005 samp_date lab_id A5K180318004 lab_id A5K180318003 lab_id A5K180318002 NM qc_type NM qc_type NM qc_type UG/KG UG/KG units units UG/KG units 81.0 Pct_Solids 80.0 86.0 Pct_Solids Pct_Solids DUP_OF: DUP_OF:

Parameter	Result	Vai Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	4.4	U	-
1,1,1-TRICHLOROETHANE	4.4	U	
1,1,2,2-TETRACHLOROETHANE	4.4	U	
1,1,2-TRICHLOROETHANE	4.4	U	
1,1-DICHLOROETHANE	4.4	U	
1,1-DICHLOROETHENE	4.4	U	
1,2-DICHLOROETHANE	4.4	U	
CARBON TETRACHLORIDE	4.4	U	
CHLOROETHANE	4.4	U	
CHLOROMETHANE	4.4	U	
CIS-1,2-DICHLOROETHENE	4.4	U	
TETRACHLOROETHENE	4.4	U	
TRANS-1,2-DICHLOROETHENE	4.4	U	
TRICHLOROETHENE	4.4	U	
VINYL CHLORIDE	4.4	U	

	Parameter	Result	Val Qual	Qual Code
1	1,1,1,2-TETRACHLOROETHANE	240	U	
1	1,1,1-TRICHLOROETHANE	120	J	Р
1	1,1,2,2-TETRACHLOROETHANE	240	U	
1	1,1,2-TRICHLOROETHANE	240	U	
1	1,1-DICHLOROETHANE	31	J	Р
1	1,1-DICHLOROETHENE	37	J	Р
1	1,2-DICHLOROETHANE	240	U	
1	CARBON TETRACHLORIDE	240	U	
1	CHLOROETHANE	240	υ	
1	CHLOROMETHANE	240	U	
1	CIS-1,2-DICHLOROETHENE	5800		
1	TETRACHLOROETHENE	9300		
1	TRANS-1,2-DICHLOROETHENE	130	J	Ρ.
1	TRICHLOROETHENE	1800		
1	VINYL CHLORIDE	38	J	Р

		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	4900	U	
1,1,1-TRICHLOROETHANE	4900	U	
1,1,2,2-TETRACHLOROETHANE	4900	U	
1,1,2-TRICHLOROETHANE	4900	U	
1,1-DICHLOROETHANE	4900	U	
1,1-DICHLOROETHENE	4900	U	
1,2-DICHLOROETHANE	4900	U	
CARBON TETRACHLORIDE	4900	U	
CHLOROETHANE	4900	UJ	С
CHLOROMETHANE	4900	U	
CIS-1,2-DICHLOROETHENE	13000		
TETRACHLOROETHENE	160000	J	G
TRANS-1,2-DICHLOROETHENE	4900	U	
TRICHLOROETHENE	10000		
VINYL CHLORIDE	4900	U	

SDG: 5K18318 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date NTC22SB211112

nsample samp_date lab_id NTC22SB220203 11/17/2005 nsample samp_date NTC22SB220708 11/17/2005

lab_id qc_type 11/17/2005 A5K180318005

qc_type

A5K180318006 NM lab_id qc_type

A5K180318007 NM

units
Pct_Solids

NM UG/KG 86.0

units
Pct_Solids

DUP_OF: 1

UG/KG 82.0

units
Pct_Solids
DUP_OF:

UG/KG 82.0

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	4.4	U	
1,1,1-TRICHLOROETHANE	4.4	U	
1,1,2,2-TETRACHLOROETHANE	4.4	U	
1,1,2-TRICHLOROETHANE	4.4	U	
1,1-DICHLOROETHANE	4.4	U	
1,1-DICHLOROETHENE	4.4	U	
1,2-DICHLOROETHANE	4.4	U	
CARBON TETRACHLORIDE	4.4	U	
CHLOROETHANE	4.4	U	
CHLOROMETHANE	4.4	U	
CIS-1,2-DICHLOROETHENE	4.4	U	
TETRACHLOROETHENE	2.4	J	P
TRANS-1,2-DICHLOROETHENE	4.4	υ	
TRICHLOROETHENE	4.4	U	
VINYL CHLORIDE	4.4	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	610	U	
1,1,1-TRICHLOROETHANE	610	U	
1,1,2,2-TETRACHLOROETHANE	610	U	
1,1,2-TRICHLOROETHANE	610	U	
1,1-DICHLOROETHANE	610	U	
1,1-DICHLOROETHENE	610	U	
1,2-DICHLOROETHANE	610	U	
CARBON TETRACHLORIDE	610	υ	
CHLOROETHANE	610	υ	
CHLOROMETHANE	610	U	
CIS-1,2-DICHLOROETHENE	110	٦	Р
TETRACHLOROETHENE	19000		
TRANS-1,2-DICHLOROETHENE	610	U	
TRICHLOROETHENE	260	J	Р
VINYL CHLORIDE	610	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	4.9	U	
1,1,1-TRICHLOROETHANE	4.9	U	
1,1,2,2-TETRACHLOROETHANE	4.9	U	
1,1,2-TRICHLOROETHANE	4.9	U	
1,1-DICHLOROETHANE	4.9	U	
1,1-DICHLOROETHENE	4.9	U	
1,2-DICHLOROETHANE	4.9	Ū	
CARBON TETRACHLORIDE	4.9	U	
CHLOROETHANE	4.9	U	
CHLOROMETHANE	4.9	U	
CIS-1,2-DICHLOROETHENE	0.56	J	Р
TETRACHLOROETHENE	1.4	J	Р
TRANS-1,2-DICHLOROETHENE	4.9	U	
TRICHLOROETHENE	4.9	U	
VINYL CHLORIDE	4.9	υ	

SDG: 5K18318 MEDIA: SOIL DATA FRACTION: OV

NTC22SB230203 NTC22SB221112 nsample NTC22SB230102 nsample nsample samp_date 11/17/2005 samp_date 11/17/2005 samp_date 11/17/2005 lab_id A5K180318009 A5K180318010 lab_id A5K180318008 lab_id NM NM NM qc_type qc_type qc_type UG/KG UG/KG units units UG/KG units 77.0 79.0 Pct_Solids 86.0 Pct_Solids Pct_Solids DUP_OF: DUP_OF: DUP_OF:

	Val	Qual
Result	Qual	Code
5800	U	
200000	J	G
5800	U	
690	J	P
5800	U	
	5800 5800 5800 5800 5800 5800 5800 5800	Result Qual 5800 U 690 J

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	270	U,	
1,1,1-TRICHLOROETHANE	270	U	
1,1,2,2-TETRACHLOROETHANE	270	U	
1,1,2-TRICHLOROETHANE	270	U	
1,1-DICHLOROETHANE	270	U	
1,1-DICHLOROETHENE	270	U	
1,2-DICHLOROETHANE	270	U	
CARBON TETRACHLORIDE	270	U	
CHLOROETHANE	270	U	
CHLOROMETHANE	270	U	
CIS-1,2-DICHLOROETHENE	270	U	
TETRACHLOROETHENE	400		
TRANS-1,2-DICHLOROETHENE	270	U	
TRICHLOROETHENE	270	U	
VINYL CHLORIDE	270	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	280	υ	
1,1,1-TRICHLOROETHANE	280	U	
1,1,2,2-TETRACHLOROETHANE	280	U	
1,1,2-TRICHLOROETHANE	280	U	
1,1-DICHLOROETHANE	280	U	
1,1-DICHLOROETHENE	280	U	
1,2-DICHLOROETHANE	280	U	
CARBON TETRACHLORIDE	280	U	
CHLOROETHANE	280	U	
CHLOROMETHANE	280	U	
CIS-1,2-DICHLOROETHENE	280	U	
TETRACHLOROETHENE	1200		
TRANS-1,2-DICHLOROETHENE	280	U	
TRICHLOROETHENE	280	U	
VINYL CHLORIDE	280	U	

SDG: 5K18318 MEDIA: SOIL DATA FRACTION: OV

 nsample
 NTC22SB240102

 samp_date
 11/17/2005

 lab_id
 A5K180318011

 qc_type
 NM

 units
 UG/KG

Pct_Solids 79.6

79.0

nsample samp_date lab_id qc_type units

Pct_Solids DUP_OF:

11/17/2005 A5K180318012 NM UG/KG 80.0

NTC22SB240203

samp_date lab_id qc_type units Pct_Solids DUP_OF:

nsample

11/17/2005 A5K180318013 NM UG/KG 77.0

NTC22SB250102

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	270	U	
1,1,1-TRICHLOROETHANE	270	U	
1,1,2,2-TETRACHLOROETHANE	270	U	
1,1,2-TRICHLOROETHANE	270	U	<u> </u>
1,1-DICHLOROETHANE	270	U	
1,1-DICHLOROETHENE	270	υ	
1,2-DICHLOROETHANE	270	U	
CARBON TETRACHLORIDE	270	U	
CHLOROETHANE	270	U	
CHLOROMETHANE	270	U	
CIS-1,2-DICHLOROETHENE	270	U	
TETRACHLOROETHENE	720		
TRANS-1,2-DICHLOROETHENE	270	U	· ·
TRICHLOROETHENE	270	U	
VINYL CHLORIDE	270	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	330	U	
1,1,1-TRICHLOROETHANE	330	U	
1,1,2,2-TETRACHLOROETHANE	330	U	
1,1,2-TRICHLOROETHANE	330	U	
1,1-DICHLOROETHANE	330	U	
1,1-DICHLOROETHENE	330	U	
1,2-DICHLOROETHANE	330	U	
CARBON TETRACHLORIDE	330	U	
CHLOROETHANE	330	U	
CHLOROMETHANE	330	U	
CIS-1,2-DICHLOROETHENE	330	U	
TETRACHLOROETHENE	1200		
TRANS-1,2-DICHLOROETHENE	330	U	
TRICHLOROETHENE	330	U	
VINYL CHLORIDE	330	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	260	U	
1,1,1-TRICHLOROETHANE	260	U	
1,1,2,2-TETRACHLOROETHANE	260	U	
1,1,2-TRICHLOROETHANE	260	U	
1,1-DICHLOROETHANE	260	U	
1,1-DICHLOROETHENE	260	U	
1,2-DICHLOROETHANE	260	U	
CARBON TETRACHLORIDE	260	U	
CHLOROETHANE	260	U	
CHLOROMETHANE	260	U	
CIS-1,2-DICHLOROETHENE	260	U	
TETRACHLOROETHENE	2800		
TRANS-1,2-DICHLOROETHENE	260	U	
TRICHLOROETHENE	260	U	
VINYL CHLORIDE	260	U	

SDG: 5K18318 MEDIA: SOIL DATA FRACTION: OV

nsample

NTC22SB250203

samp_date

11/17/2005

lab_id

A5K180318014

qc_type

NM ·

units

UG/KG

Pct_Solids

83.0

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	5	· U	
1,1,1-TRICHLOROETHANE	5	U	
1,1,2,2-TETRACHLOROETHANE	5	U	
1,1,2-TRICHLOROETHANE	5	U	
1,1-DICHLOROETHANE	5	U	N
1,1-DICHLOROETHENE	5	U	
1,2-DICHLOROETHANE	5	U	
CARBON TETRACHLORIDE	5	U	
CHLOROETHANE	5	U	
CHLOROMETHANE	5	U	
CIS-1,2-DICHLOROETHENE	5	υ	
TETRACHLOROETHENE	1.3	J	P
TRANS-1,2-DICHLOROETHENE	5	U	
TRICHLOROETHENE	5	U	
VINYL CHLORIDE	5	U	

SDG: 5K18318 MEDIA: WATER DATA FRACTION: OV

nsample samp_date lab_id qc_type

NTC22FD03 11/20/2005

A5K220298005 NM UG/L

samp_date lab_id qc_type units Pct_Solids

nsample

NTC22MW05S02 11/20/2005 A5K220298001 NM

UG/L

samp_date lab_id qc_type units Pct_Solids

nsample

11/20/2005 A5K220298004

NTC22MW06S02

NM UG/L

Pct_Solids

units

DUP_OF:

NTC22MW06S02

DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1400	U	
1,1,1-TRICHLOROETHANE	1400	U	
1,1,2,2-TETRACHLOROETHANE	1400	U	
1,1,2-TRICHLOROETHANE	1400	U	
1,1-DICHLOROETHANE	1400	U	
1,1-DICHLOROETHENE	1400	U	
1,2-DICHLOROETHANE	1400	Ü	
CARBON TETRACHLORIDE	1400	U	
CHLOROETHANE	1400	U	
CHLOROMETHANE	1400	U	
CIS-1,2-DICHLOROETHENE	870	J	P
TETRACHLOROETHENE	43000		
TRANS-1,2-DICHLOROETHENE	1400	U	
TRICHLOROETHENE	730	J	P
VINYL CHLORIDE	1400	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U,	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	1	U	
TETRACHLOROETHENE	1	U	
TRANS-1,2-DICHLOROETHENE	1	U	
TRICHLOROETHENE	1	U	
VINYL CHLORIDE	1	· U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1400	U	
1,1,1-TRICHLOROETHANE	1400	U	
1,1,2,2-TETRACHLOROETHANE	1400	U	
1,1,2-TRICHLOROETHANE	1400	U	
1,1-DICHLOROETHANE	1400	U	
1,1-DICHLOROETHENE	1400	U	
1,2-DICHLOROETHANE	1400	U	
CARBON TETRACHLORIDE	1400	U	
CHLOROETHANE	1400	U	
CHLOROMETHANE	1400	U	
CIS-1,2-DICHLOROETHENE	930	J	Ρ.
TETRACHLOROETHENE	45000		
TRANS-1,2-DICHLOROETHENE	1400	U	
TRICHLOROETHENE	760	J	P
VINYL CHLORIDE	1400	Ü	

00202

SDG: 5K18318 MEDIA: WATER DATA FRACTION: OV

nsample samp_date lab_id

NTC22MW10D02

11/20/2005 A5K220298002

NM qc_type UG/L units

Pct_Solids DUP_OF:

samp_date lab_id qc_type

nsample

A5K220298003 NM units

UG/L

NTC22MW10S02

11/20/2005

nsample samp_date

lab_id qc_type units

NTC22TB01 11/17/2005 A5K180318017

NM UG/L

Pct_Solids DUP_OF:

Pct_Solids DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	Ų	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	4		
TETRACHLOROETHENE	1	U	
TRANS-1,2-DICHLOROETHENE	0.38	J	Р
TRICHLOROETHENE	1	U	
VINYL CHLORIDE	1.3		

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	2	U	
1,1,1-TRICHLOROETHANE	2	U	
1,1,2,2-TETRACHLOROETHANE	2	U	
1,1,2-TRICHLOROETHANE	2	U	
1,1-DICHLOROETHANE	2	U	
1,1-DICHLOROETHENE	2	U	
1,2-DICHLOROETHANE	2	U	
CARBON TETRACHLORIDE	2	U	
CHLOROETHANE	2	U	
CHLOROMETHANE	2	U	
CIS-1,2-DICHLOROETHENE	52		
TETRACHLOROETHENE	3.5	BJ	Α
TRANS-1,2-DICHLOROETHENE	0.56	J	Р
TRICHLOROETHENE	2	U	
VINYL CHLORIDE	2	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	ט	
1,1,1-TRICHLOROETHANE	1	υ	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	υ	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	IJ	
CIS-1,2-DICHLOROETHENE	. 1	U	
TETRACHLOROETHENE	1	Ü	
TRANS-1,2-DICHLOROETHENE	1	כ	
TRICHLOROETHENE	1	U	
VINYL CHLORIDE	1	Ü	

APPENDIX B

RESULTS AS REPORTED BY THE LABORATORY

Client Sample ID: NTC22FD01

GC/MS Volatiles

Lot-Sample #: A5K180318-015 Date Sampled: 11/17/05 Prep Date: 11/18/05 Prep Batch #: 5333323 Dilution Factor: 7.96	Work Order #: Date Received: Analysis Date:	11/18/05 11/29/05	<pre>Matrix: S0 Final Wgt/Vol: 5 mL</pre>
% Moisture: 15	<pre>Initial Wgt/Vol: Method:</pre>	-	<u> </u>
		REPORTING	
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	2300	ug/kg
Chloroethane	ND	2300	ug/kg
Chloromethane	ND	2300	ug/kg
1,1-Dichloroethane	ND	2300	ug/kg
1,2-Dichloroethane	ND	2300	ug/kg
1,1-Dichloroethene	ND	2300	ug/kg
cis-1,2-Dichloroethene	11000	2300	ug/kg
trans-1,2-Dichloroethene	ND	2300	ug/kg
1,1,1,2-Tetrachloroethane	ND	2300	ug/kg
1,1,2,2-Tetrachloroethane	ND	2300	ug/kg
Tetrachloroethene	74000	2300	ug/kg
1,1,1-Trichloroethane	160 J	2300	ug/kg
1,1,2-Trichloroethane	ND	2300	ug/kg
Trichloroethene	7900	2300	ug/kg
Vinyl chloride	ND	2300	ug/kg
	PERCENT	RECOVERY	
SURROGATE	RECOVERY	LIMITS	
Dibromofluoromethane	75 DIL	(59 - 138)	
1,2-Dichloroethane-d4	79 DIL	(61 - 130)	
Toluene-d8	75 DIL	(60 - 143)	
4-Bromofluorobenzene	59 DIL	(47 - 158)	

NOTE (S):

DIL The concentration is estimated or not reported due to dilution or the presence of interfering analytes.

Results and reporting limits have been adjusted for dry weight.

J Estimated result. Result is less than RL.

Client Sample ID: NTC22FD02

GC/MS Volatiles

Lot-Sample #: A5K180318-016 Date Sampled: 11/17/05 Prep Date: 11/18/05 Prep Batch #: 5333323	Work Order #: Date Received: Analysis Date:	11/18/05	Matrix: SO
Dilution Factor: 10.74	<pre>Initial Wgt/Vol:</pre>	6.65 g	Final Wgt/Vol: 5 mL
% Moisture: 17	Method:	-	В
		REPORTING	*****
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	3200	ug/kg
Chloroethane	ND	3200	ug/kg
Chloromethane	ND	3200	ug/kg
1,1-Dichloroethane	ND	3200	ug/kg
1,2-Dichloroethane	ND	3200	ug/kg
1,1-Dichloroethene	ND	3200	ug/kg
cis-1,2-Dichloroethene	ND	3200	ug/kg
trans-1,2-Dichloroethene	ND	3200	ug/kg
1,1,1,2-Tetrachloroethane	ND	3200	ug/kg
1,1,2,2-Tetrachloroethane	ND	3200	ug/kg
Tetrachloroethene	100000	3200	ug/kg
1,1,1-Trichloroethane	ND	3200	ug/kg
1,1,2-Trichloroethane	ND	3200	ug/kg
Trichloroethene	620 J	3200	ug/kg
Vinyl chloride	ND	3200	ug/kg
	PERCENT	RECOVERY	
CUDDOCA WE		LIMITS	
SURROGATE	RECOVERY		•
Dibromofluoromethane	64 DIL	(59 - 138)	
1,2-Dichloroethane-d4	59 DIL,*	(61 - 130)	
Toluene-d8	56 DIL,*	(60 - 143)	
4-Bromofluorobenzene	48 DIL	(47 - 158)	

NOTE (S):

DIL The concentration is estimated or not reported due to dilution or the presence of interfering analytes.

Surrogate recovery is outside stated control limits.

J Estimated result. Result is less than RL.

Client Sample ID: NTC22SB200203

GC/MS Volatiles

Lot-Sample #: A5K180318-001 Date Sampled: 11/17/05 14:20 Prep Date: 11/18/05 Prep Batch #: 5333323		11/18/05	Matrix:		so
Dilution Factor: 2.76 % Moisture: 18	<pre>Initial Wgt/Vol: Method:</pre>	6.03 g	Final	Wgt/Vol:	: 5 mL
		SW846 8260E	3		
	•	REPORTING			
PARAMETER	RESULT	LIMIT	UNITS		
Carbon tetrachloride	ND	850	ug/kg	-	
Chloroethane	ND	850	ug/kg		
Chloromethane	ND	850	ug/kg		
1,1-Dichloroethane	ND.	850	ug/kg		
1,2-Dichloroethane	ND	850	ug/kg		
1,1-Dichloroethene	ND	850	ug/kg		
cis-1,2-Dichloroethene	ND	850	ug/kg		
trans-1,2-Dichloroethene	ND	850	ug/kg		
1,1,1,2-Tetrachloroethane	ND	850	ug/kg		
1,1,2,2-Tetrachloroethane	ND .	850	ug/kg		
Tetrachloroethene	26000	850	ug/kg		
1,1,1-Trichloroethane	ND ·	850	ug/kg		
1,1,2-Trichloroethane	ND	850	ug/kg		
Trichloroethene	ND	850	ug/kg		
Vinyl chloride	ND	850	ug/kg		
	PERCENT	RECOVERY			
SURROGATE	RECOVERY	LIMITS			
Dibromofluoromethane	66 DIL	(59 - 138)			
1,2-Dichloroethane-d4	68 DIL	(61 - 130)			
Toluene-d8	65 DIL	(60 - 143)			
4-Bromofluorobenzene	50 DIL	(47 - 158)			

NOTE (S):

DIL The concentration is estimated or not reported due to dilution or the presence of interfering analytes.

Client Sample ID: NTC22SB200506

GC/MS Volatiles

Lot-Sample #: A5K180318-002 Date Sampled: 11/17/05 14:4 Prep Date: 11/29/05 Prep Batch #: 5334268		11/18/05	Matri	x:	SO
Dilution Factor: 0.76	<pre>Initial Wgt/Vol:</pre>	-		Wgt/Vol:	5 mL
% Moisture: 14	Method:	SW846 8260	В		
		REPORTING			
PARAMETER	RESULT	LIMIT	UNITS	_	
Carbon tetrachloride	ND	4.4	ug/kg		•
Chloroethane	ND	4.4	ug/kg		
Chloromethane	ND	4.4	ug/kg		
1,1-Dichloroethane	ND	4.4	ug/kg		
1,2-Dichloroethane	ND	4.4	ug/kg		
1,1-Dichloroethene	ND .	4.4	ug/kg		
cis-1,2-Dichloroethene	ND	4.4	ug/kg		•
trans-1,2-Dichloroethene	ND	4.4	ug/kg		
1,1,1,2-Tetrachloroethane	ND	4.4	ug/kg		
1,1,2,2-Tetrachloroethane	ND	4.4	ug/kg		
Tetrachloroethene	ND	4.4	ug/kg		
1,1,1-Trichloroethane	ND	4.4	ug/kg		
1,1,2-Trichloroethane	ND	4.4	ug/kg		
Trichloroethene	ND	4.4	ug/kg	•	
Vinyl chloride	ИД	4.4	ug/kg	V	
SURROGATE	PERCENT RECOVERY	RECOVERY LIMITS			
Dibromofluoromethane	99	(59 - 138)	•		
1,2-Dichloroethane-d4	93	(61 - 130)			
Toluene-d8	99	(60 - 143)			
4-Bromofluorobenzene	70	(47 - 158)			
NOTE (S):			······		

Client Sample ID: NTC22SB210203

GC/MS Volatiles

Lot-Sample #: A5K180318-003 Date Sampled: 11/17/05 15:15 Prep Date: 11/18/05 Prep Batch #: 5333323			11/18/05	Matrix SO
	Dilution Factor: 0.79 % Moisture: 19	<pre>Initial Wgt/Vol: Method:</pre>	•	Final Wgt/Vol: 5 mL
	PARAMETER	RESULT	REPORTING LIMIT	UNITS
	Carbon tetrachloride	ND	240	ug/kg
	Chloroethane	ND	240	
	Chloromethane	ND	240	ug/kg ug/kg
		31 J	240	ug/kg
	1,1-Dichloroethane 1,2-Dichloroethane	ND	240	ug/kg
	1,1-Dichloroethene	37 J	240	ug/kg
	•	5800	240	
	cis-1,2-Dichloroethene		240	ug/kg
	trans-1,2-Dichloroethene	130 J		ug/kg
	1,1,1,2-Tetrachloroethane	ND	240	ug/kg
	1,1,2,2-Tetrachloroethane	ND	240	ug/kg
	Tetrachloroethene	9300	240	ug/kg
	1,1,1-Trichloroethane	120 J	240	ug/kg
	1,1,2-Trichloroethane	ND	240	ug/kg
	Trichloroethene	1800	240	ug/kg
	Vinyl chloride	38 J	240	ug/kg
		PERCENT	RECOVERY	
	SURROGATE	RECOVERY	LIMITS	
	Dibromofluoromethane '	68	(59 - 138)	

(61 - 130)

(60 - 143)

(47 - 158)

68

70

56

NOTE (S):

Toluene-d8

Results and reporting limits have been adjusted for dry weight.

1,2-Dichloroethane-d4

4-Bromofluorobenzene

J Estimated result. Result is less than RL.

Client Sample ID: NTC22SB210405

GC/MS Volatiles

Dilution Factor: 15.8 Initial Wgt/Vol: 6.33 g Final Wgt/Vol.: 5 mI % Moisture: 20 Method: SW846 8260B	
% Moisture: 20 Method: SW846 8260B	L
REPORTING	
PARAMETER RESULT LIMIT UNITS	
Carbon tetrachloride ND 4900 ug/kg	
Chloroethane ND 4900 ug/kg	
Chloromethane ND 4900 ug/kg	
1,1-Dichloroethane ND 4900 ug/kg	
1,2-Dichloroethane ND 4900 ug/kg	
1,1-Dichloroethene ND 4900 ug/kg	
cis-1,2-Dichloroethene 13000 4900 ug/kg	
trans-1,2-Dichloroethene ND 4900 ug/kg	
1,1,1,2-Tetrachloroethane ND 4900 ug/kg	
1,1,2,2-Tetrachloroethane ND 4900 ug/kg	
Tetrachloroethene 160000 4900 ug/kg	
1,1,1-Trichloroethane ND 4900 ug/kg	
1,1,2-Trichloroethane ND 4900 ug/kg	
Trichloroethene 10000 4900 ug/kg	
Vinyl chloride ND 4900 ug/kg	
PERCENT RECOVERY	
SURROGATE RECOVERY LIMITS	
Dibromofluoromethane 68 DIL (59 - 138)	
1,2-Dichloroethane-d4 0.0 DIL,* (61 - 130)	
Toluene-d8 66 DIL (60 - 143)	
4-Bromofluorobenzene 66 DIL (47 - 158)	

NOTE (S):

DIL The concentration is estimated or not reported due to dilution or the presence of interfering analytes.

Surrogate recovery is outside stated control limits.

Client Sample ID: NTC22SB211112

GC/MS Volatiles

Lot-Sample #: A5K180318-005 Date Sampled: 11/17/05 16:00 Prep Date: 11/29/05 Prep Batch #: 5334268		11/18/05	Matrix SO
Dilution Factor: 0.76	<pre>Initial Wgt/Vol:</pre>	5 g	Final Wgt/Vol: 5 mL
% Moisture: 14	Method:	SW846 8260	B
		REPORTING	
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	4.4	ug/kg
Chloroethane	ND	4.4	ug/kg
Chloromethane	ND	4.4	ug/kg
1.1-Dichloroethane	ND	4.4	ug/kg
1,2-Dichloroethane	ND	4.4	ug/kg
1,1-Dichloroethene	ND	4.4	ug/kg
cis-1,2-Dichloroethene	ND	4.4	ug/kg
trans-1,2-Dichloroethene	ND	4.4	ug/kg
1,1,1,2-Tetrachloroethane	ND	4.4	ug/kg
1,1,2,2-Tetrachloroethane	ND	4.4	ug/kg
Tetrachloroethene	2.4 J	4.4	ug/kg
1,1,1-Trichloroethane	ND	4.4	ug/kg
1,1,2-Trichloroethane	ND	4.4	ug/kg
Trichloroethene	ND	4.4	ug/kg
Vinyl chloride	ND	4.4	ug/kg
	PERCENT	RECOVERY	
SURROGATE	RECOVERY	LIMITS	
Dibromofluoromethane	102·	$\frac{111113}{(59 - 138)}$	·
1,2-Dichloroethane-d4	91	(61 - 130)	
Toluene-d8	94	(60 - 143)	
4-Bromofluorobenzene	59	(47 - 158)	
	1	(2)	
NOTE (S):	P. C. D. T. C.		

J Estimated result. Result is less than RL.

Client Sample ID: NTC22SB220203

GC/MS Volatiles

Matrix....: SO

Date Sampled: 11/17/05	17:00	Date Received:	11/18/05			
Prep Date: 11/18/05		Analysis Date:	11/29/05			
Prep Batch #: 5333323						
Dilution Factor: 2.02		<pre>Initial Wgt/Vol:</pre>	6.18 g	Final	Wgt/Vol: 5	mL
% Moisture: 18		Method:	SW846 8260)B		
			REPORTING			
PARAMETER		RESULT	LIMIT	UNITS		
Carbon tetrachloride		ND	610	ug/kg		
Chloroethane		ND	610	ug/kg	•	
Chloromethane		ND	610	ug/kg		
1,1-Dichloroethane		ND	610	ug/kg		
1,2-Dichloroethane		ND .	610	ug/kg		
1,1-Dichloroethene		ND	610	ug/kg		
cis-1,2-Dichloroethene		110 J	610	ug/kg	•	
trans-1,2-Dichloroethene		ND	610	ug/kg		

610

610

610

610

610

610

610

ug/kg

ug/kg

ug/kg

ug/kg

ug/kg

ug/kg

ug/kg

	PERCENT.	RECOVERY
SURROGATE.	RECOVERY	LIMITS
Dibromofluoromethane	61 DIL	(59 - 138)
1,2-Dichloroethane-d4	62 DIL	(61 - 130)
Toluene-d8	62 DIL	(60 - 143)
4-Bromofluorobenzene	51 DIL	(47 - 158)

ND

ND

ND

ND

ND

19000

260 J

Lot-Sample #...: A5K180318-006 Work Order #...: HQKDG1AC

NOTE (S):

1,1,1,2-Tetrachloroethane

1,1,2,2-Tetrachloroethane

Tetrachloroethene

Trichloroethene

Vinyl chloride

1,1,1-Trichloroethane

1,1,2-Trichloroethane

DIL The concentration is estimated or not reported due to dilution or the presence of interfering analytes.

Results and reporting limits have been adjusted for dry weight.

J Estimated result. Result is less than RL.

Client Sample ID: NTC22SB220708

GC/MS Volatiles

Lot-Sample #: A5K180318-007 Date Sampled: 11/17/05 17:10 Prep Date: 11/29/05 Prep Batch #: 5334268	Work Order #: Date Received: Analysis Date:	11/18/05	Matri	K:	so
Dilution Factor: 0.81	<pre>Initial Wgt/Vol:</pre>	5 g	Final	Wgt/Vol:	5 mL
% Moisture: 18	Method:	SW846 8260	В		
		REPORTING		•	
PARAMETER	RESULT	LIMIT	UNITS		
Carbon tetrachloride	ND	4.9	ug/kg	-	
Chloroethane	ND	4.9	ug/kg		
Chloromethane	ND	4.9	ug/kg		
1,1-Dichloroethane	ND	4.9	ug/kg		
1,2-Dichloroethane	ND	4.9	ug/kg		•
1,1-Dichloroethene	ND	4.9	ug/kg		
cis-1,2-Dichloroethene	0.56 J	4.9	ug/kg		
trans-1,2-Dichloroethene	ND	4.9	ug/kg		
1,1,1,2-Tetrachloroethane	ND	4.9	ug/kg		
1,1,2,2-Tetrachloroethane	ND	4.9	ug/kg		
Tetrachloroethene	1.4 J	4.9	ug/kg		
1,1,1-Trichloroethane	ND	4.9	ug/kg		
1,1,2-Trichloroethane	ND	4.9	ug/kg		
Trichloroethene	ND	4.9	ug/kg		
Vinyl chloride	ND /	4.9	ug/kg		
	PERCENT	RECOVERY			
SURROGATE	RECOVERY	LIMITS			
Dibromofluoromethane	100	(59 - 138)			
1,2-Dichloroethane-d4	91	(61 - 130)			
Toluene-d8	97	(60 - 143)			
4-Bromofluorobenzene	62	(47 - 158)			

NOTE (S):

J Estimated result. Result is less than RL.

Client Sample ID: NTC22SB221112

GC/MS Volatiles

Lot-Sample #: A5K180318-008 Date Sampled: 11/17/05 17:30 Prep Date: 11/18/05 Prep Batch #: 5333323 Dilution Factor: 19.92 % Moisture: 14	Work Order #: Date Received: Analysis Date: Initial Wgt/Vol: Method:	11/18/05 11/28/05 5.02 g	Matrix: SO Final Wgt/Vol: 5 mL
		REPORTING	
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	5800	ug/kg
Chloroethane	ND	5800	ug/kg
Chloromethane	ND	5800	ug/kg
1,1-Dichloroethane	ND	5800	ug/kg
1,2-Dichloroethane	ND	5800	ug/kg
1,1-Dichloroethene	ND	5800	ug/kg
cis-1,2-Dichloroethene	ND	5800	ug/kg
trans-1,2-Dichloroethene	ND	5800	ug/kg
1,1,1,2-Tetrachloroethane	ND	5800	ug/kg
1,1,2,2-Tetrachloroethane	ND	5800	ug/kg
Tetrachloroethene	200000	5800	ug/kg
1,1,1-Trichloroethane	ND	5800	ug/kg
1,1,2-Trichloroethane	ND	5800	ug/kg
Trichloroethene	690 J	5800	ug/kg
Vinyl chloride	ND	5800	ug/kg
SURROGATE	PERCENT RECOVERY	RECOVERY LIMITS	
Dibromofluoromethane	69 DIL	(59 - 138)	
1,2-Dichloroethane-d4	73 DIL	(61 - 130)	
Toluene-d8	63 DIL	(60 - 143)	
4-Bromofluorobenzene	56 DIL	(47 - 158)	

NOTE(S):

DIL The concentration is estimated or not reported due to dilution or the presence of interfering analytes.

Results and reporting limits have been adjusted for dry weight.

J Estimated result. Result is less than RL.

Client Sample ID: NTC22SB230102

GC/MS Volatiles

Lot-Sample #: A5K180318-010	Work Order #: HQKDW1AC	Matrix SO
-----------------------------	------------------------	-----------

Date Sampled...: 11/17/05 13:10 Date Received..: 11/18/05 Prep Date....: 11/18/05 Analysis Date..: 11/29/05

Prep Date....: 11/18/05
Prep Batch #...: 5333323

Dilution Factor: 0.84 Initial Wgt/Vol: 5.94 g Final Wgt/Vol.: 5 mL

% Moisture....: 21 **Method.....:** SW846 8260B

PARAMETER	RESULT	REPORTING LIMIT	UNITS		
Carbon tetrachloride	ND ND	270	ug/kg	 • *	
Chloroethane	ND	270	ug/kg		
Chloromethane	ND	270	ug/kg		
1,1-Dichloroethane	ND	270	ug/kg		
1,2-Dichloroethane	ND	270	ug/kg		
1,1-Dichloroethene	ND	270	ug/kg		
cis-1,2-Dichloroethene	ND	270	ug/kg		
trans-1, 2-Dichloroethene	ND	270	ug/kg		
1,1,1,2-Tetrachloroethane	ND	270	ug/kg		
1,1,2,2-Tetrachloroethane	ND	270	ug/kg		
Tetrachloroethene	400	270	ug/kg		
1,1,1-Trichloroethane	ND	270	ug/kg		
1,1,2-Trichloroethane	ND	270	ug/kg		
Trichloroethene	ND	270	ug/kg		
Vinyl chloride	ND	270	ug/kg		•
tana di Kabupatèn K Kabupatèn Kabupatèn	PERCENT	RECOVERY	• .		
SURROGATE	RECOVERY	LIMITS			
Dibromofluoromethane	64	(59 - 138)	- 1	. 1	
1,2-Dichloroethane-d4	64	(61 - 130)			
Toluene-d8	66	(60 - 143)			
4-Bromofluorobenzene	56	(47 - 158)	r ·		

NOTE (S):

Client Sample ID: NTC22SB230203

GC/MS Volatiles

Lot-Sample #: A5K180318-009 Date Sampled: 11/17/05 13:30 Prep Date: 11/18/05 Prep Batch #: 5333323	Work Order #: Date Received: Analysis Date:	11/18/05	Matrix	ks
Dilution Factor: 0.88	<pre>Initial Wgt/Vol:</pre>	5.69 g	Final	Wgt/Vol: 5 mL
% Moisture: 23	Method:	SW846 82601	3	
		REPORTING		
PARAMETER	RESULT	LIMIT	UNITS	
Carbon tetrachloride	ND	280	ug/kg	
Chloroethane	ND	280	ug/kg	
Chloromethane	ND	280	ug/kg	
1,1-Dichloroethane	ND	280	ug/kg	
1,2-Dichloroethane	ND	280	ug/kg	
1,1-Dichloroethene	ND	280	ug/kg	
cis-1,2-Dichloroethene	ND	280	ug/kg	
trans-1,2-Dichloroethene	ND	280	ug/kg	*
1,1,1,2-Tetrachloroethane	ND	280	ug/kg	
1,1,2,2-Tetrachloroethane	ND	280	ug/kg	
Tetrachloroethene	1200	280	ug/kg	
1,1,1-Trichloroethane	ND	280	ug/kg	
1,1,2-Trichloroethane	ND	280	ug/kg	
Trichloroethene	ND	280	ug/kg	
	ND	280	ug/kg	
Vinyl chloride	ND	200	ug/ ng	
	PERCENT	RECOVERY		
SURROGATE	RECOVERY	LIMITS		
Dibromofluoromethane	68	(59 - 138)		
1,2-Dichloroethane-d4	67	(61 - 130)		

72

58

(60 - 143)

(47 - 158)

Results and reporting limits have been adjusted for dry weight.

Toluene-d8

NOTE (S):

4-Bromofluorobenzene

Client Sample ID: NTC22SB240102

GC/MS Volatiles

Lot-Sample #: A5K180318-011 Date Sampled: 11/17/05 12:30 Prep Date: 11/18/05 Prep Batch #: 5333323		11/18/05	Matrix: S	0
Dilution Factor: 0.85	<pre>Initial Wgt/Vol:</pre>	5.86 g	Final Wgt/Vol: 5	mL
% Moisture: 21	Method:	SW846 8260	В	
		REPORTING	· ·	
PARAMETER	RESULT	LIMIT	UNITS	
Carbon tetrachloride	ND	270	ug/kg	
Chloroethane	ND	270	ug/kg	
Chloromethane	ND	270	ug/kg	
1,1-Dichloroethane	ND	270	ug/kg	
1,2-Dichloroethane	ND	270	ug/kg	
1,1-Dichloroethene	ND	270	ug/kg	
cis-1,2-Dichloroethene	ND	270	ug/kg	
trans-1,2-Dichloroethene	ND	270	ug/kg	
1,1,1,2-Tetrachloroethane	ND	270	ug/kg	
1,1,2,2-Tetrachloroethane	ND ·	270	ug/kg	
Tetrachloroethene	720	270	ug/kg	
1,1,1-Trichloroethane	ND .	270	ug/kg	
1,1,2-Trichloroethane	ND	270	ug/kg	
Trichloroethene	ND	270	ug/kg	
Vinyl chloride	ND	270	ug/kg	
	DEDCENT	DECOVERY		

	PERCENT	RECOVERY
SURROGATE	RECOVERY	LIMITS
Dibromofluoromethane	68	(59 - 138)
1,2-Dichloroethane-d4	66	(61 - 130)
Toluene-d8	70	(60 - 143)
4-Bromofluorobenzene	57	(47 - 158)

NOTE (S):

Client Sample ID: NTC22SB240203

GC/MS Volatiles

	Lot-Sample #: A5K180318-012 Date Sampled: 11/17/05 12:30 Prep Date: 11/18/05 Prep Batch #: 5333323	Work Order #: Date Received: Analysis Date:	11/18/05	Matrix SO
	Dilution Factor: 1.05	<pre>Initial Wgt/Vol:</pre>	4.76 g	Final Wgt/Vol: 5 mL
	% Moisture: 20	Method:	SW846 8260I	3
			REPORTING	
		DDGIT B		UNITS
	PARAMETER	RESULT ND	LIMIT 330	ug/kg
	Carbon tetrachloride	ND	330	ug/kg
	Chloroethane		330	ug/kg
	Chloromethane	ND ND	330	ug/kg
	1,1-Dichloroethane	ND	330	ug/kg
	1,2-Dichloroethane 1,1-Dichloroethane	ND	330	ug/kg
	cis-1,2-Dichloroethene	ND	330	ug/kg
	•	ND	330	ug/kg
	trans-1,2-Dichloroethene	ND	330	ug/kg
	1,1,1,2-Tetrachloroethane 1,1,2,2-Tetrachloroethane	ND	330	ug/kg
	Tetrachloroethene	1200	330 330	ug/kg
		ND	330	ug/kg
	1,1,1-Trichloroethane		330	ug/kg
٠	1,1,2-Trichloroethane	ND	330	ug/kg
	Trichloroethene	ND	330	ug/kg
	Vinyl chloride	ND	330	ug/ kg
		PERCENT	RECOVERY	N
	SURROGATE	RECOVERY	LIMITS	
	Dibromofluoromethane	73	(59 - 138)	
	1,2-Dichloroethane-d4	74	(61 - 130)	
	Toluene-d8	.77	(60 - 143)	
	4-Bromofluorobenzene	63	(47 - 158)	
			•	

NOTE(S):

Client Sample ID: NTC22SB250102

GC/MS Volatiles

Lot-Sample #: A5K180318-013 Date Sampled: 11/17/05 Prep Date: 11/18/05 Prep Batch #: 5333323	Work Order #: Date Received: Analysis Date:	11/18/05	Matri	x:	SO
Dilution Factor: 0.8	Initial Wgt/Vol:			Wgt/Vol:	5 mL
% Moisture: 23	Method:	SW846 8260	В		
		REPORTING			
PARAMETER	RESULT	LIMIT	UNITS	_	
Carbon tetrachloride	ND	260	ug/kg		
Chloroethane	ND	260	ug/kg		
Chloromethane	ND	260	ug/kg		
1,1-Dichloroethane	ND	260	ug/kg		
1,2-Dichloroethane	ND	260	ug/kg		
1,1-Dichloroethene	ND	260	ug/kg		
cis-1,2-Dichloroethene	ND	260	ug/kg		
trans-1,2-Dichloroethene	ND	260	ug/kg		
1,1,1,2-Tetrachloroethane	ND	260	ug/kg		
1,1,2,2-Tetrachloroethane	ND	260	ug/kg		
Tetrachloroethene	2800	260	ug/kg		
1,1,1-Trichloroethane	ND	260	ug/kg		
1,1,2-Trichloroethane	ND	260	ug/kg		
Trichloroethene	ND	260	ug/kg		
Vinyl chloride	ND	260	ug/kg		
	PERCENT	RECOVERY			
SURROGATE	RECOVERY	LIMITS			
Dibromofluoromethane	69	(59 - 138)			
1,2-Dichloroethane-d4	72	(61 - 130)			
Toluene-d8	72	(60 - 143)			
4-Bromofluorobenzene	58	(47 - 158)	•		
NOTE (S):					

Client Sample ID: NTC22SB250203

GC/MS Volatiles

Lot-Sample #: A5K180318-014 Date Sampled: 11/17/05 Prep Date: 11/30/05 Prep Batch #: 5335163	Work Order #: Date Received: Analysis Date:	11/18/05	Matrix: SO
Dilution Factor: 0.83	<pre>Initial Wgt/Vol:</pre>	5 g	Final Wgt/Vol: 5 mL
% Moisture: 17	Method:	SW846 8260	В
		REPORTING	
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	5.0	ug/kg
Chloroethane	ND	5.0	ug/kg
Chloromethane	ND	5.0	ug/kg
1,1-Dichloroethane	ND	5.0	ug/kg
1,2-Dichloroethane	ND	5.0	ug/kg
1,1-Dichloroethene	ND	5.0	ug/kg
cis-1,2-Dichloroethene	ND ·	5.0	ug/kg
trans-1,2-Dichloroethene	ND	5.0	ug/kg
1,1,1,2-Tetrachloroethane	ND	5.0	ug/kg
1,1,2,2-Tetrachloroethane	ND .	5.0	ug/kg
Tetrachloroethene	1.3 J	5.0	ug/kg
1,1,1-Trichloroethane	ND	5.0	ug/kg
1,1,2-Trichloroethane	ND	5.0	ug/kg
Trichloroethene	ND	5.0	ug/kg
Vinyl chloride	ND	5.0	ug/kg
	PERCENT	RECOVERY	
SURROGATE	RECOVERY	LIMITS	
Dibromofluoromethane	89	(59 - 138)	
1,2-Dichloroethane-d4	85	(61 - 130)	
Toluene-d8	113	(60 - 143)	
4-Bromofluorobenzene	64	(47 - 158)	

NOTE(S):

J Estimated result. Result is less than RL.

Client Sample ID: NTC22FD03

GC/MS Volatiles

Lot-Sample #:	A5K220298-005	Work Order	#: HQRE41AA	Matrix	: WG

Date Sampled...: 11/20/05 Date Received..: 11/22/05 Prep Date....: 12/01/05 Analysis Date..: 12/01/05

Prep Batch #...: 5336244

Dilution Factor: 1428.6 Initial Wgt/Vol: 5 mL Final Wgt/Vol..: 5 mL

Method..... SW846 8260B

		REPORTING	
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	1400	ug/L
Chloroethane	ND	1400	ug/L
Chloromethane	ND	1400	ug/L
1,1-Dichloroethane	ND	1400	ug/L
1,2-Dichloroethane	ND	1400	ug/L
cis-1,2-Dichloroethene	870 J	1400	ug/L
trans-1,2-Dichloroethene	ND	1400	ug/L
1,1-Dichloroethene	ND	1400	ug/L
1,1,1,2-Tetrachloroethane	ND	1400	ug/L
1,1,2,2-Tetrachloroethane	ND	1400	ug/L
Tetrachloroethene	43000 B	1400	ug/L
1,1,1-Trichloroethane	ND	1400	ug/L
1,1,2-Trichloroethane	ND	1400	ug/L
Trichloroethene	730 J	1400	ug/L
Vinyl chloride	ND	1400	ug/L
	PERCENT	RECOVERY	
SURROGATE	RECOVERY	LIMITS	
Dibromofluoromethane	107	(73 - 122)	- } .
1,2-Dichloroethane-d4	108	(61 - 128)	•
Toluene-d8	107	(76 - 110)	1
4-Bromofluorobenzene	86	(74 - 116)	1

NOTE(S):

J Estimated result. Result is less than RL.

B Method blank contamination. The associated method blank contains the target analyte at a reportable level.

Client Sample ID: NTC22MW05S02

GC/MS Volatiles

Matrix.... WG Lot-Sample #...: A5K220298-001 Work Order #...: HQREP1AA

Date Sampled...: 11/20/05 11:40 Date Received..: 11/22/05 Prep Date....: 11/30/05 Prep Batch #...: 5335104 Analysis Date..: 11/30/05

Final Wgt/Vol..: 5 mL Dilution Factor: 1 Initial Wgt/Vol: 5 mL

	Method: SW846 8260B				
		REPORTIN	IG		
PARAMETER	RESULT	LIMIT	UNITS		
Carbon tetrachloride	ND	1.0	ug/L		
Chloroethane	ND	1.0	ug/L		
Chloromethane	ND	1.0	ug/L		
1,1-Dichloroethane	ND	1.0	ug/L		
1,2-Dichloroethane	ND	1.0	ug/L		
cis-1,2-Dichloroethene	ND	1.0	ug/L		
trans-1,2-Dichloroethene	ND	1.0	ug/L		
1,1-Dichloroethene	ND	1.0	ug/L		
1,1,1,2-Tetrachloroethane	ND	1.0	ug/L		
1,1,2,2-Tetrachloroethane	ND	1.0	ug/L		
Tetrachloroethene	ND	1.0	ug/L		
1,1,1-Trichloroethane	ND	1.0	ug/L		
1,1,2-Trichloroethane	ND	1.0	ug/L		
Trichloroethene	ND	1.0	ug/L		
Vinyl chloride	ND	1.0	ug/L		
	PERCENT	RECOVERY	ľ		
SURROGATE	RECOVERY	LIMITS	·		
Dibromofluoromethane	106	(73 - 12	22)		
1,2-Dichloroethane-d4	108	(61 - 12	28)		
Toluene-d8	104	(76 - 11	10)		
4-Bromofluorobenzene	85	(74 - 11)	16)		

	PERCENT	RECOVERY
SURROGATE	RECOVERY	LIMITS
Dibromofluoromethane	106	(73 - 122)
1,2-Dichloroethane-d4	108	(61 - 128)
Toluene-d8	104	(76 - 110)
4-Bromofluorobenzene	85	(74 - 116)

Client Sample ID: NTC22MW06S02

GC/MS Volatiles

Matrix....: WG

Date Sampled: 11/20/05 17:00	Date Received:	11/22/05		
Prep Date: 12/01/05	Analysis Date:	12/01/05		
Prep Batch #: 5336244				
Dilution Factor: 1428.6	<pre>Initial Wgt/Vol:</pre>	5 mL	Final	Wgt/Vol: 5 mL
	Method:	SW846 82601	3	
		REPORTING		
PARAMETER	RESULT	LIMIT	UNITS	<u> </u>
Carbon tetrachloride	ND	1400	ug/L	
Chloroethane	ND	1400	ug/L	
Chloromethane	ND	1400	ug/L	

carson cocraciisoriae	115	. 1100	49/2	
Chloroethane	ND	1400	ug/L	
Chloromethane	ND	1400	ug/L	
1,1-Dichloroethane	ND	1400	ug/L	
1,2-Dichloroethane	ND	1400	ug/L	
cis-1,2-Dichloroethene	930 Ј	1400	ug/L	
trans-1,2-Dichloroethene	ND	1400	ug/L	
1,1-Dichloroethene	ND	1400	ug/L	
1,1,1,2-Tetrachloroethane	ND	1400	ug/L	
1,1,2,2-Tetrachloroethane	ND .	1400	ug/L	
Tetrachloroethene	45000 B	1400	ug/L	
1,1,1-Trichloroethane	ND	1400	ug/L	
1,1,2-Trichloroethane	ND	1400	ug/L	
Trichloroethene	760 J	1400	ug/L	
Vinyl chloride	ND	1400	ug/L	

SURROGATE	PERCENT RECOVERY	RECOVERY LIMITS
SURVOGATE	RECOVERI	
Dibromofluoromethane	100	(73 - 122)
1,2-Dichloroethane-d4	104	(61 - 128)
Toluene-d8	106	(76 - 110)
4-Bromofluorobenzene	81	(74 - 116)

Lot-Sample #...: A5K220298-004 Work Order #...: HQREX1AA

NOTE (S):

J Estimated result. Result is less than RL.

B Method blank contamination. The associated method blank contains the target analyte at a reportable level.

Client Sample ID: NTC22MW10D02

GC/MS Volatiles

Lot-Sample #...: A5K220298-002 Work Order #...: HQRER1AA Matrix...... WG

Date Sampled...: 11/20/05 13:30 Date Received..: 11/22/05 Prep Date.....: 12/01/05 Analysis Date..: 12/01/05

Prep Batch #...: 5335104

Dilution Factor: 1 Initial Wgt/Vol: 5 mL Final Wgt/Vol..: 5 mL

Method.....: SW846 8260B

		REPORTING	•
PARAMETER	RESULT	LIMIT	UNITS
Carbon tetrachloride	ND	1.0	ug/L
Chloroethane	ND	1.0	ug/L
Chloromethane	ND	1.0	ug/L
1,1-Dichloroethane	ND	1.0	ug/L
1,2-Dichloroethane	ND	1.0	ug/L
cis-1,2-Dichloroethene	4.0	1.0	ug/L
trans-1,2-Dichloroethene	0.38 Ј	1.0	ug/L
1,1-Dichloroethene	ND	1.0	ug/L
1,1,1,2-Tetrachloroethane	ND	1.0	ug/L
1,1,2,2-Tetrachloroethane	ND	1.0	ug/L
Tetrachloroethene	ND	1.0	ug/L
1,1,1-Trichloroethane	ND	1.0	ug/L
1,1,2-Trichloroethane	ND	1.0	ug/L
Trichloroethene	ND	1.0	ug/L
Vinyl chloride	1.3	1.0	ug/L
	PERCENT	RECOVERY	
SURROGATE	RECOVERY	LIMITS	<u> </u>
Dibromofluoromethane	103	(73 - 122)	<u></u>
1,2-Dichloroethane-d4	107	(61 - 128)	<u>, </u>
Toluene-d8	106	(76 - 110)	
4-Bromofluorobenzene	84	(74 - 116)	

NOTE(S):

J Estimated result. Result is less than RL.

Client Sample ID: NTC22MW10S02

GC/MS Volatiles

Lot-Sample #:	A5K220298-003	Work Order	#:	HOREV1AA	Matrix	.: WG
---------------	---------------	------------	----	----------	--------	-------

Date Sampled...: 11/20/05 15:00 Date Received..: 11/22/05 Prep Date.....: 12/01/05 Analysis Date..: 12/01/05

Prep Batch #...: 5336244

Dilution Factor: 2 Initial Wgt/Vol: 5 mL Final Wgt/Vol.: 5 mL

Method.....: SW846 8260B

		REPORTING		
PARAMETER	RESULT	LIMIT	UNITS	
Carbon tetrachloride	ND ND	2.0	ug/L	
Chloroethane	ND	2.0	ug/L	•
Chloromethane	ND	2.0	ug/L	
1,1-Dichloroethane	ND	2.0	ug/L	
1,2-Dichloroethane	ND	2.0	ug/L	
cis-1,2-Dichloroethene	52	2.0	ug/L	
trans-1,2-Dichloroethene	0.56 J	2.0	ug/L	
1,1-Dichloroethene	ND	2.0	ug/L	
1,1,1,2-Tetrachloroethane	ND	2.0	ug/L	
1,1,2,2-Tetrachloroethane	ND	2.0	ug/L	
Tetrachloroethene	3.5 B	2.0	ug/L	
l,1,1-Trichloroethane	ND	2.0	ug/L	
1,1,2-Trichloroethane	ND	2.0	ug/L	
Trichloroethene	ND	2.0	ug/L	
Vinyl chloride	ND	2.0	ug/L	
	PERCENT	RECOVERY		
SURROGATE	RECOVERY	LIMITS		
Dibromofluoromethane	106	(73 - 122	<u>)</u>	
1,2-Dichloroethane-d4	104	(61 - 128	•	
Toluene-d8	108	(76 - 110	•	
4-Bromofluorobenzene	85	(74 - 116	•	

NOTE (S):

STL North Canton 731

J Estimated result. Result is less than RL.

B Method blank contamination. The associated method blank contains the target analyte at a reportable level.

Client Sample ID: NTC22TB01

GC/MS Volatiles

Lot-Sample #: A5K180318-017	Work Order #: HQKE61AA	Matrix WQ
Date Sampled: 11/17/05	Date Received: 11/18/05	

Prep Date....: 11/28/05 Prep Batch #...: 5333173 Analysis Date..: 11/28/05

Initial Wgt/Vol: 5 mL Final Wgt/Vol..: 5 mL Dilution Factor: 1

Method.....: SW846 8260B

· ·					
		REPORTING			
PARAMETER	RESULT	LIMIT	UNITS		
Carbon tetrachloride	ND	1.0	ug/L		
Chloroethane	ND	1.0	ug/L		
Chloromethane	ND	1.0	ug/L		
1,1-Dichloroethane	ND	1.0	ug/L		
1,2-Dichloroethane	ND	1.0	ug/L		
cis-1,2-Dichloroethene	ND	1.0	ug/L		
trans-1,2-Dichloroethene	ND	1.0	ug/L		
1,1-Dichloroethene	ND	1.0	ug/L		
1,1,1,2-Tetrachloroethane	ND	1.0	ug/L		
1,1,2,2-Tetrachloroethane	ND	1.0	ug/L		
Tetrachloroethene	ND	1.0	ug/L	•	
1,1,1-Trichloroethane	ND	1.0	ug/L		
1,1,2-Trichloroethane	ND	1.0	ug/L		
Trichloroethene	ND	1.0	ug/L		
Vinyl chloride	ND	1.0	ug/L		
	PERCENT	RECOVERY			
SURROGATE	RECOVERY	LIMITS			
Dibromofluoromethane	89	73 - 122)		
1,2-Dichloroethane-d4	99	(61 - 128)		
Toluene-d8	96	(76 - 110)		

(74 - 116)

94

4-Bromofluorobenzene

Client Sample ID: NTC22TB02

GC/MS Volatiles

Lot-Sample #: A5K220298-006 Work Order #.	: HQRE91AA	Matrix: WQ
---	------------	------------

Date Sampled...: 11/20/05 Date Received..: 11/22/05
Prep Date....: 12/01/05 Analysis Date..: 12/01/05

Prep Batch #...: 5336227

Dilution Factor: 1 Initial Wgt/Vol: 5 mL Final Wgt/Vol.: 5 mL

Method..... SW846 8260B

		REPORTING		
PARAMETER	RESULT	LIMIT	UNITS	
Carbon tetrachloride	ND	1.0	ug/L	
Chloroethane	ND	1.0	ug/L	
Chloromethane	ND	1.0	ug/L	
1,1-Dichloroethane	ND	1.0	ug/L	
1,2-Dichloroethane	ND	1.0	ug/L	
cis-1,2-Dichloroethene	ND	1.0	ug/L	
trans-1,2-Dichloroethene	ND	1.0	ug/L	
1,1-Dichloroethene	ND	1.0	ug/L	
1,1,1,2-Tetrachloroethane	ND	1.0	ug/L	
1,1,2,2-Tetrachloroethane	ND	1.0	ug/L	
Tetrachloroethene	0.98 Ј	1.0	ug/L	
1,1,1-Trichloroethane	ND	1.0	ug/L	
1,1,2-Trichloroethane	ND	1.0	ug/L	
Trichloroethene	ND	1.0	ug/L	
Vinyl chloride	ND	1.0	ug/L	
	PERCENT	RECOVERY		
SURROGATE	RECOVERY	LIMITS	_	
Dibromofluoromethane	93	(73 - 122)		
1,2-Dichloroethane-d4	101	(61 - 128)		
Toluene-d8	95	(76 - 110)		
4-Bromofluorobenzene	87	(74 - 116)	*	
				•

NOTE(S):

STL North Canton 766

J Estimated result. Result is less than RL.

Chain of Custody Record



STL-4(24 (0901)		
TetraTech NUS Address	Kobert Davis	Date 11-17-05 Chain of Custody Number 245250
661 Andersen Dr.	Telephone Number (Arga Code)/Fax Number (412) 921 - 725	(330) 966-7269 Page 1 of 2
Pittsburgh PA 15220	Jeff Schubert Lois Ezzo Analy	rsis (Attach list if space is needed)
NS Great Lakes - Site 22 Contract/Purchase Ordel Quote No.)	Carrier/Waybill Number 8494-1921-4725 9	Special Instructions/
67660	Matrix Containers & Z Preservatives	Conditions of Receipt
sample may be combined on one line;	Advectors Sed Anneous Sed Anneous Sed Anneous Sed Anneous H2SO4 HNO3 Anneous Sed Anneous S	
NTC 22 SB 20 05 06 11-17-05 2	220 V 3	chlorinated
NTC 225B21 0203 11-17-05	3:15	VOC compounds
NTC225B210405 11-17-05	3:45 / 31	per ITNUS
NTC225B211112 11-17-05 NTC225B220203 11-17-05	- 4:00 V 31 31 31 31 31 31 31 31 31 31 31 31 31	purchase
NTC2258220708 11-17-05		order #
N.TC 22 SB 22 11 12 11-17-05	5:30 1 931	1005085, dated
NTC225B230203 11-17-05 NTC225B230102 11-17-05		10/21/05
NTC225B240102 11-17-05	1230 1	(see Attach.
NTC228B24020311-17-05 Possible Hazard Identification	12:30 / 31	
Non-Hazard		(A fee may be assessed if samples are retained Months longer than 1 month)
· 그렇게 그는 사람이 그를 보고 있는 것 같아	OC Requirements (Specify)	
2. Relinquished By	1)-17-05 8/30 Pula Hines	Date Time (11-18-15) 9:30
3. Relinquished By	Date * Time 2. Received By	Date Time
Comments	Date Time 3. Received By	Date Time

Chain of Custody Record



STL-4124 (0901)				Lewi Hanni arou ies' file:	
Tetra Tack NUS	_	Manager Rolpost	Davis	Page 17-17-05	Chain of Custody Number 245251
661 Anderson Dr	Teleph	oné Number (Area Gode)/Fa. 		Lab Number 330 966 T2	2 7 7
Pitts bush 14 152	Site C	ontact Lab	Contact	Analysis (Attach list if	2 Page of
Project Name and Location (State)	201	Waybill Number	Lois Erro	more space is needed)	
15 6 rest Lakes Si	te 22 81	Waybill Number +94 — 1921 —	4725 n		
Contract/Purchase Order/Quote No.		Matrix	Containers & Preservatives		Special Instructions/ Conditions of Receipt
2 W. 19 W. 10 W. 1	Date Time	Air Aqueous Sed: Borr	HINO3 HINO3 HCI NaOH NaOH NaOH		
NTC225B 250102 11	1-17-05		3		
	1-17-05				
NIC 22FDOL 11	1-17-05		3		
NTC 22 FD02 11	1-17-05		$\ddot{\mathbf{z}}$		B210405
NTC 22 TBOI II	-17-05			1 1 22 MZ4 ZZ	SB 22/1/Z
	4. 34. 3. 4. 3. 4. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3.				
	7.0				
	* 1				
Possible Hazard Identification		Sample Disposal			
Non-Hazard	ison B 📜 🔲 Unknown	Return To Client	Disposal By Lab Archive	(A fee may be a	ssessed if samples are retained
Turn Around Time Required 24 Hours 48 Hours 7 Days 14 Days	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	7.10	C Requirements (Specify)	Months Tonger than 1 m	onin)
1. Relinquished By	☐ 21 Days ☐ Othe		Received By		
2. Relinguished by		17-05 8:30	n 2. in 1/	2.1	Date Time 9:30
- roundainth by	Date	Time	Received By		Date Time
3. Relinquished By	Date	Time	Received By		000
Comments					Date Time
DISTRIBUTION WHITE B	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		SAN AND CONTRACT OF THE CONTRA		(2) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1

Chain of Custody Record



STL-4124 (0901)									
Client Tetra Tech NUS		Project Ma	nager R ø	26+7	Davis		Date	20-05 Ch	ain of Custody Number
661 Anderson Dr.	*	Telephone	Number (Aréa (412	Code//Fax N	umber 1 – 1251			166-7269 Pa	
City Pittsburge PAZ	15220	Site Conta	Schule		Lois Ez	Zo 8	Analysis (Attach more space is ne	list if	ge of
	ite 22	Carrier/Wa	ybill Number	1921	4298	8260	Technology (Control of Control of		
Contragt/Purcipase Orger/Quote No.	7.		Matrix		Containers & Preservatives				Special Instructions/ Conditions of Receipt
Sample I.D. No and Description (Containers for each sample may be combined on one line	Date 1	Time ₹	Aqueous Sed.	Unpress H2SO4	HOO3 NaOH NaOH	K			and finely
NTC 22MW05502	11-20-05	11:40	12		3				
NTCZZMWIODOZ	11-20-05	13:30	1		3				
NTC 22MW 10502	11-20-05	15:00			3				06502
NTC 22 MW 06502	11-20-05	17:00			3				may have vocs
NTC 22 FD03	11-20-05	•			3	74	19	8	SSOZ
NTC 22 TB 02	11-20-05								2630Z
	14								
	24	, ?	5,						
	41								
	24	7 .							<u> </u>
	7.3								
	7.4								
Pospible Hazard Identification Non-Hazard	☐ Poison B ☐	Unknown	Sample Disposa	al. Sient 🔲	Disposal Bv Lab	☐ Archive For	Months ic	A fee may be assessed onger than 1 month)	if samples are retained
Turn Around Time Required 24 Hours	124				Requirements (Spe				
1. Relinquished By	Oays Landays	Date	Time	11	Received By				ate , Time
2 Relinquished B	er	11-21	-05 2:	30 jam	Eng 3	B.5			1/a2/05 0945
	*1	Date	Time -		Réceived By			D	arte Time
8. Relinquished By		Date	Time	3 (3 /	Received By	-		4 E 10	ate Time
Comments		4	$-1v_{i,i,j}$	<u>*</u>				1.77.1	
DISTRIBUTION: WHITE Reformed to Client with Report.									
VIOLITE - HEIDING IN SILENT WITH Report	CANARY - Stave With	n the Samole	PINK - FIRM C	anie C		- 3		A RY WEST CONTRACTOR	

JULY 2006



INTERNAL CORRESPONDENCE

TO:

MR. B. DAVIS

DATE:

JANUARY 23, 2007

FROM:

EDWARD SEDLMYER

COPIES:

DV FILE

SUBJECT:

ORGANIC DATA VALIDATION- VOA

CTO 009, NTC GREAT LAKES

SDG 6G12170

SAMPLES:

2/Aqueous

TRIP BLANK

TRIP BLANK-A

17/Solid

GL95105S120001R

GL95105S120203R

NTC22FD002

NTC22FD01

NTC22MW10D0708R NTC22SB151112R NTC22MW10D11112R

NTC22SB150001R NTC22SB200203R

NTC22SB131112R

NTC22SB191920R NTC22SB210910R

NTC22SB211314R

NTC22SB220708R

NTC22SB221819R

NTCMW05S0001R

NTCMW06D0708R

OVERVIEW

The sample set for CTO 009 NTC Great Lakes, SDG 6G12170 consists of, two (2) trip blanks and seventeen (17) soil environmental samples. All samples were analyzed for select volatile organic compounds (VOCs). Two field duplicate pairs were associated with this SDG: NTC22FD01 / NTC22MW10D0708R and NTC22FD002 / NTC22SB191920R.

The samples were collected by TetraTech NUS on July 11 and 12, 2006 and analyzed by Severn Trent Laboratories, Inc., North Canton, OH. All analyses were conducted in accordance with USEPA SW 846 Method 8260B analytical and reporting protocol. The data contained in this SDG were validated with regard to the following parameters:

- Data Completeness
- Holding Times
- Initial and Continuing Calibration
- Laboratory Blank Analyses
- Field Duplicate Results
- Detection Limits

In addition, samples NTC22SB151112R and NTC22SB211314R was also validated with regard to the following parameters:

- Surrogate Recoveries
- Blank Spike/Blank Spike Duplicate Results
- Matrix Spike/Matrix Spike Duplicate Results
- * Internal Standard Recoveries
- Compound Quantitation
- Compound Identification

TO: B. DAVIS

DATE: JANUARY 23, 2007 - PAGE 2

The symbol (*) indicates that quality control criteria were met for this parameter. Problems affecting data quality are discussed below; documentation supporting these findings is presented in Appendix C. Qualified Analytical results are presented in Appendix A. Results as reported by the laboratory are presented in Appendix B.

Volatile

The following compound was detected in the medium level method blank:

Compound Tetrachloroethene⁽¹⁾ Maximum
Concentration
13 μg/kg

Blank Action Level 65 µg/kg

1- Concentration detected in a method blank associated with QC batch 6197248. Only diluted samples analyzed on this date were evaluated relative to this blank.

No action was taken for blank contamination because the tetrachloroethene concentrations in all associated samples greater than 10X the blank action level.

A continuing calibration had a %D outside the 25% quality control limit on 7/17/06 at 11:20 on instrument A3UX8A for chloroethane. No action was taken on this basis because this is a limited review.

The field duplicate precision exceeded the 50% relative percent difference (RPD) quality control limit for tetrachloroethene in the field duplicate pair NTC22MW10D0708R / NTC22FD01. Positive results for tetrachloroethene in the duplicate samples NTC22MW10D0708R / NTC22FD01 were qualified as estimated (J).

All samples except NTC22SB220708R required a dilution for tetrachloroethene and/or trichloroethene. No qualification of the data was necessary.

Additional Comments:

Positive results less than the reporting limit (RL) were qualified as estimated, J, due to uncertainty near the detection limit.

The laboratory incorrectly transposed a sample ID on the VOA Form I. The sample ID NTCMW05S120001R has been corrected in the database to NTCMW05S10001R.

Detection limits for all samples, except NTC22SB220708R, are elevated due to the medium level preparation procedure. Detection limits for all compounds exceed those listed in the laboratory specification.

EXECUTIVE SUMMARY

Laboratory Performance Issues: Tetrachloroethene was detected in an aqueous laboratory preparation blank.

Other factors affecting data quality: Field duplicate imprecision resulted in qualification of samples NTC22MW10D0708R and NTC22FD01.

TO: B. DAVIS

DATE: JANUARY 23, 2007 - PAGE 3

The data for these analyses were reviewed with reference to the EPA Functional Guidelines for Organic Data Validation (October 1999) and the Department of Defense (DoD) document entitled "Quality Systems Manual (QSM) for Environmental Laboratories" (January 2006). The text of this report has been formulated to address only those problem areas affecting data quality.

"I attest that the data referenced herein were validated according to the agreed upon validation criteria as specified in the DoD QSM."

Tetra Tech NUS

Edward Sedlmyer Chemist/Data Validator

TetraTech NUS

Joseph A. Samchuck Data Validation Quality Assurance Officer

Attachments:

Appendix A - Qualified Analytical Results

Appendix B - Results as Reported by the Laboratory

Appendix C - Support Documentation

APPENDIX A

QUALIFIED ANALYTICAL RESULTS

Data Validation Qualifier Codes:

A = Lab Blank Contamination

B = Field Blank Contamination

C = Calibration Noncompliance (e.g. % RSDs, %Ds, ICVs, CCVs, RRFs, etc.)

C01 = GC/MS Tuning Noncompliance

D = MS/MSD Recovery Noncompliance

E = LCS/LCSD Recovery Noncompliance

F = Lab Duplicate Imprecision

G = Field Duplicate Imprecision

H = Holding Time Exceedance

I = ICP Serial Dilution Noncompliance

J = GFAA PDS - GFAA MSA's r < 0.995 / ICP PDS Recovery Noncompliance

K = ICP Interference - includes ICS % R Noncompliance

L = Instrument Calibration Range Exceedance

M = Sample Preservation Noncompliance

N = Internal Standard Noncompliance

N01 = Internal Standard Recovery Noncompliance Dioxins

N02 = Recovery Standard Noncompliance Dioxins

N03 = Clean-up Standard Noncompliance Dioxins

O = Poor Instrument Performance (e.g. base-line drifting)

P = Uncertainty near detection limit (< 2 x IDL for inorganics and <CRQL for organics)

Q = Other problems (can encompass a number of issues; e.g. chromatography, interferences, etc.)

R = Surrogates Recovery Noncompliance

S = Pesticide/PCB Resolution

T = % Breakdown Noncompliance for DDT and Endrin

U = % Difference between columns/detectors >25% for positive results determined via GC/HPLC

V = Non-linear calibrations; correlation coefficient r < 0.995

W = EMPC result

X = Signal to noise response drop

Y = Percent solids <30%

Z = Uncertainty at 2 sigma deviation is greater than sample activity

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date

lab_id

GL95105S120001RDL

7/11/2006

A6G120170004

 qc_type
 NM

 units
 UG/KG

 Pct_Solids
 86.0

DUP_OF:

nsample samp_date

lab_id

7/11/2006 A6G120170005 NM

qc_type units Pct_Solids DUP_OF: GL95105S120203RDL 7/11/2006

A6G120170005 NM UG/KG 82.0 nsample samp_date lab_id qc_type units Pct_Solids

7/12/2006 A6G130157004 NM UG/KG 86.0

DUP_OF:

NTC22SB191920R

NTC22FD002DL

		Val	Qual
Parameter	Result		Code
1,1,1,2-TETRACHLOROETHANE	750	U	
1,1,1-TRICHLOROETHANE	750	U	
1,1,2,2-TETRACHLOROETHANE	750	U	
1,1,2-TRICHLOROETHANE	750	U	
1,1-DICHLOROETHANE	750	U.	
1,1-DICHLOROETHENE	750	U	
1,2-DICHLOROETHANE	750	U	
CARBON TETRACHLORIDE	750	U	
CHLOROETHANE	750	U	
CHLOROMETHANE	750	U	
CIS-1,2-DICHLOROETHENE	170	J	Р
TETRACHLOROETHENE	20000		
TRANS-1,2-DICHLOROETHENE	750	U	
TRICHLOROETHENE	410	J	Р
VINYL CHLORIDE	750	U	
VINYL CHLORIDE			_

Parameter	Result	Vai Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	880	U	
1,1,1-TRICHLOROETHANE	880	Ü	
1,1,2,2-TETRACHLOROETHANE	880	U	
1,1,2-TRICHLOROETHANE	880	U	
1,1-DICHLOROETHANE	880	U	
1,1-DICHLOROETHENE	880	U	
1,2-DICHLOROETHANE	880	U	
CARBON TETRACHLORIDE	880	U	
CHLOROETHANE	880	U	
CHLOROMETHANE	880	U	
CIS-1,2-DICHLOROETHENE	58	J	Р
TETRACHLOROETHENE	21000		
TRANS-1,2-DICHLOROETHENE	880	U	
TRICHLOROETHENE	100	J	Р
VINYL CHLORIDE	880	U	

		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	81000	U	
1,1,1-TRICHLOROETHANE	81000	U	
1,1,2,2-TETRACHLOROETHANE	81000	U	
1,1,2-TRICHLOROETHANE	81000	U	
1,1-DICHLOROETHANE	81000	U	
1,1-DICHLOROETHENE	81000	U	
1,2-DICHLOROETHANE	81000	U	
CARBON TETRACHLORIDE	81000	U	
CHLOROETHANE	81000	U	
CHLOROMETHANE	81000	U .	
CIS-1,2-DICHLOROETHENE	81000	U	
TETRACHLOROETHENE	2500000		
TRANS-1,2-DICHLOROETHENE	81000	U	
TRICHLOROETHENE	5100	J	Р
VINYL CHLORIDE	81000	υ	

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date lab_id NTC22FD01DL

7/11/2006 A6G120170010

 qc_type
 NM

 units
 UG/KG

 Pct_Solids
 79.0

DUP_OF:

NTC22MW10D0708R

nsample samp_date

lab_id

units

qc_type

Pct_Solids

DUP_OF:

NTC22MW10D0708RDL

7/11/2006

A6G120170008

NM UG/KG 79.0

.

nsample

samp_date

lab_id qc_type units

Pct_Solids

DUP_OF:

NTC22MW10D1112RDL

7/11/2006

A6G120170009 NM

UG/KG 85.0

Parameter	Result	Val Qual	Qual Code	
1,1,1,2-TETRACHLOROETHANE	270	U		
1,1,1-TRICHLOROETHANE	270	U		
1,1,2,2-TETRACHLOROETHANE	270	U		
1,1,2-TRICHLOROETHANE	270	U		
1,1-DICHLOROETHANE	270	U		
1,1-DICHLOROETHENE	270	U		
1,2-DICHLOROETHANE	270	U		
CARBON TETRACHLORIDE	270	U		
CHLOROETHANE	270	U		
CHLOROMETHANE	270	U		
CIS-1,2-DICHLOROETHENE	270	U		
TETRACHLOROETHENE	770	J	G	
TRANS-1,2-DICHLOROETHENE	270	·U		
TRICHLOROETHENE	270	U		
VINYL CHLORIDE	270	U		

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	280	U	
1,1,1-TRICHLOROETHANE	280	· U	
1,1,2,2-TETRACHLOROETHANE	280	U	
1,1,2-TRICHLOROETHANE	280	U	
1,1-DICHLOROETHANE	280	U	
1,1-DICHLOROETHENE	280	U	
1,2-DICHLOROETHANE	280	U	
CARBON TETRACHLORIDE	280	U	
CHLOROETHANE	280	U	
CHLOROMETHANE	280	U	
CIS-1,2-DICHLOROETHENE	280	U	
TETRACHLOROETHENE	350	J	G
TRANS-1,2-DICHLOROETHENE	280	U	
TRICHLOROETHENE	280	U	
VINYL CHLORIDE	280	U	

		Val	Qual
Parameter	Result	Quai	Code
1,1,1,2-TETRACHLOROETHANE	1200	U	
1,1,1-TRICHLOROETHANE	1200	U	
1,1,2;2-TETRACHLOROETHANE	1200	U	
1,1,2-TRICHLOROETHANE	1200	U	
1,1-DICHLOROETHANE	1200	U	
1,1-DICHLOROETHENE	1200	U	
1,2-DICHLOROETHANE	1200	U	
CARBON TETRACHLORIDE	1200	U	
CHLOROETHANE	1200	U	
CHLOROMETHANE	1200	U	
CIS-1,2-DICHLOROETHENE	1200	Ü	
TETRACHLOROETHENE	36000		
TRANS-1,2-DICHLOROETHENE	1200	U	
TRICHLOROETHENE	120	J	Р
VINYL CHLORIDE	1200	U	

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date

lab id

NTC22SB150001RDL

Result

230

230

230

230

230

230

230

230

230

230

28

3100

230

36

230

Val

Qual

Ū

υ

U

Ū

U

Ų

U

U

Ü

U

J

U

Ū

Qual

Code

P

Р

7/11/2006

A6G120170006

samp_date lab_id qc_type

nsample

ate 7/11/2006 A6G120170007 NM

NTC22SB151112RDL

UG/KG

85.0

units
Pct_Solids
DUP_OF:

nsample samp_date lab_id qc_type

A6G130157003 NM UG/KG 87.0

7/12/2006

NTC22SB191920RDL

Pct_Solids DUP OF:

units

Parameter
1,1,1,2-TETRACHLOROETHANE
1,1,1-TRICHLOROETHANE
1,1,2,2-TETRACHLOROETHANE
1,1,2-TRICHLOROETHANE

1.1-DICHLOROETHANE

1,1-DICHLOROETHENE

1,2-DICHLOROETHANE

CHLOROETHANE

CHLOROMETHANE

CARBON TETRACHLORIDE

CIS-1.2-DICHLOROETHENE

TRANS-1,2-DICHLOROETHENE

TETRACHLOROETHENE

TRICHLOROETHENE

VINYL CHLORIDE

Val Qual Parameter Result Qual Code 1,1,1,2-TETRACHLOROETHANE 10000 u 1,1,1-TRICHLOROETHANE 10000 U 1,1,2,2-TETRACHLOROETHANE 10000 U 1.1.2-TRICHLOROETHANE 10000 U 1,1-DICHLOROETHANE 10000 Ū 1.1-DICHLOROETHENE 10000 U 1,2-DICHLOROETHANE 10000 Ū CARBON TETRACHLORIDE 10000 U CHLOROETHANE 10000 U CHLOROMETHANE 10000 U CIS-1,2-DICHLOROETHENE 10000 U TETRACHLOROETHENE 250000 TRANS-1,2-DICHLOROETHENE 10000 u TRICHLOROETHENE 5300 Ρ VINYL CHLORIDE 10000 U

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE			Oode
	120000	U	
1,1,1-TRICHLOROETHANE	120000	U	
1,1,2,2-TETRACHLOROETHANE	120000	U	
1,1,2-TRICHLOROETHANE	120000	U	
1,1-DICHLOROETHANE	120000	U	-
1,1-DICHLOROETHENE	120000	U	-
1,2-DICHLOROETHANE	120000	U	
CARBON TETRACHLORIDE	120000	U	
CHLOROETHANE	120000	U	
CHLOROMETHANE	120000	U	
CIS-1,2-DICHLOROETHENE	120000	U	
TETRACHLOROETHENE	3300000		
TRANS-1,2-DICHLOROETHENE	120000	U	
TRICHLOROETHENE	5700	J.	Р
VINYL CHLORIDE	120000	U	

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date NTC22SB200203RDL

7/11/2006

lab_id qc_type units

A6G120170001 NM

UG/KG Pct_Solids 89.0

DUP_OF:

nsample samp_date

lab_id qc_type units Pct_Solids

DUP_OF:

A6G120170002 NM UG/KG 87.0

7/11/2006

NTC22SB200607RDL

nsample

samp_date lab_id

qc_type units Pct_Solids NTC22SB210910RDL

7/12/2006 A6G130157001

NM UG/KG 81.0

DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	2100	U	<u> </u>
1,1,1-TRICHLOROETHANE	2100	U	· · · · · ·
1,1,2,2-TETRACHLOROETHANE	2100	U	
1,1,2-TRICHLOROETHANE	2100	U	
1,1-DICHLOROETHANE	2100	U	
1,1-DICHLOROETHENE	2100	Ü	
1,2-DICHLOROETHANE	2100	U	
CARBON TETRACHLORIDE	2100	U	
CHLOROETHANE	2100	U	
CHLOROMETHANE	2100	U	
CIS-1,2-DICHLOROETHENE	2100	U	
TETRACHLOROETHENE	58000		
TRANS-1,2-DICHLOROETHENE	2100	U	
TRICHLOROETHENE	160	J	Р
VINYL CHLORIDE	2100	U	
<i>y</i> *			

_		Val	Qual
Parameter	Result	Qual	Code
44407575401110005711111	 		
1,1,1,2-TETRACHLOROETHANE	430	U	
1,1,1-TRICHLOROETHANE	430	U	
1,1,2,2-TETRACHLOROETHANE	430	U	
1,1,2-TRICHLOROETHANE	430	U	
1,1-DICHLOROETHANE	430	U	
1,1-DICHLOROETHENE	430	U	
1,2-DICHLOROETHANE	430	U	
CARBON TETRACHLORIDE	430	Ü	
CHLOROETHANE	430	Ū	
CHLOROMETHANE	430	Ü	
CIS-1,2-DICHLOROETHENE	430	U	
TETRACHLOROETHENE	11000	-	
TRANS-1,2-DICHLOROETHENE	430	U	
TRICHLOROETHENE	47	J	Р
VINYL CHLORIDE	430	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1700	U	
1,1,1-TRICHLOROETHANE	1700	U	-
1,1,2,2-TETRACHLOROETHANE	1700	Ų	
1,1,2-TRICHLOROETHANE	1700	U	
1,1-DICHLOROETHANE	1700	U	
1,1-DICHLOROETHENE	1700	Ų	
1,2-DICHLOROETHANE	1700	U	
CARBON TETRACHLORIDE	1700	U	
CHLOROETHANE	1700	U	
CHLOROMETHANE	1700	Ū	
CIS-1,2-DICHLOROETHENE	1700	U	
TETRACHLOROETHENE	57000		
TRANS-1,2-DICHLOROETHENE	1700	U	
TRICHLOROETHENE	700	J	P
VINYL CHLORIDE	1700	U	

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date NTC22SB211314RDL

7/12/2006

lab_id qc_type

A6G130157002 NM UG/KG

88.0

units Pct_Solids DUP_OF:

nsample samp_date lab_id

qc_type units

Pct_Solids DUP_OF:

NTC22SB220708RDL

7/11/2006 A6G120170012

NM UG/KG

77.0

nsample

samp_date lab_id qc_type

units Pct_Solids DUP_OF:

NTC22SB221819RDL

7/11/2006 A6G120170013

NM UG/KG 86.0

_		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	5700	U	
1,1,1-TRICHLOROETHANE	5700	U	
1,1,2,2-TETRACHLOROETHANE	5700	U	
1,1,2-TRICHLOROETHANE	5700	U	
1,1-DICHLOROETHANE	5700	U	
1,1-DICHLOROETHENE	5700	U	
1,2-DICHLOROETHANE	5700	U	
CARBON TETRACHLORIDE	5700	U	
CHLOROETHANE	5700	·U	
CHLOROMETHANE	5700	U	
CIS-1,2-DICHLOROETHENE	5700	U	
TETRACHLOROETHENE	210000	-	
TRANS-1,2-DICHLOROETHENE	5700	U	
TRICHLOROETHENE	11000		
VINYL CHLORIDE	5700	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	6.3	U	
1,1,1-TRICHLOROETHANE	6.3	U	
1,1,2,2-TETRACHLOROETHANE	6.3	U	
1,1,2-TRICHLOROETHANE	6.3	U	
1,1-DICHLOROETHANE	6.3	U	
1,1-DICHLOROETHENE	6.3	U	
1,2-DICHLOROETHANE	6.3	U	
CARBON TETRACHLORIDE	6.3	U	
CHLOROETHANE	6.3	U	
CHLOROMETHANE	6.3	U	
CIS-1,2-DICHLOROETHENE	6.3	U	
TETRACHLOROETHENE	2.1	J	P
TRANS-1,2-DICHLOROETHENE	6.3	U	
TRICHLOROETHENE	6.3	U	
VINYL CHLORIDE .	6.3	Ü	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	230	U	
1,1,1-TRICHLOROETHANE	230	U	:
1,1,2,2-TETRACHLOROETHANE	230	U	
1,1,2-TRICHLOROETHANE	230	U	
1,1-DICHLOROETHANE	230	U	-
1,1-DICHLOROETHENE	230	U	
1,2-DICHLOROETHANE	230	U	
CARBON TETRACHLORIDE	230	U	
CHLOROETHANE	230	U	
CHLOROMETHANE	230	U	
CIS-1,2-DICHLOROETHENE	46	J	Р
TETRACHLOROETHENE	260		-
TRANS-1,2-DICHLOROETHENE	230	U	
TRICHLOROETHENE	490		
VINYL CHLORIDE	230	U	

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date NTCMW05S0001RDL

7/11/2006

lab_id qc_type units

A6G120170003 NM

UG/KG Pct_Solids 79.0

DUP_OF:

samp_date lab_id

qc_type units Pct_Solids

DUP_OF:

nsample

NTCMW06D0708RDL

7/11/2006 A6G120170011

NM UG/KG

82.0

nsample samp_date lab_id

qc_type

Pct_Solids

DUP_OF:

units

TRIP BLANK 7/11/2006 A6G120170014 NM

UG/L

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	280	U	<u> </u>
1,1,1-TRICHLOROETHANE	280	U	
1,1,2,2-TETRACHLOROETHANE	280	U	
1,1,2-TRICHLOROETHANE	280	U	
1,1-DICHLOROETHANE	280	U	
1,1-DICHLOROETHENE	280	U	
1,2-DICHLOROETHANE	280	U	
CARBON TETRACHLORIDE	280	U	
CHLOROETHANE	280	U	
CHLOROMETHANE	280	U	
CIS-1,2-DICHLOROETHENE	280	U	,
TETRACHLOROETHENE	4500		•
TRANS-1,2-DICHLOROETHENE	280	U	
TRICHLOROETHENE	280	U	
VINYL CHLORIDE	280	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	250	U	
1,1,1-TRICHLOROETHANE	250	U	
1,1,2,2-TETRACHLOROETHANE	250	U	
1,1,2-TRICHLOROETHANE	250	U	
1,1-DICHLOROETHANE	250	U	
1,1-DICHLOROETHENE	250	U	
1,2-DICHLOROETHANE	250	U	· ·
CARBON TETRACHLORIDE	250	U	
CHLOROETHANE	250	U	
CHLOROMETHANE	250	U	
CIS-1,2-DICHLOROETHENE	250	U	
TETRACHLOROETHENE	2500		
TRANS-1,2-DICHLOROETHENE	250	U	
TRICHLOROETHENE	22	J	P
VINYL CHLORIDE	250	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	1	U	
,1,2-TRICHLOROETHANE	1	U	
,1-DICHLOROETHANE	1	U	
,1-DICHLOROETHENE	1	U	
,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	1	U	
ETRACHLOROETHENE	1	U	
RANS-1,2-DICHLOROETHENE	1	U	
RICHLOROETHENE	1	U	
/INYL CHLORIDE	1	U	

SDG: 6G12170 MEDIA: SOIL DATA FRACTION: OV

nsample

TRIP BLANK-A

samp_date

7/12/2006

lab_id

A6G130157005

qc_type

NM

units

UG/L

Pct_Solids

DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	1	U	
TETRACHLOROETHENE	1	U	
TRANS-1,2-DICHLOROETHENE	1	U	
TRICHLOROETHENE	1	U	
VINYL CHLORIDE	1	U	

PAGE / OF /

PROJECT NO						PHONE NUMBER			L	LABORATORY NAME AND CONTACT:									
SAMPLERS (SIGNAT	<u>~ /</u>	NS GREAT LA	KES	FIELD OPERATIONS LEADER					412 92/-7251 PHONE NUMBER				STL ADDRESS					
													1 1 7						
/ look	. 7 1	royl			CARR	K ME	NGF O	NIINGED	12	724-777-0035				4101 Shuffle Drive NW					
		•														ATAN	i. 0	H 447	120
						Τ		1		CONTAINER TYPE					0 /	0			
STANDARD T	·AT []				4		٠.,			PLAS	TIC (P)	or GLAS	SS (G)	$-\!\!\!\!/-$	\rightarrow				
RUSH TAT	RUSH TAT X 48 hr. X 72 hr. 7 day 14 day							PRESERVATIVE USED											
24 hr. 48 hr. 24 72 hr. 7 day 14 day						ВОТТОМ DЕРТН (FT)	MATRIX (GW, SO, SW, SD, ETC.)	COLLECTION METHOD GRAB (G) COMP (C)	No. OF CONTAINERS	THE	Cr NW	302	('/	mossi				CON	MENTS
7/			MPLE ID			+			-		/								
	O NITO	C22.5B2	200203R		<u> </u>	-	50		4	3	/				<u> </u>				
	NT	CZZSB	200607 R			ļ	50		4	<u> 3</u>	1								
7/11 0900	NTO	C MW05.	\$ 0001 R				50		4	3	1								
7/11 0930	64	95105\$	120001 R				50		4	3	i								
7/11 0933	5 66	951051	12 0203 R			ŀ	50		4	3	1					-			
			50001 R				50		4	1 3 1 72 Apre TURNAR					en akou	wd			
/			51112 R				50		4	3	1								
1	- 1		100 6708 R			٠	50		4	3	1								
21			100 1112 R				50		4	3	1								
		76 ZZ <i>F</i>		···			50		4	3	1								
			00708R				ه د		4	3	,						1		
1			22 0708 R				50		4	3	1,								
7/ /30	سبد ا د	~ -> /4	22 10 10 0		 	†	50		4	3	1						,		
1. RELINQUIS	SHED B	3Y-20-1	in	,	DATE	11-06		TIME/LO	-	RECEIVE	D BY	1	7				DA	2-12-00	TIME9:45
2. RELINQUIS	1. RELINQUISHED BY Mark & Mings 2. RELINQUISHED BY					17-06		TIME		RECEIVE	D BY			t			DA		TIME
3. RELINQUI	3. RELINQUISHED BY						DATE TO			3. RECEIVED BY				DATE TIME					
COMMENTS									<u>. L</u>							·····	L		
DISTRIBUTIO	M.	WHITE	(ACCOMPANIES	SAMPLE)			YELL	OW (FIELD	COPY	Y)			PIN	K (FILE	COPY	<u> </u>			4/02R

2151 | PAGE___OF__

PROJECT NO: FACILITY:							PROJECT MANAGER BOB DAVIS					PHONE NUMBER				LABORATORY NAME AND CONTACT:						
0.445	6000	2 <i>02</i> Snature)	NTC	GREAT	LAKES	150,	OPED!	HUIS	LEADER	15	4/12 -92/- 725/ PHONE NUMBER				STL ADDRESS							
			1	-						- 1					· ·							
	lank,	1. Ming	u			CAPPI	EDANA	ENGL	E L IUMBER		724-771-0035				4101 SHUFFEL DRIVE NW							
-										101			,							,,,,,,		
							ED I	e X	-83	774	/94877/296 CONTAINER TYPE				NOET	TH C.	ANTO	N,O	H 4	14720		
								1						SS (G)		P /I	0 /			/ / /		
STANDARD TAT						1		ő,			PLASTIC (P) or GLASS (PRESERVATIVE											
RUSH TAT					7 44 3						USED	FILANI	IVE									
1 24	nr. 📋	48 hr. 120 /	2 nr.	J/day L		-		\ <u>\</u> \	ا وا					\prec	/ 3	<i>y</i>	/		/-/	/-/-		
VATE 2006					гор DЕРТН (FT)	BOTTOM DEPTH (FT)	MATRIX (GW, SO, SW, SD, ETC.)	COLLECTION METHOD GRAB (G) COMP (C)	No. OF CONTAINERS	TIPE	OF AMILY		Party)	noiste								
변종					₹		Ĕ	E G	₽8E	Ö	'/	0	N									
DATE YEAR	TIME		SAMPLE	·	Ž	₽	8	₹ ¥	888	ģ	//		v/						/ 00	NAMENTS		
 		N7C ZZ 5						50		4	3	,										
7/2	0820	NTCZZS	SB211	314 R				30		4	3	,								·		
1 – . 1	i	NTC ZZ			,			50		4	3	1			7	2 %	UK					
		NTCZZ						50		4	3	1			TI	in.	AROL	wd				
						-		-	† †		1		T									
							!	 	} -			<u> </u>	 			-	 					
							<u> </u>							<u> </u>								
						·					į					*						
							1	1.	 		+	 	 		t		t					
							<u> </u>		1 .			1	1	ļ <u>-</u>		ļ	<u> </u>	ļ	· · · · · · · · · · · · · · · · · · ·	11		
					-	1																
																}						
		-				+	1	 	1		+	1	1	-		 	 					
							ļ	ļ	ļ		 					ļ	<u> </u>					
															1							
1. REI	INQUISH	ED BY	01-	2.0	1	DATE	2/00	<u>, </u>	TIME	1.4	(CEIVE	D BY	1		A			DA		TIME		
A ==	B1011161	100	ok to	Mengel	<u> </u>		2/00		1500 TIME	- 	RECEIVE	D BY	How					DA DA	<u> 13-06</u>	19:20 TIME		
2. RE	1. RELINQUISHED BY Mort A. Mengel 2. RELINQUISHED BY					DATE			IIVE	ı								JA.	16	LIME		
3. RE	3. RELINQUISHED BY					DATE TIME			3. F	3. RECEIVED BY			DATE TIME			TIME						
COM	COMMENTS																					

AUGUST 2006



INTERNAL CORRESPONDENCE

TO:

MR. B. DAVIS

DATE:

JANUARY 23, 2007

FROM:

EDWARD SEDLMYER

COPIES:

DV FILE

SUBJECT:

ORGANIC DATA VALIDATION- VOA

CTO 009, NTC GREAT LAKES

SDG 6H09143

SAMPLES:

1/Aqueous

TRIP BLANK-6H09143

6/Solid

NTC22SB151112R1

NTC22SB191920R1

NTC22SB200203R1

NTC22SB210910R1

NTC22SB211314R1

NTCFD01

OVERVIEW

The sample set for CTO 009 NTC Great Lakes, SDG 6H09143 consists of, one (1) trip blank and six (6) soil environmental samples. All samples were analyzed for select volatile organic compounds (VOCs). One field duplicate pair was associated with this SDG: NTCFD01 / NTC22SB191920R1.

The samples were collected by TetraTech NUS on August 7 and 8, 2006 and analyzed by Severn Trent Laboratories, Inc., North Canton, OH. All analyses were conducted in accordance with USEPA SW 846 Method 8260B analytical and reporting protocol. The data contained in this SDG were validated with regard to the following parameters:

- Data Completeness
- Holding Times
- * Initial and Continuing Calibration
- Laboratory Blank Analyses
 - Field Duplicate Results
- Detection Limits

In addition, sample NTC22SB191920R1 was also validated with regard to the following parameters:

- * Surrogate Recoveries
- Blank Spike/Blank Spike Duplicate Results
- Matrix Spike/Matrix Spike Duplicate Results
- Internal Standard Recoveries
 - Compound Quantitation
- Compound Identification

The symbol (*) indicates that quality control criteria were met for this parameter. Problems affecting data quality are discussed below; documentation supporting these findings is presented in Appendix C. Qualified Analytical results are presented in Appendix A. Results as reported by the laboratory are presented in Appendix B.

TO:

B. DAVIS

DATE: JANUARY 23, 2007 - PAGE 2

Volatile

All samples except NTC22SB200203R required a dilution for tetrachloroethene and/or trichloroethene. No qualification of the data was necessary.

Additional Comments:

Positive results less than the reporting limit (RL) were qualified as estimated, J, due to uncertainty near the detection limit.

Detection limits for all samples, except NTC22SB200203R, are elevated due to the medium level preparation procedure. Detection limits for all compounds exceed those listed in the laboratory specification.

EXECUTIVE SUMMARY

Laboratory Performance Issues: None.

Other factors affecting data quality: None.

The data for these analyses were reviewed with reference to the EPA Functional Guidelines for Organic Data Validation (October 1999) and the Department of Defense (DoD) document entitled "Quality Systems Manual (QSM) for Environmental Laboratories" (January 2006). The text of this report has been formulated to address only those problem areas affecting data quality.

"I attest that the data referenced herein were validated according to the agreed upon validation criteria as specified in the DoD QSM."

Tetra Tech NUS

Edward SedImyer Chemist/Data Validator

Joseph A. Samchuck

Tetra Tech NUS

Data Validation Quality Assurance Officer

Attachments:

Appendix A - Qualified Analytical Results

Appendix B - Results as Reported by the Laboratory

Appendix C - Support Documentation

APPENDIX A

QUALIFIED ANALYTICAL RESULTS

SDG: 6H09143 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date

lab_id

NTC22SB151112R1DL

8/7/2006

A6H090143002

qc_type units NM UG/KG

80.0

Pct_Solids DUP_OF:

nsample samp_date lab_id

qc_type
units
Pct_Solids

DUP_OF:

NTC22SB191920R1DL

8/8/2006 A6H090143005

NM UG/KG 88.0

qc_type units Pct_Solids

nsample samp_date lab_id NTC22SB200203R1DL

8/7/2006 A6H090143001

NM UG/KG 83.0

F.

DUP_OF:

			·
Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	510	U	
1,1,1-TRICHLOROETHANE	510	U	
1,1,2,2-TETRACHLOROETHANE	510	U	
1,1,2-TRICHLOROETHANE	510	U	
1,1-DICHLOROETHANE	510	U	
1,1-DICHLOROETHENE	510	U	
1,2-DICHLOROETHANE	510	U	
CARBON TETRACHLORIDE	510	U	
CHLOROETHANE	510	U	
CHLOROMETHANE	510	U	
CIS-1,2-DICHLOROETHENE	510	U	*****
TETRACHLOROETHENE	15000		
TRANS-1,2-DICHLOROETHENE	510	U	
TRICHLOROETHENE	200	J	P
VINYL CHLORIDE	510	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	46000	U	
1,1,1-TRICHLOROETHANE	46000	U	
1,1,2,2-TETRACHLOROETHANE	46000	U	
1,1,2-TRICHLOROETHANE	46000	U	
1,1-DICHLOROETHANE	46000	U	-
1,1-DICHLOROETHENE	46000	U	
1,2-DICHLOROETHANE	46000	U	
CARBON TETRACHLORIDE	46000	U	
CHLOROETHANE	46000	U	
CHLOROMETHANE	46000	U	
CIS-1,2-DICHLOROETHENE	46000	U	
TETRACHLOROETHENE	1000000		
TRANS-1,2-DICHLOROETHENE	46000	U	
TRICHLOROETHENE	33000	J	Р
VINYL CHLORIDE	46000	U	

Parameter	Result	Val Qual	Qual Code
	-		
1,1,1,2-TETRACHLOROETHANE	5.2	U	
1,1,1-TRICHLOROETHANE	5.2	U	
1,1,2,2-TETRACHLOROETHANE	5.2	U	
1,1,2-TRICHLOROETHANE	5.2	U	
1,1-DICHLOROETHANE	5.2	U	
1,1-DICHLOROETHENE	5.2	U	
1,2-DICHLOROETHANE	5.2	U	
CARBON TETRACHLORIDE	5.2	U	
CHLOROETHANE	5.2	U	
CHLOROMETHANE	5.2	Ü	
CIS-1,2-DICHLOROETHENE	5.2	U	
TETRACHLOROETHENE	0.91	J	Р
TRANS-1,2-DICHLOROETHENE	5.2	U	
TRICHLOROETHENE	5.2	U	
VINYL CHLORIDE	5.2	U	

SDG: 6H09143 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date NTC22SB210910R1DL

8/7/2006

A6H090143003

qc_type units

lab_id

NM UG/KG

Pct_Solids 90.0

DUP_OF:

nsample samp_date lab_id qc_type

Pct_Solids

DUP_OF:

units

NTC22SB211314R1DL 8/7/2006

A6H090143004

NM UG/KG 89.0

nsample samp_date lab_id qc_type units

NTCFD01DL 8/8/2006 A6H090143006

NM UG/KG 88.0

Pct_Solids DUP_OF:

NTC22SB191920R1

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	230	U	
1,1,1-TRICHLOROETHANE	230	U	
1,1,2,2-TETRACHLOROETHANE	230	U	
1,1,2-TRICHLOROETHANE	230	U	
1,1-DICHLOROETHANE	230	U	
1,1-DICHLOROETHENE	230	U	
1,2-DICHLOROETHANE	230	U	-
CARBON TETRACHLORIDE	230	U	-
CHLOROETHANE	230	U	
CHLOROMETHANE	230	U	
CIS-1,2-DICHLOROETHENE	230	U	
TETRACHLOROETHENE	920		
TRANS-1,2-DICHLOROETHENE	230	U	
TRICHLOROETHENE	230	U	
VINYL CHLORIDE	230	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	220	U	
1,1,1-TRICHLOROETHANE	220	U	
1,1,2,2-TETRACHLOROETHANE	220	U	
1,1,2-TRICHLOROETHANE	220	Ų	
1,1-DICHLOROETHANE	220	U	
1,1-DICHLOROETHENE	220	U	
1,2-DICHLOROETHANE	220	U	
CARBON TETRACHLORIDE	220	U	
CHLOROETHANE	220	U	
CHLOROMETHANE	220	U	
CIS-1,2-DICHLOROETHENE	220	U	
TETRACHLOROETHENE	560		***************************************
TRANS-1,2-DICHLOROETHENE	220	U	
TRICHLOROETHENE	220		
VINYL CHLORIDE	220	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	44000	Ū	
1,1,1-TRICHLOROETHANE	44000	U	
1,1,2,2-TETRACHLOROETHANE	44000	U	
1,1,2-TRICHLOROETHANE	44000	U	
1,1-DICHLOROETHANE	44000	Ų	
1,1-DICHLOROETHENE	44000	U	
1,2-DICHLOROETHANE	44000	U	
CARBON TETRACHLORIDE	44000	U	
CHLOROETHANE	44000	Ų	
CHLOROMETHANE	44000	Ü	•
CIS-1,2-DICHLOROETHENE	44000	U	
TETRACHLOROETHENE	1400000		
TRANS-1,2-DICHLOROETHENE	44000	U	
TRICHLOROETHENE	44000		
VINYL CHLORIDE	44000	U	

SDG: 6H09143 MEDIA: SOIL DATA FRACTION: OV

nsample

TRIP BLANK-6H09143

samp_date

8/8/2006

lab_id

A6H090143007

qc_type

NM

units

UG/L

Pct_Solids DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	1	U.	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	1	U	
TETRACHLOROETHENE	. 1	· U	
TRANS-1,2-DICHLOROETHENE	1	U	
TRICHLOROETHENE	1	U	
VINYL CHLORIDE	1	U	

Chain of Custody Record



Client NS GREAT LAKES		Project		•	Bod												Da		18	100	;		G	hain of C	ustody (143	
Address		Teleph		umber 12					ber								Lat	Num	ber				P	age	/	_ of _	/
City State Zip	Code	Site Co		neno	SEL	- 1		Contact	d E22	0			121					(Attace is			7			Ţ			
Project Name and Location (State) NTC ZZ		Carrier FEO				45	47	732	5:	55	ۍ		CUOC											s	pecial	instruc	tions/
Contract/Purchase Order/Quote No.				Mat	rix				ontair eserv				ste-	מנכ	İ									C	onditio	ns of Ri	eceipt
Sample I.D. No. and Description (Containers for each sample may be combined on one line)	Date	Time	3	Sed	Soil	دعر	Charge	12SQ	3	Neon	ZnAc/ NeOH		ENCORE	MOSTUR											* :		
NTC 2258200203 R1	8-7-06	H15			X		χ					4	3	1		1											
NTCZZ SBISIIIZ RA	8-7-06	1505			X	·)	X L						3	1	ξ	1											
NTC 2258210910 R1	8-7-06	1620			X		x		<u> </u>				3	1	74 3			72	H	901	7	ועי	2n	ARO	UNP		
NTC225B21/314R1	8-7-06	1430			X		X	, -			7		3	1						à							
NTC22 58191920R1	8-8-06	0850	Ш		x		x	\perp	\perp				3	ı		2											
NTC FOOL	8-8-06	0000		\perp	X		x					,	3		~,*				1	1							i in die
	To provide the	rivb.	Ш																	L	- 1		4				
							\perp																				
			Ш																								
							\perp																				
																		Γ									
Possible Hazard Identification X Non-Hazard Flammable Skin Irritant	Poison B	☐ Unknowr		mple [Retui					posal	-				ive Fo	×		_ M	onths		fee n ger ti				ed if sam	pies are	retained	
Turn Around Time Required 24 Hours 48 Hours 7 Days 14 D	ays 🗌 21 Da	ys 💆 Otl	7er 7	Z- 16	TUL.		_ '	JG HE	equire	ment	s (Sp	ecity)															
1. Relinquished By Mark L. Mangel		Date 8-		۱,	ime 12 8	0	1	. Rec	eived	Ву	7	1	<u>,</u>				_	5					Ī	Date 8:9	:04	Time 9:	20
2. Relinquished By		Date			ime		2	?. Flec	eived	Ву				4									.	Date		Time	
3. Relinquished By		Date		1	ime		3	3. Flec	eived	Ву										**		-		Date		Time	· · · · · · · · · · · · · · · · · · ·
				I_			- 1																			1	

SEPTEMBER 2006



INTERNAL CORRESPONDENCE

TO:

MR. B. DAVIS

DATE:

JANUARY 23, 2007

FROM:

EDWARD SEDLMYER

COPIES:

DV FILE

SUBJECT:

ORGANIC DATA VALIDATION- VOA

CTO 009, NTC GREAT LAKES

SDG 6l13153

SAMPLES:

17/Solid

GL95105S0001R2

GL95105S0203R2

NTL22FD001

NTC22FD002

NTC22MW06D0708R2

NTC22MW10D0708R2

NTC22MW10D1112R2 NTC22SB150001R2 NTC22SB191920R2

NTC22SB200203R2

NTC22SB151112R2 NTC22SB200607R2

NTC22SB210910R2 NTCSB221819R2

NTC22SB211314R2 NTCMW05S0001R2 NTC22SB220708R2

OVERVIEW

The sample set for CTO 009 NTC Great Lakes, SDG 6l13153 consists of, seventeen (17) soil environmental samples. All samples were analyzed for select volatile organic compounds (VOCs). Two field duplicate pairs were associated with this SDG: NTC22FD001 / NTC22MW06D0708R2 and NTC22FD002 / NTC22SB191920R2.

The samples were collected by TetraTech NUS on September 12 and 13, 2006 and analyzed by Severn Trent Laboratories, Inc., North Canton, OH. All analyses were conducted in accordance with USEPA SW 846 Method 8260B analytical and reporting protocol. The data contained in this SDG were validated with regard to the following parameters:

- **Data Completeness**
- **Holding Times**
- Initial and Continuing Calibration
- Laboratory Blank Analyses
 - Field Duplicate Results
- **Detection Limits**

In addition, samples GL95105S0001R2 and NTL22SB191920R2 were also validated with regard to the following parameters:

- Surrogate Recoveries
- Blank Spike/Blank Spike Duplicate Results
- Matrix Spike/Matrix Spike Duplicate Results
 - Internal Standard Recoveries
 - **Compound Quantitation**
- Compound Identification

TO: B. DAVIS

DATE: JANUARY 23, 2007 - PAGE 2

The symbol (*) indicates that quality control criteria were met for this parameter. Problems affecting data quality are discussed below; documentation supporting these findings is presented in Appendix C. Qualified Analytical results are presented in Appendix A. Results as reported by the laboratory are presented in Appendix B.

Volatile

The surrogate dibromofluoromethane had percent recoveries less than the quality control limit for the matrix spike / matrix spike duplicate (MS/MSD) associated with batch A6I130153. No action was taken on this basis because the MS/MSD sample was not a TetraTech sample.

The surrogate 4-bromofluorobenzene had a percent recovery less than the quality control limit for sample NTC22SB191920R2. The positive and non-detected results for sample NTC22SB191920R2 were qualified as estimated (J) and (UJ), respectively.

The internal standard 1,4-dichlorobenzene-d4 had low area counts for samples NTC22SB191920R2 and NTC22FD002. The non-detected result for 1,1,2,2-tetrachloroethane in sample NTC22SB191920R2 was qualified as estimated (UJ). No action was taken on sample NTC22FD002 because this is a limited review.

The MS/MSD performed on sample NTC22SB151112R2 had a percent recovery greater than the quality control limit for trichloroethene in the MS and less than the quality control limit in the MSD. In addition, the relative percent difference exceeded the quality control limit. No action was taken on this basis because only a limited review was performed on this sample and the amount spiked was greater than 2 times the sample concentration.

The field duplicate precision exceeded the 50% relative percent difference (RPD) quality control limit for cis-1,2-dichloroethene, tetrachloroethene, and trichloroethene in the field duplicate pair NTC22MW06D0708R2 / NTC22FD001. Sample NTC22MW06D0708R2 was analyzed as a low level soil and sample NTC22FD001 was analyzed as a medium level soil. Positive results for the aforementioned compounds in the duplicate samples NTC22MW06D0708R2 / NTC22FD001 were qualified as estimated (J).

All samples except NTC22FD002, NTC22MW06D0708R2, NTC22MW10D0708R2, NTC22SB150001R2, NTC22SB191920R2, and NTC22SB220708R2 required dilutions for tetrachloroethane and/or trichloroethene.

Additional Comments:

Positive results less than the reporting limit (RL) were qualified as estimated, J, due to uncertainty near the detection limit.

Detection limits for all samples, except NTC22FD002, NTC22MW06D0708R2, NTC22MW10D0708R2, NTC22SB150001R2, NTC22SB191920R2, and NTC22SB220708R2 are elevated due to the medium level preparation procedure. Detection limits for all compounds exceed those listed in the laboratory specification.

EXECUTIVE SUMMARY

Laboratory Performance Issues: None.

Other factors affecting data quality: Field duplicate imprecision resulted in qualification of the data. Surrogate and internal standard non-compliances resulted in qualification of the data for one sample.

TO: B. DAVIS

DATE: JANUARY 23, 2007 – PAGE 3

The data for these analyses were reviewed with reference to the EPA Functional Guidelines for Organic Data Validation (October 1999) and the Department of Defense (DoD) document entitled "Quality Systems Manual (QSM) for Environmental Laboratories" (January 2006). The text of this report has been formulated to address only those problem areas affecting data quality.

"I attest that the data referenced herein were validated according to the agreed upon validation criteria as specified in the DoD QSM."

Tetra Tech NUS

Edward SedImyer Chemist/Data Validator

TetraTech MUS

Joseph A. Samchuck

Data Validation Quality Assurance Officer

Attachments:

Appendix A - Qualified Analytical Results

Appendix B - Results as Reported by the Laboratory

Appendix C – Support Documentation

APPENDIX A

QUALIFIED ANALYTICAL RESULTS

Data Validation Qualifier Codes:

A = Lab Blank Contamination

B = Field Blank Contamination

C = Calibration Noncompliance (e.g. % RSDs, %Ds, ICVs, CCVs, RRFs, etc.)

C01 = GC/MS Tuning Noncompliance

D = MS/MSD Recovery Noncompliance

E = LCS/LCSD Recovery Noncompliance

F = Lab Duplicate Imprecision

G = Field Duplicate Imprecision

H = Holding Time Exceedance

I = ICP Serial Dilution Noncompliance

J = GFAA PDS - GFAA MSA's r < 0.995 / ICP PDS Recovery Noncompliance

K = ICP Interference - includes ICS % R Noncompliance

L = Instrument Calibration Range Exceedance

M = Sample Preservation Noncompliance

N = Internal Standard Noncompliance

N01 = Internal Standard Recovery Noncompliance Dioxins

N02 = Recovery Standard Noncompliance Dioxins

N03 = Clean-up Standard Noncompliance Dioxins

O = Poor Instrument Performance (e.g. base-line drifting)

P = Uncertainty near detection limit (< 2 x IDL for inorganics and <CRQL for organics)

Q = Other problems (can encompass a number of issues; e.g. chromatography,interferences, etc.)

R = Surrogates Recovery Noncompliance

S = Pesticide/PCB Resolution

T = % Breakdown Noncompliance for DDT and Endrin

U = % Difference between columns/detectors >25% for positive results determined via GC/HPLC

V = Non-linear calibrations; correlation coefficient r < 0.995

W = EMPC result

X = Signal to noise response drop

Y = Percent solids <30%

Z = Uncertainty at 2 sigma deviation is greater than sample activity

SDG: 6113153 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date GL95105S0001R2DL

9/12/2006

lab_id qc_type A6I130153004

 qc_type
 NM

 units
 UG/KG

 Pct_Solids
 86.0

DUP_OF:

nsample

samp_date
lab_id
ac_type

qc_type
units
Pct_Solids
DUP_OF:

GL95105S0203R2

9/12/2006 A6I130153005

NM UG/KG 82.0 nsample samp_date lab_id qc_type units NTC22FD001DL 9/12/2006 A6I130153011 NM

units UG/KG
Pct_Solids 81.0

DUP_OF:

NTC22MW06D0708R2

Parameter Result Qual Co 1,1,1,2-TETRACHLOROETHANE 700 U 1,1,1-TRICHLOROETHANE 700 U 1,1,2,2-TETRACHLOROETHANE 700 U 1,1,2-TRICHLOROETHANE 700 U 1,1-DICHLOROETHANE 700 U 1,1-DICHLOROETHANE 700 U 1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000				
1,1,1-TRICHLOROETHANE 700 U 1,1,2,2-TETRACHLOROETHANE 700 U 1,1,2-TRICHLOROETHANE 700 U 1,1-DICHLOROETHANE 700 U 1,2-DICHLOROETHANE 700 U 1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	Parameter	Result		Qual Code
1,1,2,2-TETRACHLOROETHANE 700 U 1,1,2-TRICHLOROETHANE 700 U 1,1-DICHLOROETHANE 700 U 1,1-DICHLOROETHANE 700 U 1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	1,1,1,2-TETRACHLOROETHANE	700	U	
1,1,2-TRICHLOROETHANE 700 U 1,1-DICHLOROETHANE 700 U 1,1-DICHLOROETHENE 700 U 1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	1,1,1-TRICHLOROETHANE	700	U	
1,1-DICHLOROETHANE 700 U 1,1-DICHLOROETHENE 700 U 1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	1,1,2,2-TETRACHLOROETHANE	700	U	
1,1-DICHLOROETHENE 700 U 1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	1,1,2-TRICHLOROETHANE	700	U	
1,2-DICHLOROETHANE 700 U CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000	1,1-DICHLOROETHANE	700	U	
CARBON TETRACHLORIDE 700 U CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	1,1-DICHLOROETHENE	700	U	
CHLOROETHANE 700 U CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000	1,2-DICHLOROETHANE	700	U	
CHLOROMETHANE 700 U CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000 F	CARBON TETRACHLORIDE	700	U	
CIS-1,2-DICHLOROETHENE 110 J F TETRACHLOROETHENE 19000	CHLOROETHANE	700	U	
TETRACHLOROETHENE 19000	CHLOROMETHANE	700	U	
	CIS-1,2-DICHLOROETHENE	110	J	P
TRANS-1.2-DICHLOROETHENE 700 LI	TETRACHLOROETHENE	19000		
700	TRANS-1,2-DICHLOROETHENE	700	U	
TRICHLOROETHENE 200 J F	TRICHLOROETHENE	200	J	Р
VINYL CHLORIDE 700 U	VINYL CHLORIDE	700	U	

	Parameter	Result	Val Qual	Qual Code
	1,1,1,2-TETRACHLOROETHANE	300	U	
].	1,1,1-TRICHLOROETHANE	300	U	
	1,1,2,2-TETRACHLOROETHANE	300	U	
]	1,1,2-TRICHLOROETHANE	300	U	
	1,1-DICHLOROETHANE	300	U	
	1,1-DICHLOROETHENE	300	U	
	1,2-DICHLOROETHANE	300	U	
	CARBON TETRACHLORIDE	300	U	
	CHLOROETHANE	300	U	
].	CHLOROMETHANE	300	U	
	CIS-1,2-DICHLOROETHENE	300	U	
	TETRACHLOROETHENE	3200		
] ,	TRANS-1,2-DICHLOROETHENE	300	U	
	TRICHLOROETHENE	30	J	Р
	VINYL CHLORIDE	300	U	

<u> </u>		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	270	Ų	
1,1,1-TRICHLOROETHANE	270	U	
1,1,2,2-TETRACHLOROETHANE	270	U	
1,1,2-TRICHLOROETHANE	270	U	
1,1-DICHLOROETHANE	270	U	
1,1-DICHLOROETHENE	270	U	
1,2-DICHLOROETHANE	270	U	
CARBON TETRACHLORIDE	270	U	
CHLOROETHANE	270	U	
CHLOROMETHANE	270	U	
CIS-1,2-DICHLOROETHENE	180	J	GP
TETRACHLOROETHENE	1100	J	G
TRANS-1,2-DICHLOROETHENE	270	U	7
TRICHLOROETHENE	26	J	GP
VINYL CHLORIDE	270	U	

SDG: 6113153 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date

lab_id

qc_type

NTC22FD002DL-RE

A6I140268006 NM

units UG/KG Pct_Solids 84.0 NTC22SB191920R2

DUP_OF:

9/13/2006

samp_date lab_id qc_type units

> Pct_Solids DUP_OF:

nsample NTC22MW06D0708R2DL

9/12/2006 A6I130153010

NM UG/KG 81.0

nsample

samp_date lab_id qc_type

units Pct_Solids DUP_OF:

NTC22MW10D0708R2DL

9/12/2006 A6I130153008

NM UG/KG 80.0

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	4.8	U	
1,1,1-TRICHLOROETHANE	4.8	U	
1,1,2,2-TETRACHLOROETHANE	4.8	U	
1,1,2-TRICHLOROETHANE	4.8	· U	
1,1-DICHLOROETHANE	4.8	U	
1,1-DICHLOROETHENE	4.8	U	
1,2-DICHLOROETHANE	4.8	U	
CARBON TETRACHLORIDE	4.8	U	
CHLOROETHANE	4.8	U	
CHLOROMETHANE	4.8	U	
CIS-1,2-DICHLOROETHENE	2.5	J	Р
TETRACHLOROETHENE	4.8	U	
TRANS-1,2-DICHLOROETHENE	4.8	Ü	
TRICHLOROETHENE	0.86	J	Р
VINYL CHLORIDE	4.8	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	5.1	U	7
1,1,1-TRICHLOROETHANE	5.1	U	
1,1,2,2-TETRACHLOROETHANE	5.1	U	
1,1,2-TRICHLOROETHANE	5.1	U	
1,1-DICHLOROETHANE	5.1	U	
1,1-DICHLOROETHENE	5.1	U	
1,2-DICHLOROETHANE	5.1	U.	7
CARBON TETRACHLORIDE	5.1	U	
CHLOROETHANE	5.1	U	
CHLOROMETHANE	5.1	U	
CIS-1,2-DICHLOROETHENE	89	J	G
TETRACHLOROETHENE	170	J	G
TRANS-1,2-DICHLOROETHENE	2.7	J	Р
TRICHLOROETHENE	5.6	J	G
VINYL CHLORIDE	5.1	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	6	U	
1,1,1-TRICHLOROETHANE	6	U	
1,1,2,2-TETRACHLOROETHANE	6	U	
1,1,2-TRICHLOROETHANE	6	U	
1,1-DICHLOROETHANE	6	U	
1,1-DICHLOROETHENE	6	U	
1,2-DICHLOROETHANE	6	U	
CARBON TETRACHLORIDE	6	U	
CHLOROETHANE	6	U	
CHLOROMETHANE	6	U	
CIS-1,2-DICHLOROETHENE	6	U	
TETRACHLOROETHENE	3.5	J	Р
TRANS-1,2-DICHLOROETHENE	6	U	
TRICHLOROETHENE	0.55	J	Р
VINYL CHLORIDE	6	U	

SDG: 6113153 MEDIA: SOIL DATA FRACTION: OV

nsample

samp_date

9/12/2006 A6I130153009

NM qc_type units UG/KG Pct_Solids 90.0

DUP_OF:

lab_id

NTC22MW10D1112R2DL

samp_date lab_id qc_type

Pct_Solids

DUP_OF:

units

nsample

NTC22SB150001R2DL 9/12/2006

A61130153006

NM UG/KG 88.0

nsample samp_date lab_id qc_type units

NTC22SB151112R2DL 9/12/2006 A6I130153007

NM UG/KG 87.0

Pct_Solids DUP_OF:

	Val	Qual
Result	Qual	Code
5000	U	
5000	U	-
5000	U	
190000		
5000	U	
2200	J	Р
5000	U	
	5000 5000 5000 5000 5000 5000 5000 500	Result Qual 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U 5000 U

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	- 5	U	
1,1,1-TRICHLOROETHANE	5	U	
1,1,2,2-TETRACHLOROETHANE	5	U.	
1,1,2-TRICHLOROETHANE	5	U	
1,1-DICHLOROETHANE	5	U	
1,1-DICHLOROETHENE	1.1	J	P
1,2-DICHLOROETHANE	5	U	
CARBON TETRACHLORIDE	5	U	
CHLOROETHANE	5	U	
CHLOROMETHANE	5	Ų.	
CIS-1,2-DICHLOROETHENE	170		
TETRACHLOROETHENE	5.3		
TRANS-1,2-DICHLOROETHENE	8		
TRICHLOROETHENE	- 39		
VINYL CHLORIDE	0.48	J	Р

		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	2600	U	
1,1,1-TRICHLOROETHANE	2600	U	
1,1,2,2-TETRACHLOROETHANE	2600	U	
1,1,2-TRICHLOROETHANE	2600	U	
1,1-DICHLOROETHANE	2600	U	
1,1-DICHLOROETHENE	2600	U	
1,2-DICHLOROETHANE	2600	U	
CARBON TETRACHLORIDE	2600	U	
CHLOROETHANE	2600	U	
CHLOROMETHANE	2600	U	
CIS-1,2-DICHLOROETHENE	2600	U	
TETRACHLOROETHENE	92000		
TRANS-1,2-DICHLOROETHENE	2600	U	
TRICHLOROETHENE	2100	J	Р
VINYL CHLORIDE	2600	U	

SDG: 6113153 MEDIA: SOIL DATA FRACTION: OV

 nsample
 NTC2SB191920R2DL

 samp_date
 9/13/2006

 lab_id
 A6I140268005

qc_typeNMunitsUG/KGPct_Solids90.0

DUP_OF:

nsample NTC22SB200203R2DL samp_date 9/12/2006 lab id A6l130153001

lab_id qc_type units Pct_Solids

DUP_OF:

NM UG/KG 84.0 nsample samp_date lab_id qc_type units

Pct_Solids

DUP_OF:

NTC22SB200607R2DL 9/12/2006 A6l130153002

NM UG/KG 89.0

DOP_OF.			
Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	4.6	UJ	R
1,1,1-TRICHLOROETHANE	4.6	UJ	R
1,1,2,2-TETRACHLOROETHANE	4.6	UJ	NR
1,1,2-TRICHLOROETHANE	4.6	UJ	R
1,1-DICHLOROETHANE	4.6	UJ	R
1,1-DICHLOROETHENE	4.6	UJ	R
1,2-DICHLOROETHANE	4.6	UJ	R
CARBON TETRACHLORIDE	4.6	UJ	R
CHLOROETHANE	4.6	UJ	R
CHLOROMETHANE	4.6	UJ	R
CIS-1,2-DICHLOROETHENE	3.5	J	PR
TETRACHLOROETHENE	4.6	UJ	· R
TRANS-1,2-DICHLOROETHENE	4.6	UJ	R
TRICHLOROETHENE	1.4	J	PR
VINYL CHLORIDE	4.6	UJ	R

		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	280	U	
1,1,1-TRICHLOROETHANE	280	U	
1,1,2,2-TETRACHLOROETHANE	280	U	
1,1,2-TRICHLOROETHANE	280	U	
1,1-DICHLOROETHANE	280	U	
1,1-DICHLOROETHENE	280	Ü	
1,2-DICHLOROETHANE	280	U	
CARBON TETRACHLORIDE	280	U	
CHLOROETHANE	280	U	
CHLOROMETHANE	280	U	
CIS-1,2-DICHLOROETHENE	280	U	
TETRACHLOROETHENE	1100		
TRANS-1,2-DICHLOROETHENE	280	U	
TRICHLOROETHENE	280	U	
VINYL CHLORIDE	280	U	

		Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	240	U	
1,1,1-TRICHLOROETHANE	240	U	
1,1,2,2-TETRACHLOROETHANE	240	U	
1,1,2-TRICHLOROETHANE	240	U	
1,1-DICHLOROETHANE	240	U	
1,1-DICHLOROETHENE	240	U	
1,2-DICHLOROETHANE	240	U	
CARBON TETRACHLORIDE	240	U	
CHLOROETHANE	240	U	
CHLOROMETHANE	240	U	
CIS-1,2-DICHLOROETHENE	240	U	
TETRACHLOROETHENE	3300		
TRANS-1,2-DICHLOROETHENE	240	U	
TRICHLOROETHENE	91	J	Р
VINYL CHLORIDE	240	υ	

SDG: 6113153 MEDIA: SOIL DATA FRACTION: OV

nsample

NTC22SB210910R2DL

nsample samp_date

lab_id

units

NTC22SB211314R2DL

nsample NTC22SB220708R2DL

samp_date lab_id

9/13/2006 A6I140268001 9/13/2006

9/13/2006 samp_date A6I140268003

qc_type units

NM

A6I140268002 NM qc_type

lab_id qc_type NM

Pct_Solids

UG/KG 83.0

UG/KG 86.0

UG/KG Pct_Solids 79.0

DUP_OF:

Pct_Solids DUP_OF:

DUP_OF:

units

Result	Val Qual	Qual Code
240	U	
240	U	
240	U	1 4.
240	U	
420		
240	U	
240	U	
240	U	
	240 240 240 240 240 240 240 240 240 240	Result Qual 240 U

			
Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	210	U	
1,1,1-TRICHLOROETHANE	210	U	
1,1,2,2-TETRACHLOROETHANE	210	U	
1,1,2-TRICHLOROETHANE	210	U	
1,1-DICHLOROETHANE	210	U	
1,1-DICHLOROETHENE	210	U	
1,2-DICHLOROETHANE	210	U	
CARBON TETRACHLORIDE	210	U	
CHLOROETHANE	210	Ü.	
CHLOROMETHANE	210	U	-
CIS-1,2-DICHLOROETHENE	250	4.	
TETRACHLOROETHENE	760		
TRANS-1,2-DICHLOROETHENE	210	U	
TRICHLOROETHENE	360		
VINYL CHLORIDE	210	U	

Result	Val Qual	Qual Code
5.4	U	
. 5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	
5.4	U	,
	5.4 5.4 5.4 5.4 5.4 5.4 5.4 5.4	Result Qual 5.4 U

SDG: 6113153 MEDIA: SOIL DATA FRACTION: OV

00202

nsample

NTC22SB221819R2DL

nsample

NTCMW05S0001R2DL

samp_date

9/13/2006

samp_date lab_id

9/12/2006 A6I130153003

lab_id qc_type units

A6I140268004 NM

qc_type

NM

Pct_Solids

UG/KG 85.0

units Pct_Solids UG/KG 84.0

DUP_OF:

DUP_OF:

			
Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1500	U	
1,1,1-TRICHLOROETHANE	1500	U	
1,1,2,2-TETRACHLOROETHANE	1500	U	
1,1,2-TRICHLOROETHANE	1500	U	
1,1-DICHLOROETHANE	1500	U	
1,1-DICHLOROETHENE	1500	U	
1,2-DICHLOROETHANE	1500	U	
CARBON TETRACHLORIDE	1500	U	
CHLOROETHANE	1500	U	-
CHLOROMETHANE	1500	U ·	
CIS-1,2-DICHLOROETHENE	1500	U	
TETRACHLOROETHENE	60000		
TRANS-1,2-DICHLOROETHENE	1500	U	
TRICHLOROETHENE	2400		
VINYL CHLORIDE	1500	U,	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	230	U	
1,1,1-TRICHLOROETHANE	230	U	
1,1,2,2-TETRACHLOROETHANE	230	U	
1,1,2-TRICHLOROETHANE	230	U	
1,1-DICHLOROETHANE	230	U	
1,1-DICHLOROETHENE	230	U	
1,2-DICHLOROETHANE	230	U	
CARBON TETRACHLORIDE	230	U	
CHLOROETHANE	230	U	
CHLOROMETHANE	230	U	
CIS-1,2-DICHLOROETHENE	230	U	
TETRACHLOROETHENE	640		
TRANS-1,2-DICHLOROETHENE	230	U	
TRICHLOROETHENE	230	U	
VINYL CHLORIDE	230	U	

Chain of Custody Record

Severn Trent Laboratories, Inc.

TL-4124 (0901)		Project	Mana	oer													Di						Che	in of Custody Nun	ber
Client Tools Took Alus		1.10,223		,	Bo.	6	DA	زرں	5										7-12	<u> 2 - C</u>	6			30878	53
TETRA Tech NUS		Telepho	one N	lumbe	er (Arc	ea Co	de)/Fa	x Nur	mber	7							La	ib Nur	nber				l_	1	ot
Address LLI Andersen Drive Chy State Zipt		41	Z	92	21	72								چ	_		1			lima 28			Pa	go _	<u>or</u>
City State Zip (Code	Site Co					Lai	Con	tact				-1	g.	Ŋ				tach i is nee						
Chy Petts bulen PA 200	15220	MA										<u>.</u>	_	ुं,	19			Т	T	T					
Project Name and Location (State)		Carrier				85	س در	1	222	, (~-·	70	ľ	7		1			ļ	1	[Special In	structions/
NS GREAT LAKES NTL ZZ				51		02	7) -						-	y	ž									Conditions	
Contract/Purchase Order/Quote No.				M	fatrix	·			Cont Pres					ENCOLE	MOISTUR										
Sample I.D. No. and Description (Containers for each sample may be combined on one line)	Date	Time	*	Aqueous	Seo.	3	Unpres	HZSON	PANO3	Ţ	NeO.	N S		-}	8		5 (§) 1 (§)		1	L		n de de la compansión d	4 -		The late of the section of the secti
NTC2258200203 RZ	9/12/06	0745				x L					\dashv			3 ↓	×		1729 4 1 124 4 144 4			\perp	1	17-			
NTC 22 5B200607 R2	9/12/06	0755				X	1	1			_ }	\dashv		3	4	-	1	\dashv	2	+	H		Н	-	
NTC MW05 \$ 0001 RZ	9/12/06	085		1 v		1	_	1	_		_	-	• •	3	<u> </u>	+		\vdash		+	H	-	-		
1665 105\$ 0001 RZ	9/12/06	0845	_		\sqcup	1	╀.	\downarrow	_			\dashv		2	X.	+	_	\vdash		+	1-		\vdash		
6495105\$ 0203 RZ	9/12/06	0850	_	_	\sqcup	*	_	┼-	lacksquare	_			- 1	3	×	+	-	¥	+		+	∂	+	72 M Tu	KAROUN C
NTCZZSBIS DOOL RZ	8/12/06	0910	-	_		X	_	_	\vdash	-				-	<u> </u>				بلر		+	#	-		
NTC 2258 15 1112 RZ	9/12/04	0925	\perp	1		X	+	_	-	-				4	/	+-	L	19	ms	100	44	H	-		
NTC22 MW100 0708 RZ	9/12/06	1110	_	↓_		X	+	-	\vdash	-	-	\vdash	\dashv	-	<u>x</u>	╁┈	\vdash	\vdash	\dashv	+	+	H	$\ -$		
NTCZZ MW1001112 RZ	9/12/06	1145	\downarrow	igapha	\sqcup	시	\perp	+-	\dotplus	\vdash	-	$\left \cdot \right $			<u>X </u>	╁	╁╌		-+	╁	╁	H	+		
N7622 MW0600708 RZ	9/12/06	1020	1	┦-	 	시	4	+	╁	-	-	\vdash		_	X	+	+			+	+	\forall	+		
NTCZZ FPODI	9/12/06	0000	1	┦-	 	X	+	╬	╀	╀	-	Н	\vdash	3	×	+	+	+	-	+	\neq	1	╁╌		
	.		1						Ш.	<u>l</u>	_	L	نـــا	لـــا			1_	ــــــــــــــــــــــــــــــــــــــ	i_	1			ــــــــــــــــــــــــــــــــــــــ	<u> </u>	
Possible Hazard Identification		_			•	sposa					D 1			Amh	ive Fo			Mon		A fee onge	may than	be as	ssess onth)	ed if samples are r	etaineu
☐ Non-Hazard ☐ Flammable ☐ Skin Irritant	Poison B	Unkno	wn	<u>U/</u>	Return	To C	Hent	_=	Disp C Re			s (Sp			10.0			10000							
Turn Around Time Required		ays 😿 (^	72	- he	øUK		-		•															
24 Hours 48 Hours 7 Days 14	Days 🗀 21 U	Date			, Ti	ime		1.	. Rec	ej¶ea	Бу		7	7	_									Date	Time 4:15
1. Retinquished By Mark & Ming			12/	66		160	0	۱,	1		-	力			\geq	<u>د</u>								9-13-06 Date	Time
2. Relinquished By		Date	•		1	ime		12	. Rec	eivec	ру														
3. Relinquished By		Date	9		17	îme		3	. Rec	eived	Ву	-												Date	Time
								L																<u> </u>	L
Comments	•																								
necrossistical: WHITE - Returned to Client with Report		a with the C	amo!	o Di	NK - I	ield (200v													· ·					



INTERNAL CORRESPONDENCE

TO:

MR. B. DAVIS

DATE:

JANUARY 23, 2007

FROM:

EDWARD SEDLMYER

COPIES:

DV FILE

SUBJECT:

ORGANIC DATA VALIDATION- VOA

CTO 009, NTC GREAT LAKES

SDG 6129215

SAMPLES:

3/Solid

NTL22MW10D1012R3 NTL22SB151112R3

NTL22SB221819R3

OVERVIEW

The sample set for CTO 009 NTC Great Lakes, SDG 6l29215 consists of, three (3) soil environmental samples. All samples were analyzed for select volatile organic compounds (VOCs).

The samples were collected by TetraTech NUS on September 28, 2006 and analyzed by Severn Trent Laboratories, Inc., North Canton, OH. All analyses were conducted in accordance with USEPA SW 846 Method 8260B analytical and reporting protocol. The data contained in this SDG were validated with regard to the following parameters:

- **Data Completeness**
- **Holding Times**
 - Initial and Continuing Calibration
- Laboratory Blank Analyses
- **Detection Limits**

In addition, sample NTL22MW10D1012R3 was also validated with regard to the following parameters:

- Surrogate Recoveries
 - Blank Spike/Blank Spike Duplicate Results
- Matrix Spike/Matrix Spike Duplicate Results
- Internal Standard Recoveries
- Compound Quantitation
- Compound Identification

The symbol (*) indicates that quality control criteria were met for this parameter. Problems affecting data quality are discussed below, documentation supporting these findings is presented in Appendix C. Qualified Analytical results are presented in Appendix A. Results as reported by the laboratory are presented in Appendix B.

TO:

B. DAVIS

DATE: JANUARY 23, 2007 - PAGE 2

Volatile

Samples NTL22MW10D1012R3 and NTL22SB221819R3 required dilutions for tetrachloroethene and/or trichloroethene. No qualification of the data was necessary.

Additional Comments:

Positive results less than the reporting limit (RL) were qualified as estimated, J, due to uncertainty near the detection limit.

Detection limits for all samples are elevated due to the medium level preparation procedure. Detection limits for all compounds exceed those listed in the laboratory specification.

EXECUTIVE SUMMARY

Laboratory Performance Issues: None.

Other factors affecting data quality: None.

TO: B. DAVIS

DATE: JANUARY 23, 2007 - PAGE 3

The data for these analyses were reviewed with reference to the EPA Functional Guidelines for Organic Data Validation (October 1999) and the Department of Defense (DoD) document entitled "Quality Systems Manual (QSM) for Environmental Laboratories" (January 2006). The text of this report has been formulated to address only those problem areas affecting data quality.

"I attest that the data referenced herein were validated according to the agreed upon validation criteria as specified in the DoD QSM."

Tetra Tech NUS

Edward SedImyer Chemist/Data Validator

Joseph A. Samchuck

Data Validation Quality Assurance Officer

Attachments:

Appendix A - Qualified Analytical Results

Appendix B - Results as Reported by the Laboratory

Appendix C – Support Documentation

Data Validation Qualifier Codes:

A = Lab Blank Contamination

B = Field Blank Contamination

C = Calibration Noncompliance (e.g. % RSDs, %Ds, ICVs, CCVs, RRFs, etc.)

C01 = GC/MS Tuning Noncompliance

D = MS/MSD Recovery Noncompliance

E = LCS/LCSD Recovery Noncompliance

F = Lab Duplicate Imprecision

G = Field Duplicate Imprecision

H = Holding Time Exceedance

I = ICP Serial Dilution Noncompliance

J = GFAA PDS - GFAA MSA's r < 0.995 / ICP PDS Recovery Noncompliance

K = ICP Interference - includes ICS % R Noncompliance

L = Instrument Calibration Range Exceedance

M = Sample Preservation Noncompliance

N = Internal Standard Noncompliance

N01 = Internal Standard Recovery Noncompliance Dioxins

N02 = Recovery Standard Noncompliance Dioxins

N03 = Clean-up Standard Noncompliance Dioxins

O = Poor Instrument Performance (e.g. base-line drifting)

P = Uncertainty near detection limit (< 2 x IDL for inorganics and <CRQL for organics)

Q = Other problems (can encompass a number of issues; e.g. chromatography, interferences, etc.)

R = Surrogates Recovery Noncompliance

S = Pesticide/PCB Resolution

T = % Breakdown Noncompliance for DDT and Endrin

U = % Difference between columns/detectors >25% for positive results determined via GC/HPLC

V = Non-linear calibrations; correlation coefficient r < 0.995

W = EMPC result

X = Signal to noise response drop

Y = Percent solids <30%

Z = Uncertainty at 2 sigma deviation is greater than sample activity

APPENDIX A

QUALIFIED ANALYTICAL RESULTS

SDG: 6129215 MEDIA: SOIL DATA FRACTION: OV

nsample samp_date NTL22MW10D1012R3DL

9/28/2006

A6I290215002

lab_id qc_type units

NM UG/KG

Pct_Solids 86.0

DUP_OF:

nsample samp_date lab_id qc_type

9/28/2006 A6I290215001

NTL22SB151112R3DL

NM · UG/KG 87.0

nsample samp_date lab_id

qc_type

Pct_Solids

units

NTL22SB221819R3DL

9/28/2006 A6I290215003

NM UG/KG 86.0

Pct_Solids DUP_OF:

units

DUP_OF:

Parameter	Result	Val Qual	Qua Code
1,1,1,2-TETRACHLOROETHANE	470	U	
1,1,1-TRICHLOROETHANE	470	U	
1,1,2,2-TETRACHLOROETHANE	470	U	
1,1,2-TRICHLOROETHANE	470	U	
1,1-DICHLOROETHANE	470	U	
1,1-DICHLOROETHENE	470	U	
1,2-DICHLOROETHANE	470	U	
CARBON TETRACHLORIDE	470	U	
CHLOROETHANE	470	U	
CHLOROMETHANE	470	U	
CIS-1,2-DICHLOROETHENE	470	Ų	
TETRACHLOROETHENE	15000		
TRANS-1,2-DICHLOROETHENE	470	U	
TRICHLOROETHENE	380	J	.P
VINYL CHLORIDE	470	U	

	1	Val	Qual
Parameter	Result		Code
i arameter	nesuit	Quai	Code
1,1,1,2-TETRACHLOROETHANE	240	U	
1,1,1-TRICHLOROETHANE	240	U	
1,1,2,2-TETRACHLOROETHANE	240	U .	
1,1,2-TRICHLOROETHANE	240	U	
1,1-DICHLOROETHANE	240	U	
1,1-DICHLOROETHENE	240	U	
1,2-DICHLOROETHANE	240	U	
CARBON TETRACHLORIDE	240	U	
CHLOROETHANE	240	U	
CHLOROMETHANE	240	U	
CIS-1,2-DICHLOROETHENE	240	U	
TETRACHLOROETHENE	960		
TRANS-1,2-DICHLOROETHENE	240	U	
TRICHLOROETHENE	56	J	Р
VINYL CHLORIDE	240	U	

			
Description	DII	Val	Qual
Parameter	Result	Qual	Code
1,1,1,2-TETRACHLOROETHANE	380	U	
1,1,1-TRICHLOROETHANE	380	U	
1,1,2,2-TETRACHLOROETHANE	380	Ų	
1,1,2-TRICHLOROETHANE	380	U	
1,1-DICHLOROETHANE	380	U	
1,1-DICHLOROETHENE	380	U	
1,2-DICHLOROETHANE	380	U	
CARBON TETRACHLORIDE	380	U	
CHLOROETHANE	380	U	
CHLOROMETHANE	380	U	
CIS-1,2-DICHLOROETHENE	74	J	Р
TETRACHLOROETHENE	11000		
TRANS-1,2-DICHLOROETHENE	380	U	
TRICHLOROETHENE	4000		
VINYL CHLORIDE	380	U	

Chain of Custody Record



STL-124 (0901) Client TETRA TECH NUS INC	.	Projec	t Mar	nager		30	6	Dr	301								Da	ite	9-	2	9-0	16		Chain of Custody N	1umber 3 7 7
Address 641 ANdersen Drive Ste		Telepi		41			2/	-7	25	/				<u>ي</u>				b Nu	mber				T	Page/	of
PITTS BURGH PA	15220	Site C	al d	H			- 1	lab Ç Lo.		Ezi	2 6			700			nalysi ore sp								
Project Name and Location (State) NAUAL STATION GREAT LAKE	'S	Carrie	rway 83	rbili N 45	umbe	シスシ	3Z	ح ۔	58	29			Ì	100	2						l			Special	Instructions
Contract/Purchase Order/Quote No. //2600202				٨	Aatrix					ntaine serva				CORE	MOISTUR			1				1		Condition	ns of Receip
Sample I.D. No. and Description (Containers for each sample may be combined on one line)	Date	Time	*	Aqueous	Sect.	NOS.	dai i ce	Unpres	HNO3	¥Ç.	NaOH	ZhAc/ NaOH		ENC	700				r)						î
NTC225B151112 R3	9/28	1325			2	x								3	4										
NTCZZMWIBD1012 R3	9/28	1410				x.				<u> </u>		Ш	_	3	1	_	14	-	7	4	1/4.		741	n AR OU	sd.
NTC225B221819 R3	9/28	1445	-	· /		X	4	-	-	-	ļ	$\frac{1}{1}$	\dashv	3	4	+		4	1	4	+				
			+	H		+	\dagger		\dagger	+	-		+	\dashv		+		+	+		\dagger	\dagger	+		
						1								. 1											
		· · · · · · · · · · · · · · · · · · ·			_	_	\downarrow	_	\downarrow	ļ	_		_	_		_		4	_	\perp	4	-			
				Н	+	+	+	+	╬		_	H	+	\dashv	+	+	H	\dashv	\dashv	\dashv	+	$^{+}$	+		
					\dashv	\top	\dagger	+	\dagger			H	1	\dashv	+	+	\prod	\dashv	+	\dashv	+	+			
									1																
Possible Hazard Identification			15	iamo	e Dis	posal	_									\perp									
☐ Non-Hazard ☐ Flammable ☐ Skin Irritant Turn Around Time Required	Poison B	Unknow			etum '	•			_	osal l		ab Is (Spe			e For	-		Mont					isses: ionth)	sed if samples are	retained
24 Hours 48 Hours 7 Days 14 Da	nys 🗌 21 Day	ys 🗷 O	her	<u>72</u>	ho	vK		_ "		quir ca	1163116	عرب د	روبداد	_	•		يسب	<u> </u>							
1. Relinquished By Mark L. Minail		Date 9/2	281	66	Tim	1e 60	0	1	Rec	eived	Ву	5) -							-		9-29-96	179:20
?. Relinquished By		Date			Tim	16		2	Rec	sived	Ву	_	_											Date	Time
3. Relinquished By		Date			Tim	10		3	Rec	eived	Ву											.		Date	Time
Comments		<u> </u>			1															-				I	1

MARCH 2007



Tetra Tech NUS

INTERNAL CORRESPONDENCE

TO:

B. DAVIS

DATE:

APRIL 17, 2007

FROM:

TERRI L. SOLOMON

COPIES:

DV FILE

SUBJECT:

ORGANIC DATA VALIDATION - VOCs

CTO - 009 NTC GREAT LAKES

SAMPLE DELIVERY GROUP (SDG) - 7C13195

SAMPLES:

4/Aqueous/

NTC22MW06SR

NTC22MW10DR

NTC22MW10SR

TRIP BLANK

Overview

The sample set for CTO 009, NTC Great Lakes, SDG 7C13195, consists of three (3) environmental samples and one (1) trip blank. No field duplicate pairs were included within this SDG.

All samples were analyzed for select volatile organic compounds (VOCs). The samples were collected by Tetra Tech NUS on March 10 and 11, 2007 and analyzed by Severn Trent Laboratories – North canton under Naval Facilities Engineering Service Center (NFESC) Quality Assurance/Quality Control (QA/QC) criteria. VOC analyses were conducted using SW-846 method 8260B.

These data were evaluated based on the following parameters:

- Data Completeness
- Holding Times
- Initial / Continuing Calibration Results
- Laboratory / Field Blank Analyses
- Detection Limits

In addition, sample NTC22MW06SR was also validated with regard to the following parameters:

- Surrogate Recoveries
- Blank Spike / Blank Spike Duplicate Results
- Matrix Spike / Matrix Spike Duplicate Results
- Internal Standard Recoveries
- Compound Quantitation
- Compound Identification
 - * All quality control criteria were met for this parameter.

TO:

B. DAVIS - PAGE 2

DATE:

APRIL 17, 2007

Initial / Continuing Calibration Results

Continuing calibration percent difference (3/15/07 8:17) for chloroethane was > 25% quality control limit. The nondetected result reported for chloroethane affecting sample NTC22MW06SR was qualified as estimated, "UJ".

Notes

Positive results reported below the reporting limit (RL) but above the method detection limit (MDL) for the organic analyses were qualified as estimated, "J".

Executive Summary

Laboratory Performance: A continuing calibration noncompliance was noted for chloroethane.

Other Factors Affecting Data Quality: None.

The data for these analyses were reviewed with reference to the "National Functional Guidelines for Organic Review", October 1999 and the DOD document entitled "Quality System Manual (QSM) for Environmental Laboratories" (Jan 2006).

The text of this report has been formulated to address only those problem areas affecting data quality.

"I attest that the data referenced herein were validated according to the agreed upon validation criteria as specified in the DOD QSM and the Quality Assurance Project Plan (QAPP)."

Tetra Tech NUS Terri L. Solomon

Environmental Scientist

Tetra Tech MUS Joseph A. Samchuck Quality Assurance Officer

Attachments:

- 1. Appendix A Qualified Analytical Results
- 2. Appendix B Results as reported by the Laboratory
- 3. Appendix C Support Documentation

APPENDIX A QUALIFIED ANALYTICAL RESULTS

Data Validation Qualifier Codes:

A = Lab Blank Contamination

B = Field Blank Contamination

C = Calibration Noncompliance (e.g. % RSDs, %Ds, ICVs, CCVs, RRFs, etc.)

C01 = GC/MS Tuning Noncompliance

D = MS/MSD Recovery Noncompliance

E = LCS/LCSD Recovery Noncompliance

F = Lab Duplicate Imprecision

G = Field Duplicate Imprecision

H = Holding Time Exceedance

1 = ICP Serial Dilution Noncompliance

J = GFAA PDS-GFAA MSA's r < 0.995 / ICP PDS Recovery Noncompliance

K = ICP Interference - includes ICS % R Noncompliance

L = Instrument Calibration Range Exceedance

M = Sample Preservation Noncompliance

N = Internal Standard Noncompliance

N01 = Internal Standard Recovery Noncompliance Dioxins

N02 = Recovery Standard Noncompliance Dioxins

N03 = Clean-up Standard Noncompliance Dioxins

Poor Instrument Performance (e.g. base-line drifting)

P = Uncertainty near detection limit (< 2 x IDL for inorganics and <CRQL for organics)

Q = Other problems (can encompass a number of issues; e.g. chromatography, interferences, etc.)

R = Surrogates Recovery Noncompliance

S = Pesticide/PCB Resolution

T = % Breakdown Noncompliance for DOT and Endrin

U = % Difference between columns/detectors >25% for positive results determined via GC/HPLC

V = Non-linear calibrations; correlation coefficient r < 0.995

W = EMPC result

X = Signal to noise response drop

Y = Percent solids <30%

Z = Uncertainty at 2 sigma deviation is greater than sample activity

SDG: 7C13195 MEDIA: WATER DATA FRACTION: OV

nsample samp_date NTC22MW06SR

3/11/2007

lab_id qc_type units

Pct_Solids DUP_OF:

A7C130195003

NM

UG/L

qc_type units

lab_id

nsample NTC22MW10DR

3/10/2007 samp_date A7C130195002

> МИ UG/L

Pct_Solids DUP_OF:

nsample samp_date

lab_id qc_type units

NTC22MW10SR

3/10/2007 A7C130195001

NM UG/L

Pct_Solids DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	. 1	U	
CHLOROETHANE	1	UJ	С
CHLOROMETHANE	0.38	J	Р
CIS-1,2-DICHLOROETHENE	2.3		
TETRACHLOROETHENE	9.2		
TRANS-1,2-DICHLOROETHENE	1	U	·
TRICHLOROETHENE	5.2		•
VINYL CHLORIDE	1	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	. U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	. 1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	0.21	J	Р
TETRACHLOROETHENE	16		
TRANS-1,2-DICHLOROETHENE	1	U	-
TRICHLOROETHENE	1.2		
VINYL CHLORIDE	1	U	

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	U	
1,1,2,2-TETRACHLOROETHANE	. 1	. U	
1,1,2-TRICHLOROETHANE	1	U	
1,1-DICHLOROETHANE	1	U	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	1.3		
TETRACHLOROETHENE	1.2		
TRANS-1,2-DICHLOROETHENE	· 1	U	
TRICHLOROETHENE	1	U	
VINYL CHLORIDE	1	U	

SDG: 7C13195 MEDIA: WATER DATA FRACTION: OV

nsample

TRIP BLANK

samp_date

3/11/2007

lab_id

A7C130195004

qc_type

NM

units

UG/L

Pct_Solids

DUP_OF:

Parameter	Result	Val Qual	Qual Code
1,1,1,2-TETRACHLOROETHANE	1	U	
1,1,1-TRICHLOROETHANE	1	· U	
1,1,2,2-TETRACHLOROETHANE	1	U	
1,1,2-TRICHLOROETHANE	. 1	٦	
1,1-DICHLOROETHANE	1	J	
1,1-DICHLOROETHENE	1	U	
1,2-DICHLOROETHANE	· 1	U	
CARBON TETRACHLORIDE	1	U	
CHLOROETHANE	1	U	
CHLOROMETHANE	1	U	
CIS-1,2-DICHLOROETHENE	1	U	
TETRACHLOROETHENE	1	U	
TRANS-1,2-DICHLOROETHENE	. 1	U	
TRICHLOROETHENE	1	· U	
VINYL CHLORIDE	1	U	

4609

PAGE ____ OF ____

11	ECT NO: 2 600	202	FACILITY: NTC GLEAT	LAKES		Bob	NAGER PAU	15	1	PHONE N 4/2 -	921-	7251		5Eu	CLA T			NTACT: 2013 E:	22 o
		GNATURE)	1					LEADER		PHONE N			A	DDRE				00.00	
1	lork i	1. Ming					YENG.	<i>EL</i> Number		412 9	21-8	723		-7/12 ITY. S7		HUF	FEL	DRIVE	
					FEC			545		32	822	4		, -		Can	TON,	Oh.	44720
				•	,,,,		T			CON	TAINER	TYPE	1						///
STAN	DARD TA	тП	· · · · · · · · · · · · · · · · · · ·				ıs					or GLASS			6/	$-\!\!\!/-$	-	/-/	
RUSH	TAT [7]			4 4), a.c.			USE	SERVAT	IVE		Her					///
<u> </u>	nr. 📋	48 nr. 121 /2	hr. 7 day 1	4 day			, SI	2	•	-			/	/ -		/	/-	/	
DATE 2007				LOCATION ID	тор Бертн (FT)	ВОТТОМ DEPTH (FT)	MATRIX (GW, SO, SW, SD, ETC.)	COLLECTION METHOD GRAB (G) COMP (C)	No. OF CONTAINERS	TIP	HO MI	pel /							NAMENTS
	TIME	- S .	AMPLE ID			750						$\overline{}$	ĺ	<u>(-) </u>	í 	<u>/ </u>	/ 		
3/10	1000	NTC ZZ	MW10\$ R		-	-	6W	6	<i>3</i>	_ 3	1 , 1	ļļ	* 1	12.3		1	37 5		
3/10	1245	NTC ZZ	MW 100 K	_		_	6W	6	3	3					<u> </u>	<u> </u>		<u> </u>	
3/11	1315	NTCZZ	MW 06 \$ R	_	-	_	GW	6	ማ	3_	ŀ			4		n j			
	esal a Sar e		BLANK				54.5									¥13.	4	840	٠.
																		7 10	
-			8-12				†								 	†	 		
						 	 			-	+					<u> </u>		-	
ļ						ļ	 				+								
							ļ		<u>. </u>			<u> </u>					ļ		
-	<u> </u>		-		1	 	1	1				 				 	†		
	\ ``			<u> </u>	-	 	+	+		 	-	+ +	n	·	 	-			
		IED DV		<u> </u>	DATE	<u> </u>	1	TIME	1	RECEIÝ	FORV			<u> </u>	!] D4	TE .	TIME
ŀ	LINQUISI							-											
2. RE	LINQUISI	IED BY	11. Mongel		DATE	-/2-0	7	TIME 1500	2.	35°	ED BY						94		18930
3. RE	LINQUIS	IED BY			DATE			TIME	3.	RECEIV				-			D/	ATE	TIME
COM	MENTS										****								
															F CODY			· · · · · · · · · · · · · · · · · · ·	4/00D

STL North Canton

APPENDIX G

NAVAL STATION GREAT LAKES GROUNDWATER USE RESTRICTIONS
MEMORANDUM



DEPARTMENT OF THE NAVY

NAVAL STATION 2801 E PAUL JONES 8T GREAT LAKES, ILLINOIS 60088-2845

> NAVSTAGLAKESINST 11130.1 ENV 29 Sep 03

NAVAL STATION GREAT LAKES INSTRUCTION 11130.1

From: Commanding Officer, Naval Station Great Lakes

Subj: Ground Water Use Restrictions

- 1. <u>Purpose</u>. To ensure compliance with environmental regulations for activities and personnel located on Naval Station Great Lakes.
- 2. Scope. This instruction applies to all geographic areas of the Naval Station.

3 Discussion.

- a. The use of ground water and surface water runoff for any purpose is strictly prohibited unless prior, written approval is obtained from the Commanding Officer, Naval Station Great Lakes. This includes, but is not limited to the installation of wells for any purpose, use of storm water run off from streams or retention ponds, etc.
- b. The only exception to this prohibition is the installation of ground water monitoring wells for the exclusive purpose of sampling ground water and monitoring of ground water/surface water. Approval for this activity must be secured in writing in advance from the Naval Station Great Lakes Environmental Department in coordination with the appropriate regulatory agencies.
- 4. Action. To initiate the process for installing a ground water well aboard the Naval Station, contact Naval Station Great Lakes Environmental Department, at (847) 688-5999 Or DSN 792-5999.

PROPROME

Distribution: NAVASTAGLAKES 5216.5 LISTS I AND II

APPENDIX H

GROUNDWATER MODELING CALCULATIONS

Steady State: $Cx = Cs^*exp((X/2^*ax)^*(1-sqrt(1+(4^*\lambda^*ax)/U)))^*erf(Sw/(4^*sqrt(ay^*X)))^*erf(Sd/(2^*sqrt(az^*X)))$

Paramete	r Value	Units	Description
Cx		ug/L	Concentration of constituent in groundwater at
			distance X downgradient of source
Cs	16.0	ug/L	Concentration of constituent in source zone
K	0.796	ft/day	Hydraulic conductivity
I	0.264	ft/ft	Hydraulic gradient
θ_{T}	0.35	unitless	Total soil porosity for silt
U	0.600	ft/day	Specific discharge, or groundwater seepage velocity (eq. F
Х	75	feet	Distance between source and point of exposure
ax	7.5	feet	=X*0.1, see eq. R16
ay	2.50	feet	=ax/3, see eq. R17
az	0.38	feet	=ax/20, see eq. R18
Sw	20	feet	Source width perpendicular to groundwater flow
Sd	15	feet	Source depth or thickness of groundwater stratum
λ	9.60E-04	days ⁻¹	First order degradation rate
exp			Exponential
erf			Error function

Сх	5.35	ug/L	Calculated concentration of constituent in groundwater arrithe unnamed tributary stream

Steady State: $Cx = Cs^*exp((X/2^*ax)^*(1-sqrt(1+(4^*\lambda^*ax)/U)))^*erf(Sw/(4^*sqrt(ay^*X)))^*erf(Sd/(2^*sqrt(az^*X)))$

Pa	ramet	er	Value	Units	Description	
	Сх			ug/L	Concentration of constituent in groundwater at distance X downgradient of source	
	Cs		16.0	ug/L	Concentration of constituent in source zone	•
	K		0.796	ft/day	Hydraulic conductivity	
	I		0.168	ft/ft	Hydraulic gradient	
	θ_{T}		0.35	unitless	Total soil porosity for silt	
	U		0.382	ft/day	Specific discharge, or groundwater seepage velocity	(eq. R19)
	Χ		75	feet	Distance between source and point of exposure	
	ax		7.5	feet	=X*0.1, see eq. R16	
	ay		2.50	feet	=ax/3, see eq. R17	a la
	az		0.38	feet	=ax/20, see eq. R18	
	Sw		20	feet	Source width perpendicular to groundwater flow	
	Sd		15	feet	Source depth or thickness of groundwater stratum	
	λ		9.60E-04	days ⁻¹	First order degradation rate	
	ехр				Exponential	
	erf				Error function	
	Сх		5.01	ug/L	Calculated concentration of constituent in groundwat the unnamed tributary stream	er arriving a

Steady State: $Cx = Cs^*exp((X/2^*ax)^*(1-sqrt(1+(4^*\lambda^*ax)/U)))^*erf(Sw/(4^*sqrt(ay^*X)))^*erf(Sd/(2^*sqrt(az^*X)))$

Param	eter	Value	Units	Description
C			ug/L	Concentration of constituent in groundwater at
				distance X downgradient of source
Cs	3	16.0	ug/L	Concentration of constituent in source zone
K		0.796	ft/day	Hydraulic conductivity
I		0.119	ft/ft	Hydraulic gradient
θ_{T}		0.35	unitless	Total soil porosity for silt
U		0.271	ft/day	Specific discharge, or groundwater seepage velocity (eq. R19)
Х		75	feet	Distance between source and point of exposure
ах	3	7.5	feet	=X*0.1, see eq. R16
ay	<i>.</i>	2.50	feet	=ax/3, see eq. R17
az	٠.	0.38	feet	=ax/20, see eq. R18
Sv	/ ** : : :	20	feet	Source width perpendicular to groundwater flow
Sc	100.	15	feet	Source depth or thickness of groundwater stratum
λ	artie in	9.60E-04	days ⁻¹	First order degradation rate
ex	o .			Exponential
er				Error function
C	•	4.65	ug/L	Calculated concentration of constituent in groundwater arriving at the unnamed tributary stream

Steady State: $Cx = Cs^*exp((X/2^*ax)^*(1-sqrt(1+(4^*\lambda^*ax)/U)))^*erf(Sw/(4^*sqrt(ay^*X)))^*erf(Sd/(2^*sqrt(az^*X)))$

Parameter	Value	Units	Description
		0	
Cx		ug/L	Concentration of constituent in groundwater at
			distance X downgradient of source
Cs	16.0	ug/L	Concentration of constituent in source zone
K	0.796	ft/day	Hydraulic conductivity
I	0.264	ft/ft	Hydraulic gradient
θ_{T}	0.35	unitless	Total soil porosity for silt
U	0.600	ft/day	Specific discharge, or groundwater seepage velocity (eq. R19)
X	1300	feet	Distance between source and point of exposure
ax	130	feet	=X*0.1, see eq. R16
ay	43.33	feet	=ax/3, see eq. R17
az	6.50	feet	=ax/20, see eq. R18
Sw	20	feet	Source width perpendicular to groundwater flow
Sd	15	feet	Source depth or thickness of groundwater stratum
λ	9.60E-04	days ⁻¹	First order degradation rate
exp			Exponential
erf			Error function
Сх	0.006	ug/L	Calculated concentration of constituent in groundwater arriving
			the unnamed tributary stream

Steady State: $Cx = Cs^*exp((X/2^*ax)^*(1-sqrt(1+(4^*\lambda^*ax)/U)))^*erf(Sw/(4^*sqrt(ay^*X)))^*erf(Sd/(2^*sqrt(az^*X)))$

Parameter	Value	Units	Description
Сх		ug/L	Concentration of constituent in groundwater at
		Ū	distance X downgradient of source
Cs	16.0	ug/L	Concentration of constituent in source zone
K	0.796	ft/day	Hydraulic conductivity
I	0.168	ft/ft	Hydraulic gradient
θ_{T}	0.35	unitless	Total soil porosity for silt
U, .	0.382	ft/day	Specific discharge, or groundwater seepage velocity (eq. R1)
X	1300	feet	Distance between source and point of exposure
ax	130	feet	=X*0.1, see eq. R16
ay	43.33	feet	=ax/3, see eq. R17
az	6.50	feet	=ax/20, see eq. R18
Sw	20	feet	Source width perpendicular to groundwater flow
Sd	15	feet	Source depth or thickness of groundwater stratum
λ 5 ±	9.60E-04	days ⁻¹	First order degradation rate
ехр			Exponential
erf			Error function
Сх	0.0026	ug/L	Calculated concentration of constituent in groundwater arriving
<u> </u>	0.0020	ug/L	the unnamed tributary stream

Steady State: $Cx = Cs^*exp((X/2^*ax)^*(1-sqrt(1+(4^*\lambda^*ax)/U)))^*erf(Sw/(4^*sqrt(ay^*X)))^*erf(Sd/(2^*sqrt(az^*X)))$

Parameter	Value	Units	Description
Сх		ug/L	Concentration of constituent in groundwater at distance X downgradient of source
Cs	16.0	ug/L	Concentration of constituent in source zone
K	0.796	ft/day	Hydraulic conductivity
I	0.119	ft/ft	Hydraulic gradient
θ_{T}	0.35	unitless	Total soil porosity for silt
U	0.271	ft/day	Specific discharge, or groundwater seepage velocity (eq. R19)
X	1300	feet	Distance between source and point of exposure
ax	130	feet	=X*0.1, see eq. R16
ay	43.33	feet	=ax/3, see eq. R17
az	6.50	feet	=ax/20, see eq. R18
Sw	20	feet	Source width perpendicular to groundwater flow
Sd	15	feet	Source depth or thickness of groundwater stratum
λ	9.60E-04	days ⁻¹	First order degradation rate
exp			Exponential
erf			Error function
Сх	0.0011	ug/L	Calculated concentration of constituent in groundwater arriving a the unnamed tributary stream



ILLINOIS EPA RCRA CORRECTIVE ACTION CERTIFICATION

This certification must accompany any document submitted to Illinois EPA in accordance with the corrective action requirements set forth in a facility's RCRA permit. The original and two copies of all documents submitted must be provided.

ACILITY IDENTIFICATION		
ame: Naval Station Great Lakes	**************************************	County: Lake
reet Address: Former Bldg 105, Sampsor	Street and Porter	Ave Site No. (IEPA): 0971255004
ity: Great Lakes		Site No. (USEPA): <u>IL7170024577</u>
WNER INFORMATION	The maybe	3.0 OPERATOR INFORMATION
ame: US Department of the Navy	and a	Same as Owner
-:11:	in a second	and the second s
ddress: Code N45 @ 201 Decatur Avenue	e, Building 1A	A rough from the second
Naval Station Great Lakes	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	en en en en en en en en en en en en en e
Navai Station Great Lakes		Control of the Contro
Great Lakes, IL 60088-5600	A PARTY OF S	
ontact Name: Mark Schultz	The state of the	The same was the same of the s
	\$10 M	
ontact Title: Environmental Director		
none No.: 847-688-5999 Ext 40		
WDE OF SUDMISSION (check applicable	la itam and pravid	o requested information as applicable)
YPE OF SUBMISSION (Check applicable	ie item and provid	e requested information, as applicable)
RFI Phase I Workplan/Report		EPA Permit Log No. C-689
		ate of Last IEPA Letter
		n Project Aril 9, 2003 og No. of Last IEPA
	ь Б	Letter on Project C-689-M-8
		oes this submittal include groundwater information: Yes
ne results of the ERH treatability study are	e being submitted.	With the remediation accomplished during the study, the docum
ates that the nazardous waste unit has been	ii ciosed in accorda	ance with a plan approved by the minors El A.
	Mark of the second	a annual and a consideration and the
	A service of the	
OCUMENTS SUBMITTED (identify al	l documents in sub	omittal, including cover letter; give dates of all documents)
as submittal includes the cover letter and	Electric Resistanc	e Heating (ERH) Treatability Study Report for Site 22 Former
uilding 105 Old Dry Cleaning Facility (Ju		
	the state of the s	STATE CONTROL OF THE
	reet Address: Former Bldg 105, Sampson ty: Great Lakes WNER INFORMATION ame: US Department of the Navy ailing Iddress: Code N45 @ 201 Decatur Avenue Naval Station Great Lakes Great Lakes, IL 60088-5600 ontact Name: Mark Schultz ontact Title: Environmental Director none No.: 847-688-5999 Ext 40 YPE OF SUBMISSION (check applicab RFI Phase I Workplan/Report RFI Phase I Workplan/Report CMP Report; Phase Other (describe): RH Treatability Study Report ate of Submittal June 2007 ESCRIPTION OF SUBMITTAL: (brief the results of the ERH treatability study are the that the hazardous waste unit has been	reet Address: Former Bldg 105, Sampson Street and Porter ty: Great Lakes WNER INFORMATION ame: US Department of the Navy ailing ddress: Code N45 @ 201 Decatur Avenue, Building 1A Naval Station Great Lakes Great Lakes, IL 60088-5600 ontact Name: Mark Schultz ontact Title: Environmental Director one No.: 847-688-5999 Ext 40 YPE OF SUBMISSION (check applicable item and provid RFI Phase I Workplan/Report RFI Phase II Workplan/Report CMP Report; Phase Other (describe): RH Treatability Study Report are of Submittal June 2007 DESCRIPTION OF SUBMITTAL: (briefly describe what the results of the ERH treatability study are being submitted. are results of the ERH treatability study are being submitted. OCUMENTS SUBMITTED (identify all documents in sult has submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes the cover letter and Electric Resistance in submittal includes in submittal electric Resistance in submittal includes in submittal includes the cover letter and Electric Resistance in submittal includes in submittal includ

Hiller ...

The state of the state of the same of the first

A RCRA Corrective Action Certification Site 22, Former Building 105				
e of Submission: June 2007	•			
2	•			
owner/operator certification set forth in 35 IAC 702.126.) All submittal signed by the person designated below (or but to be a corporation, by a prince the corporation of the corporati	cipal executive off oprietorship, by a good by either a principal of the cither and cither a principal of the cither and cither a principal of the cither and cither a principal of the cither and cit	icer of at least the level of vegeneral partner or the proprial executive officer or a rank	rice-president. ietor, respectively	y.
A person is a duly authorized representative	e only if:	appropriate the state of the		•
 the authorization is made in the written authorization is pused). 	writing by a perso	n described above, and	ously submitted a	authorization can be
	1, 4	and the second s		
Owner Signature:			(D. 1.)	
Title:	A STATE OF STATE	And the second s	(Date)	
Title:				
Operator Signature:		1. (a.c.)***		····
	All Sound		(Date)	
Title:		The second secon		
PROFESSIONAL CERTIFICATION (if to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approximately appro	es, such as the Illir essional Geologist with these laws an ws must be perform	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted poned in compliance with ther	reyor Act of 1989 actural Engineering ursuant to these l), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted po ned in compliance with ther ag authority.	eyor Act of 1989 ctural Engineerir ursuant to these l m. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the ap	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted po ned in compliance with ther ag authority.	reyor Act of 1989 actural Engineering ursuant to these l), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature:	es, such as the Illir essional Geologist with these laws an ws must be perforn propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted point ned in compliance with ther ag authority.	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted po ned in compliance with ther ag authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature:	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted po ned in compliance with ther ag authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted po ned in compliance with ther ag authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I	es, such as the Illir essional Geologist with these laws an ws must be perforn propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pi ned in compliance with ther g authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I	es, such as the Illir essional Geologist with these laws an ws must be perforn propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pi ned in compliance with ther g authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152	es, such as the Illir essional Geologist with these laws an ws must be perforn propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pi ned in compliance with ther g authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I	es, such as the Illir essional Geologist with these laws an ws must be perforn propriate regulatin	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pi ned in compliance with ther g authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois E), the Professional ng Licensing Act of laws. All work that fi
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pointed in compliance with ther ag authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois Expanded. Date: anal's Seal:	paration and analysis
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152 Professional's Phone No.: 412-921-7251 LABORATORY CERTIFICATION (if nefforts for which this laboratory was response)	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pointed in compliance with ther ag authority. Professio	reyor Act of 1989 actural Engineering ursuant to these lem. The Illinois Expanded. Date: anal's Seal:	paration and analysis
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152 Professional's Phone No.: 412-921-7251 LABORATORY CERTIFICATION (if n	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Stru d the regulations adopted pointed in compliance with ther ag authority. Professio	Date: preservation, precedures approved	paration and analysis
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152 Professional's Phone No.: 412-921-7251 LABORATORY CERTIFICATION (if nefforts for which this laboratory was response.)	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Strud the regulations adopted puned in compliance with their gauthority. Professional Profession	Date: preservation, precedures approved	paration and analysis by Illinois EPA.
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152 Professional's Phone No.: 412-921-7251 LABORATORY CERTIFICATION (if nefforts for which this laboratory was response)	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Strud the regulations adopted puned in compliance with their gauthority. Professional Profession	preyor Act of 1989 actural Engineering ursuant to these lem. The Illinois Engineering Date: Date: mal's Seal: preservation, precedures approved	paration and analysis by Illinois EPA. Date
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152 Professional's Phone No.: 412-921-7251 LABORATORY CERTIFICATION (if nefforts for which this laboratory was response.)	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Strud the regulations adopted puned in compliance with their gauthority. Professional Profession	preyor Act of 1989 actural Engineering ursuant to these lem. The Illinois Engineering Date: Date: mal's Seal: preservation, precedures approved	paration and analysis by Illinois EPA. Date
to other laws governing professional service Engineering Practice Act of 1989, the Profe 1989. No one is relieved from compliance within the scope and definitions of these law discovered violation of these laws to the approfessional's Signature: Professional's Name: Robert F. Davis, PE Professional's Address: Tetra Tech NUS, I 661 Andersen Roa Pittsburgh, PA 152 Professional's Phone No.: 412-921-7251 LABORATORY CERTIFICATION (if nefforts for which this laboratory was response.)	es, such as the Illir essional Geologist with these laws an ws must be perform propriate regulatin Inc. ad 220 necessary) - The sa	nois Professional Land Surv Licensing Act, and the Strud the regulations adopted puned in compliance with their gauthority. Professional Profession	preyor Act of 1989 actural Engineering ursuant to these lem. The Illinois Engineering Date: Date: mal's Seal: preservation, precedures approved	paration and analysis by Illinois EPA. Date

RCRA Interim Status Closure Certification Statement

To meet the requirements of 35 Ill. Adm. Code 725.215, this statement is to be completed by a responsible officer of the owner/operator (as defined in 35 Ill. Adm. Code 702.126) and an independent licensed professional engineer upon completion of interim status closure of a hazardous waste management unit.

Facility Name: Naval Station Great Lakes	and the second		
Illinois EPA Identification Number: 097125500	04	· · · · · · · · · · · · · · · · · · ·	
	tropologija kaj providento de la julije je		
USEPA Identification Number: <u>IL7170024577</u>			
Illinois EPA Closure Log No.: <u>C-689</u>	1.		
Name of Unit(s) Being Closed: Site 22, Former	Building 105 Old D	ry Cleaning F	acility

The hazardous waste management unit(s) identified above has/have been closed in accordance with the specifications in a plan approved with conditions and modifications by Illinois EPA. A report demonstrating closure was carried out in accordance with the approved plan is attached.

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Signature of Owner/Operator Responsible Officer	Date	Name and Title of Owner/Operator
		And the state of t
	14 3 h 4 4 1 4 1 5 m	to the second second second second second second second second second second second second second second second
Signature of Licensed P.E.	Date	Name of Licensed P.E. and Ill. License No.
No. 1 A 11 CD E .		Licensed P.E.'s Seal:
Mailing Address of P.E.:		Licensed P.E. S Seai.
	ethio a	Company of the Marie
Robert F. Davis, PE	1. 1. 1.	
	and the second s	en en en en en en en en en en en en en e
Tetra Tech NUS, Inc., 661 Ander	sen Drive_	A Community of the Comm
	A State Stat	And the second of the second o
Pittsburgh, PA 15220		The present of the first of the state of the
	and the state of t	and the second s

JKM:bjh\rcra-interim-status-closure-certification.doc